



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247 TEST REPORT

For

olibra llc

45 legion dr, CRESSKILL, New Jersey, United States 07626

FCC ID: 2AME8EMB1KU

Report Type: Original Report	Product Type: WIFI Bluetooth Module
Test Engineer:	Max Min
Report Number:	RSHA180720003-00A
Report Date:	2018-08-08
Reviewed By:	Oscar Ye RF Leader
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	9
TEST EQUIPMENT LIST	10
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)	11
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	19
APPLICABLE STANDARD	19
EUT SETUP.....	19
EMI TEST RECEIVER SETUP.....	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST RESULTS SUMMARY	20
TEST DATA	21
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	38
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	44
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50

TEST DATA	50
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST DATA	53
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	69
APPLICABLE STANDARD	69
TEST PROCEDURE	69
TEST DATA	69
FCC §15.247(d) - BAND EDGES TESTING	75
APPLICABLE STANDARD	75
TEST PROCEDURE	75
TEST DATA	75

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	olibra llc
Tested Model:	EMB-1000-U
Product Type:	WIFI Bluetooth Module
Dimension:	18.1mm(L)*19.3mm(W)*3.3mm(H)
Power Supply:	DC 3.3V

**All measurement and test data in this report was gathered from production sample serial number: 20180720003.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2018-07-20)*

Objective

This test report is prepared on behalf of *olibra llc* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submission with FCC ID: 2AME8EMB1KU.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth V3.0:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF test tool: SecureCRT

GFSK Power level: 4

π /4-DQPSK Power level: 4

8DPSK Power level: 4

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263
ESPRESSIF	Debug Board	ESP-WROOM-03	/
ESPRESSIF	Control Board	ESP32_Module_Test board 2L V1	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Data Cable	0.3	Debug Board	Control Board
USB Cable	0.8	Notebook	Debug Board
USB Cable-2	1.5	Notebook	Control Board

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2017-08-15	2018-08-14
BEST	DC Power Supply	PS-1502D+	/	2017-10-10	2018-10-09
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2017-08-27	2018-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band notch Filter	BRM50702	/	2017-08-05	2018-08-04
Narda	Attenuator/10dB	10dB	/	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2017-08-15	2018-08-14
BEST	DC Power Supply	PS-1502D+	/	2017-10-10	2018-10-09
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2018-07-23	2019-07-22
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
olibra llc	RF Cable	/	/	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ENV216	3560655016	2017-11-15	2018-11-14
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2017-08-15	2018-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
		(dBi)	(numeric)	(dBm)	(mW)			
BT 3.0	2402-2480	2.33	1.71	3.50	2.24	20	0.0008	1.000
BLE	2402-2480	2.33	1.71	0.00	1.00	20	0.0003	1.000
802.11b	2412-2462	2.33	1.71	25.00	316.23	20	0.1076	1.000
802.11g		2.33	1.71	25.00	316.23	20	0.1076	1.000
802.11 n-HT20		2.33	1.71	25.00	316.23	20	0.1076	1.000
802.11 n-HT40	2422-2452	2.33	1.71	22.50	177.83	20	0.0605	1.000

Note: 1. The tune-up conducted power was declared by the manufacturer.

2. Wi-Fi and BT can't transmit simultaneously.

Conclusion: The EUT meets exemption requirement - RF exposure evaluation greater than 20cm distance specified in § 2.1091. If the device built into a host as a portable usage, the additional RF exposure evaluation may be required as specified by § 2.1093.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has two types of antennas as below, which used a unique coupling to the intentional radiator, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	Antenna Gain
PIFA Antenna	1.82dBi
Dipole Antenna	2.33dBi


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data

Environmental Conditions


Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Max Min on 2018-08-07.

EUT operation mode: Transmitting in high channel of 8DPSK mode (Worst case)

Data for PIFA Antenna:**AC 120V/60 Hz, Line**

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.155	47.04	QP	9.000	L1	16.06	65.86	18.82	Compliance
0.155	23.29	AV	9.000	L1	16.06	55.86	32.57	Compliance
0.375	31.00	QP	9.000	L1	16.05	59.57	28.57	Compliance
0.375	26.45	AV	9.000	L1	16.05	49.57	23.12	Compliance
0.455	29.91	QP	9.000	L1	16.07	57.29	27.38	Compliance
0.455	27.28	AV	9.000	L1	16.07	47.29	20.01	Compliance
1.200	29.08	QP	9.000	L1	15.87	56.00	26.92	Compliance
1.200	24.39	AV	9.000	L1	15.87	46.00	21.61	Compliance
1.700	30.06	QP	9.000	L1	15.86	56.00	25.94	Compliance
1.700	24.73	AV	9.000	L1	15.86	46.00	21.27	Compliance
2.600	29.01	QP	9.000	L1	15.85	56.00	26.99	Compliance
2.600	20.77	AV	9.000	L1	15.85	46.00	25.23	Compliance


AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.160	46.42	QP	9.000	N	16.06	65.71	19.29	Compliance
0.160	25.45	AV	9.000	N	16.06	55.71	30.26	Compliance
0.455	29.88	QP	9.000	N	16.10	57.29	27.41	Compliance
0.455	28.88	AV	9.000	N	16.10	47.29	18.41	Compliance
1.200	28.85	QP	9.000	N	15.93	56.00	27.15	Compliance
1.200	25.47	AV	9.000	N	15.93	46.00	20.53	Compliance
1.700	30.06	QP	9.000	N	15.92	56.00	25.94	Compliance
1.700	23.83	AV	9.000	N	15.92	46.00	22.17	Compliance
2.850	29.16	QP	9.000	N	15.90	56.00	26.84	Compliance
2.850	19.87	AV	9.000	N	15.90	46.00	26.13	Compliance
5.400	26.37	QP	9.000	N	15.88	60.00	33.63	Compliance
5.400	19.50	AV	9.000	N	15.88	50.00	30.50	Compliance


Note:

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

Data for Dipole Antenna:**AC 120V/60 Hz, Line**

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.160	46.27	QP	9.000	L1	16.05	65.71	19.44	Compliance
0.160	22.78	AV	9.000	L1	16.05	55.71	32.93	Compliance
0.415	30.86	QP	9.000	L1	16.06	58.43	27.57	Compliance
0.415	29.10	AV	9.000	L1	16.06	48.43	19.33	Compliance
1.200	25.94	QP	9.000	L1	15.87	56.00	30.06	Compliance
1.200	21.20	AV	9.000	L1	15.87	46.00	24.80	Compliance
1.700	28.11	QP	9.000	L1	15.86	56.00	27.89	Compliance
1.700	21.89	AV	9.000	L1	15.86	46.00	24.11	Compliance
2.850	23.12	QP	9.000	L1	15.85	56.00	32.88	Compliance
2.850	12.01	AV	9.000	L1	15.85	46.00	33.99	Compliance
18.450	22.45	QP	9.000	L1	16.37	60.00	37.55	Compliance
18.450	16.96	AV	9.000	L1	16.37	50.00	33.04	Compliance

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.155	46.95	QP	9.000	N	16.06	65.86	18.91	Compliance
0.155	23.24	AV	9.000	N	16.06	55.86	32.62	Compliance
0.375	31.32	QP	9.000	N	16.08	59.57	28.25	Compliance
0.375	25.76	AV	9.000	N	16.08	49.57	23.81	Compliance
0.830	27.84	QP	9.000	N	15.97	56.00	28.16	Compliance
0.830	23.56	AV	9.000	N	15.97	46.00	22.44	Compliance
1.650	29.93	QP	9.000	N	15.92	56.00	26.07	Compliance
1.650	24.59	AV	9.000	N	15.92	46.00	21.41	Compliance
2.850	29.34	QP	9.000	N	15.90	56.00	26.66	Compliance
2.850	20.73	AV	9.000	N	15.90	46.00	25.27	Compliance
5.400	26.62	QP	9.000	N	15.88	60.00	33.38	Compliance
5.400	20.68	AV	9.000	N	15.88	50.00	29.32	Compliance



Note:

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**


Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Max Min from 2018-08-05 to 2018-08-08.

EUT operation mode: Transmitting

Data for PIFA Antenna:**Spurious Emission Test:****30MHz-1GHz:**

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case **8DPSK Mode in X-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
51.433400	25.73	101.0	V	299.0	-17.6	40.00	14.27
99.681550	29.12	101.0	V	299.0	-15.0	43.50	14.38
120.073200	31.67	101.0	V	200.0	-11.2	43.50	11.83
144.403100	29.91	101.0	V	0.0	-12.1	43.50	13.59
276.589450	30.65	199.0	V	218.0	-11.2	46.00	15.35
319.998200	34.39	101.0	H	198.0	-10.1	46.00	11.61

1GHz-18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.600000	---	30.43	150.0	V	357.0	-0.6	54.00	23.57
1591.600000	40.83	---	150.0	V	357.0	-0.6	74.00	33.17
3199.800000	---	40.94	100.0	H	268.0	6.5	54.00	13.06
3199.800000	50.69	---	100.0	H	268.0	6.5	74.00	23.31
4804.000000	---	38.79	250.0	V	148.0	10.8	54.00	15.21
4804.000000	48.16	---	250.0	V	148.0	10.8	74.00	25.84
7206.000000	---	42.70	100.0	V	186.0	15.2	54.00	11.30
7206.000000	51.28	---	100.0	V	186.0	15.2	74.00	22.72
11366.600000	---	47.06	250.0	H	95.0	18.5	54.00	6.94
11366.600000	54.70	---	250.0	H	95.0	18.5	74.00	19.30
17309.800000	---	46.88	100.0	V	109.0	18.3	54.00	7.12
17309.800000	53.97	---	100.0	V	109.0	18.3	74.00	20.03

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1588.200000	---	32.71	250.0	V	71.0	-0.6	54.00	21.29
1588.200000	41.49	---	250.0	V	71.0	-0.6	74.00	32.51
3254.200000	---	42.66	100.0	H	190.0	6.7	54.00	11.34
3254.200000	52.00	---	100.0	H	190.0	6.7	74.00	22.00
4882.000000	---	38.56	100.0	V	203.0	11.1	54.00	15.44
4882.000000	47.45	---	100.0	V	203.0	11.1	74.00	26.55
7323.000000	---	43.06	250.0	V	163.0	15.4	54.00	10.94
7323.000000	52.38	---	250.0	V	163.0	15.4	74.00	21.62
10972.200000	---	47.03	100.0	V	358.0	19.0	54.00	6.97
10972.200000	55.33	---	100.0	V	358.0	19.0	74.00	18.67
16810.000000	---	47.44	200.0	H	285.0	18.1	54.00	6.56
16810.000000	53.96	---	200.0	H	285.0	18.1	74.00	20.04

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1591.600000	40.02	---	250.0	V	284.0	-0.6	74.00	33.98
1591.600000	---	32.05	250.0	V	284.0	-0.6	54.00	21.95
3305.200000	53.25	---	100.0	H	24.0	6.8	74.00	20.75
3305.200000	---	43.43	100.0	H	24.0	6.8	54.00	10.57
4960.000000	48.40	---	200.0	V	149.0	11.5	74.00	25.60
4960.000000	---	39.89	200.0	V	149.0	11.5	54.00	14.11
7440.000000	50.90	---	250.0	V	75.0	15.6	74.00	23.10
7440.000000	---	42.63	250.0	V	75.0	15.6	54.00	11.37
11047.000000	53.31	---	100.0	V	332.0	19.0	74.00	20.69
11047.000000	---	47.86	100.0	V	332.0	19.0	54.00	6.14
17918.400000	54.04	---	200.0	V	333.0	19.1	74.00	19.96
17918.400000	---	47.32	200.0	V	333.0	19.1	54.00	6.68

18GHz - 25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded

Horizontal

Date: 8.AUG.2018 00:35:20

Vertical

Date: 8.AUG.2018 09:06:11

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation,, the worst case 8DPSK Mode in X-axis of orientation was recorded

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	96.55	---	150.0	V	87.0	2.9	/	/
2402.000000	---	95.66	150.0	V	87.0	2.9	/	/
2402.000000	94.09	---	150.0	H	314.0	2.9	/	/
2402.000000	---	93.17	150.0	H	314.0	2.9	/	/
2390.000000	52.79	---	200.0	V	180.0	2.8	74.00	21.21
2390.000000	---	46.63	200.0	V	180.0	2.8	54.00	7.37
Middle Channel: 2441MHz								
2441.000000	96.77	---	250.0	V	113.0	3.0	/	/
2441.000000	---	96.11	250.0	V	113.0	3.0	/	/
2441.000000	94.22	---	150.0	H	210.0	3.0	/	/
2441.000000	---	93.61	150.0	H	210.0	3.0	/	/
High Channel: 2480MHz								
2480.000000	96.32	---	200.0	V	62.0	3.0	/	/
2480.000000	---	95.63	200.0	V	62.0	3.0	/	/
2480.000000	93.80	---	150.0	H	336.0	3.0	/	/
2480.000000	---	93.10	150.0	H	336.0	3.0	/	/
2483.500000	53.16	---	200.0	V	180.0	3.0	74.00	20.84
2483.500000	---	46.73	200.0	V	180.0	3.0	54.00	7.27

Data for Dipole Antenna:**Spurious Emission Test:****30MHz-1GHz:**

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
99.648750	32.02	101.0	V	294.0	-15.0	43.50	11.48
120.027650	32.54	101.0	V	147.0	-11.2	43.50	10.96
144.161450	28.69	101.0	V	0.0	-12.1	43.50	14.81
276.559750	31.89	198.0	V	211.0	-11.2	46.00	14.11
331.916750	30.61	101.0	V	325.0	-9.8	46.00	15.39
479.988200	36.97	198.0	H	161.0	-6.7	46.00	9.03

1GHz - 18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case 8DPSK Mode in X-axis of orientation was recorded

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.600000	42.38	---	150.0	V	68.0	-0.6	74.00	31.62
1591.600000	---	31.26	150.0	V	68.0	-0.6	54.00	22.74
3199.800000	51.65	---	100.0	V	273.0	6.5	74.00	22.35
3199.800000	---	41.63	100.0	V	273.0	6.5	54.00	12.37
4804.000000	47.66	---	200.0	V	310.0	10.7	74.00	26.34
4804.000000	---	38.21	200.0	V	310.0	10.7	54.00	15.79
7206.000000	51.85	---	100.0	V	245.0	15.2	74.00	22.15
7206.000000	---	43.81	100.0	V	245.0	15.2	54.00	10.19
10023.600000	54.19	---	200.0	V	75.0	18.3	74.00	19.81
10023.600000	---	46.72	200.0	V	75.0	18.3	54.00	7.28
17915.000000	55.41	---	100.0	H	174.0	19.1	74.00	18.59
17918.400000	---	47.02	100.0	H	174.0	19.1	54.00	6.98

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1197.200000	39.19	---	200.0	V	308.0	-3.0	74.00	34.81
1197.200000	---	29.53	200.0	V	308.0	-3.0	54.00	24.47
3254.200000	51.39	---	100.0	V	307.0	6.7	74.00	22.61
3254.200000	---	43.00	100.0	V	307.0	6.7	54.00	11.00
4882.000000	48.17	---	100.0	V	108.0	11.1	74.00	25.83
4882.000000	---	38.48	100.0	V	108.0	11.1	54.00	15.52
7323.000000	52.03	---	200.0	V	118.0	15.4	74.00	21.97
7323.000000	---	43.21	200.0	V	118.0	15.4	54.00	10.79
11019.800000	55.66	---	150.0	H	10.0	19.0	74.00	18.34
11019.800000	---	47.26	150.0	H	10.0	19.0	54.00	6.74
17775.600000	54.59	---	250.0	V	172.0	18.9	74.00	19.41
17775.600000	---	46.98	250.0	V	172.0	18.9	54.00	7.02

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1197.200000	---	31.32	250.0	H	106.0	-3.0	54.00	22.68
1197.200000	41.36	---	250.0	H	106.0	-3.0	74.00	32.64
3305.200000	---	43.81	100.0	V	256.0	6.8	54.00	10.19
3305.200000	52.36	---	100.0	V	256.0	6.8	74.00	21.64
4960.000000	---	40.34	200.0	V	217.0	11.4	54.00	13.66
4960.000000	47.69	---	200.0	V	217.0	11.4	74.00	26.31
7440.000000	---	42.29	200.0	V	160.0	15.6	54.00	11.71
7440.000000	51.44	---	200.0	V	160.0	15.6	74.00	22.56
11016.400000	---	47.00	100.0	H	76.0	19.0	54.00	7.00
11016.400000	54.53	---	100.0	H	76.0	19.0	74.00	19.47
17918.400000	---	47.16	250.0	V	162.0	19.1	54.00	6.84
17921.800000	54.95	---	250.0	V	162.0	19.1	74.00	19.05

18GHz - 25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded

Horizontal

Date: 8.AUG.2018 09:57:02

Vertical

Date: 8.AUG.2018 10:06:05

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X, Y and Z axes of orientation, the worst case 8DPSK Mode in X-axis of orientation was recorded


Note:

- Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	97.01	---	200.0	V	274.0	2.9	/	/
2402.000000	---	96.39	200.0	V	274.0	2.9	/	/
2402.000000	94.55	---	250.0	H	92.0	2.9	/	/
2402.000000	---	93.90	250.0	H	92.0	2.9	/	/
2390.000000	53.76	---	200.0	V	312.0	2.8	74.00	20.24
2390.000000	---	47.43	200.0	V	312.0	2.8	54.00	6.57
Middle Channel: 2441MHz								
2441.000000	97.29	---	250.0	V	113.0	3.0	/	/
2441.000000	---	96.23	250.0	V	113.0	3.0	/	/
2441.000000	94.74	---	150.0	H	210.0	3.0	/	/
2441.000000	---	93.73	150.0	H	210.0	3.0	/	/
High Channel: 2480MHz								
2480.000000	96.85	---	200.0	V	157.0	3.0	/	/
2480.000000	---	96.11	200.0	V	157.0	3.0	/	/
2480.000000	94.33	---	200.0	H	184.0	3.0	/	/
2480.000000	---	93.58	200.0	H	184.0	3.0	/	/
2483.500000	53.67	---	150.0	V	154.0	3.0	74.00	20.33
2483.500000	---	47.28	150.0	V	154.0	3.0	54.00	6.72

Conducted Spurious Emissions at Antenna Port


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel



EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 5 AUG 2018 16:41:26

EDR ($\pi/4$ -DQPSK): High Channel




Date: 5 AUG 2018 16:39:51


EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



Date: 5 AUG 2018 16:38:25

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- Span: Wide enough to capture the peaks of two adjacent channels.
- RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- Video (or average) bandwidth (VBW) $\geq$ RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Max Min on 2018-08-05.


EUT operation mode: Transmitting

Test Result: Compliance.


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	0.999	≥ 0.942	Pass
	Adjacent	2403			
	Middle	2441	0.999	≥ 0.942	Pass
	Adjacent	2442			
	High	2480	0.999	≥ 0.942	Pass
	Adjacent	2479			
EDR ($\pi/4$-DQPSK)	Low	2402	0.999	≥ 0.869	Pass
	Adjacent	2403			
	Middle	2441	0.999	≥ 0.869	Pass
	Adjacent	2442			
	High	2480	0.999	≥ 0.869	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	0.999	≥ 0.851	Pass
	Adjacent	2403			
	Middle	2441	0.999	≥ 0.851	Pass
	Adjacent	2442			
	High	2480	0.999	≥ 0.851	Pass
	Adjacent	2479			

Note: For BDR mode, Limit = 20 dB bandwidth; For EDR mode, Limit = 20 dB bandwidth*2/3


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel

Date: 5 AUG 2018 15:42:11


EDR ($\pi/4$ -DQPSK): Middle Channel

Date: 5 AUG 2018 15:40:07


EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Max Min on 2018-08-05.

EUT operation mode: Transmitting


Test Result: Compliance.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.942
	Middle	2441	0.942
	High	2480	0.942
EDR ($\pi/4$-DQPSK)	Low	2402	1.303
	Middle	2441	1.303
	High	2480	1.303
EDR (8DPSK)	Low	2402	1.276
	Middle	2441	1.276
	High	2480	1.276


BDR (GFSK): Low Channel

Date: 5 AUG 2018 14:31:01


BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel

Date: 5 AUG 2018 14:36:24

EDR (8DPSK): Low Channel


Date: 5 AUG 2018 14:43:08

EDR (8DPSK): Middle Channel



Date: 5 AUG 2018 14:46:11

EDR (8DPSK): High Channel



Date: 5 AUG 2018 14:47:51

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400 - 2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Max Min on 2018-08-05.


EUT operation mode: Hopping

Test Result: Compliance.


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400 - 2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400 - 2483.5	79	≥ 15
EDR (8DPSK)	2400 - 2483.5	79	≥ 15

BDR (GFSK): Number of Hopping Channels

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1 Span: Zero span, centered on a hopping channel.

2 RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.

3 Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

4 Detector function: Peak.

5 Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	23.4 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2018-08-05.


EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.388	0.124	≤ 0.4	Pass
		Middle	0.388	0.124	≤ 0.4	Pass
		High	0.388	0.124	≤ 0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.657	0.265	≤ 0.4	Pass
		Middle	1.657	0.265	≤ 0.4	Pass
		High	1.657	0.265	≤ 0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.912	0.311	≤ 0.4	Pass
		Middle	2.912	0.311	≤ 0.4	Pass
		High	2.912	0.311	≤ 0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.400	0.128	≤ 0.4	Pass
		Middle	0.400	0.128	≤ 0.4	Pass
		High	0.400	0.128	≤ 0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.665	0.266	≤ 0.4	Pass
		Middle	1.665	0.266	≤ 0.4	Pass
		High	1.665	0.266	≤ 0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.917	0.311	≤ 0.4	Pass
		Middle	2.917	0.311	≤ 0.4	Pass
		High	2.917	0.311	≤ 0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.400	0.128	≤ 0.4	Pass
		Middle	0.400	0.128	≤ 0.4	Pass
		High	0.400	0.128	≤ 0.4	Pass
		Note: 3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.665	0.266	≤ 0.4	Pass
		Middle	1.665	0.266	≤ 0.4	Pass
		High	1.665	0.266	≤ 0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.917	0.311	≤ 0.4	Pass
		Middle	2.917	0.311	≤ 0.4	Pass
		High	2.917	0.311	≤ 0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1




BDR (GFSK): Pulse time, Middle Channel, DH1




BDR (GFSK): Pulse time, High Channel, DH1




BDR (GFSK): Pulse time, Low Channel, DH3




BDR (GFSK): Pulse time, Middle Channel, DH3




BDR (GFSK): Pulse time, High Channel, DH3





BDR (GFSK): Pulse time, Low Channel, DH5




BDR (GFSK): Pulse time, Middle Channel, DH5




BDR (GFSK): Pulse time, High Channel, DH5**EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1**


EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1




EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1





EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3**EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5**


EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH5




EDR ($\pi/4$ -DQPSK): Pulse time, High Channel, 2DH5





EDR (8DPSK): Pulse time, Low Channel, 3DH1




EDR (8DPSK): Pulse time, Middle Channel, 3DH1




EDR (8DPSK): Pulse time, High Channel, 3DH1**EDR (8DPSK): Pulse time, Low Channel, 3DH3**


EDR (8DPSK): Pulse time, Middle Channel, 3DH3




EDR (8DPSK): Pulse time, High Channel, 3DH3




EDR (8DPSK): Pulse time, Low Channel, 3DH5



EDR (8DPSK): Pulse time, Middle Channel, 3DH5



EDR (8DPSK): Pulse time, High Channel, 3DH5



Date: 5 AUG 2018 16:13:07

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by Max Min on 2018-08-05.

EUT operation mode: Transmitting


Test Result: Compliance.

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	0.23	1.05	≤ 1000
	2441	0.42	1.10	≤ 1000
	2480	0.60	1.15	≤ 1000
EDR ($\pi/4$-DQPSK)	2402	2.71	1.87	≤ 125
	2441	2.87	1.94	≤ 125
	2480	3.03	2.01	≤ 125
EDR (8DPSK)	2402	3.13	2.06	≤ 125
	2441	3.29	2.13	≤ 125
	2480	3.43	2.20	≤ 125


BDR (GFSK): 2402MHz

Date: 5 AUG 2018 14:16:07


BDR (GFSK): 2441MHz




BDR (GFSK): 2480MHz




EDR($\pi/4$ -DQPSK): 2402MHz




EDR($\pi/4$ -DQPSK): 2441MHz




EDR($\pi/4$ -DQPSK): 2480MHz




EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Max Min on 2018-08-05.

EUT operation mode: Transmitting & Hopping


Test Result: Compliance.

Band Edge


BDR (GFSK): Left Side




BDR (GFSK): Right Side




EDR ($\pi/4$ -DQPSK): Left Side




EDR ($\pi/4$ -DQPSK): Right Side




EDR (8DPSK): Left Side




EDR (8DPSK): Right Side




BDR (GFSK): Left Side - Hopping




BDR (GFSK): Right Side- Hopping





EDR ($\pi/4$ -DQPSK): Left Side- Hopping



EDR ($\pi/4$ -DQPSK): Right Side- Hopping



EDR (8DPSK): Left Side- Hopping**EDR (8DPSK): Right Side- Hopping**

***** END OF REPORT *****