





FCC Part 15.249 TEST REPORT

For

3Egreen Technology, INC.

5F, No. 283 Songjiang Road, Zhongshan District, Taipei, Taiwan

FCC ID: 2AMHJGW08000000

Report Type: Product Type:

Original Report Tiny WIFI to Sub-1G Gateway

Report Producer: Kaylee Chiang Foyle Chiang

Report Number : RXZ190226005-00B

Report Date : <u>2019-06-06</u>

Reviewed By: Jerry Chang

Prepared By: Bay Area Compliance Laboratories Corp.(Taiwan)

70, Lane 169, Sec. 2, Datong Road, Xizhi Dist.,

New Taipei City 22183, Taiwan, R.O.C.

Tel: +886 (2) 2647 6898 Fax: +886 (2) 2647 6895

www.bacl.com.tw

Revision History

Revision	No.	Report Number	Issue Date	Description	Author/ Revised by
1.0	RXZ190226005	RXZ190226005-00B	2019-06-06	Original Report	Kaylee Chiang

TABLE OF CONTENTS

1	Gen	eral Information	4
	1.1	Product Description for Equipment under Test (EUT)	4
	1.2	Objective	
	1.3	Related Submittal(s)/Grant(s).	
	1.4	Test Methodology	
	1.5	Test Facility	
2		stem Test Configuration	
	2.1	Description of Test Configuration	
	2.2	Equipment Modifications	
	2.3	EUT Exercise Software	
	2.4	Support Equipment List and Details	
	2.5 2.6	External Cable List and Details	
2		Block Diagram of Test Setup	
3	Sun	nmary of Test Results	9
4	Tes	Equipment List and Details	. 10
5	F(CC §15.203 – Antenna Requirements	12
	5.1	Applicable Standard	
	5.2	Antenna Information	12
6	FC	C §15.207(a) – AC Line Conducted Emissions	. 13
	6.1	Applicable Standard	13
	6.2	Measurement Uncertainty	
	6.3	EUT Setup	
	6.4	EMI Test Receiver Setup	
	6.5	Test Procedure	. 14
	6.6	Corrected Factor & Margin Calculation	15
	6.7	Environmental Conditions	. 15
	6.8	Test Results	. 16
7	FC	C §15.209, §15.205, §15.249 - Radiated Emissions	. 18
	7.1	Applicable Standard	18
	7.2	Measurement Uncertainty	
	7.3	EUT Setup	
	7.4	EMI Test Receiver & Spectrum Analyzer Setup	
	7.5	Test Procedure	
	7.6	Corrected Factor & Margin Calculation	20
	7.7	Test Results Summary	
	7.8	Environmental Conditions	
	7.9	Test Results	. 21
8	FC	C §15.215(c) – 20 dB Bandwidth Testing	. 26
	8.1	Applicable Standard	26
	8.2	Test Procedure	
	8.3	Environmental Conditions	
	8.4	Test Results	27

1 General Information

1.1 Product Description for Equipment under Test (EUT)

.1 Product Description for Equipment under Test (EUT)				
Applicant	3Egreen Technology, INC.			
	5F, No. 283 Songjiang Road, Zhongshan District, Taipei, Taiwan			
Manufacturer	3Egreen Technology, INC.			
	5F, No. 283 Songjiang Road, Zhongshan District, Taipei, Taiwan			
Brand(Trade) Name	3Egreen			
Product (Equipment)	Tiny WIFI to Sub-1G Gateway			
Main Model Name	GW08 Series			
Series Model Name	N/A			
Frequency Range	920.5 MHz ~ 924.5MHz			
Antenna Specification	Dipole Antenna / 3 dBi			
	☐ AC 120V/60Hz ☐ Adapter I/P: 100-240Vac,1.2A; O/P: 12Vdc, 3A ☐ By AC Power Cord ☐ PoE			
Power Operation (Voltage Range)	 ☑ DC Type ☐ Battery ☐ DC Power Supply ☑ External from USB Cable: 5Vdc ☐ External DC Adapter 			
	Host System			
Received Date	Feb 26, 2019			
Date of Test	May 20, 2019 ~ May 31, 2019			

^{*}All measurement and test data in this report was gathered from production sample serial number: 190226005 (Assigned by BACL, Taiwan).

1.2 Objective

This report is prepared on behalf of *3Egreen Technology, INC*. in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communication Commission's rules.

No.: RXZ190226005-00B

The tests were performed in order to determine of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

1.3 Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submission with FCC ID: 2AMHJGW08000000.

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

1.5 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Taiwan) to collect test data is located on

70, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

68-3, Lane 169, Sec. 2, Datong Road, Xizhi Dist., New Taipei City 22183, Taiwan, R.O.C.

Bay Area Compliance Laboratories Corp. (Taiwan) Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 3180) and the FCC designation No.TW3180 under the Mutual Recognition Agreement (MRA) in FCC Test. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.10.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 974454. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

2 System Test Configuration

2.1 Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

No.: RXZ190226005-00B

The engineering mode was configured the system transmitting with maximum power.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	920.5	6	923
2	921	7	923.5
3	921.5	8	924
4	922	9	924.5
5	922.5	-	-

Were tested with channel 1 and 9.

2.2 Equipment Modifications

No modification was made to the EUT.

2.3 EUT Exercise Software

The software was used "SmartRF_Studio_7-2.6.1".

2.4 Support Equipment List and Details

Description	cription Manufacturer Model Number		BSMI	FCC ID	S/N
NB	DELL	E6410	N/A	PD98260NGU	10912240367
FIX	N/A	N/A	N/A	N/A	N/A

2.5 External Cable List and Details

Cable Description	Length (m)	From	То
Micro USB Cable	1.5	NB	EUT
Micro USB Cable	1.5	NB	FIX
Control Cable	0.5	FIX	EUT


2.6 Block Diagram of Test Setup

See test photographs attached in setup photos for the actual connections between EUT and support equipment.


No.: RXZ190226005-00B

Radiation:


Below 1GHz:



Above 1GHz:



Conduction:



3 Summary of Test Results

FCC Rules	Description of Test	Results
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209,§15.249	Radiated Emissions	Compliance
§15.215 (c)	20 dB Emission Bandwidth	Compliance

4 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
	AC Lin	e Conduction Roor	n (CON-A)		
LISN	Rohde & Schwarz	ENV216	101612	2019/02/21	2020/02/20
EMI Test Receiver	Rohde & Schwarz	ESR7	101419	2018/10/23	2019/10/22
Pulse Limiter	Rohde & Schwarz	ESH3Z2	TXZEM104	2018/08/03	2019/08/02
RF Cable	EMEC	EM-CB5D	001	2018/07/02	2019/07/01
Software	AUDIX	Е3	V9.150826k	N.C.R	N.C.R
		Radiated Room (96	6-A)		
Bilog Antenna with 6 dB Attenuator	SUNOL SCIENCES & MINI- CIRCUITS	JB6/UNAT-6+	A050115/1554 2_01	2018/12/11	2019/12/10
Horn Antenna	EMCO	3115	9311-4158	2019/04/17	2020/04/16
Horn Antenna	ETS-Lindgren	3116	62638	2018/08/29	2019/08/28
Preamplifier	Sonoma	310N	130602	2018/07/04	2019/07/03
Preamplifier	EM Electronics Corp.	EM01G18G	060657	2018/12/07	2019/12/06
Microware Preamplifier	EM Electronics Corporation	EM18G40G	060656	2019/01/11	2020/01/10
EMI Test Receiver	Rohde & Schwarz	ESR7	101419	2018/10/23	2019/10/22
Spectrum Analyzer	Rohde & Schwarz	FSV40	101435	2019/02/13	2020/02/12
Micro flex Cable	UTIFLEX	FSCM 64639 / (2M)	93D0127	2018/07/31	2019/07/30
Micro flex Cable	UTIFLEX	UFA210A-1- 3149-300300	MFR64639 226389-001	2018/11/19	2019/11/18
Micro flex Cable	ROSNOL	K1K50-UP0264- K1K50-450CM	160309-1	2019/03/04	2020/03/03
Micro flex Cable	ROSNOL	K1K50-UP0264- K1K50-80CM	160309-2	2019/01/16	2020/01/15
Turn Table	Champro	TT-2000	060772-Т	N.C.R	N.C.R
Antenna Tower	Champro	AM-BS-4500-B	060772-A	N.C.R	N.C.R
Controller	Champro	EM1000	60772	N.C.R	N.C.R
Software	Farad	EZ_EMC	BACL-03A1	N.C.R	N.C.R

Description	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date	
	Conducted Room					
Spectrum Analyzer	Rohde & Schwarz	FSV40	101140	2018/11/14	2019/11/13	
Cable	WOKEN	SFL402	S02-160323- 07	2019/02/11	2020/02/10	
Attenuator	MINI-CIRCUITS	BW-S10W5+	N/A	2019/03/07	2020/03/07	

^{*}Statement of Traceability: BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to the SI System of Units via the R.O.C. Center for Measurement Standards of the Electronics Testing Center, Taiwan (ETC) or to another internationally recognized National Metrology Institute (NMI), and were compliant with the current Taiwan Accreditation Foundation (TAF) requirements

5 FCC §15.203 – Antenna Requirements

5.1 Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

No.: RXZ190226005-00B

5.2 Antenna Information

Manufacturer	Туре	Antenna Gain	Result
Chengdu Ebyte Electronic Technology Co.,Ltd.	Dipole Antenna	3 dBi	Compliance

The antenna connection is fixed with glue and is not removable. It complies with the provisions of 15.203. Like the photo below:



Result: Compliance.

6 FCC §15.207(a) – AC Line Conducted Emissions

6.1 Applicable Standard

According to §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

No.: RXZ190226005-00B

Frequency of Emission	Conducted Limit (dBuV)		
(MHz)	Quasi-Peak	Average	
0.15-0.5	66 to 56 Note 1	56 to 46 Note 2	
0.5-5	56	46	
5-30	60	50	

Note 1: Decreases with the logarithm of the frequency.

Note 2: A linear average detector is required


6.2 Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN/ISN and receiver, LISN/ISN voltage division factor, LISN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Taiwan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Expanded Measurement uncertainty	
AC Mains	4.22 dB (k=2, 95% level of confidence)	

6.3 EUT Setup



No.: RXZ190226005-00B

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

6.4 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations

Frequency Range	IF B/W		
150kHz – 30MHz	9kHz		

6.5 Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

6.6 Corrected Factor & Margin Calculation

The factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

No.: RXZ190226005-00B

Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Over Limit" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for Over Limit calculation is as follows:

Over Limit = Level – Limit Line

6.7 Environmental Conditions


Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	1010 hPa

The testing was performed by Tom Hsu on 2019-05-31.

6.8 Test Results

Test Mode: Transmitting

Main: AC120 V, 60 Hz, Line



No.: RXZ190226005-00B

No.	Frequency	Reading	Correct	Result	Limit	Over limit	Remark
	(MHz)	(dBµV)	Factor(dB)	(dBµV)	(dBµV)	(dB)	
1	0.196	-0.87	19.46	18.59	63.76	-45.17	QP
2	0.196	-7.71	19.46	11.75	53.76	-42.02	Average
3	0.309	6.22	19.47	25.69	60.00	-34.31	QP
4	0.309	5.73	19.47	25.20	50.00	-24.80	Average
5	0.383	3.41	19.47	22.88	58.22	-35.34	QP
6	0.383	-0.54	19.47	18.92	48.22	-29.29	Average
7	0.676	12.63	19.48	32.11	56.00	-23.89	QP
8	0.676	1.06	19.48	20.55	46.00	-25.45	Average
9	0.739	5.45	19.49	24.93	56.00	-31.07	QP
10	0.739	-0.98	19.49	18.51	46.00	-27.49	Average
11	2.519	1.56	19.56	21.12	56.00	-34.88	QP
12	2.519	-2.82	19.56	16.74	46.00	-29.26	Average


Note:

Level = Read Level + Factor

Over Limit = Level - Limit Line

Factor = (LISN, ISN, PLC or current probe) Factor + Cable Loss + Attenuator

Main: AC120 V, 60 Hz, Neutral



No.: RXZ190226005-00B

No.	Frequency	Reading	Correct	Result	Limit	Over limit	Remark
	(MHz)	(dBµV)	Factor(dB)	(dBµV)	(dBµV)	(dB)	
1	0.192	-1.72	19.46	17.73	63.93	-46.20	QP
2	0.192	-10.44	19.46	9.02	53.93	-44.91	Average
3	0.306	4.97	19.46	24.43	60.08	-35.65	QP
4	0.306	4.23	19.46	23.69	50.08	-26.39	Average
5	0.385	15.94	19.46	35.40	58.18	-22.78	QP
6	0.385	6.62	19.46	26.08	48.18	-22.10	Average
7	0.603	-1.22	19.47	18.25	56.00	-37.75	QP
8	0.603	-7.56	19.47	11.91	46.00	-34.09	Average
9	0.676	12.87	19.47	32.34	56.00	-23.66	QP
10	0.676	1.50	19.47	20.97	46.00	-25.03	Average
11	0.736	5.43	19.48	24.91	56.00	-31.09	QP
12	0.736	-1.23	19.48	18.25	46.00	-27.75	Average

Note:

 $Level = Read \ Level + Factor$

Over Limit = Level - Limit Line

 $Factor = (LISN, ISN, PLC \ or \ current \ probe) \ Factor + Cable \ Loss + Attenuator$

7 FCC §15.209, §15.205, §15.249 - Radiated Emissions

7.1 Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

No.: RXZ190226005-00B

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (millivolts/meter)	
920-928 MHz	50	500	
2400-2483.5 MHz	50	500	
5725-5875 MHz	50	500	
24.0-24.25 GHz	250	2500	

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

7.2 Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Taiwan) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Frequency	Measurement uncertainty
30 MHz~200 MHz	3.75 dB (k=2, 95% level of confidence)
200 MHz~1 GHz	4.21 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	4.83 dB (k=2, 95% level of confidence)
6 GHz~18 GHz	5.18 dB (k=2, 95% level of confidence)
18 GHz~26 GHz	4.55 dB (k=2, 95% level of confidence)
26 GHz~40 GHz	4.67 dB (k=2, 95% level of confidence)


7.3 EUT Setup

Below 1 GHz:



No.: RXZ190226005-00B

Above 1 GHz:



Radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.249 limits.

7.4 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 10 GHz. During the radiated emission test, the EMI test receiver was set with the following configurations measurement method 6.3 in ANSI C63.10.

Frequency Range	RBW	VBW	Detector	Duty cycle	Measurement method
30-1000 MHz	120 kHz	/	QP	/	QP
Above 1 GHz	1 MHz	3 MHz	PK	/	PK
	1 MHz	3 MHz	RMS	>98%	Ave
	1 MHz	1/T	PK	<98%	Ave

7.5 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

No.: RXZ190226005-00B

7.6 Corrected Factor & Margin Calculation

The Correct Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

7.7 Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.209 Limit.

7.8 Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	1010 hPa

The Radiation Spurious Emissions testing was performed by Tom Hsu on 2019-05-20 \sim 2019-05-28.

7.9 Test Results


Test Mode: Transmitting

(Pre-scan with three orthogonal axis, and worse case as Y axis.)

Worst Plots (920.5 MHz)


Horizontal

30MHz-1GHz:




No.: RXZ190226005-00B

1GHz-10GHz:




Vertical

30MHz-1GHz:



No.: RXZ190226005-00B

1GHz-10GHz:



Below 1GHz

Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
(MHz)	(dBµV)	Factor(dB/m)	(dBµV/m)	(dBµV/m)	(dB)	(cm)	(°)	
51.3400	36.33	-16.38	19.95	40.00	-20.05	100	102	QP
99.8400	42.10	-14.54	27.56	43.50	-15.94	100	144	QP
191.9900	42.76	-12.35	30.41	43.50	-13.09	100	348	QP
288.0200	34.49	-9.92	24.57	46.00	-21.43	100	198	QP
367.5600	32.43	-8.41	24.02	46.00	-21.98	100	99	QP
892.3300	29.06	1.25	30.31	46.00	-15.69	100	225	QP

No.: RXZ190226005-00B

Vertical

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
(MHz)	(dBµV)	Factor(dB/m)	(dBµV/m)	(dBµV/m)	(dB)	(cm)	(°)	
51.3400	39.09	-16.38	22.71	40.00	-17.29	100	190	QP
102.7500	38.92	-13.80	25.12	43.50	-18.38	100	62	QP
136.7000	31.72	-10.80	20.92	43.50	-22.58	100	252	QP
152.2200	31.43	-11.23	20.20	43.50	-23.30	100	62	QP
191.9900	46.25	-12.35	33.90	43.50	-9.60	100	172	QP
440.3100	31.79	-6.77	25.02	46.00	-20.98	100	322	QP

 $\overline{Result = Reading + Correct Factor}$

Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

Above 1GHz

Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark		
(MHz)	(dBµV)	Factor(dB/m)	(dBµV/m)	(dBµV/m)	(dB)	(cm)	(°)			
	920.5MHz									
1841.000	47.33	-6.81	40.52	74.00	-33.48	150	32	peak		
1841.000	41.20	-6.81	34.39	54.00	-19.61	150	32	AVG		
2761.500	54.56	-2.55	52.01	74.00	-21.99	150	359	peak		
2761.500	52.68	-2.55	50.13	54.00	-3.87	150	359	AVG		
			924.5	5MHz						
1849.000	44.13	-6.76	37.37	74.00	-36.63	150	308	peak		
1849.000	33.14	-6.76	26.38	54.00	-27.62	150	308	AVG		
2773.500	54.11	-2.59	51.52	74.00	-22.48	150	2	peak		
2773.500	52.12	-2.59	49.53	54.00	-4.47	150	2	AVG		

No.: RXZ190226005-00B

Vertical

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark			
(MHz)	(dBµV)	Factor(dB/m)	(dBµV/m)	(dBµV/m)	(dB)	(cm)	(°)				
	920.5MHz										
1841.000	50.79	-6.81	43.98	74.00	-30.02	150	336	peak			
1841.000	47.56	-6.81	40.75	54.00	-13.25	150	336	AVG			
2761.500	53.54	-2.55	50.99	74.00	-23.01	150	2	peak			
2761.500	55.50	-2.55	52.95	54.00	-1.05	150	2	AVG			
			924.5	5MHz							
1849.000	51.19	-6.76	44.43	74.00	-29.57	150	329	peak			
1849.000	47.97	-6.76	41.21	54.00	-12.79	150	329	AVG			
2773.500	51.30	-2.59	48.71	74.00	-25.29	150	101	peak			
2773.500	48.04	-2.59	45.45	54.00	-8.55	150	101	AVG			

Result = Reading + Correct Factor

Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

Fundamental Test

Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
(MHz)	(dBµV)	Factor(dB/m)	(dBµV/m)	(dBµV/m)	(dB)	(cm)	(°)	
920.5MHz								
902.0000	30.10	0.70	30.80	46.00	-15.20	100	88	QP
920.5000	84.87	1.13	86.00	93.98	-7.98	100	168	QP
924.5MHz								
924.5000	85.90	1.22	87.12	93.98	-6.86	100	318	QP
928.0000	25.48	1.30	26.78	46.00	-19.22	100	268	QP

No.: RXZ190226005-00B

Vertical

Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
(MHz)	(dBµV)	Factor(dB/m)	(dBµV/m)	(dBµV/m)	(dB)	(cm)	(°)	
920.5MHz								
902.0000	29.30	0.70	30.00	46.00	-16.00	100	77	QP
920.5000	92.65	1.13	93.78	93.98	-0.20	100	235	QP
924.5MHz								
924.5000	91.90	1.22	93.12	93.98	-0.86	100	268	QP
928.0000	26.38	1.30	27.68	46.00	-18.32	100	312	QP

Result = Reading + Correct Factor

Margin = Result - Limit

Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain

Spurious emissions more than 20 dB below the limit were not reported.

8 FCC §15.215(c) – 20 dB Bandwidth Testing

8.1 Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

No.: RXZ190226005-00B

8.2 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

8.3 Environmental Conditions

Temperature:	25 °C			
Relative Humidity:	55 %			
ATM Pressure:	1010 hPa			

The testing was performed by Tom Hsu on 2019-05-25.


8.4 Test Results

Frequency	20 dB Emission Bandwidth		
(MHz)	(MHz)		
920.5	0.094		
924.5	0.102		

No.: RXZ190226005-00B

Please refer to the following plots


920.5 MHz



Date: 25.MAY.2019 17:15:23

924.5 MHz

No.: RXZ190226005-00B



Date: 25.MAY.2019 17:20:48

***** END OF REPORT *****