

## 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

### 1.1 Standard Applicable

According to § 1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

#### (a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

#### (b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; \* = Plane-wave equivalents power density

### 1.2 MPE Calculation Method

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

### 1.3 MPE Calculation Result

#### 1.3.1 Result for operational ISM Band

For WiFi function, operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing.

Modulation Type: BPSK, QPSK, 16QAM, 64QAM for OFDM. CCK, DQPSK, DBPSK for DSSS.

Antenna Type: SMD antenna (Inverted F Antenna)

Antenna Gain: 0dBi

The nominal conducted peak output power specified: 17.5 dBm (Tolerance: +/-1dB)

The maximum conducted output peak power for the EUT is 17.52 dBm in the frequency 2.462GHz 802.11g mode which is within the production variation.

The maximum EIRP=  $17.5 + 1 + 0 = 18.5 \text{ dBm} = \underline{70.795 \text{mW}}$

The worst case is power density at prediction frequency at 20cm:  $0.01408(\text{mw/cm}^2)$

MPE limit for general population exposure at prediction frequency:  $1 (\text{mw/cm}^2)$

$0.01408(\text{mw/cm}^2) < 1 (\text{mw/cm}^2)$

Result: Pass