

# Test Report

**Report No.:** MTi211011017-02E2

**Date of issue:** Jan. 12, 2022

**Applicant:** Hangzhou Great Star Industrial Co., Ltd.

**Product:** Swiss Tech 20000mAh Wireless Solar Power Bank

**Model(s):** 31655

**FCC ID:** 2AMI2-31655

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

## Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

# Contents

<b>1 General Description .....</b>	<b>5</b>
1.1 Description of the EUT .....	5
1.2 Description of test modes .....	5
1.3 Description of support units .....	6
<b>2 Test facilities and accreditations.....</b>	<b>7</b>
2.1 Test laboratory .....	7
<b>3 List of test equipment .....</b>	<b>7</b>
<b>4 Test result .....</b>	<b>8</b>
4.2 Test setup .....	9
4.3 Test Procedures .....	9
4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01 .....	10
4.5 Test results .....	11
<b>Photographs of the Test Setup.....</b>	<b>12</b>
<b>Photographs of the EUT.....</b>	<b>12</b>

<b>Test Result Certification</b>	
<b>Applicant:</b>	<b>Hangzhou Great Star Industrial Co., Ltd.</b>
Address:	No.35, Jiuhuan Road, Jianggan District, Hangzhou, Zhejiang Province, China
<b>Manufacturer:</b>	<b>Hangzhou Great Star Industrial Co., Ltd.</b>
Address:	No.35, Jiuhuan Road, Jianggan District, Hangzhou, Zhejiang Province, China
<b>Product description</b>	
Product name:	Swiss Tech 20000mAh Wireless Solar Power Bank
Trademark:	Swiss Tech
Model name:	31655
Serial No.:	MTi211011017-02S1001
Standards:	FCC CFR 47 PART 1, § 1.1310
Test method:	KDB 680106 v03r01
<b>Date of Test</b>	
Date of test:	2021-12-06 ~ 2021-12-30
Test result:	Pass

**Test Engineer :**


(Yanice Xie)

**Reviewed By:**


(Leon Chen)

**Approved By:**


(Tom Xue)

## 1 General Description

### 1.1 Description of the EUT

Product name:	Swiss Tech 20000mAh Wireless Solar Power Bank
Model name:	31655
Series Model:	N/A
Model difference:	N/A
Electrical rating:	Rated Capacity: 20000mAh/3.7V/74.0Wh Actual Capacity: 11000mAh/5.0V Type-C Input: 5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A Micro USB Input: 5.0V=2.0A Solar pad Input: 6.0V=0.22A Type-C Output: 5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A USB A1 Output: 5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A, 5.0V=4.5A, 4.5V=5.0A USB A2 Output: 5.0V=3.0A, 9.0V=2.0A, 12.0V=1.5A TX Wireless Output: 5.0V=1.0A(5.0W) All Ways of Above Output: 5.0V=3.0A(Max)
Accessories:	Cable: USB-A to USB-C cable (1.0m)
Hardware version:	V2
Software version:	IP5568-QI-ULXKO-M
<b>RF specification:</b>	
Operation frequency:	115 kHz – 205 kHz
Modulation type:	ASK
Antenna type:	Coil Antenna

### 1.2 Description of test modes

All the test modes were carried out with the EUT in normal operation, the final test mode of the EUT was the worst test mode for emission test, which was shown in this report and defined as:

No.	Emission test modes
Mode 1	Stand-by mode
Mode 2	Charger(Micro USB)+Wireless charger (5W)
Mode 3	Charger(Type-c)+Wireless charger (5W)
Mode 4	Wireless charger (5W)
<b>The test data only show worst test mode: Mode 3</b>	

### 1.3 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

<b>Support equipment list</b>			
Description	Model	Serial No.	Manufacturer
Mobile Phone	S9+	/	Samsung
<b>Support cable list</b>			
Description	Length (m)	From	To
/	/	/	/

## 2 Test facilities and accreditations

### 2.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573

## 3 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
MTI-E115	Electric and Magnetic Field Probe – Analyzer	Narda	EHP-200A	101166	2021/06/02	2022/06/01

## 4 Test result

### 4.1.1 Requirement

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

**Table 1 to §1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1500			f/300	<6
1500-100000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1500			f/1500	<30
1500-100000			1.0	<30


f = frequency in MHz

\* = Plane-wave equivalent power density

**Note 1:** Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

**Note 2:** General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

## 4.2 Test setup



## 4.3 Test Procedures

- The RF exposure test was performed in anechoic chamber.
- E and H-field measurements should be made with the center of the probe at a distance of 15 cm surrounding the device and 20 cm above the top surface of the primary/client pair.
- The highest emission level was recorded and compared with limit.
- The EUT was measured according to the dictates of KDB 680106 v03r01.

**4.4 Equipment Approval Considerations item 5 b) of KDB 680106 D01 v03r01**

Requirement	Device
1. Power transfer frequency is less than 1 MHz.	Yes. The operating frequencies are: 115 kHz – 205 kHz
2. Output power from each primary coil is less than or equal to 15 watts	Yes. The maximum output power is: 5W
3. The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes. The EUT has one source primary coils.
4. Client device is placed directly in contact with the transmitter.	Yes. The client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	Yes. Mobile exposure conditions only.
6. The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes. See the test result in item 4.5.



#### 4.5 Test results

##### Test condition 1: Mode 3 operating mode with client device (1 % battery status of client device)

Antenna	Probe Position	E-field (V/m)			H-field (A/m)		
		Measurement	Limit	Max. Percentage (%)	Measurement	Limit	Max. Percentage (%)
1	Z axis	0.9764	614	0.16%	0.0502	1.63	3.21%
	Left	0.5280			0.0488		
	Right	0.5426			0.0517		
	Front	0.4411			0.0488		
	Rear	0.5185			0.0523		
	Bottom	0.3701			0.0515		

##### Test condition 2: Mode 3 operating mode with client device (50 % battery status of client device)

Antenna	Probe Position	E-field (V/m)			H-field (A/m)		
		Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
1	Z axis	0.9766	614	0.16%	0.0503	1.63	3.22%
	Left	0.5282			0.0485		
	Right	0.5424			0.0516		
	Front	0.4413			0.0483		
	Rear	0.5188			0.0525		
	bottom	0.3704			0.0512		

##### Test condition 3: Mode 3 operating mode with client device (99 % battery status of client device)

Antenna	Probe Position	E-field (V/m)			H-field (A/m)		
		Measurement	Limit	Percentage (%)	Measurement	Limit	Percentage (%)
1	Z axis	0.9765	614	0.16%	0.0504	1.63	3.24%
	Left	0.5284			0.0487		
	Right	0.5425			0.0515		
	Front	0.4414			0.0487		
	Rear	0.5186			0.0528		
	bottom	0.3703			0.0513		

## Photographs of the Test Setup

See the Appendix - Test Setup Photos.

## Photographs of the EUT

See the Appendix - EUT Photos.

----End of Report----