



REPORT No.: SZ19090095W01

TEST REPORT

APPLICANT : Hangzhou Great Star Industrial Co., Ltd.

PRODUCT NAME : WIFI MODULE

MODEL NAME : IM-3K01

BRAND NAME : iMagic

FCC ID : 2AMI2-IM-3K01

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2019-09-12

TEST DATE : 2019-10-08 to 2019-12-05

ISSUE DATE : 2019-12-06

Edited by: Peng Mi
Peng Mi (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	4
1.1. Applicant and Manufacturer Information	4
1.2. Equipment Under Test (EUT) Description	4
1.3. Modulation Type and Data Rate of EUT	5
1.4. The Channel Number and Frequency	5
1.5. Test Standards and Results	6
1.6. Environmental Conditions	7
2. 47 CFR Part 15C Requirements	8
2.1. Antenna Requirement	8
2.2. Duty Cycle of Test Signal	9
2.3. Maximum Peak and Average Conducted Output Power	12
2.4. Bandwidth	15
2.5. Conducted Spurious Emissions and Band Edge	25
2.6. Power Spectral Density (PSD)	41
2.7. Conducted Emission	51
2.8. Restricted Frequency Bands	55
2.9. Radiated Emission	71
Annex A Test Uncertainty	90
Annex B Testing Laboratory Information	91



REPORT No.: SZ19090095W01

Change History		
Version	Date	Reason for change
1.0	2019-12-06	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Hangzhou Great Star Industrial Co., Ltd.
Applicant Address:	NO.35, Jiuhuan Road, Jianggan District, Hangzhou, China
Manufacturer:	Hangzhou Great Star Industrial Co., Ltd.
Manufacturer Address:	NO.35, Jiuhuan Road, Jianggan District, Hangzhou, China

1.2. Equipment Under Test (EUT) Description

Product Name:	WIFI MODULE
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	V1.0
Software Version:	V1.0
Equipment Type:	WLAN2.4G
Modulation Technology:	DSSS, OFDM
Modulation Type:	Refer to section1.3
Operating Frequency Range:	802.11b/g/ n(HT20): 2412MHz-2472MHz
Antenna Type:	PCB Antenna
Antenna Gain:	3dBi

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Modulation Type and Data Rate of EUT

Modulation technology	Modulation Type	Data Rate (Mbps) ^{Note1}
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n (HT20))	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

1.4. The Channel Number and Frequency

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/ n(HT20)	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		

Note 1: The black bold channels were selected for test.



1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle Of Test Signal	Oct 11, 2019	Ouyang Feng	PASS	No deviation
3	15.247(b)	Maximum Peak and Average Conducted Output Power	Oct 11, 2019	Ouyang Feng	PASS	No deviation
4	15.247(a)	Bandwidth	Oct 12 & Nov 28, 2019	Ouyang Feng	PASS	No deviation
5	15.247(d)	Conducted Spurious Emission and Band Edge	Oct 12 & Nov 28, 2019	Ouyang Feng	PASS	No deviation
6	15.247(e)	Power Spectral Density (PSD)	Oct 12 & Nov 28, 2019	Ouyang Feng	PASS	No deviation
7	15.207	Conducted Emission	Oct 11, 2019	Lin Jiayong	PASS	No deviation
8	15.247(d)	Restricted Frequency Bands	Dec 05, 2019	Peng Xuwei	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Oct 08, 2019	Peng Xuwei	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013, KDB558074 D01 v05r02.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12dB contains two parts that cable loss 2dB and



Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.




2.2.3. Test Result


A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
802.11b	100.00	0.00
802.11g	100.00	0.00
802.11n(HT20)	100.00	0.00


B. Test Plots



(Channel 1, 802.11b)



(Channel 1, 802.11g)



(Channel 1, 802.11 n (HT20))

2.3. Maximum Peak and Average Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



2.3.3. Test Result

Maximum Peak Conducted Output Power

802.11b Test Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	15.74	0.037	30	1	PASS
6	2437	14.97	0.031			PASS
11	2462	14.44	0.028			
12	2467	19.36	0.086			
13	2472	19.16	0.082			PASS

802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	16.14	0.041	30	1	PASS
6	2437	15.83	0.038			PASS
11	2462	15.37	0.034			PASS
12	2467	20.14	0.103			PASS
13	2472	20.08	0.102			PASS

802.11n (HT20) Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	16.11	0.041	30	1	PASS
6	2437	15.73	0.037			PASS
11	2462	15.64	0.037			PASS
12	2467	20.30	0.107			PASS
13	2472	20.23	0.105			PASS

**Maximum Average Conducted Output Power****802.11b Test Mode**

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	14.29	0.00	14.29	0.027	30	1	PASS
6	2437	14.19		14.19	0.026			PASS
11	2462	13.55		13.55	0.023			PASS
12	2467	17.62		17.62	0.058			PASS
13	2472	17.60		17.60	0.058			PASS

802.11g Test mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	14.00	0.00	14.00	0.025	30	1	PASS
6	2437	13.54		13.54	0.023			PASS
11	2462	13.16		13.16	0.021			PASS
12	2467	16.74		16.74	0.047			PASS
13	2472	16.68		16.68	0.047			PASS

802.11n (HT20) Test mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	14.08	0.00	14.20	0.026	30	1	PASS
6	2437	16.34		16.46	0.044			PASS
11	2462	13.05		13.05	0.020			PASS
12	2467	17.10		17.10	0.051			PASS
13	2472	14.47		14.59	0.029			PASS


2.4. Bandwidth

2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ω; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.4.3. Test Procedure

KDB 558074 Section 8.2 was used in order to prove compliance.




2.4.4. Test Result

802.11b Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	9.13	≥500	PASS
6	2437	8.66	≥500	PASS
11	2462	9.10	≥500	PASS
12	2467	10.07	≥500	PASS
13	2472	10.06	≥500	PASS


B. Test Plots




(Channel 1, 802.11b)




(Channel 6, 802.11b)



(Channel 11, 802.11b)



(Channel 12, 802.11b)



(Channel 13, 802.11b)




802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.40	≥500	PASS
6	2437	16.40	≥500	PASS
11	2462	16.40	≥500	PASS
12	2467	16.43	≥500	PASS
13	2472	16.46	≥500	PASS


B. Test Plots:




(Channel 1, 802.11g)




(Channel 6, 802.11g)



(Channel 11, 802.11g)



(Channel 12, 802.11g)



(Channel 13, 802.11g)




802.11n (HT20) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.06	≥500	PASS
6	2437	17.06	≥500	PASS
11	2462	17.27	≥500	PASS
12	2467	17.32	≥500	PASS
13	2472	17.33	≥500	PASS


B. Test Plots:




(Channel 1, 802.11n (HT20))




(Channel 6, 802.11n (HT20))



(Channel 11, 802.11n (HT20))



(Channel 12, 802.11n (HT20))



(Channel 13, 802.11n (HT20))


2.5. Conducted Spurious Emissions and Band Edge

2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.5.4. Test Result

802.11b Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.67	1.72	-18.28	PASS
6	2437	-44.03	-0.24	-20.24	PASS
11	2462	-43.41	-0.99	-20.99	PASS
12	2467	-44.45	2.30	-17.70	PASS
13	2472	-44.18	3.46	-16.54	PASS


B. Test Plots:




(Channel 1, 30MHz to 25GHz)



(Band Edge, Channel 1)




(Channel 6, 30MHz to 25GHz)



(Channel 11, 30MHz to 25GHz)




(Channel 12, 30MHz to 25GHz)



(Band Edge, Channel 12)



(Channel 13, 30MHz to 25GHz)



(Band Edge, Channel 13)




802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.94	-3.79	-23.79	PASS
6	2437	-43.67	-4.92	-24.92	PASS
11	2462	-43.50	-8.63	-28.63	PASS
12	2467	-43.89	-3.76	-23.76	PASS
13	2472	-44.06	-4.59	-24.59	PASS


B. Test Plots:




(Channel 1, 30MHz to 25GHz)



(Band Edge, Channel 1)




(Channel 6, 30MHz to 25GHz)



(Channel 11, 30MHz to 25GHz)




(Channel 12, 30MHz to 25GHz)



(Band Edge, Channel 12)



(Channel 13, 30MHz to 25GHz)



(Band Edge, Channel 13)




802.11n (HT20) Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-43.19	-3.33	-23.33	PASS
6	2437	-43.56	-4.45	-24.45	PASS
11	2462	-43.25	-8.72	-28.72	PASS
12	2467	-44.49	-3.21	-23.21	PASS
13	2472	-43.82	-3.42	-23.42	PASS


B. Test Plots:




(Channel 1, 30MHz to 25GHz)



(Band Edge, Channel 1)




(Channel 6, 30MHz to 25GHz)



(Channel 11, 30MHz to 25GHz)




(Channel 12, 30MHz to 25GHz)



(Band Edge, Channel 12)



(Channel 13, 30MHz to 25GHz)



(Band Edge, Channel 13)


2.6. Power Spectral Density (PSD)

2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.6.3. Test Procedure

KDB 558074 Section 8.4 was used in order to prove compliance.




2.6.4. Test Result

802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-12.17	8	PASS
6	2437	-13.82	8	PASS
11	2462	-17.23	8	PASS
12	2467	-11.33	8	PASS
13	2472	-11.33	8	PASS


B. Test Plots:




(Channel 1, 802.11b)




(Channel 6, 802.11b)



(Channel 11, 802.11b)



(Channel 12, 802.11b)




(Channel 13, 802.11b)




A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-17.66	8	PASS
6	2437	-19.19	8	PASS
11	2462	-22.62	8	PASS
12	2467	-16.57	8	PASS
13	2472	-17.54	8	PASS


B. Test Plots:




(Channel 1, 802.11g)




(Channel 6, 802.11g)



(Channel 11, 802.11g)



(Channel 12, 802.11g)



(Channel 13, 802.11g)




802.11n (HT20) Test mode


A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-18.00	8	PASS
6	2437	-19.48	8	PASS
11	2462	-22.69	8	PASS
12	2467	-17.17	8	PASS
13	2472	-16.86	8	PASS


B. Test Plots:




(Channel 1, 802.11n (HT20))




(Channel 6, 802.11n (HT20))



(Channel 11, 802.11n (HT20))



(Channel 12, 802.11n (HT20))



(Channel 13, 802.11n (HT20))

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT + PC + Adapter + WIFI TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plots:



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1502	49.32	40.19	65.99	55.99	Line	PASS
2	0.1726	53.77	42.79	64.83	54.83		PASS
3	0.1951	52.81	42.87	63.82	53.82		PASS
4	0.2042	51.61	40.41	63.44	53.44		PASS
5	0.4601	42.64	33.09	56.69	46.69		PASS
6	0.9877	37.72	27.91	56.00	46.00		PASS



(N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1859	53.55	43.14	64.22	54.22	Neutral	PASS
2	0.2443	45.03	33.45	61.95	51.95		PASS
3	0.2760	43.79	33.24	60.93	50.93		PASS
4	0.3703	41.69	30.54	58.49	48.49		PASS
5	0.4605	41.27	29.58	56.68	46.68		PASS
6	2.7048	40.38	27.66	56.00	46.00		PASS


2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.8.3. Test Procedure

KDB 558074 Section 8.6 and 8.7 was used in order to prove compliance.

2.8.4. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


802.11b Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2385.23	PK	54.92	-29.67	32.56	57.81	74	PASS
1	2385.68	AV	44.54	-29.67	32.56	47.43	54	PASS
11	2489.53	PK	56.10	-29.67	32.56	58.99	74	PASS
11	2488.62	AV	44.99	-29.67	32.56	47.88	54	PASS
12	2483.89	PK	49.29	-29.67	32.56	52.18	74	PASS
12	2484.08	AV	48.04	-29.67	32.56	50.93	54	PASS
13	2484.51	PK	49.19	-29.67	32.56	52.08	74	PASS
13	2486.18	AV	48.00	-29.67	32.56	50.89	54	PASS



B. Test Plots:



(PEAK, Channel 1, 802.11b)



(AVG, Channel 1, 802.11b)



(PEAK, Channel 11, 802.11b)




(AVG, Channel 11, 802.11b)




(PEAK, Channel 12, 802.11b)



(AVG, Channel 12, 802.11b)



(PEAK, Channel 13, 802.11b)




(AVG, Channel 13, 802.11b)

**802.11g Test mode****A. Test Verdict:**

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
1	2390.00	PK	65.16	-29.67	32.56	68.05	74	PASS
1	2390.00	AV	40.27	-29.67	32.56	43.16	54	PASS
11	2489.53	PK	56.10	-29.67	32.56	58.99	74	PASS
11	2488.62	AV	44.99	-29.67	32.56	47.88	54	PASS
12	2483.89	PK	49.29	-29.67	32.56	52.18	74	PASS
12	2484.08	AV	48.04	-29.67	32.56	50.93	54	PASS
13	2487.86	PK	55.98	-29.67	32.56	58.87	74	PASS
13	2488.65	AV	45.44	-29.67	32.56	48.33	54	PASS




B. Test Plots:



(PEAK, Channel 1, 802.11g)



(AVG, Channel 1, 802.11g)




(PEAK, Channel 11, 802.11g)




(AVG, Channel 11, 802.11g)




(PEAK, Channel 12, 802.11g)



(AVG, Channel 12, 802.11g)



(PEAK, Channel 13, 802.11g)




(AVG, Channel 13, 802.11g)

**802.11 n (HT20) Test mode****A. Test Verdict:**

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
1	2390.00	PK	66.10	-29.67	32.56	68.99	74	PASS
1	2390.00	AV	42.83	-29.67	32.56	45.72	54	PASS
11	2485.26	PK	57.21	-29.67	32.56	60.10	74	PASS
11	2483.50	AV	38.86	-29.67	32.56	41.75	54	PASS
12	2483.81	PK	57.98	-29.67	32.56	60.87	74	PASS
12	2483.50	AV	41.07	-29.67	32.56	43.96	54	PASS
13	2489.64	PK	57.02	-29.67	32.56	59.91	74	PASS
13	2487.93	AV	44.59	-29.67	32.56	47.48	54	PASS




B. Test Plots:



(PEAK, Channel 1, 802.11n (HT20))



(AVG, Channel 1, 802.11n (HT20))




(PEAK, Channel 11, 802.11n (HT20))



(AVG, Channel 11, 802.11n (HT20))




(PEAK, Channel 12, 802.11n (HT20))



(AVG, Channel 12, 802.11n (HT20))



(PEAK, Channel 13, 802.11n (HT20))



(AVG, Channel 13, 802.11n (HT20))



2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.9.2. Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading



For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**802.11b Test mode**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	29.00	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
320.150	34.96	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
480.401	31.49	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1997.519	48.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4824.100	53.65	N/A	42.40	74.00	N/A	54.00	Horizontal	PASS
11046.336	47.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	29.01	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
240.025	26.14	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1993.677	49.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4820.804	50.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9133.588	48.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
15014.657	47.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	29.70	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
320.150	36.94	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2406.643	46.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4873.800	53.61	N/A	41.52	74.00	N/A	54.00	Horizontal	PASS
7976.978	47.29	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11833.279	48.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.140	29.71	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
278.874	29.31	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1314.366	45.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2331.733	46.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4874.013	47.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8439.062	47.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plots for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.642	31.43	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
320.150	35.74	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2461.064	47.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4923.800	51.90	N/A	42.54	74.00	N/A	54.00	Horizontal	PASS
8299.036	46.85	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12186.143	47.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	29.65	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
320.150	29.26	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2465.546	47.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3283.324	46.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4924.423	48.94	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9035.570	46.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 12



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	27.46	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	27.88	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2356.062	47.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4932.824	45.91	N/A	41.52	74.00	N/A	54.00	Horizontal	PASS
8436.261	47.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12847.063	47.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	28.19	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	26.69	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2462.985	47.93	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4932.824	49.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8497.872	47.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12606.219	47.98	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 13



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	27.70	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	27.21	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2474.510	46.88	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4944.026	46.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5602.146	47.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10363.011	46.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	27.64	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
159.900	25.94	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2468.747	46.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4941.226	47.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7887.361	46.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12258.956	47.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**802.11g Test mode**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
320.150	35.66	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1991.116	48.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2389.996	49.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4819.800	52.22	N/A	42.49	74.00	N/A	54.00	Horizontal	PASS
8489.471	47.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12188.943	47.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	29.45	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
320.150	29.06	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1998.159	47.25	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2389.996	50.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4823.604	47.95	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12581.015	47.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
39.712	29.54	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
320.150	36.64	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2174.870	46.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4871.213	50.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8366.248	46.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13180.324	48.33	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.140	29.37	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
100.413	26.43	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2414.966	46.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4874.013	48.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8397.054	46.00	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12194.544	46.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plots for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	28.74	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
320.150	30.46	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2510.364	47.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4927.223	49.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9015.967	47.20	N/A	42.40	74.00	N/A	54.00	Horizontal	PASS
12188.943	48.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	30.38	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
295.870	30.20	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2000.720	46.40	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4473.541	45.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4921.622	46.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8945.954	46.33	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 12



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	28.17	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
192.678	26.96	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1998.159	47.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2464.266	47.55	N/A	41.52	74.00	N/A	54.00	Horizontal	PASS
5834.588	45.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12258.956	46.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	28.51	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
192.678	28.12	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1763.185	45.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2461.705	47.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4473.541	45.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9133.588	47.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 13



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	27.28	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	27.25	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2476.431	47.92	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4946.827	46.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7915.366	45.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12513.803	47.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.140	28.25	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	28.06	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1492.997	44.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2493.717	47.49	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5688.962	46.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9077.578	48.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**802.11n (HT20) Test mode**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	29.63	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
320.150	36.50	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2373.349	48.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2661.611	47.33	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4821.800	52.27	N/A	40.10	74.00	N/A	54.00	Horizontal	PASS
8436.261	46.85	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
31.214	37.26	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
106.483	26.63	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
358.999	28.04	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2380.392	48.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4818.003	48.43	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9021.568	48.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	29.68	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
320.150	33.52	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1997.519	46.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4868.412	51.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8377.450	46.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12611.820	48.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	30.13	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
277.660	29.89	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2233.133	46.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4879.614	50.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9010.366	46.81	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12191.744	47.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plots for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
53.066	30.14	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
320.150	36.03	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2505.242	46.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4927.223	50.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8439.062	46.99	N/A	42.40	74.00	N/A	54.00	Horizontal	PASS
12205.746	47.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.642	30.98	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
281.302	28.64	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2653.210	48.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4924.423	47.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8377.450	46.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12886.270	47.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 12



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
50.638	27.62	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	25.27	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1998.159	45.87	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3395.345	45.02	N/A	41.52	74.00	N/A	54.00	Horizontal	PASS
5767.376	45.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8909.547	46.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	27.49	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	28.39	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2462.345	47.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4930.024	47.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8649.100	46.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12536.207	47.93	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 13



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	26.91	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
192.678	28.23	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1923.890	45.96	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4179.487	44.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5733.770	45.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9027.169	47.03	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	28.08	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
192.678	27.64	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2239.536	46.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3454.155	46.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5882.197	46.40	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10351.809	46.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Attenuator 1	(N/A.)	10dB	Resent	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2019.04.09	2020.04.08
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2019.04.16	2020.04.15
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2019.05.08	2020.05.09
LISN	812744	NSLK 8127	Schwarzbeck	2019.05.08	2020.05.09
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2019.05.08	2020.05.09
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A
ADAPTER	OKXTTW	LA45NM1 40	DELL	N/A	N/A
NOTEBOOK	DF2DR A01 DPC	VOSTRO 5370	DELL	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Townsend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V1.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2019.07.26	2020.07.25
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.08	2020.05.09
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2019.02.15	2020.02.14
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2020.07.25
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2019.07.26	2020.07.25
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2018.12.01	2019.11.30
ADAPTER	OKXTTW	LA45NM140	DELL	N/A	N/A
NOTEBOOK	DF2DR A01 DPC	VOSTRO 5370	DELL	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18

_____ END OF REPORT _____