

FCC 47 CFR PART15 SUBPART E**For****Prepared by****Product Name: Mi Home Security Camera****Brand Name: MI ,****Model No.: SXJ01ZM****Series Model.: N/A****FCC ID: 2AMIN-SXJ01ZM****Test Report Number:****C170307R01-RPW1****Issued for****ZIMI CORPORATION****Room A913, No. 159 Chengjiang Road, Jiangyin City, Jiangsu Province, P.R.China****Issued by****Compliance Certification Services Inc.****Kun shan Laboratory****No.10 Weiye Rd., Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, China****TEL: 86-512-57355888****FAX: 86-512-57370818**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	4
2 EUT DESCRIPTION.....	5
3 TEST METHODOLOGY.....	6
3.1 EUT CONFIGURATION	6
3.2 EUT EXERCISE.....	6
3.3 GENERAL TEST PROCEDURES.....	6
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	7
3.5 DESCRIPTION OF TEST MODES.....	8
3.6 ANTENNA DESCRIPTION.....	9
4 INSTRUMENT CALIBRATION	10
4.1 MEASUREMENT EQUIPMENT USED	10
4.2 MEASUREMENT UNCERTAINTY	11
5 FACILITIES AND ACCREDITATIONS	12
5.1 FACILITIES.....	12
5.2 EQUIPMENT.....	12
5.3 TABLE OF ACCREDITATIONS AND LISTINGS	12
5.4 TABLE OF ACCREDITATIONS AND LISTINGS.....	13
6 SETUP OF EQUIPMENT UNDER TEST	14
6.1 SETUP CONFIGURATION OF EUT.....	14
6.2 SUPPORT EQUIPMENT.....	14
7 FCC PART 15 REQUIREMENTS	15
7.1 26 DB EMISSION BANDWIDTH	15
7.2 99% DB EMISSION BANDWIDTH.....	25
7.3 MAXIMUM CONDUCTED OUTPUT POWER	31
7.4 BAND EDGES MEASUREMENT	34
7.5 MAXIMUM POWER SPECTRAL DENSITY.....	41
7.6 FREQUENCY STABILITY MEASUREMENT	51
7.7 RADIATED UNDESIRABLE EMISSION	53
7.8 POWERLINE CONDUCTED EMISSIONS	65

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	April 28, 2017	C170307R01-RPW1	ALL	N/A
01	August 11,2017	C170307R01-RPW1	P25~P30	Add 99% Bandwidth data for 5.15-5.25GHz

1 TEST RESULT CERTIFICATION

Product Name:	Mi Home Security Camera
Trade Name:	MI , 
Model Name.:	SXJ01ZM
Series Model:	N/A
Applicant Discrepancy:	Initial
Device Category:	Mobile unit
Date of Test:	April 12, 2017 ~ April 21, 2017 & August 11, 2017
Applicant:	ZIMI CORPORATION Room A913, No. 159 Chengjiang Road, Jiangyin City, Jiangsu Province, P.R.China
Manufacturer:	ZIMI CORPORATION Room A913, No. 159 Chengjiang Road, Jiangyin City, Jiangsu Province, P.R.China
Application Type:	Certification

APPLICABLE STANDARDS

STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart E	No non-compliance noted

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.407 and KDB 789033.


The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:



Jeff.Fang
RF Manager
Compliance Certification Service Inc.

Tested by:



Lily.Wang
Test Engineer
Compliance Certification Service Inc.

2 EUT DESCRIPTION

Product Name:	Mi Home Security Camera				
Brand Name:	MI , 				
Model Name:	SXJ01ZM				
Series Model:	N/A				
Model Discrepancy:	N/A				
Power Adapter:	Model:A194-050200C-US1 INPUT: 100-240V~50/60Hz 0.35A MAX OUTPUT : 5.0V---2000mA				
Frequency Range :	Band	Mode	Frequency Range(MHz)	Number of Channels	
	Band I UNII-1	IEEE802.11a mode	5150 MHz~5250 MHz	4	
		IEEE802.11n HT20 mode		4	
		IEEE802.11n HT40 mode		2	
	Band II UNII-2A	IEEE802.11a mode	5250 MHz ~5350 MHz	4	
		IEEE802.11n HT20 mode		4	
		IEEE802.11n HT40 mode		2	
Transmit Power :	IEEE802.11a mode: 16.89dBm IEEE802.11an HT20 mode: 14.98dBm IEEE802.11an HT40 mode: 14.72dBm				
Modulation Technique :	IEEE802.11a mode: OFDM (6,9,12,18,24,36,48 and 54 Mbps) IEEE802.11n HT20 mode: OFDM (MCS0~MCS7) IEEE802.11n HT40 mode: OFDM (MCS0~MCS7)				
Antenna Specification:	PCB Antenna Gain: 2.37 dBi				
Operating Mode:	<input type="checkbox"/> Master <input type="checkbox"/> Client with radar detection <input checked="" type="checkbox"/> Client without radar detection				

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: 2AMIN-SXJ01ZM filing to comply with FCC Part 15, Subpart E Rules.

3 TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10:2013 and FCC CFR 47 15.207, 15.209 and 15.407.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed for RF field strength measurement to meet the Commissions requirement, and is operated in a manner intended to generate the maximum emission in a continuous normal application.

3.2 EUT EXERCISE

The EUT is operated in the engineering mode to fix the Tx frequency for the purposes of measurement.

According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is positioned at 0.8 m above the ground plane. According to the requirements in Section 13.3 of ANSI C63.10:2013, the conducted emission from the EUT is measured in the frequency range between 0.15 MHz and 30MHz, using the CISPR Quasi-Peak detector mode.

Radiated Emissions

Under 1GHz

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

Above 1GHz

The EUT is placed on a turn table, which is 1.5 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	
0.495 - 0.505 ⁽¹⁾	16.69475 - 16.69525	608 - 614	4.50 - 5.15
2.1735 - 2.1905	16.80425 - 16.80475	960.0 - 1240	5.35 - 5.46
4.125 - 4.128	25.50 - 25.67	1300 - 1427	7.25 - 7.75
4.17725 - 4.17775	37.50 - 38.25	1435.0 - 1626.5	8.025 - 8.500
4.20725 - 4.20775	73.00 - 74.60	1645.5 - 1646.5	9.0 - 9.2
6.215 - 6.218	74.80 - 75.20	1660 - 1710	9.3 - 9.5
6.26775 - 6.26825	108.00 - 121.94	1718.8 - 1722.2	10.6 - 12.7
6.31175 - 6.31225	123 - 138	2200 - 2300	13.25 - 13.4
8.291 - 8.294	149.90 - 150.05	2310 - 2390	14.47 - 14.5
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500.0	15.35 - 16.2
8.37625 - 8.38675	156.70 - 156.90	2655 - 2900	17.7 - 21.4
8.41425 - 8.41475	162.0125 - 167.1700	3260 - 3267	22.01 - 23.12
12.29 - 12.293	167.72 - 173.20	3332 - 3339	23.6 - 24.0
12.51975 - 12.52025	240 - 285	3345.8 - 3358.0	31.2 - 31.8
12.57675 - 12.57725	322.0 - 335.4	3600 - 4400	36.43 - 36.5. ⁽²⁾
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5 DESCRIPTION OF TEST MODES

Description	Modulation Technology	Modulation Type
26dB Bandwidth and 99% bandwidth	OFDM	BPSK
Maximum conducted output power	OFDM	BPSK
Band edges measurement	OFDM	BPSK
Peak Power Spectral Density	OFDM	BPSK
Radiated undesirable emission	OFDM	BPSK
Powerline conducted emission	OFDM	BPSK

IEEE 802.11a mode:

Channel (5180MHz),Channel (5220MHz) and Channel (5240MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 mode:

Channel (5180MHz),Channel (5220MHz) and Channel (5240MHz) with MCS0 data rate were chosen for full testing.

IEEE 802.11n HT40 mode:

Channel (5190MHz) and Channel (5230MHz) with MCS0 data rate were chosen for full testing.

IEEE 802.11a mode:

Channel (5260MHz),Channel (5280MHz) and Channel (5320MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 mode:

Channel (5260MHz),Channel (5280MHz) and Channel (5320MHz) with MCS0 data rate were chosen for full testing.

IEEE 802.11n HT40 mode:


Channel (5270MHz) and Channel (5310MHz) with MCS0 data rate were chosen for full testing.

3.6 ANTENNA DESCRIPTION

an intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached or an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section"

* the antenna of this EUT is a unique(PCB Antenna for WiFi).

* the EUT complies with the requirement of 15.203.



4 INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.1 MEASUREMENT EQUIPMENT USED

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2016-9-10	2017-9-9
Spectrum Analyzer	RS	FSU26	200789	2016-7-21	2017-7-20
Power meter	Anritsu	ML2495A	1445010	2016-5-16	2017-5-15
Power sensor	Anritsu	MA2411B	1339220	2016-5-16	2017-5-15
Power SPLITTER	Mini-Circuits	ZN2PD-9G	SF078500430	N.C.R	N.C.R
DC Power Supply	AGILENT	E3632A	MY50340053	N.C.R	N.C.R
Temp. / Humidity Gauge	Anymetre	TH603	CCS007	2016-11-1	2017-10-31

977 Chamber					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2016-9-10	2017-9-9
Spectrum Analyzer	RS	FSU26	200789	2016-7-21	2017-7-20
Spectrum Analyzer	RS	FSU26	200789	2017-7-20	2018-7-19
EMI Test Receiver	R&S	ESCI	101378	2017-1-5	2018-1-4
Pre-Amplifier	MINI	ZFL-1000VH2	070306	2017-1-5	2018-1-4
Pre-Amplifier	Miteq	JS41-00101800-32-10P	1675713	2016-7-21	2017-7-20
Bilog Antenna	Sunol	JB1	A062604	2016-5-29	2017-5-28
Bilog Antenna	Sunol	JB1	A110204-1	2016-5-29	2017-5-28
Loop Antenna	SCHWARZBECK	HXYZ9170	9170-108	2017-3-4	2018-3-3
Horn-antenna	SCHWARZBECK	9120D	D:266	2017-3-5	2018-3-4
Horn-antenna	SCHWARZBECK	9120D	D:267	2016-11-10	2017-11-9
Turn Table	CT	CT123	4165	N.C.R	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R	N.C.R
Controller	CT	CT100	95637	N.C.R	N.C.R
Test Software			EZ-EMC		

Conducted Emission					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EMI TEST RECEIVER	R&S	ESCI	100781	2017-2-28	2018-2-27
V (V-LISN)	SCHWARZBECK	NNLK 8129	8129-143	2016-11-1	2017-10-31
TWO-LINE V-NETWORK	R&S	ENV216	101604	2016-11-1	2017-10-31
Pulse LIMITER	R&S	ESH3-Z2	100524	2017-1-5	2018-1-4
Test Software	EZ-EMC				

Remark: Each piece of equipment is scheduled for calibration once a year.

4.2 MEASUREMENT UNCERTAINTY

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 6 is based on such expansion factors.

Table 6: Maximum measurement uncertainty

Parameter	UNCERTAINTY
Radio frequency	$\pm 0.8 \times 10^{-7}$
RF power, conducted	0.2054
Maximum frequency deviation: -within 300 Hz and 6 kHz of audio frequency -within 6 kHz and 25 kHz of audio frequency	1.3% 0.65 dB
Adjacent channel power	0.2054
Conducted spurious emission of transmitter, valid up to 6 GHz	0.2892
Conducted emission of receivers	+1.2/-1.1 dB
Radiated emission of transmitter, valid up to 6 GHz	± 3.94 dB
Radiated emission of receiver, valid up to 6 GHz	± 3.94 dB
RF level uncertainty for a given BER	± 0.3 dB
Temperature	0.1979
Humidity	± 1 %

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10Weiye Rd., Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

The sites are constructed in conformance with the requirements of ANSI C63.10:2013 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 TABLE OF ACCREDITATIONS AND LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 200581-0 to perform Electromagnetic Interference tests according to FCC Part 15 and CISPR 22 requirements. In addition, the test facilities are listed with USA, Certification and Engineering Bureau, 424105 for 10m chamber, 238958 for 3m chamber.

5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	47 CFR FCC Part 15/18 (using ANSI C63.10 :2013); VCCI V3; CNS 13438; CNS 13439; CNS 13803; CISPR 11; EN 55011; CISPR 13; EN 55013; CISPR 22:2005; CISPR 22:1997 +A1 :2000+A2 :2002; EN 55022:2006; EN55022 :1998 +A1 :2001+A2 :2003; EN 61000-6-3 (excluding discontinuous interference); EN 61000-6-4; AS/NZS CISPR 22; CAN/CSA-CEI/IEC CISPR 22; EN 61000-3-2; EN 61000-3-3; EN550024; EN 61000-4-2; EN 61000-4-3; EN61000-4-4; EN 61000-4-5; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-11; IEC61000-3-2; IEC61000-3-3; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11; EN 300 220-3; EN 300 328; EN 300 330-2; EN 300 440-1; EN 300-440-2; EN 300 893; EN 301 489-01; EN 301 489-3; EN 301 489-07; EN 301 489-17; 47 CFR FCC Part 15, 22, 24	
USA	FCC	3/10 meter Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	3/10 meter Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-1600 C-1707 G-216

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID
1.	Notebook	Dell	E5430	N/A	N/A

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

7 FCC PART 15 REQUIREMENTS


7.1 26 DB EMISSION BANDWIDTH

LIMIT

According to §15.403(i), for purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Compliance with the emissions limits is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

Test Configuration

TEST PROCEDURE



1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = approximately 1% of the emission bandwidth, VBW > RBW, Detector = Peak ,Span >26dB bandwidth, and Sweep = auto ,Trace mode = max hold.
4. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
5. Repeat until all the rest channels were investigated.

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode

5150~5250MHz

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	20.272
Mid	5220	20.192
High	5240	20.144

5250~5350MHz

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5260	20.272
Mid	5280	20.272
High	5320	20.189

Test mode: IEEE 802.11n HT20MHz mode

5150~5250MHz

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	20.433
Mid	5220	20.433
High	5240	20.385

5250~5350MHz

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5260	20.497
Mid	5280	20.449
High	5320	20.433

Test mode: IEEE 802.11n HT40MHz mode

5150~5250MHz



Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5190	41.250
High	5230	41.154

5250~5350MHz


Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5270	41.250
High	5310	41.250

Test PlotIEEE 802.11a mode:

5150~5250MHz


CH Low**CH Mid**

CH High




5250~5350MHz


CH Low



CH Mid




CH High




IEEE 802.11n HT20 mode

5150~5250MHz


CH Low



CH Mid




CH High




5250~5350MHz


CH Low



CH Mid


**1 PK
MAXH**



CH High


**1 PK
MAXH**



IEEE 802.11n HT40 mode

5150~5250MHz

CH Low




CH High




5250~5350MHz

CH Low



CH High




7.2 99% DB EMISSION BANDWIDTH

LIMIT

None; for reporting purposes only.

Test Configuration



Test Procedure

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot \text{RBW}$
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode**5150~5250MHz**

Channel	Frequency (MHz)	Bandwidth (MHz)
Low	5180	16.987
Mid	5220	16.987
High	5240	16.987

Test mode: IEEE 802.11n HT20MHz mode**5150~5250MHz**



Channel	Frequency (MHz)	Bandwidth (MHz)
Low	5180	17.788
Mid	5220	17.788
High	5240	17.788

Test mode: IEEE 802.11n HT40MHz mode**5150~5250MHz**


Channel	Frequency (MHz)	Bandwidth (MHz)
Low	5190	36.346
High	5230	36.250

Test PlotIEEE 802.11a mode:

5150~5250MHz


CH Low**CH Mid**

CH High


IEEE 802.11n HT20 mode

5150~5250MHz


CH Low



CH Mid




CH High




IEEE 802.11n HT40 mode

5150~5250MHz

CH Low



CH High



7.3 MAXIMUM CONDUCTED OUTPUT POWER

LIMIT


According to §15.407(a),

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

The peak power shall not exceed the limit as follow:

Test Configuration



The EUT was connected to a spectrum analyzer through a 50Ω RF cable.

TEST PROCEDURE

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF peak power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.

TEST RESULTS

No non-compliance noted

TEST RESULTS

No non-compliance noted

Test Data**Test mode: IEEE 802.11a mode****5150~5250MHz**

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	5180	16.20	24.00
Mid	5220	16.67	24.00
High	5240	16.89	24.00

Channel	Frequency (MHz)	Average Conducted Power(dBm)
Low	5180	5.81
Mid	5220	6.25
High	5240	6.47

5250~5350MHz

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	5260	16.15	24.00
Mid	5280	16.30	24.00
High	5320	16.64	24.00

Channel	Frequency (MHz)	Average Conducted Power(dBm)
Low	5260	5.72
Mid	5280	5.88
High	5320	6.24

Test mode: IEEE 802.11n HT20MHz mode**5150~5250MHz**

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	5180	14.67	24.00
Mid	5220	14.98	24.00
High	5240	14.38	24.00

Channel	Frequency (MHz)	Average Conducted Power(dBm)
Low	5180	4.96
Mid	5220	5.34
High	5240	4.65

5250~5350MHz

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	5260	14.57	24.00
Mid	5280	14.76	24.00
High	5320	14.97	24.00

Channel	Frequency (MHz)	Average Conducted Power(dBm)
Low	5260	4.86
Mid	5280	5.05
High	5320	5.15

Test mode: IEEE 802.11n HT40MHz mode

5150~5250MHz

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	5190	14.29	24.00
High	5230	14.72	24.00

Channel	Frequency (MHz)	Average Conducted Power(dBm)
Low	5190	5.05
High	5230	5.48

5250~5350MHz

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	5270	14.17	24.00
High	5310	14.46	24.00

Channel	Frequency (MHz)	Average Conducted Power(dBm)
Low	5270	4.90
High	5310	5.23

7.4 BAND EDGES MEASUREMENT


LIMIT

According to §15.407(b),

(1) The provisions of Section 15.205 of this part apply to intentional radiators operating under this section.

(2) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency block edges as the design of the equipment permits.

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / Sweep=AUTO

VBW=10Hz, when duty cycle is no less than 98 percent.

VBW $\geq 1/T$, when duty cycle is less than 98 percent, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
IEEE 802.11 a	100	-	-	10Hz
IEEE 802.11n HT20	100	-	-	10Hz
IEEE 802.11n HT20	100	-	-	10Hz


TEST RESULTS

Refer to attach spectrum analyzer data chart.


Band Edges (IEEE 802.11a mode)

5180MHz

Polarity: Vertical




Polarity: Horizontal




5320MHz

Polarity: Vertical




Polarity: Horizontal




Band Edges (IEEE 802.11n HT20 mode)

5180MHz

Polarity: Vertical



Polarity: Horizontal




5320MHz

Polarity: Vertical



Polarity: Horizontal




Band Edges (IEEE 802.11n HT40 mode)


Page 38 of 69

5190MHz

Polarity: Vertical



Polarity: Horizontal



5310MHz

Polarity: Vertical

108.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5350.000	48.27	-3.44	44.83	74.00	-29.17	100	206	peak
2	5357.692	49.95	-3.41	46.54	74.00	-27.46	100	89	peak

Polarity: Horizontal

108.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5350.000	49.88	-3.44	46.44	74.00	-27.56	100	219	peak
2	5355.689	50.91	-3.42	47.49	74.00	-26.51	100	219	peak

7.5 MAXIMUM POWER SPECTRAL DENSITY


LIMIT

According to §15.407(a),

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 1MHz, VBW = 3MHz, Span must be greater than 26dB bandwidth, adjust as necessary, Sweep= auto, Detector RMS
3. Record the max. reading.

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode

5150~5250MHz

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5180	-6.19	11.00	PASS
Mid	5220	-6.13	11.00	PASS
High	5240	-6.41	11.00	PASS

5250~5350MHz

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5260	-7.28	11.00	PASS
Mid	5280	-7.14	11.00	PASS
High	5320	-7.64	11.00	PASS

Test mode: IEEE 802.11n HT20MHz mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5180	-7.43	11.00	PASS
Mid	5220	-7.31	11.00	PASS
High	5240	-8.31	11.00	PASS

5250~5350MHz

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5260	-8.39	11.00	PASS
Mid	5280	-8.23	11.00	PASS
High	5320	-8.61	11.00	PASS

Test mode: IEEE 802.11n HT40MHz mode



5150~5250MHz

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5190	-9.93	11.00	PASS
High	5230	-9.66	11.00	PASS


5250~5350MHz

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5270	-9.41	11.00	PASS
High	5310	-9.22	11.00	PASS

Note:Duty factor has been offseted with cableloss


Test Plot**IEEE 802.11a mode:****5150~5250MHz****CH Low****CH Mid**

CH High




5250~5350MHz


CH Low



CH Mid





CH High




IEEE 802.11n HT20 mode

5150~5250MHz


CH Low**CH Mid**

CH High




5250~5350MHz


CH Low



CH Mid





CH High




IEEE 802.11n HT40 mode

5150~5250MHz


CH Low**CH High**

5250~5350MHz

CH Low



CH High




7.6 FREQUENCY STABILITY MEASUREMENT

LIMIT

According to §15.407(g), Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

TEST CONFIGURATION



TEST PROCEDURE

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

TEST RESULTS

U-NII-1-(5150MHz-5250MHz)					
Freq.(MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)
5180	5179.989	-0.011	-2.123552124	25	V _{min}
5180	5180.009	0.009	1.737451737	25	V _{max}
5180	5179.998	-0.002	-0.386100386	25	V _{nor}
5180	5179.993	-0.007	-1.351351351	-10	V _{nor}
5180	5179.995	-0.005	-0.965250965	40	V _{nor}

7.7 RADIATED UNDESIRABLE EMISSION

LIMIT

Radiated emissions from 9 kHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT was placed above the ground plane, 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

1. For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.



2. KDB789033 v01 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.
3. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

4. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration**Below 30MHz****Below 1 GHz**

Above 1 GHz**TEST PROCEDURE**

1. The EUT is placed on a turntable above ground plane, which is 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / Sweep=AUTO

VBW=10Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
IEEE 802.11 a	100	--	--	10Hz
IEEE 802.11n HT20	100	--	--	10Hz
IEEE 802.11n HT40	100			10Hz

7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS**Test Result of Radiated Emission****30MHz-1GHz**

Operation Mode:	Normal Link	Test Date:	2017-4-17
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	48% RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
44.5500	V	15.33	14.48	29.81	40.00	-10.19	peak
350.1000	V	11.89	18.50	30.39	46.00	-15.61	peak
425.7600	V	11.22	20.94	32.16	46.00	-13.84	peak
567.3800	V	10.82	22.66	33.48	46.00	-12.52	peak
709.0000	V	9.06	25.39	34.45	46.00	-11.55	peak
851.5900	V	8.66	25.93	34.59	46.00	-11.41	peak
<hr/>							
217.2100	H	14.25	16.40	30.65	46.00	-15.35	peak
250.1900	H	16.49	16.44	32.93	46.00	-13.07	peak
341.3700	H	18.23	18.15	36.38	46.00	-9.62	peak
345.2500	H	18.67	18.30	36.97	46.00	-9.03	peak
350.1000	H	19.80	18.50	38.30	46.00	-7.70	peak
375.3200	H	15.49	19.51	35.00	46.00	-11.00	peak

Remark:

1. Measuring frequencies from 30 MHz to the 1GHz.(no emission found from the lowest internal used/generated frequency to 30MHz)
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).

Note: Below 30MHz and above 18GHz. The measured value have enough margin over 20dB than the limit, therefore they are not reported.

Above 1 GHz**5150~5250MHz**

Operation Mode:	Tx / IEEE 802.11a mode CH Low	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10562.500	39.99	11.21	51.20	74.00	-22.80	100	133	peak
2	15343.750	37.10	12.25	49.35	74.00	-24.65	100	141	peak
N/A									

Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10358.173	42.32	10.19	52.51	74.00	-21.49	100	206	peak
2	14403.846	37.08	16.06	53.14	74.00	-20.86	100	299	peak
N/A									

Operation Mode:	Tx / IEEE 802.11a mode CH Mid	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10439.904	40.52	10.64	51.16	74.00	-22.84	100	103	peak
2	16692.308	34.78	17.24	52.02	74.00	-21.98	100	178	peak
N/A									

Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10439.904	41.55	10.64	52.19	74.00	-21.81	100	202	peak
2	14689.904	36.02	16.51	52.53	74.00	-21.47	100	360	peak
N/A									

Operation Mode:	Tx / IEEE 802.11a mode CH High	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10480.769	40.68	10.86	51.54	74.00	-22.46	100	169	peak
2	14649.039	35.03	16.53	51.56	74.00	-22.44	100	259	peak
N/A									

Vertical

No	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10480.769	42.00	10.86	52.86	74.00	-21.14	100	201	peak
2	16733.173	35.42	17.33	52.75	74.00	-21.25	100	332	peak
N/A									

5250~5350MHz

Operation Mode:	Tx / IEEE 802.11a mode CH Low	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10521.635	40.80	11.05	51.85	74.00	-22.15	100	140	peak
2	14649.039	35.61	16.53	52.14	74.00	-21.86	100	47	peak
N/A									

Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10644.231	39.11	11.53	50.64	74.00	-23.36	100	360	peak
2	15221.154	32.93	13.73	46.66	74.00	-27.34	100	299	peak
N/A									

Operation Mode:	Tx / IEEE 802.11a mode CH Mid	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10562.500	41.89	11.21	53.10	74.00	-20.90	100	125	peak
2	14240.385	34.57	15.17	49.74	74.00	-24.26	100	143	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11012.019	38.93	12.89	51.82	74.00	-22.18	100	228	peak
2	13259.615	38.02	14.10	52.12	74.00	-21.88	100	270	peak
N/A									

Operation Mode:	Tx / IEEE 802.11a mode CH High	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11012.019	38.07	12.89	50.96	74.00	-23.04	100	251	peak
2	16161.058	35.49	13.49	48.98	74.00	-25.02	100	236	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	12401.442	37.94	12.00	49.94	74.00	-24.06	100	163	peak
2	15466.346	35.17	10.77	45.94	74.00	-28.06	100	360	peak
N/A									

5150~5250MHz

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH Low	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10358.173	39.35	10.19	49.54	74.00	-24.46	100	241	peak
2	16447.115	34.54	16.30	50.84	74.00	-23.16	100	251	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10358.173	40.10	10.19	50.29	74.00	-23.71	100	195	peak
2	15875.000	33.26	11.52	44.78	74.00	-29.22	100	22	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH Mid	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	9540.865	39.71	7.64	47.35	74.00	-26.65	100	255	peak
2	13831.731	37.33	14.07	51.40	74.00	-22.60	100	192	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10807.692	39.39	12.17	51.56	74.00	-22.44	100	278	peak
2	12401.442	38.27	12.00	50.27	74.00	-23.73	100	143	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH High	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10603.365	38.90	11.37	50.27	74.00	-23.73	100	27	peak
2	14362.981	36.44	15.83	52.27	74.00	-21.73	100	297	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10725.961	38.87	11.85	50.72	74.00	-23.28	100	100	peak
2	13995.192	36.83	13.87	50.70	74.00	-23.30	100	35	peak
N/A									

5250~5350MHz

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH Low	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11134.615	39.76	12.54	52.30	74.00	-21.70	100	0	peak
2	13872.596	36.80	14.02	50.82	74.00	-23.18	100	174	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10971.154	38.14	12.81	50.95	74.00	-23.05	100	63	peak
2	13423.077	36.93	14.36	51.29	74.00	-22.71	100	112	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH Mid	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10562.500	40.86	11.21	52.07	74.00	-21.93	100	178	peak
2	16569.712	34.72	16.97	51.69	74.00	-22.31	100	342	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11216.346	38.68	12.31	50.99	74.00	-23.01	100	360	peak
2	13300.481	37.15	14.16	51.31	74.00	-22.69	100	88	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH High	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10480.769	39.82	10.86	50.68	74.00	-23.32	100	345	peak
2	14689.904	34.23	16.51	50.74	74.00	-23.26	100	0	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10848.558	39.04	12.33	51.37	74.00	-22.63	100	215	peak
2	16937.500	33.93	17.77	51.70	74.00	-22.30	100	328	peak
N/A									

5150~5250MHz

Operation Mode:	TX / IEEE 802.11n HT40 mode /CH Low	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10480.769	42.02	10.86	52.88	74.00	-21.12	100	140	peak
2	15343.750	38.12	12.25	50.37	74.00	-23.63	100	153	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10562.500	40.98	11.21	52.19	74.00	-21.81	100	237	peak
2	15343.750	37.37	12.25	49.62	74.00	-24.38	100	72	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT40 mode /CH High	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	9213.942	42.78	7.23	50.01	74.00	-23.99	100	254	peak
2	14649.039	37.11	16.53	53.64	74.00	-20.36	100	79	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	9009.615	42.38	6.97	49.35	74.00	-24.65	100	160	peak
2	14689.904	36.21	16.51	52.72	74.00	-21.28	100	31	peak
N/A									

5250~5350MHz

Operation Mode:	TX / IEEE 802.11n HT40 mode /CH Low	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11257.211	38.75	12.19	50.94	74.00	-23.06	100	313	peak
2	14649.039	34.81	16.53	51.34	74.00	-22.66	100	235	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11134.615	40.51	12.54	53.05	74.00	-20.95	100	77	peak
2	13872.596	37.28	14.02	51.30	74.00	-22.70	100	245	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT40 mode /CH High	Test Date:	2017-4-19
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11216.346	39.37	12.31	51.68	74.00	-22.32	100	322	peak
2	17141.827	33.06	18.68	51.74	74.00	-22.26	100	112	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11093.750	38.94	12.66	51.60	74.00	-22.40	100	245	peak
2	13300.481	37.36	14.16	51.52	74.00	-22.48	100	216	peak
N/A									

7.8 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE


1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data


Job No.:	C170307R01	Date:	2017-4-21
Model No.:	SXJ01ZM	Time:	10:57:03
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 120V/60Hz
Model:		Description:	



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1702	21.03	5.05	20.56	41.59	25.61	64.95	54.95	-23.36	-29.34	Pass
2	0.4208	15.00	3.27	20.52	35.52	23.79	57.43	47.43	-21.91	-23.64	Pass
3*	0.4953	19.47	8.89	20.49	39.96	29.38	56.08	46.08	-16.12	-16.70	Pass
4	0.7182	6.17	-1.08	20.50	26.67	19.42	56.00	46.00	-29.33	-26.58	Pass
5	0.9294	8.79	-0.53	20.51	29.30	19.98	56.00	46.00	-26.70	-26.02	Pass
6	6.2164	5.74	-3.06	20.68	26.42	17.62	60.00	50.00	-33.58	-32.38	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Job No.:	C170307R01	Date:	2017-4-21
Model No.:	SXJ01ZM	Time:	11:02:35
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 120V/60Hz
Model:		Description:	



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1763	21.05	7.28	20.38	41.43	27.66	64.65	54.66	-23.22	-27.00	Pass
2	0.3957	13.70	5.92	20.46	34.16	26.38	57.94	47.94	-23.78	-21.56	Pass
3*	0.4968	19.06	13.30	20.45	39.51	33.75	56.05	46.05	-16.54	-12.30	Pass
4	0.8989	6.42	-0.61	20.47	26.89	19.86	56.00	46.00	-29.11	-26.14	Pass
5	1.7680	2.80	-2.46	20.51	23.31	18.05	56.00	46.00	-32.69	-27.95	Pass
6	5.9095	4.18	-2.00	20.77	24.95	18.77	60.00	50.00	-35.05	-31.23	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Job No.:	C170307R01	Date:	2017-4-21
Model No.:	SXJ01ZM	Time:	10:43:32
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 240V/60Hz
Model:		Description:	



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1517	24.30	8.64	20.36	44.66	29.00	65.90	55.91	-21.24	-26.91	Pass
2	0.2427	18.07	4.11	20.43	38.50	24.54	62.00	52.00	-23.50	-27.46	Pass
3*	0.4998	19.40	8.10	20.45	39.85	28.55	56.00	46.00	-16.15	-17.45	Pass
4	0.8252	12.20	1.49	20.46	32.66	21.95	56.00	46.00	-23.34	-24.05	Pass
5	0.9205	12.63	1.62	20.47	33.10	22.09	56.00	46.00	-22.90	-23.91	Pass
6	7.1467	8.95	-1.90	20.81	29.76	18.91	60.00	50.00	-30.24	-31.09	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Job No.:	C170307R01	Date:	2017-4-21
Model No.:	SXJ01ZM	Time:	10:48:41
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 240V/60Hz
Model:		Description:	



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.1533	23.63	8.86	20.36	43.99	29.22	65.81	55.82	-21.82	-26.60	Pass
2	0.1977	18.96	4.65	20.40	39.36	25.05	63.70	53.71	-24.34	-28.66	Pass
3	0.5093	13.48	2.81	20.45	33.93	23.26	56.00	46.00	-22.07	-22.74	Pass
4	0.8040	12.86	5.60	20.46	33.32	26.06	56.00	46.00	-22.68	-19.94	Pass
5*	0.9182	14.36	6.37	20.47	34.83	26.84	56.00	46.00	-21.17	-19.16	Pass
6	6.9443	7.64	0.15	20.80	28.44	20.95	60.00	50.00	-31.56	-29.05	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Remark:

- 1.The measuring frequencies range between 0.15 MHz and 30 MHz.
- 2.The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
- 3.“---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
- 4.The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

END OF REPORT