

**C2-1. Radiated Spurious Emission Test Modes**

<Sample 2>

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 70	U-NII-4	5.85-5.895	1	802.11ax HE80	171	5855	MCS0	Full RU	-
Mode 71	U-NII-4	5.85-5.895	1	802.11ax HE80	171	5855	MCS0	Full RU	LF

C2-2. Summary of each worse mode

<Sample 2>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
70	802.11ax HE80	171	5626.26	64.99	68.20	-3.21	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE80	171	17565.00	53.24	68.20	-14.96	V	Peak	Pass	Full RU	Harmonic
71	LF	171	51.34	33.01	40.00	-6.99	V	Peak	Pass	-	LF



<Sample 2>

Mode	70																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																																										
ANT	1																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: PEAK_BE(UNII 4) 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5648.71</td><td>61.90</td><td>68.20</td><td>-6.30</td><td>46.84</td><td>33.16</td><td>11.69</td><td>29.79</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr><tr><td>2</td><td>5650.45</td><td>57.98</td><td>68.53</td><td>-10.55</td><td>42.88</td><td>33.20</td><td>11.70</td><td>29.80</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr><tr><td>3</td><td>5700.30</td><td>66.17</td><td>105.28</td><td>-39.11</td><td>50.64</td><td>33.60</td><td>11.76</td><td>29.83</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr><tr><td>4</td><td>5720.07</td><td>62.69</td><td>110.95</td><td>-48.26</td><td>47.07</td><td>33.68</td><td>11.78</td><td>29.84</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5648.71	61.90	68.20	-6.30	46.84	33.16	11.69	29.79	0.00	289	23	Peak	2	5650.45	57.98	68.53	-10.55	42.88	33.20	11.70	29.80	0.00	289	23	Peak	3	5700.30	66.17	105.28	-39.11	50.64	33.60	11.76	29.83	0.00	289	23	Peak	4	5720.07	62.69	110.95	-48.26	47.07	33.68	11.78	29.84	0.00	289	23	Peak	Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: PEAK(UNII 4) 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5855.00</td><td>101.81</td><td>-----</td><td>-----</td><td>85.61</td><td>34.21</td><td>11.91</td><td>29.92</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	101.81	-----	-----	85.61	34.21	11.91	29.92	0.00	289	23	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5648.71	61.90	68.20	-6.30	46.84	33.16	11.69	29.79	0.00	289	23	Peak																																																																																																																															
2	5650.45	57.98	68.53	-10.55	42.88	33.20	11.70	29.80	0.00	289	23	Peak																																																																																																																															
3	5700.30	66.17	105.28	-39.11	50.64	33.60	11.76	29.83	0.00	289	23	Peak																																																																																																																															
4	5720.07	62.69	110.95	-48.26	47.07	33.68	11.78	29.84	0.00	289	23	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5855.00	101.81	-----	-----	85.61	34.21	11.91	29.92	0.00	289	23	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: AVG(UNII 4) 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5855.00</td><td>94.05</td><td>-----</td><td>-----</td><td>77.82</td><td>34.23</td><td>11.92</td><td>29.92</td><td>0.00</td><td>289</td><td>23</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	94.05	-----	-----	77.82	34.23	11.92	29.92	0.00	289	23	Average																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5855.00	94.05	-----	-----	77.82	34.23	11.92	29.92	0.00	289	23	Average																																																																																																																															



Mode	70																																																					
	Band Edge - R																																																					
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																					
ANT	1																																																					
Pol.	Horizontal	Fundamental																																																				
Peak	Level (dBuV/m) Date: 2025-06-05 PEAK_BE(UNII 4) Site : 03CH16-HY Condition: PEAK_BE(UNII 4) 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5923.25</td><td>73.93</td><td>89.48</td><td>-15.55</td><td>57.63</td><td>34.30</td><td>11.96</td><td>29.96</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr><tr><td>2</td><td>5942.25</td><td>74.23</td><td>88.20</td><td>-13.97</td><td>57.92</td><td>34.30</td><td>11.98</td><td>29.97</td><td>0.00</td><td>289</td><td>23</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5923.25	73.93	89.48	-15.55	57.63	34.30	11.96	29.96	0.00	289	23	Peak	2	5942.25	74.23	88.20	-13.97	57.92	34.30	11.98	29.97	0.00	289	23	Peak	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	5923.25	73.93	89.48	-15.55	57.63	34.30	11.96	29.96	0.00	289	23	Peak																																										
2	5942.25	74.23	88.20	-13.97	57.92	34.30	11.98	29.97	0.00	289	23	Peak																																										
Avg	Level (dBuV/m) Date: 2025-06-05 AVG_BE(UNII 4) Site : 03CH16-HY Condition: AVG_BE(UNII 4) 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3.600kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5895.25</td><td>68.57</td><td>90.02</td><td>-21.45</td><td>52.28</td><td>34.29</td><td>11.94</td><td>29.94</td><td>0.00</td><td>289</td><td>23</td><td>Average</td></tr><tr><td>2</td><td>5926.00</td><td>62.96</td><td>68.20</td><td>-5.24</td><td>46.65</td><td>34.30</td><td>11.97</td><td>29.96</td><td>0.00</td><td>289</td><td>23</td><td>Average</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5895.25	68.57	90.02	-21.45	52.28	34.29	11.94	29.94	0.00	289	23	Average	2	5926.00	62.96	68.20	-5.24	46.65	34.30	11.97	29.96	0.00	289	23	Average	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	5895.25	68.57	90.02	-21.45	52.28	34.29	11.94	29.94	0.00	289	23	Average																																										
2	5926.00	62.96	68.20	-5.24	46.65	34.30	11.97	29.96	0.00	289	23	Average																																										



Mode	70																																																																																																																							
	Band Edge - L																																																																																																																							
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																							
ANT	1																																																																																																																							
Pol.	Vertical					Fundamental																																																																																																																		
Peak	Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: PEAK_BE(UNII 4) 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5626.26</td><td>64.99</td><td>68.20</td><td>-3.21</td><td>49.98</td><td>33.11</td><td>11.68</td><td>29.78</td><td>0.00</td><td>300 12 Peak</td></tr><tr><td>2 5651.33</td><td>61.07</td><td>69.19</td><td>-8.12</td><td>45.96</td><td>33.21</td><td>11.70</td><td>29.80</td><td>0.00</td><td>300 12 Peak</td></tr><tr><td>3 5700.30</td><td>68.53</td><td>105.28</td><td>-36.75</td><td>53.00</td><td>33.60</td><td>11.76</td><td>29.83</td><td>0.00</td><td>300 12 Peak</td></tr><tr><td>4 5720.66</td><td>66.85</td><td>112.29</td><td>-45.44</td><td>51.23</td><td>33.68</td><td>11.78</td><td>29.84</td><td>0.00</td><td>300 12 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5626.26	64.99	68.20	-3.21	49.98	33.11	11.68	29.78	0.00	300 12 Peak	2 5651.33	61.07	69.19	-8.12	45.96	33.21	11.70	29.80	0.00	300 12 Peak	3 5700.30	68.53	105.28	-36.75	53.00	33.60	11.76	29.83	0.00	300 12 Peak	4 5720.66	66.85	112.29	-45.44	51.23	33.68	11.78	29.84	0.00	300 12 Peak	Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: PEAK(UNII 4) 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5855.00</td><td>104.72</td><td>-----</td><td>88.54</td><td>34.19</td><td>11.90</td><td>29.91</td><td>0.00</td><td>300</td><td>12 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5855.00	104.72	-----	88.54	34.19	11.90	29.91	0.00	300	12 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5626.26	64.99	68.20	-3.21	49.98	33.11	11.68	29.78	0.00	300 12 Peak																																																																																																															
2 5651.33	61.07	69.19	-8.12	45.96	33.21	11.70	29.80	0.00	300 12 Peak																																																																																																															
3 5700.30	68.53	105.28	-36.75	53.00	33.60	11.76	29.83	0.00	300 12 Peak																																																																																																															
4 5720.66	66.85	112.29	-45.44	51.23	33.68	11.78	29.84	0.00	300 12 Peak																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5855.00	104.72	-----	88.54	34.19	11.90	29.91	0.00	300	12 Peak																																																																																																															
Avg	Blank					Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: AVG(UNII 4) 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5855.00</td><td>95.05</td><td>-----</td><td>78.82</td><td>34.23</td><td>11.92</td><td>29.92</td><td>0.00</td><td>300</td><td>12 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5855.00	95.05	-----	78.82	34.23	11.92	29.92	0.00	300	12 Average																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5855.00	95.05	-----	78.82	34.23	11.92	29.92	0.00	300	12 Average																																																																																																															



Mode	70																																																																																																																							
	Harmonic																																																																																																																							
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																							
ANT	1																																																																																																																							
Pol.	Horizontal								Vertical																																																																																																															
Peak Avg	Level (dBuV/m) Date: 2025-06-05 1000800016600244003220040000 Frequency (MHz) Site : 03CH16-HY Condition: PEAK(UNII) 3m 91200-1522_250327 HORIZONTAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>11710.00</td><td>47.58</td><td>74.00</td><td>-26.42</td><td>57.26</td><td>38.62</td><td>16.92</td><td>65.79</td><td>0.57</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17565.00</td><td>52.79</td><td>68.20</td><td>-15.41</td><td>54.84</td><td>39.52</td><td>21.44</td><td>63.63</td><td>0.62</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>									Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11710.00	47.58	74.00	-26.42	57.26	38.62	16.92	65.79	0.57	--	--	Peak	2	17565.00	52.79	68.20	-15.41	54.84	39.52	21.44	63.63	0.62	--	--	Peak	Level (dBuV/m) Date: 2025-06-05 1000800016600244003220040000 Frequency (MHz) Site : 03CH16-HY Condition: PEAK(UNII) 3m 91200-1522_250327 VERTICAL <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>11710.00</td><td>47.76</td><td>74.00</td><td>-26.24</td><td>57.40</td><td>38.66</td><td>16.94</td><td>65.80</td><td>0.56</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17565.00</td><td>53.24</td><td>68.20</td><td>-14.96</td><td>55.36</td><td>39.49</td><td>21.42</td><td>63.65</td><td>0.62</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>									Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11710.00	47.76	74.00	-26.24	57.40	38.66	16.94	65.80	0.56	--	--	Peak	2	17565.00	53.24	68.20	-14.96	55.36	39.49	21.42	63.65	0.62	--	--	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																																											
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																												
1	11710.00	47.58	74.00	-26.42	57.26	38.62	16.92	65.79	0.57	--	--	Peak																																																																																																												
2	17565.00	52.79	68.20	-15.41	54.84	39.52	21.44	63.63	0.62	--	--	Peak																																																																																																												
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																													
1	11710.00	47.76	74.00	-26.24	57.40	38.66	16.94	65.80	0.56	--	--	Peak																																																																																																												
2	17565.00	53.24	68.20	-14.96	55.36	39.49	21.42	63.65	0.62	--	--	Peak																																																																																																												




Mode	71																																																																																																																																																																																					
	LF																																																																																																																																																																																					
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																																																																																					
ANT	1																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																				
QP/ Peak	Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06_241005 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>84.32</td><td>32.30</td><td>40.00</td><td>-7.70</td><td>49.21</td><td>14.15</td><td>1.44</td><td>32.57</td><td>0.07 196 54 QP</td></tr><tr><td>2</td><td>94.02</td><td>37.30</td><td>43.50</td><td>-6.20</td><td>52.96</td><td>15.33</td><td>1.50</td><td>32.56</td><td>0.07 -- -- Peak</td></tr><tr><td>3</td><td>216.24</td><td>33.62</td><td>46.00</td><td>-12.38</td><td>48.62</td><td>15.19</td><td>2.28</td><td>32.54</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>508.21</td><td>28.49</td><td>46.00</td><td>-17.51</td><td>33.88</td><td>23.88</td><td>3.49</td><td>32.91</td><td>0.15 -- -- Peak</td></tr><tr><td>5</td><td>752.65</td><td>30.05</td><td>46.00</td><td>-15.95</td><td>29.35</td><td>28.37</td><td>4.27</td><td>32.08</td><td>0.14 -- -- Peak</td></tr><tr><td>6</td><td>942.77</td><td>32.71</td><td>46.00</td><td>-13.29</td><td>28.67</td><td>30.83</td><td>4.79</td><td>31.83</td><td>0.25 -- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	84.32	32.30	40.00	-7.70	49.21	14.15	1.44	32.57	0.07 196 54 QP	2	94.02	37.30	43.50	-6.20	52.96	15.33	1.50	32.56	0.07 -- -- Peak	3	216.24	33.62	46.00	-12.38	48.62	15.19	2.28	32.54	0.07 -- -- Peak	4	508.21	28.49	46.00	-17.51	33.88	23.88	3.49	32.91	0.15 -- -- Peak	5	752.65	30.05	46.00	-15.95	29.35	28.37	4.27	32.08	0.14 -- -- Peak	6	942.77	32.71	46.00	-13.29	28.67	30.83	4.79	31.83	0.25 -- -- Peak	Level (dBuV/m) Date: 2025-06-05 Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06_241005 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>51.34</td><td>33.01</td><td>40.00</td><td>-6.99</td><td>50.26</td><td>13.96</td><td>1.12</td><td>32.38</td><td>0.05 -- -- Peak</td></tr><tr><td>2</td><td>93.05</td><td>32.74</td><td>43.50</td><td>-10.76</td><td>48.58</td><td>15.16</td><td>1.50</td><td>32.57</td><td>0.07 -- -- Peak</td></tr><tr><td>3</td><td>216.24</td><td>31.15</td><td>46.00</td><td>-14.85</td><td>46.15</td><td>15.19</td><td>2.28</td><td>32.54</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>490.75</td><td>27.47</td><td>46.00</td><td>-18.53</td><td>33.09</td><td>23.61</td><td>3.43</td><td>32.81</td><td>0.15 -- -- Peak</td></tr><tr><td>5</td><td>741.01</td><td>29.88</td><td>46.00</td><td>-16.12</td><td>29.29</td><td>28.31</td><td>4.23</td><td>32.09</td><td>0.14 -- -- Peak</td></tr><tr><td>6</td><td>942.77</td><td>32.46</td><td>46.00</td><td>-13.54</td><td>28.42</td><td>30.83</td><td>4.79</td><td>31.83</td><td>0.25 -- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	51.34	33.01	40.00	-6.99	50.26	13.96	1.12	32.38	0.05 -- -- Peak	2	93.05	32.74	43.50	-10.76	48.58	15.16	1.50	32.57	0.07 -- -- Peak	3	216.24	31.15	46.00	-14.85	46.15	15.19	2.28	32.54	0.07 -- -- Peak	4	490.75	27.47	46.00	-18.53	33.09	23.61	3.43	32.81	0.15 -- -- Peak	5	741.01	29.88	46.00	-16.12	29.29	28.31	4.23	32.09	0.14 -- -- Peak	6	942.77	32.46	46.00	-13.54	28.42	30.83	4.79	31.83	0.25 -- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																												
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	84.32	32.30	40.00	-7.70	49.21	14.15	1.44	32.57	0.07 196 54 QP																																																																																																																																																																													
2	94.02	37.30	43.50	-6.20	52.96	15.33	1.50	32.56	0.07 -- -- Peak																																																																																																																																																																													
3	216.24	33.62	46.00	-12.38	48.62	15.19	2.28	32.54	0.07 -- -- Peak																																																																																																																																																																													
4	508.21	28.49	46.00	-17.51	33.88	23.88	3.49	32.91	0.15 -- -- Peak																																																																																																																																																																													
5	752.65	30.05	46.00	-15.95	29.35	28.37	4.27	32.08	0.14 -- -- Peak																																																																																																																																																																													
6	942.77	32.71	46.00	-13.29	28.67	30.83	4.79	31.83	0.25 -- -- Peak																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	51.34	33.01	40.00	-6.99	50.26	13.96	1.12	32.38	0.05 -- -- Peak																																																																																																																																																																													
2	93.05	32.74	43.50	-10.76	48.58	15.16	1.50	32.57	0.07 -- -- Peak																																																																																																																																																																													
3	216.24	31.15	46.00	-14.85	46.15	15.19	2.28	32.54	0.07 -- -- Peak																																																																																																																																																																													
4	490.75	27.47	46.00	-18.53	33.09	23.61	3.43	32.81	0.15 -- -- Peak																																																																																																																																																																													
5	741.01	29.88	46.00	-16.12	29.29	28.31	4.23	32.09	0.14 -- -- Peak																																																																																																																																																																													
6	942.77	32.46	46.00	-13.54	28.42	30.83	4.79	31.83	0.25 -- -- Peak																																																																																																																																																																													



Appendix D. Duty Cycle Plots


<Sample 1>

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
802.11a	98.92	-	-	10Hz
5GHz 802.11ac VHT80	95.13	332	3.01	3.6kHz
5GHz 802.11ax HE20 Full RU	98.58	-	-	10Hz
5GHz 802.11ax HE20 106 RU	95.44	1360	0.74	750Hz
5GHz 802.11ax HE40 Full RU	97.53	552	1.81	2kHz
5GHz 802.11ax HE80 Full RU	94.50	292	3.42	3.6kHz







5GHz 802.11ax HE20 Full RU




5GHz 802.11ax HE20 106 RU



5GHz 802.11ax HE40 Full RU



5GHz 802.11ax HE80 Full RU





<Sample 2>

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
5GHz 802.11ax HE80	94.50	292	3.42	10KHz

