

Statement of compliance to Maximum Permissible Exposure (MPE)

Applicant : WANG XING DA (FENGSHUN) ELECRTRONICS CO., LTD.

Wang Xing Da Technology Park, Tongpan Village, Tangkeng town, Fengshun County, Meizhou City, Guangdong Province, China

Manufacturer : Same as applicant

Product Name : TROLLY SPEAKER

Type/Model : K18

TEST RESULT : PASS

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The $S = PG / (4\pi R^2)$

Where S = power density in mW/cm^2

P = transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

For bluetooth, as we can see from the test report 170800863SHA-001

Frequency band (MHz)	Max power		Antenna Gain		R	S
2400-2483.5MHz	-14.6	0.03	0.5	1.12	20	0.000008

The sum of the MPE ratios = 0.000008 mW/cm^2

This level is below the simultaneous transmission MPE test exclusion requirements (≤ 1.0).

Date of issue: Jan 23, 2018

Prepared by:



Eric Li (Project Engineer)

Reviewed by:



Daniel Zhao (Reviewer)

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.