

TEST REPORT

Applicant: Shenzhen Jimi IoT Co., Ltd.
Address: 3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China
Equipment Type: 4G Mini Dashcam
Model Name: JC182 (refer to section 2.3)
Brand Name: Jimi IoT
FCC ID: 2AMLF-JC182NA
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Apr. 29, 2025
Test Date: Apr. 30, 2025
Date of Issue: May. 28, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: LI JunFeng**Checked by: Liu Zhen Xiang****Approved by: Tolan Tu**

(Technical Director)



Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>May. 28, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	General Description for Equipment under Test (EUT).....	4
2.4	Ancillary Equipment.....	4
2.5	Technical Information	4
3	SUMMARY OF TEST RESULTS	5
3.1	Test Standards	5
3.2	Verdict	5
3.3	Test Uncertainty	5
4	GENERAL TEST CONFIGURATIONS	6
4.1	Test Enclosure List.....	6
4.2	Test Configurations	6
4.3	Test Setups	7
5	TEST ITEMS	9
5.1	Emission Tests	9
ANNEX A	TEST RESULTS.....	14
A.1	Radiated Emission.....	14
A.2	Conducted Emission, AC Ports.....	21
ANNEX B	TEST SETUP PHOTOS	22
ANNEX C	EUT EXTERNAL PHOTOS.....	22

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China ☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	4G Mini Dashcam
Model Name Under Test	JC182
Series Model Name	JC182-NA, JC182S, JC182P, TripVue, R42, LN-R42
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the customer)
Hardware Version	C182_MB_V1.2_0125
Software Version	C182_0_3_STD_JM_JC182_V1.2.0.4_250414.1100
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Power Supply Cable	
	Model No.	N/A
	Length (Approx.)	> 3m

2.5 Technical Information

Network and Wireless connectivity	4G Network LTE FDD Band 2/4/5/7/12/14/17/25/26/66 LTE TDD Band 41 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) GPS, BDS, AGPS
Classification of equipment	Class B

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	N/A	Note1
Note1: The EUT has no AC Port, so this test item is not applicable.				

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Vehicle battery	CAMEL	6-QWLZ-45(370)	N/A	N/A	N/A	☒
TF Card	SAMSUNG	MB-MD256KA	N/A	N/A	256G	☒

4.2 Test Configurations

All test modes of EUT are listed in the table below.


Test Mode Configuration	Description
Mode 1	<u>The Standby Test Mode</u> EUT + Power supply line + Vehicle battery + TF Card
Mode 2	<u>The Video Test Mode</u> EUT + Power supply line + Vehicle battery + TF Card
Mode 3	<u>The Speaker Work Test Mode</u> EUT + Power supply line + Vehicle battery + TF Card

Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 3	2


Note: All operation modes were tested, but only test data of the worst mode was presented in this report.

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60
NOTE:			
1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.			
2) In the emission tables above, the tighter limit applies at the band edges.			
3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.			

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80
Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.					
Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:					
$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$					
Where:					
L_{3m} is Average Class A limit at 3m;					
L_{10m} is Average Class A limit at 10m;					
d_{10m} is Measurement distance in 10m;					
d_{3m} is Measurement distance in 3m.					
For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).					

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission


Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Sample No.	S01	Temperature	22.2℃
Humidity	45%RH	Pressure	101kPa
Test Engineer	Chen Jingran	Test Date	2025.04.30


Test Mode 2

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	72.777	20.98	-29.76	40.0	19.02	Peak	263.00	100	Vertical	Pass
2	105.854	18.58	-26.71	43.5	24.92	Peak	306.00	100	Vertical	Pass
3	152.850	24.30	-29.93	43.5	19.20	Peak	284.00	100	Vertical	Pass
4	211.439	23.64	-26.59	43.5	19.86	Peak	302.00	100	Vertical	Pass
5	236.319	25.92	-25.27	46.0	20.08	Peak	129.00	100	Vertical	Pass
6	960.958	29.95	-9.08	54.0	24.05	Peak	331.00	100	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	47.993	11.90	-24.90	40.0	28.10	Peak	101.00	100	Horizontal	Pass
2	113.614	10.97	-27.17	43.5	32.53	Peak	240.00	100	Horizontal	Pass
3	263.479	14.63	-24.65	46.0	31.37	Peak	162.00	100	Horizontal	Pass
4	481.293	21.41	-19.23	46.0	24.59	Peak	341.00	100	Horizontal	Pass
5	735.190	26.16	-13.19	46.0	19.84	Peak	158.00	100	Horizontal	Pass
6	923.758	28.47	-9.78	46.0	17.53	Peak	321.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	00883	2025.03.23	2028.03.22	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

3) Test Antenna Vertical, 1 GHz – 14 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1317.460	38.51	-15.53	74.0	35.49	Peak	337.00	100	Vertical	Pass
1**	1317.460	29.15	-15.53	54.0	24.85	AV	337.00	100	Vertical	Pass
2	2174.290	41.01	-12.06	74.0	32.99	Peak	115.00	100	Vertical	Pass
2**	2174.290	31.39	-12.06	54.0	22.61	AV	115.00	100	Vertical	Pass
3	3591.550	45.47	-5.09	74.0	28.53	Peak	2.00	100	Vertical	Pass
3**	3591.550	36.45	-5.09	54.0	17.55	AV	2.00	100	Vertical	Pass
4	6318.540	51.22	-0.16	74.0	22.78	Peak	71.00	100	Vertical	Pass
4**	6318.540	40.86	-0.16	54.0	13.14	AV	71.00	100	Vertical	Pass
5	9325.100	52.40	2.17	74.0	21.60	Peak	207.00	100	Vertical	Pass
5**	9325.100	43.87	2.17	54.0	10.13	AV	207.00	100	Vertical	Pass
6	13653.500	54.73	5.03	74.0	19.27	Peak	234.00	100	Vertical	Pass
6**	13653.500	45.71	5.03	54.0	8.29	AV	234.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 14GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1052.650	37.26	-15.82	74.0	36.74	Peak	220.00	100	Horizontal	Pass
1**	1052.650	28.26	-15.82	54.0	25.74	AV	220.00	100	Horizontal	Pass
2	1993.460	40.16	-13.50	74.0	33.84	Peak	101.00	100	Horizontal	Pass
2**	1993.460	31.43	-13.50	54.0	22.57	AV	101.00	100	Horizontal	Pass
3	3596.880	46.32	-5.07	74.0	27.68	Peak	250.00	100	Horizontal	Pass
3**	3596.880	35.31	-5.07	54.0	18.69	AV	250.00	100	Horizontal	Pass
4	5899.880	52.81	2.13	74.0	21.19	Peak	250.00	100	Horizontal	Pass
4**	5899.880	43.32	2.13	54.0	10.68	AV	250.00	100	Horizontal	Pass
5	7989.660	52.58	0.83	74.0	21.42	Peak	117.00	100	Horizontal	Pass
5**	7989.660	42.27	0.83	54.0	11.73	AV	117.00	100	Horizontal	Pass
6	13348.400	55.09	5.18	74.0	18.91	Peak	360.00	100	Horizontal	Pass
6**	13348.400	46.29	5.18	54.0	7.71	AV	360.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.2 Conducted Emission, AC Ports

Note: Not applicable.

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2541550-AE-1.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2541550-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2541550-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--