

TEST REPORT

Applicant: Shenzhen Jimi IoT Co., Ltd.
Address: 3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China
Equipment Type: 4G AI Dashcam
Model Name: JC371 (refer to section 2.3)
Brand Name: Jimi IoT
FCC ID 2AMLF-JC371NA
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Feb. 07, 2025
Test Date: Feb. 18, 2025
Date of Issue: Apr. 10, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Qiu Yongjing **Checked by:** Liu Zhenxiang **Approved by:** Tolan Tu
(Testing Director)



Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Apr. 10, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1 GENERAL INFORMATION	3
1.1 Test Laboratory	3
1.2 Test Location.....	3
2 PRODUCT INFORMATION	4
2.1 Applicant Information.....	4
2.2 Manufacturer Information	4
2.3 General Description for Equipment under Test (EUT).....	4
2.4 Ancillary Equipment.....	4
2.5 Technical Information	5
3 SUMMARY OF TEST RESULTS	6
3.1 Test Standards.....	6
3.2 Verdict.....	6
3.3 Test Uncertainty	6
4 GENERAL TEST CONFIGURATIONS.....	7
4.1 Test Enclosure List.....	7
4.2 Test Configurations	7
4.3 Test Setups	8
5 TEST ITEMS.....	10
5.1 Emission Tests.....	10
ANNEX A TEST RESULTS.....	15
A.1 Radiated Emission	15
A.2 Conducted Emission, AC Ports	28
ANNEX B TEST SETUP PHOTOS	29
ANNEX C EUT EXTERNAL PHOTOS	29

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	4G AI Dashcam
Model Name Under Test	JC371
Series Model Name	JC371-NA, JC371S, JC371C, JC371PLUS, JC371PRO, JC371LITE, R47
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	C371_MB_V1.3
Software Version	C371_0_0_STD_JM_JC371_V1.2.8a
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Note: Not applicable.

2.5 Technical Information

Network and Wireless connectivity	3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/12/13/14/66/71 WIFI 802.11b, 802.11g, 802.11n(HT20) GPS, BDS, AGPS
Classification of equipment	Class B
The highest internal frequency of EUT	2472MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	N/A	--
Note 1: The EUT has no AC Port, so this test item is not applicable.				

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Camera	N/A	N/A	N/A	N/A	N/A	☒
Vehicle battery	CAMEL	6-QWLZ-45(370)	N/A	N/A	N/A	☒
TF Card	Samsung	N/A	N/A	N/A	256G	☒
Laptop	Lenovo	N/A	N/A	N/A	N/A	☒
USB Cable	N/A	N/A	N/A	N/A	N/A	☒

4.2 Test Configurations


All test modes of EUT are listed in the table below.

Test Mode Configuration	Description
Mode 1	<u>The Standby Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 2	<u>The Camera Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 3	<u>The SOS key Work Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 4	<u>The Speaker Work Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 5	<u>The USB Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card + Laptop + USB Cable


Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 5	4, 5
Note: All operation modes were tested, but only test data of the worst mode was presented in this report.		

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$

Where:

L_{3m} is Average Class A limit at 3m;

L_{10m} is Average Class A limit at 10m;

d_{10m} is Measurement distance in 10m;

d_{3m} is Measurement distance in 3m.

For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of “--” in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report.

Sample No.	S03	Temperature	22.7℃
Humidity	39%RH	Pressure	101kPa
Test Engineer	He Shichang	Test Date	2025.02.18


Test Mode 4

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	50.419	32.25	-25.50	40.0	7.75	Peak	67.00	100	Vertical	Pass
2	88.830	27.82	-29.05	43.5	15.68	Peak	264.00	100	Vertical	Pass
3	107.309	31.02	-26.48	43.5	12.48	Peak	107.00	100	Vertical	Pass
4	136.264	31.01	-29.99	43.5	12.49	Peak	63.00	100	Vertical	Pass
5	146.352	30.26	-30.30	43.5	13.24	Peak	330.00	100	Vertical	Pass
6	179.720	28.34	-28.18	43.5	15.16	Peak	107.00	100	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	53.910	19.97	-25.17	40.0	20.03	Peak	71.00	100	Horizontal	Pass
2	136.846	23.71	-30.22	43.5	19.79	Peak	6.00	200	Horizontal	Pass
3	146.642	24.20	-30.29	43.5	19.30	Peak	303.00	200	Horizontal	Pass
4	165.994	23.92	-29.09	43.5	19.58	Peak	6.00	200	Horizontal	Pass
5	296.992	25.58	-23.54	46.0	20.42	Peak	22.00	200	Horizontal	Pass
6	396.030	25.77	-21.05	46.0	20.23	Peak	146.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00867	2022.04.12	2025.04.11	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

3) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1423.930	39.21	-15.59	74.0	34.79	Peak	352.00	100	Vertical	Pass
1**	1423.930	30.09	-15.59	54.0	23.91	AV	352.00	100	Vertical	Pass
2	3161.250	47.38	-6.37	74.0	26.62	Peak	360.00	100	Vertical	Pass
2**	3161.250	36.60	-6.37	54.0	17.40	AV	360.00	100	Vertical	Pass
3	4995.020	53.51	0.59	74.0	20.49	Peak	26.00	100	Vertical	Pass
3**	4995.020	42.55	0.59	54.0	11.45	AV	26.00	100	Vertical	Pass
4	5895.920	54.45	2.19	74.0	19.55	Peak	188.00	100	Vertical	Pass
4**	5895.920	43.36	2.19	54.0	10.64	AV	188.00	100	Vertical	Pass
5	7780.880	53.81	0.43	74.0	20.19	Peak	244.00	100	Vertical	Pass
5**	7780.880	43.75	0.43	54.0	10.25	AV	244.00	100	Vertical	Pass
6	13147.000	56.28	4.25	74.0	17.72	Peak	169.00	100	Vertical	Pass
6**	13147.000	46.05	4.25	54.0	7.95	AV	169.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1592.020	39.80	-15.64	74.0	34.20	Peak	123.00	100	Horizontal	Pass
1**	1592.020	29.79	-15.64	54.0	24.21	AV	123.00	100	Horizontal	Pass
2	2132.170	43.09	-12.61	74.0	30.91	Peak	36.00	100	Horizontal	Pass
2**	2132.170	32.84	-12.61	54.0	21.16	AV	36.00	100	Horizontal	Pass
3	3149.810	47.22	-6.62	74.0	26.78	Peak	74.00	100	Horizontal	Pass
3**	3149.810	38.02	-6.62	54.0	15.98	AV	74.00	100	Horizontal	Pass
4	5882.280	53.85	2.40	74.0	20.15	Peak	75.00	100	Horizontal	Pass
4**	5882.280	43.98	2.40	54.0	10.02	AV	75.00	100	Horizontal	Pass
5	7323.060	53.95	-0.43	74.0	20.05	Peak	198.00	100	Horizontal	Pass
5**	7323.060	43.38	-0.43	54.0	10.62	AV	198.00	100	Horizontal	Pass
6	13806.000	56.97	5.74	74.0	17.03	Peak	79.00	100	Horizontal	Pass
6**	13806.000	47.75	5.74	54.0	6.25	AV	79.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

Sample No.	S03	Temperature	22.7℃
Humidity	39%RH	Pressure	101kPa
Test Engineer	He Shichang	Test Date	2025.02.18


Test Mode 5

5) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	50.419	33.28	-25.50	40.0	6.72	Peak	61.00	100	Vertical	Pass
2	89.315	29.93	-29.02	43.5	13.57	Peak	213.00	100	Vertical	Pass
3	107.406	32.97	-26.46	43.5	10.53	Peak	253.00	100	Vertical	Pass
4	143.102	35.66	-30.37	43.5	7.84	Peak	44.00	100	Vertical	Pass
5	260.521	31.18	-24.85	46.0	14.82	Peak	28.00	200	Vertical	Pass
6	959.987	35.75	-9.09	46.0	10.25	Peak	169.00	100	Vertical	Pass


6) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	51.146	18.12	-24.26	40.0	21.88	Peak	329.00	100	Horizontal	Pass
2	96.008	21.60	-27.49	43.5	21.90	Peak	155.00	200	Horizontal	Pass
3	143.442	27.43	-30.48	43.5	16.07	Peak	132.00	200	Horizontal	Pass
4	165.509	23.88	-29.32	43.5	19.62	Peak	33.00	200	Horizontal	Pass
5	297.041	30.44	-23.54	46.0	15.56	Peak	27.00	100	Horizontal	Pass
6	396.030	25.94	-21.05	46.0	20.06	Peak	235.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00867	2022.04.12	2025.04.11	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

7) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1500.240	39.42	-15.50	74.0	34.58	Peak	12.00	100	Vertical	Pass
1**	1500.240	30.05	-15.50	54.0	23.95	AV	12.00	100	Vertical	Pass
2	3128.490	47.82	-6.17	74.0	26.18	Peak	316.00	100	Vertical	Pass
2**	3128.490	37.14	-6.17	54.0	16.86	AV	316.00	100	Vertical	Pass
3	4060.680	50.34	-1.44	74.0	23.66	Peak	83.00	100	Vertical	Pass
3**	4060.680	40.13	-1.44	54.0	13.87	AV	83.00	100	Vertical	Pass
4	5884.040	54.69	2.29	74.0	19.31	Peak	0.00	100	Vertical	Pass
4**	5884.040	45.38	2.29	54.0	8.62	AV	0.00	100	Vertical	Pass
5	7015.720	54.04	-0.17	74.0	19.96	Peak	242.00	100	Vertical	Pass
5**	7015.720	44.23	-0.17	54.0	9.77	AV	242.00	100	Vertical	Pass
6	13375.500	56.52	5.06	74.0	17.48	Peak	207.00	100	Vertical	Pass
6**	13375.500	46.64	5.06	54.0	7.36	AV	207.00	100	Vertical	Pass

8) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1248.040	39.30	-15.72	74.0	34.70	Peak	271.00	100	Horizontal	Pass
1**	1248.040	30.40	-15.72	54.0	23.60	AV	271.00	100	Horizontal	Pass
2	3374.970	47.45	-5.55	74.0	26.55	Peak	204.00	100	Horizontal	Pass
2**	3374.970	37.37	-5.55	54.0	16.63	AV	204.00	100	Horizontal	Pass
3	4028.340	50.03	-2.32	74.0	23.97	Peak	243.00	100	Horizontal	Pass
3**	4028.340	40.36	-2.32	54.0	13.64	AV	243.00	100	Horizontal	Pass
4	5862.480	53.67	2.46	74.0	20.33	Peak	214.00	100	Horizontal	Pass
4**	5862.480	44.33	2.46	54.0	9.67	AV	214.00	100	Horizontal	Pass
5	7108.340	53.56	0.15	74.0	20.44	Peak	63.00	100	Horizontal	Pass
5**	7108.340	43.76	0.15	54.0	10.24	AV	63.00	100	Horizontal	Pass
6	13581.500	56.31	4.72	74.0	17.69	Peak	244.00	100	Horizontal	Pass
6**	13581.500	46.60	4.72	54.0	7.40	AV	244.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.2 Conducted Emission, AC Ports

Note: Not applicable.

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2510718-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2510718-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2510718-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--