

FCC Radio Test Report

FCC ID: XMR202112EC200AAU

This report concerns: Original Grant

Project No. : 2110H020
Equipment : LTE Module
Brand Name : Quectel
Test Model : EC200A-AU
Series Model : N/A
Applicant : Quectel Wireless Solutions Co., Ltd
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233.
Manufacturer : Quectel Wireless Solutions Co., Ltd
Address : Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233.
Date of Receipt : Nov. 15, 2021
Date of Test : Nov. 16, 2021 ~ Dec. 06, 2021
Issued Date : Dec. 09, 2021
Report Version : R00
Test Sample : Engineering Sample No.: SH20211115155 for EUT, SH20211115153-3 for adapter.
Standard(s) : 47 CFR FCC Part 22 Subpart H
ANSI/TIA/EIA-603-E-2016
FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Maker Qi

Prepared by : Maker Qi

Ryan. Wang

Approved by : Ryan Wang



TESTING CERT #5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and is not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	5
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES AND TEST CONDITION	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED	12
3.4 DESCRIPTION OF SUPPORT UNITS	12
3 . TEST RESULT	13
3.1 OUTPUT POWER MEASUREMENT	13
3.1.1 LIMIT	13
3.1.2 TEST PROCEDURE	13
3.1.3 TEST SETUP LAYOUT	13
3.1.4 TEST DEVIATION	13
3.1.5 TEST RESULTS	13
3.2 OCCUPIED BANDWIDTH MEASUREMENT	14
3.2.1 TEST PROCEDURE	14
3.2.2 TEST SETUP LAYOUT	14
3.2.3 TEST DEVIATION	14
3.2.4 TEST RESULTS	14
3.3 CONDUCTED EMISSIONS MEASUREMENT	15
3.3.1 LIMIT	15
3.3.2 TEST PROCEDURES	15
3.3.3 TEST SETUP LAYOUT	15
3.3.4 TEST DEVIATION	15
3.3.5 TEST RESULTS	15
3.4 RADIATED EMISSIONS MEASUREMENT	16
3.4.1 LIMIT	16
3.4.2 TEST PROCEDURES	16
3.4.3 TEST SETUP LAYOUT	17
3.4.4 TEST DEVIATION	18
3.4.5 TEST RESULTS (9KHZ TO 30MHZ)	18
3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)	18
3.4.7 TEST RESULTS (ABOVE 1000MHZ)	18
3.5 BAND EDGE MEASUREMENT	19
3.5.1 LIMIT	19

Table of Contents	Page
3.5.2 TEST PROCEDURES	19
3.5.3 TEST SETUP LAYOUT	19
3.5.4 TEST DEVIATION	19
3.5.5 TEST RESULTS	19
3.6 PEAK TO AVERAGE RATIO MEASUREMENT	20
3.6.1 LIMIT	20
3.6.2 TEST PROCEDURES	20
3.6.3 TEST SETUP LAYOUT	20
3.6.4 TEST DEVIATION	20
3.6.5 TEST RESULTS	20
3.7 FREQUENCY STABILITY MEASUREMENT	21
3.7.1 LIMIT	21
3.7.2 TEST PROCEDURES	21
3.7.3 TEST SETUP LAYOUT	21
3.7.4 TEST DEVIATION	21
3.7.5 TEST RESULTS	21
5. LIST OF MEASUREMENT EQUIPMENTS	22
6. EUT TEST PHOTO	24
APPENDIX A - OUTPUT POWER	26
APPENDIX B - OCCUPIED BANDWIDTH	33
APPENDIX C - CONDUCTED EMISSIONS	45
APPENDIX D - RADIATED EMISSION (9KHZ TO 30MHZ)	51
APPENDIX E - RADIATED EMISSION (30MHZ TO 1GHZ)	52
APPENDIX F - RADIATED EMISSION (ABOVE 1GHZ)	59
APPENDIX G - BAND EDGE	66
APPENDIX H - PEAK TO AVERAGE RATIO	73
APPENDIX I - FREQUENCY STABILITY	80

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Dec. 09, 2021

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 22 Subpart H			
Standard(s) Section	Test Item	Judgment	Remark
2.1046 22.913(a)	Effective Radiated Power	PASS	-----
2.1049	Occupied Bandwidth	PASS	-----
2.1051 22.917(a)	Conducted Spurious Emissions	PASS	-----
2.1053 22.917(a)	Radiated Spurious Emissions	PASS	-----
22.917(a)	Band Edge Measurements	PASS	-----
-	Peak To Average Ratio	PASS	-----
2.1055 22.355	Frequency Stability	PASS	-----

Note:

For the verdict, the “N/A” denotes “not applicable”, the “N/T” denotes “not tested”.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China.

BTL's Test Firm Registration Number for FCC: 476765

BTL's Designation Number for FCC: CN1241

1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainty figures shall be calculated according the methods described in the ETSI TR 100 028 and shall correspond to an expansion factor (coverage factor) $k=1.96$ or $k=2$ (which provide confidence levels of respectively 90% and 95.45% in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$.

The BTL measurement uncertainty as below table:

A. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
SH-CB02	CISPR	9 KHz~30 MHz	-	2.16
		30 MHz~200 MHz	V	4.04
		30 MHz~200 MHz	H	2.90
		200 MHz~1,000 MHz	V	3.76
		200 MHz~1,000 MHz	H	3.82

Test Site	Method	Measurement Frequency Range	U,(dB)
SH-CB02 (3m)	CISPR	1GHz ~ 6GHz	4.56
		6GHz ~ 18GHz	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
Output Power & ERP	24°C	35%	DC 3.8V	Danny Dang
Occupied Bandwidth	24°C	35%	DC 3.8V	Danny Dang
Conducted Spurious Emissions	24°C	35%	DC 3.8V	Danny Dang
Radiated Spurious Emissions	26°C	61%	DC 3.8V	Jane Wang
Band Edge	24°C	35%	DC 3.8V	Danny Dang
Peak to Average Ratio	24°C	35%	DC 3.8V	Danny Dang
Frequency Stability	Normal and Extreme			Danny Dang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	LTE Module	
Brand Name	Quectel	
Test Model	EC200A-AU	
Series Model	N/A	
Model Difference(s)	N/A	
Software Version	EC200AAUHAR01A01M16	
Hardware Version	R1.0	
Power Source	DC Voltage supplied from AC/DC adapter(support unit)	
Power Rating	Supply voltage: 3.4–4.5V, Typical supply voltage: 3.8 V	
Antenna Type	Dipole	
Antenna Gain	GSM850	2.53 dBi
	WCDMA V	
	LTE Band 5	
Modulation Type	GSM	GMSK
	GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	UL: QPSK DL: QPSK, 16QAM
	LTE	UL: QPSK, 16QAM DL: QPSK, 16QAM, 64QAM
Operation Frequency	EDGE/GSM/GPRS	824.2MHz ~ 848.8MHz
	WCDMA Band V	826.4MHz ~ 846.6MHz
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	824.7 MHz ~ 848.3 MHz
	LTE Band 5 (Channel Bandwidth: 3MHz)	825.5 MHz ~ 847.5 MHz
	LTE Band 5 (Channel Bandwidth: 5MHz)	826.5 MHz ~ 846.5 MHz
	LTE Band 5 (Channel Bandwidth: 10MHz)	829.0 MHz ~ 844.0 MHz

Max. ERP Power	GSM	GMSK	32.52	dBm
	GPRS	GMSK	32.51	dBm
	EDGE	8PSK	28.10	dBm
	WCDMA	QPSK	23.80	dBm
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	QPSK	24.56	dBm
		16QAM	23.65	dBm
	LTE Band 5 (Channel Bandwidth: 3MHz)	QPSK	24.05	dBm
		16QAM	23.46	dBm
	LTE Band 5 (Channel Bandwidth: 5MHz)	QPSK	23.93	dBm
		16QAM	23.17	dBm
	LTE Band 5 (Channel Bandwidth: 10MHz)	QPSK	23.66	dBm
		16QAM	23.04	dBm

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. GSM (GMSK) mode was found to be the worst case and recorded.

2.2 DESCRIPTION OF TEST MODES AND TEST CONDITION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X-plane for EIRP and X-axis for radiated emission.


Following channel(s) was (were) selected for the final test as listed below:

GSM MODE			
Test Item	Available Channel	Tested Channel	Mode
ERP	128 to 251	128, 190, 251	GSM, GPRS, EDGE
Output Power	128 to 251	128, 190, 251	GSM, GPRS, EDGE
Occupied Bandwidth	128 to 251	128, 190, 251	GSM, EDGE
Conducuted Emission	128 to 251	190	GSM, EDGE
Radiated Emission	128 to 251	190	GSM
Band Edge	128 to 251	128, 251	GSM, EDGE
Peak to Average Ratio	128 to 251	128, 190, 251	GSM, EDGE
Frequency Stability	128 to 251	190	GSM

WCDMA MODE			
Test Item	Available Channel	Tested Channel	Mode
ERP	4132 to 4233	4132, 4182, 4233	WCDMA, HSDPA, HSUPA
Output Power	4132 to 4233	4132, 4182, 4233	WCDMA, HSDPA, HSUPA
Conducted Emission	4132 to 4233	4182	WCDMA
Radiated Emission	4132 to 4233	4182	WCDMA
Band Edge	4132 to 4233	4132, 4233	WCDMA
Peak to Average Ratio	4132 to 4233	4132, 4182, 4233	WCDMA
Frequency Stability	4132 to 4233	4182	WCDMA

LTE BAND 5					
Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Output Power & ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1RB/3RB/6RB
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1RB/8RB/15RB
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1RB/12RB/25RB
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1RB/25RB/50RB
Occupied Bandwidth	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	6 RB
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	15 RB
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	25 RB
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	50 RB
Conducted Emission	20407 to 20643	20525	1.4MHz	QPSK	1 RB
	20425 to 20625	20525	5MHz	QPSK	1 RB
	20450 to 20600	20525	10MHz	QPSK	1 RB
Radiated Emission	20407 to 20643	20525	1.4MHz	QPSK	1 RB
	20425 to 20625	20525	5MHz	QPSK	1 RB
	20450 to 20600	20525	10MHz	QPSK	1 RB
Band Edge	20407 to 20643	20407	1.4MHz	QPSK	1 RB
		20643	1.4MHz	QPSK	6 RB
	20415 to 20635	20415	3MHz	QPSK	1 RB
		20635	3MHz	QPSK	15 RB
	20425 to 20625	20425	5MHz	QPSK	1 RB
		20625	5MHz	QPSK	25 RB
	20450 to 20600	20450	10MHz	QPSK	1 RB
		20600	10MHz	QPSK	50 RB
	20407 to 20643	20407	1.4MHz	QPSK	1 RB
		20643	1.4MHz	QPSK	6 RB
	20415 to 20635	20415	3MHz	QPSK	1 RB
		20635	3MHz	QPSK	15 RB
Peak To Average Ratio	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK, 16QAM	1 RB
	20415 to 20635	20415, 20525, 20635	3MHz	QPSK, 16QAM	1 RB
	20425 to 20625	20425, 20525, 20625	5MHz	QPSK, 16QAM	1 RB
	20450 to 20600	20450, 20525, 20600	10MHz	QPSK, 16QAM	1 RB
Frequency Stability	20407 to 20643	20525	1.4MHz	QPSK	1 RB
	20415 to 20635	20525	3MHz	QPSK	1 RB
	20425 to 20625	20525	5MHz	QPSK	1 RB
	20450 to 20600	20525	10MHz	QPSK	1 RB

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATIONOFSYSTEMTESTED



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
A	CMW500	N/A	N/A	129246

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	DC	N/A	N/A	1m

3. TEST RESULT

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMIT

Mobile / Portable station are limited to 7 watts e.r.p.

3.1.2 TEST PROCEDURE

EIRP/ ERP:


1. EIRP= Output Power +Antenan gain
ERP power= EIPR power-2.15dBi.

Output Power:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP LAYOUT

Output Power Measurement



3.1.4 TEST DEVIATION

No deviation

3.1.5 TEST RESULTS


Please refer to the Appendix A.

3.2 OCCUPIED BANDWIDTH MEASUREMENT

3.2.1 TEST PROCEDURE

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth and 26dB bandwidth.

3.2.2 TEST SETUP LAYOUT



3.2.3 TEST DEVIATION

No deviation

3.2.4 TEST RESULTS

Please refer to the Appendix B.

3.3 CONDUCTED EMISSIONS MEASUREMENT


3.3.1 LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

3.3.2 TEST PROCEDURES

1. The testing follows FCC KDB 971168 v03r01 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.3.3 TEST SETUP LAYOUT



3.3.4 TEST DEVIATION

No deviation

3.3.5 TEST RESULTS

Please refer to the Appendix C.

3.4 RADIATED EMISSIONS MEASUREMENT

3.4.1 LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

3.4.2 TEST PROCEDURES


1. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
2. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
3. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
4. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi}.$
5. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


3.4.3 TEST SETUP LAYOUT

Below 30MHz



30MHz to 1GHz





3.4.4 TEST DEVIATION

No deviation

3.4.5 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix D.

3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix E.

3.4.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix F.

3.5 BAND EDGE MEASUREMENT


3.5.1 LIMIT

A Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.5.2 TEST PROCEDURES

1. All measurements were done at low and high operational frequency range.
2. The center frequency of spectrum is the band edge frequency and span is 1.5MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/EDGE).
3. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
4. The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 15kHz and VB of the spectrum is 43kHz (LTE Bandwidth 1.4MHz).
5. The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 30kHz and VB of the spectrum is 91kHz (LTE Bandwidth 3MHz).
6. The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 51kHz and VB of the spectrum is 150kHz (LTE Bandwidth 5MHz).
7. The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Bandwidth 10MHz).
8. The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 150kHz and VB of the spectrum is 470kHz (LTE Bandwidth 15MHz).
9. The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 200kHz and VB of the spectrum is 620kHz (LTE Bandwidth 20MHz).

3.5.3 TEST SETUP LAYOUT



3.5.4 TEST DEVIATION

No deviation

3.5.5 TEST RESULTS

Please refer to the Appendix G.

3.6 PEAK TO AVERAGE RATIO MEASUREMENT


3.6.1 LIMIT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.6.2 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.6.3 TEST SETUP LAYOUT



3.6.4 TEST DEVIATION

No deviation

3.6.5 TEST RESULTS

Please refer to the Appendix H.

3.7 FREQUENCY STABILITY MEASUREMENT


3.7.1 LIMIT

± 1.5 ppm is for base and fixed station. ± 2.5 ppm is for mobile station.

3.7.2 TEST PROCEDURES

1. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
2. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
3. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.
4. The frequency error was recorded frequency error from the communication simulator.

3.7.3 TEST SETUP LAYOUT



3.7.4 TEST DEVIATION

No deviation

3.7.5 TEST RESULTS

Please refer to the Appendix I.

5. LIST OF MEASUREMENT EQUIPMENTS

Radiated Emission Measurement(9K-30M)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Loop Antenna	EMCI	EMCI LPA600	275	May. 20, 2022
2	MXE EMI Receiver	Keysight	N9038A	MY56400088	Mar. 21, 2022
3	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
4	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

Radiated Emission Measurement(30M-1G)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	TRILOG Broadband Antenna	Schwarzbeck	VULB 9160	9160-3233	Mar. 26, 2022
2	Pre-Amplifier	emci	EMC9135	980401	Mar. 20, 2022
3	MXE EMI Receiver	Keysight	N9038A	MY56400088	Mar. 21, 2022
4	Test Cable	emci	EMC104-SM-SM-7000	181020	Apr. 11, 2022
5	Test Cable	emci	EMC104-SM-SM-2500	170618	Apr. 11, 2022
6	Test Cable	emci	EMC104-SM-SM-800	170647	Apr. 11, 2022
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

Radiated Emission Measurement(1G-18G)					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1817	Mar. 26, 2022
2	Pre-Amplifier	emci	EMC051845SE	980725	Aug. 23, 2022
3	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
4	Test Cable	emci	EMC104-SM-SM-7000	181020	Apr. 11, 2022
5	Test Cable	emci	EMC104-SM-SM-2500	170618	Apr. 11, 2022
6	Test Cable	emci	EMC104-SM-SM-800	170647	Apr. 11, 2022
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

For WCDMA

Conducted Emission & Band Edge & Occupied Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022
2	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
3	Power Divider	JUK	PD-2SF-2060	N/A	N/A

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022
2	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
3	Power Divider	JUK	PD-2SF-2060	N/A	N/A
4	Temperature And Humidity Box	Blue pand	BPHS-120B	170616454	Aug. 23, 2022

For LTE

Conducted Emission & Band Edge & Occupied Bandwidth Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
2	Power Divider	JUK	PD-4SF-2060	N/A	N/A
3	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022

Frequency Stability Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EXA Spectrum Analyzer	Keysight	N9010A	MY56480579	Mar. 21, 2022
2	Power Divider	JUK	PD-4SF-2060	N/A	N/A
3	Wideband Radio Communication Test	R&S	CMW500	129246	Aug. 23, 2022
4	Temperature And Humidity Box	Blue pand	BPHS-120B	170616454	Aug. 23, 2022



Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

6. EUT TEST PHOTO



Radiated Emissions Test Photos

30 MHz to 1000 MHz



Radiated Emissions Test Photos

Above 1 GHz



APPENDIX A - OUTPUT POWER

Output Power (dBm):

GSM850		Burst Output Power		
		128CH	190CH	251CH
		824.2MHz	836.6MHz	848.8MHz
GSM(GMSK)		32.14	32.07	32.09
GPRS/EDGE (GMSK)	1 Tx Slot	32.00	32.10	32.03
	2 Tx Slot	31.99	32.00	32.02
	3 Tx Slot	31.13	31.01	31.04
	4 Tx Slot	29.56	29.41	29.47
EDGE (8PSK)	1 Tx Slot	27.25	27.29	27.72
	2 Tx Slot	27.21	27.15	27.38
	3 Tx Slot	25.30	25.32	25.82
	4 Tx Slot	23.01	23.10	23.50

Modulation	Band	WCDMA V		
	Tx Channel	4132CH	4182CH	4233CH
	Frequency	826.4MHz	836.4MHz	846.6MHz
QPSK	RMC 12.2K	22.96	23.12	22.94
	RMC 64K	22.95	23.07	22.37
	RMC 144K	22.94	23.04	22.31
	RMC 384K	21.74	23.05	22.7
	HSDPA Subtest-1	23.31	23.38	23.39
	HSDPA Subtest-2	22.51	22.76	22.85
	HSDPA Subtest-3	22.08	22.10	22.17
	HSDPA Subtest-4	22.09	22.09	22.16
	HSUPA Subtest-1	23.31	23.11	23.31
	HSUPA Subtest-2	23.34	23.18	23.32
	HSUPA Subtest-3	22.87	22.67	22.84
	HSUPA Subtest-4	23.42	23.31	23.37
	HSUPA Subtest-5	22.86	22.69	22.82

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20407CH	20525CH	20643CH
				824.7MHz	836.5MHz	848.3MHz
5 / 1.4M	QPSK	1	0	23.57	23.30	22.87
		1	2	24.11	23.10	23.54
		1	5	23.39	23.23	22.84
		3	0	23.26	23.11	23.54
		3	1	24.18	23.12	23.56
		3	2	24.14	23.07	23.59
	16QAM	6	0	23.10	22.15	22.50
		1	0	22.90	22.77	22.11
		1	2	23.20	22.25	22.53
		1	5	22.81	22.37	22.41
		3	0	22.28	22.19	22.57
		3	1	23.27	22.19	22.50
		3	2	23.11	22.20	22.76
		6	0	22.23	21.47	21.71

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20415CH	20525CH	20635CH
				825.5MHz	836.5MHz	847.5MHz
5 / 3M	QPSK	1	0	23.05	22.98	23.35
		1	7	23.67	23.05	23.52
		1	14	23.59	22.99	22.66
		8	0	22.82	22.09	22.45
		8	4	22.67	22.06	22.50
		8	7	22.59	21.98	22.45
		15	0	22.68	22.03	22.47
	16QAM	1	0	22.44	22.40	22.50
		1	7	23.08	22.24	22.62
		1	14	23.02	22.54	21.78
		8	0	21.94	21.11	21.55
		8	4	21.68	21.19	21.63
		8	7	21.72	21.20	21.47
		15	0	21.75	21.15	21.60

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20425CH	20525CH	20625CH
				826.5MHz	836.5MHz	846.5MHz
5 / 5M	QPSK	1	0	22.97	22.95	23.55
		1	13	23.54	23.01	23.44
		1	24	23.51	23.08	22.65
		12	0	22.74	22.02	22.47
		12	6	22.59	22.09	22.46
		12	11	22.44	22.11	22.56
		25	0	22.57	22.00	22.50
	16QAM	1	0	22.51	22.15	22.61
		1	13	22.79	22.55	22.70
		1	24	22.44	22.13	22.18
		12	0	21.70	21.14	21.58
		12	6	21.70	21.16	21.55
		12	11	21.58	21.13	21.65
		25	0	21.71	21.02	21.57

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20450CH	20525CH	20600CH
				829.0MHz	836.5MHz	844.0MHz
5 / 10M	QPSK	1	0	22.95	23.11	23.22
		1	25	23.16	22.79	23.20
		1	49	23.06	23.28	22.60
		25	0	22.32	21.61	21.96
		25	13	22.18	21.78	22.21
		25	25	21.89	21.73	22.06
		50	0	22.11	21.65	22.09
	16QAM	1	0	22.39	22.16	22.04
		1	25	22.43	21.99	22.66
		1	49	22.44	22.44	21.78
		25	0	21.45	20.69	21.00
		25	13	21.29	20.93	21.34
		25	25	21.03	20.86	21.13
		50	0	21.09	20.81	21.24

ERP Power (dBm):

GSM850		ERP Power		
		128CH	190CH	251CH
		824.2MHz	836.6MHz	848.8MHz
GSM(GMSK)		32.52	32.45	32.47
GPRS/EDGE (GMSK)	1 Tx Slot	32.38	32.48	32.41
	2 Tx Slot	32.37	32.38	32.40
	3 Tx Slot	31.51	31.39	31.42
	4 Tx Slot	29.94	29.79	29.85
EDGE (8PSK)	1 Tx Slot	27.63	27.67	28.10
	2 Tx Slot	27.59	27.53	27.76
	3 Tx Slot	25.68	25.70	26.20
	4 Tx Slot	23.39	23.48	23.88

Modulation	Band	WCDMA V		
	Tx Channel	4132CH	4182CH	4233CH
	Frequency	826.4MHz	836.4MHz	846.6MHz
QPSK	RMC 12.2K	23.34	23.50	23.32
	RMC 64K	23.33	23.45	22.75
	RMC 144K	23.32	23.42	22.69
	RMC 384K	22.12	23.43	23.08
	HSDPA Subtest-1	23.69	23.76	23.77
	HSDPA Subtest-2	22.89	23.14	23.23
	HSDPA Subtest-3	22.46	22.48	22.55
	HSDPA Subtest-4	22.47	22.47	22.54
	HSUPA Subtest-1	23.69	23.49	23.69
	HSUPA Subtest-2	23.72	23.56	23.70
	HSUPA Subtest-3	23.25	23.05	23.22
	HSUPA Subtest-4	23.80	23.69	23.75
	HSUPA Subtest-5	23.24	23.07	23.20

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20407CH	20525CH	20643CH
				824.7MHz	836.5MHz	848.3MHz
5 / 1.4M	QPSK	1	0	23.95	23.68	23.25
		1	2	24.49	23.48	23.92
		1	5	23.77	23.61	23.22
		3	0	23.64	23.49	23.92
		3	1	24.56	23.50	23.94
		3	2	24.52	23.45	23.97
	16QAM	6	0	23.48	22.53	22.88
		1	0	23.28	23.15	22.49
		1	2	23.58	22.63	22.91
		1	5	23.19	22.75	22.79
		3	0	22.66	22.57	22.95
		3	1	23.65	22.57	22.88
		3	2	23.49	22.58	23.14
		6	0	22.61	21.85	22.09

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20415CH	20525CH	20635CH
				825.5MHz	836.5MHz	847.5MHz
5 / 3M	QPSK	1	0	23.43	23.36	23.73
		1	7	24.05	23.43	23.90
		1	14	23.97	23.37	23.04
		8	0	23.20	22.47	22.83
		8	4	23.05	22.44	22.88
		8	7	22.97	22.36	22.83
		15	0	23.06	22.41	22.85
	16QAM	1	0	22.82	22.78	22.88
		1	7	23.46	22.62	23.00
		1	14	23.40	22.92	22.16
		8	0	22.32	21.49	21.93
		8	4	22.06	21.57	22.01
		8	7	22.10	21.58	21.85
		15	0	22.13	21.53	21.98

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20425CH	20525CH	20625CH
				826.5MHz	836.5MHz	846.5MHz
5 / 5M	QPSK	1	0	23.35	23.33	23.93
		1	13	23.92	23.39	23.82
		1	24	23.89	23.46	23.03
		12	0	23.12	22.40	22.85
		12	6	22.97	22.47	22.84
		12	11	22.82	22.49	22.94
		25	0	22.95	22.38	22.88
	16QAM	1	0	22.89	22.53	22.99
		1	13	23.17	22.93	23.08
		1	24	22.82	22.51	22.56
		12	0	22.08	21.52	21.96
		12	6	22.08	21.54	21.93
		12	11	21.96	21.51	22.03
		25	0	22.09	21.40	21.95

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				20450CH	20525CH	20600CH
				829.0MHz	836.5MHz	844.0MHz
5 / 10M	QPSK	1	0	23.33	23.49	23.60
		1	25	23.54	23.17	23.58
		1	49	23.44	23.66	22.98
		25	0	22.70	21.99	22.34
		25	13	22.56	22.16	22.59
		25	25	22.27	22.11	22.44
		50	0	22.49	22.03	22.47
	16QAM	1	0	22.77	22.54	22.42
		1	25	22.81	22.37	23.04
		1	49	22.82	22.82	22.16
		25	0	21.83	21.07	21.38
		25	13	21.67	21.31	21.72
		25	25	21.41	21.24	21.51
		50	0	21.47	21.19	21.62

APPENDIX B - OCCUPIED BANDWIDTH

GSM850					
GSM			EDGE		
GMSK			8PSK		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
128	824.2	0.2418	128	824.2	0.2418
190	836.6	0.2416	190	836.6	0.2418
251	848.8	0.2436	251	848.8	0.2451
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
128	824.2	0.3128	128	824.2	0.3054
190	836.6	0.3035	190	836.6	0.3071
251	848.8	0.3197	251	848.8	0.3091

Spectrum Plot

GSM -128



GSM -190



GSM -251



GSM -128



GSM -190



GSM -251




WCDMA Band V

QPSK

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
4132	826.4	4.1829	4132	826.4	4.736
4182	836.4	4.1816	4182	836.4	4.774
4233	846.6	4.1726	4233	846.6	4.731

Spectrum Plot




LTE Band 5_1.4M					
QPSK			16QAM		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
20407	824.7	1.0908	20407	824.7	1.1009
20525	836.5	1.0997	20525	836.5	1.1011
20643	848.3	1.1039	20643	848.3	1.0917
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20407	824.7	1.264	20407	824.7	1.262
20525	836.5	1.252	20525	836.5	1.241
20643	848.3	1.260	20643	848.3	1.258

Spectrum Plot


QPSK-20407




QPSK-20525




QPSK-20643



16QAM-20407



16QAM-20525




16QAM-20643




LTE Band 5_3M					
QPSK			16QAM		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
20415	825.5	2.6948	20415	825.5	2.6966
20525	836.5	2.6986	20525	836.5	2.6998
20635	847.5	2.6950	20635	847.5	2.6986
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20415	825.5	2.923	20415	825.5	2.917
20525	836.5	2.908	20525	836.5	2.925
20635	847.5	2.917	20635	847.5	2.918

Spectrum Plot


QPSK-20415




QPSK-20525



QPSK-20635




16QAM-20415



16QAM-20525



16QAM-20635



LTE Band 5_5M					
QPSK			16QAM		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
20425	826.5	4.5041	20425	826.5	4.5006
20525	836.5	4.4943	20525	836.5	4.4900
20625	846.5	4.4982	20625	846.5	4.4886
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20425	826.5	4.837	20425	826.5	4.858
20525	836.5	4.846	20525	836.5	4.863
20625	846.5	4.842	20625	846.5	4.828

Spectrum Plot

QPSK-20425



QPSK-20525



QPSK-20625




16QAM-20425



16QAM-20525



16QAM-20625




LTE Band 5_10M					
QPSK			16QAM		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
20450	829.0	8.9748	20450	829.0	8.9749
20525	836.5	8.9349	20525	836.5	8.9277
20600	844.0	8.9623	20600	844.0	8.9043
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	Channel	Frequency (MHz)	26dB Bandwidth (MHz)
20450	829.0	9.693	20450	829.0	9.689
20525	836.5	9.617	20525	836.5	9.609
20600	844.0	9.653	20600	844.0	9.623

Spectrum Plot

QPSK-20450




QPSK-20525



QPSK-20600




16QAM-20450




16QAM-20525






16QAM-20600








APPENDIX C - CONDUCTED EMISSIONS





LTE Band 5_1.4M			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
20525	836.5	20525	836.5
			
Channel	Frequency(MHz)		
20525	836.5	-	-
			

LTE Band 5_5M			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
20525	836.5	20525	836.5
			
Channel	Frequency(MHz)	-	-
20525	836.5	-	-
			


LTE Band 5_10M			
Channel	Frequency(MHz)	Channel	Frequency(MHz)
20525	836.5	20525	836.5
			
Channel	Frequency(MHz)	-	-
20525	836.5	-	-
			

APPENDIX D - RADIATED EMISSION (9KHZ TO 30MHZ)

Note: Below 30MHz, The measured value have enough margin over 20dB than the limit, therefore they are not reported.

APPENDIX E - RADIATED EMISSION (30MHZ TO 1GHZ)

Test Mode: GSM850_TX Mode



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		35.8200	-60.54	-14.12	-74.66	-13.00	-61.66	RMS	
2	*	99.8400	-76.65	2.53	-74.12	-13.00	-61.12	RMS	
3		356.4050	-81.43	-0.20	-81.63	-13.00	-68.63	RMS	
4		448.5550	-78.17	0.93	-77.24	-13.00	-64.24	RMS	
5		606.6650	-81.39	4.15	-77.24	-13.00	-64.24	RMS	
6		669.7150	-81.49	4.09	-77.40	-13.00	-64.40	RMS	

Test Mode: GSM850_TX Mode


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		35.8200	-74.32	-4.02	-78.34	-13.00	-65.34	RMS	
2		165.3150	-75.93	-3.24	-79.17	-13.00	-66.17	RMS	
3		416.5450	-80.30	0.56	-79.74	-13.00	-66.74	RMS	
4	*	471.3500	-72.46	1.19	-71.27	-13.00	-58.27	RMS	
5		617.3350	-79.68	4.10	-75.58	-13.00	-62.58	RMS	
6		677.9600	-78.40	4.11	-74.29	-13.00	-61.29	RMS	

Test Mode: WCDMA Band V_TX Mode


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	35.8200	-61.44	-14.12	-75.56	-13.00	-62.56	RMS	
2		97.9000	-79.88	1.74	-78.14	-13.00	-65.14	RMS	
3		127.9700	-79.41	1.43	-77.98	-13.00	-64.98	RMS	
4		355.9200	-81.83	-0.21	-82.04	-13.00	-69.04	RMS	
5		449.5250	-78.85	0.94	-77.91	-13.00	-64.91	RMS	
6		586.7800	-81.20	3.85	-77.35	-13.00	-64.35	RMS	

Test Mode: WCDMA Band V_TX Mode


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1		36.3050	-73.90	-4.07	-77.97	-13.00	-64.97	RMS	
2		162.4050	-75.57	-3.16	-78.73	-13.00	-65.73	RMS	
3		394.7200	-79.91	0.29	-79.62	-13.00	-66.62	RMS	
4	*	467.4700	-72.44	1.13	-71.31	-13.00	-58.31	RMS	
5		618.3050	-79.63	4.10	-75.53	-13.00	-62.53	RMS	
6		678.9300	-79.38	4.11	-75.27	-13.00	-62.27	RMS	

Test Mode: LTE Band 5_TX Mode_10M

Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		98.8700	-78.92	2.14	-76.78	-13.00	-63.78	RMS	
2		209.9350	-80.95	-3.53	-84.48	-13.00	-71.48	RMS	
3		371.9250	-81.85	0.09	-81.76	-13.00	-68.76	RMS	
4		453.4050	-79.45	0.97	-78.48	-13.00	-65.48	RMS	
5		583.8700	-80.41	3.78	-76.63	-13.00	-63.63	RMS	
6	*	720.1550	-81.17	4.78	-76.39	-13.00	-63.39	RMS	

Test Mode: LTE Band 5_TX Mode_10M


Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1		35.8200	-75.34	-4.02	-79.36	-13.00	-66.36	RMS	
2		165.3150	-75.59	-3.24	-78.83	-13.00	-65.83	RMS	
3		395.6900	-79.55	0.31	-79.24	-13.00	-66.24	RMS	
4	*	467.4700	-71.79	1.13	-70.66	-13.00	-57.66	RMS	
5		619.2750	-80.35	4.10	-76.25	-13.00	-63.25	RMS	
6		686.6900	-79.29	4.12	-75.17	-13.00	-62.17	RMS	

APPENDIX F - RADIATED EMISSION (ABOVE 1GHZ)


Test Mode: GSM850_TX Mode



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1672.800	-35.29	-11.19	-46.48	-13.00	-33.48	RMS	
2		2509.200	-48.22	-7.53	-55.75	-13.00	-42.75	RMS	
3		3345.600	-51.82	-6.24	-58.06	-13.00	-45.06	RMS	
4		4182.000	-57.59	-4.09	-61.68	-13.00	-48.68	RMS	
5		5018.800	-51.47	-2.42	-53.89	-13.00	-40.89	RMS	
6		5854.400	-60.30	-1.41	-61.71	-13.00	-48.71	RMS	
7		6691.600	-58.77	0.48	-58.29	-13.00	-45.29	RMS	

Test Mode: GSM850_TX Mode


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector	Comment
		MHz	dBm	dB	dBm	dBm	dB		
1	*	1672.800	-32.99	-11.01	-44.00	-13.00	-31.00	RMS	
2		2509.200	-48.34	-7.92	-56.26	-13.00	-43.26	RMS	
3		3345.600	-51.79	-6.21	-58.00	-13.00	-45.00	RMS	
4		4181.600	-62.12	-4.20	-66.32	-13.00	-53.32	RMS	
5		5018.400	-60.63	-2.60	-63.23	-13.00	-50.23	RMS	
6		5855.200	-62.77	-1.60	-64.37	-13.00	-51.37	RMS	
7		6691.600	-61.92	0.44	-61.48	-13.00	-48.48	RMS	

Test Mode: WCDMA Band V_TX Mode


Vertical



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1670.800	-49.16	-11.18	-60.34	-13.00	-47.34	RMS	
2		2506.000	-57.95	-7.54	-65.49	-13.00	-52.49	RMS	


Test Mode: WCDMA Band V_TX Mode

Horizontal



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1674.400	-48.08	-11.02	-59.10	-13.00	-46.10	RMS	
2		2509.200	-60.22	-7.92	-68.14	-13.00	-55.14	RMS	


Test Mode: LTE Band 5_ TX Mode_10M



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBm	dB	dBm	dBm	dB	Detector	Comment
1	*	1664.000	-40.73	-11.15	-51.88	-13.00	-38.88	RMS	
2		2496.400	-55.17	-7.57	-62.74	-13.00	-49.74	RMS	


Test Mode: LTE Band 5_ TX Mode_10M


Horizontal





No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Margin dB	Detector	Comment
1	*	1664.400	-40.69	-10.99	-51.68	-13.00	-38.68	RMS	
2		2496.000	-49.01	-7.91	-56.92	-13.00	-43.92	RMS	


APPENDIX G - BAND EDGE















APPENDIX H - PEAK TO AVERAGE RATIO

GSM 850 Spectrum Plot




WCDMA Band V Spectrum Plot


4132



4182




4233




LTE Band 5 Spectrum Plot_1.4M


QPSK-20407




QPSK-20525




QPSK-20643




16QAM-20407



16QAM-20525




16QAM-20643




LTE Band 5 Spectrum Plot_3M


QPSK-20415




QPSK-20525




QPSK-20635




16QAM-20415



16QAM-20525




16QAM-20635




LTE Band 5 Spectrum Plot_5M


QPSK-20425




QPSK-20525




QPSK-20625




16QAM-20425



16QAM-20525




16QAM-20625




LTE Band 5 Spectrum Plot_10M


QPSK-20450




QPSK-20525




QPSK-20600




16QAM-20450



16QAM-20525



16QAM-20600



APPENDIX I - FREQUENCY STABILITY

Test Mode:	GSM850_CH190
------------	--------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	-4.69	-0.005606024	± 2.5
-10	-2.73	-0.003263208	
0	5.27	0.006299307	
10	4.95	0.005916806	
20	-3.04	-0.003633756	
30	4.62	0.005522352	
40	3.27	0.003908678	
50	2.15	0.002569926	
Max. Deviation (ppm)	5.27	0.006299307	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	-7.60	-0.009084389	± 2.5
3.8	-5.43	-0.006490557	
3.4	-5.87	-0.007016495	
Max. Deviation (ppm)	7.60	-0.006490557	

Test Mode:	WCDMA Band V_CH4407
------------	---------------------

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	-4.83	0.005774749	± 2.5
-10	-4.25	0.005081301	
0	-2.71	0.003240077	
10	5.67	0.006779053	
20	4.33	0.005176949	
30	-3.65	0.004363941	
40	-4.05	0.004842181	
50	-4.46	0.005332377	
Max. Deviation (ppm)	5.67	0.006779053	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	-8.56	0.010234338	± 2.5
3.8	-7.42	0.008871353	
3.4	-7.18	0.008584409	
Max. Deviation (ppm)	8.56	0.010234338	

Test Mode: LTE Band 5_CH20525_1.4M

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	-4.33	-0.005181924	± 2.5
-10	2.74	0.003279735	
0	1.54	0.001838565	
10	-3.30	-0.003946842	
20	-1.24	-0.001485057	
30	-1.44	-0.001719467	
40	-3.71	-0.004435742	
50	4.10	0.004896058	
Max. Deviation (ppm)	-4.33	-0.005181924	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	6.08	0.007266283	± 2.5
3.8	-5.04	-0.006022534	
3.4	1.90	0.002272747	
Max. Deviation (ppm)	6.08	0.007266283	

Test Mode: LTE Band 5_CH20525_3M

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	3.33	0.003984112	± 2.5
-10	1.26	0.001512136	
0	3.23	0.003862377	
10	-5.20	-0.006221706	
20	2.77	0.00331317	
30	3.33	0.00397734	
40	-1.57	-0.001881274	
50	5.27	0.006302306	
Max. Deviation (ppm)	5.27	0.006302306	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	-3.60	-0.00430806	± 2.5
3.8	2.03	0.002428898	
3.4	-1.51	-0.001804824	
Max. Deviation (ppm)	-3.60	-0.00430806	

Test Mode: LTE Band 5_CH20525_5M

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	-6.47	-0.007737344	± 2.5
-10	2.16	0.002587005	
0	-4.14	-0.004951759	
10	3.97	0.0047518	
20	-4.07	-0.004860426	
30	-5.34	-0.006377793	
40	4.19	0.005008667	
50	2.75	0.003283336	
Max. Deviation (ppm)	-6.47	-0.007737344	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	-5.33	-0.006368903	± 2.5
3.8	-4.77	-0.00569723	
3.4	-4.74	-0.005670529	
Max. Deviation (ppm)	-5.33	-0.006368903	

Test Mode: LTE Band 5_CH20525_10M

Temperature vs. Frequency Stability

Temperature(°C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
-20	2.75	0.003285022	± 2.5
-10	-4.70	-0.005617441	
0	-3.95	-0.00472478	
10	-2.76	-0.003305024	
20	4.56	0.005454262	
30	-1.61	-0.001922897	
40	-3.74	-0.004468128	
50	-4.00	-0.004781048	
Max. Deviation (ppm)	-4.70	-0.005617441	

Voltage vs. Frequency Stability

Voltage(Volts)	Frequency Error (Hz)	Frequency Error (ppm)	Limit(ppm)
4.5	2.73	0.003259905	± 2.5
3.8	5.54	0.006628086	
3.4	-3.84	-0.004584999	
Max. Deviation (ppm)	5.54	0.006628086	

End of Test Report