

ATTACHMENT

* Standalone SAR test exclusion considerations

- Min. transmitting frequency = 2441 MHz
- Min. test separation distance = 5 mm
- Max. Power with tune-up tolerance = 3.90 dBm = 2.45 mW
(Measured power 3.40 dBm ± 0.5 dB)

Step 1)

SAR Test exclusion thresholds for 100 MHz to 6 GHz at test separation distance \leq 50 mm = **Used**

$[(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}]$

$$=[2.45 / 5] * [\sqrt{2.441}] = 0.767 \leq 3, \text{ for } 1\text{g SAR}$$

Thus, SAR for this device is not required.

Step 2)

SAR Test exclusion thresholds for 100 MHz to 1500 MHz at test separation distance $>$ 50 mm = **N/A**

$[\text{Threshold at } 50 \text{ mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) * (\sqrt{f(\text{MHz})}/150)] \text{ mW}$

Step 3)

SAR Test exclusion thresholds for 1500 MHz to 6 GHz at test separation distance $>$ 50 mm = **N/A**

$[\text{Threshold at } 50 \text{ mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) * 10] \text{ mW}$