

## RF Exposure evaluation

### FCC-ID: 2AMPW- SABBATX11

According to 447498 D01 General RF Exposure Guidance v06

#### 4.3. General SAR test exclusion guidance

##### 4.3.1. Standalone SAR test exclusion considerations

- a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR,<sup>30</sup> where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>31</sup>
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

<sup>30</sup> This is equivalent to the formula written as:  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (60 / \sqrt{f(\text{GHz})} \text{ mW})] \cdot [20 \text{ mm} / (\text{min. test separation distance, mm})] \leq 1.0$  for 1-g SAR; also see Appendix A for approximate exclusion threshold numerical values at selected frequencies and distances.

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{EXd})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10((\text{dBuV/m})/20)/10^6$

d = measurement distance in meters (m)---3m

$$\text{So pt} = (\text{EXd})^2 / 30 \times \text{gt}$$

**RF Exposure evaluation**

Copied from the FCC test report: clause9.4 Maximum Peak Output Power

**Test Result:**

For GFSK

| Channel        | Frequency<br>MHz | Measured Value<br>dBm | Output Power<br>mW | Limit<br>mW |
|----------------|------------------|-----------------------|--------------------|-------------|
| Low Channel    | 2402             | -1.11                 | 0.774              | 125         |
| Middle Channel | 2441             | 1.69                  | 1.465              | 125         |
| High Channel   | 2480             | 2.49                  | 1.774              | 125         |

For Pi/4 QDPSK

| Channel        | Frequency<br>MHz | Measured Value<br>dBm | Output Power<br>mW | Limit<br>mW |
|----------------|------------------|-----------------------|--------------------|-------------|
| Low Channel    | 2402             | -4.57                 | 0.349              | 125         |
| Middle Channel | 2441             | -1.20                 | 0.759              | 125         |
| High Channel   | 2480             | -0.68                 | 0.855              | 125         |

For 8DPSK

| Channel        | Frequency<br>MHz | Measured Value<br>dBm | Output Power<br>mW | Limit<br>mW |
|----------------|------------------|-----------------------|--------------------|-------------|
| Low Channel    | 2402             | -4.16                 | 0.384              | 125         |
| Middle Channel | 2441             | -1.50                 | 0.708              | 125         |
| High Channel   | 2480             | -0.48                 | 0.895              | 125         |

*Note: the antenna gain of 1dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*

Then we choose Normal mode channel as the worst case of Maximum Peak Output Power:

| Channel        | Frequency<br>MHz | Measured Value<br>dBm | Output Power<br>mW | Limit<br>mW |
|----------------|------------------|-----------------------|--------------------|-------------|
| Low Channel    | 2402             | -1.11                 | 0.774              | 125         |
| Middle Channel | 2441             | 1.69                  | 1.465              | 125         |
| High Channel   | 2480             | 2.49                  | 1.774              | 125         |

$EIRP/ \text{dBm} = \text{Conducted Max Output Power/ dBm} + \text{Antenna gain /dBi}$ .

Since the distance from the internal BT-antenna to the outer is more than 10mm, we choose the min. test separation distance = 5mm

General RF Exposure:

$$(0.77\text{mW})/(5.0\text{mm}) \times \sqrt{2.402 \text{ GHz}} = 0.235$$

$$(1.47\text{mW})/(5.0\text{mm}) \times \sqrt{2.441 \text{ GHz}} = 0.461$$

$$(1.77\text{mW})/(5.0\text{mm}) \times \sqrt{2.480 \text{ GHz}} = 0.557$$

SAR requirement:  $S=3.0$

General RF Exposure  $< 3$

Then SAR evaluation is not required