Measurement Data

TestMode	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Low	2402	2.39	-40.43	≤-17.61	PASS
	High	2480	2.21	-49.45	≤-17.79	PASS
	Low	Hop_2402	1.75	-41.29	≤-18.25	PASS
	High	Hop_2480	1.85	-51.65	≤-18.15	PASS
2DH5	Low	2402	2.45	-40.24	≤-17.55	PASS
	High	2480	2.29	-49.26	≤-17.71	PASS
	Low	Hop_2402	0.32	-43.2	≤-19.68	PASS
	High	Hop_2480	2.38	-50.21	≤-17.62	PASS

Test plot as follows:

DH5_Ant1_Low_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.402015 GHz	2.39 dBm		
M2		1	2.4 GHz	-47.43 dBm		
M3		1	2.39 GHz	-55.36 dBm		
M4		1	2.3991014 GHz	-40.43 dBm		

Date: 22.APR.2025 17:01:35

DH5_Ant1_High_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48001 GHz	2.21 dBm		
M2		1	2.4835 GHz	-47.54 dBm		
M3		1	2.5 GHz	-55.22 dBm		
M4		1	2.483565 GHz	-49.45 dBm		

Date: 22.APR.2025 17:21:28

DH5_Ant1_Low_Hop_2402



DH5_Ant1_High_Hop_2480



2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4799 GHz	2.29 dBm		
M2		1	2.4835 GHz	-46.53 dBm		
M3		1	2.5 GHz	-55.64 dBm		
M4		1	2.483565 GHz	-49.26 dBm		

Date: 22.APR.2025 17:30:12

2DH5_Ant1_Low_Hop_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40305 GHz	0.32 dBm		
M2		1	2.4 GHz	-43.55 dBm		
M3		1	2.39 GHz	-56.05 dBm		
M4		1	2.3999783 GHz	-43.20 dBm		

Date: 22.APR.2025 17:36:09

2DH5_Ant1_High_Hop_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47585 GHz	2.38 dBm		
M2		1	2.4835 GHz	-54.77 dBm		
M3		1	2.5 GHz	-56.58 dBm		
M4		1	2.505246 GHz	-50.21 dBm		

Date: 22.APR.2025 17:39:05

5.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 *Remark: Offset=cable loss+ attenuation factor.*
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worst case of GFSK modulation type, 2-DH5 of data type is the worst case of π/4DQPSK modulation type.
Test Results:	Pass

DH5_Ant1_2402_0~Reference



Date: 22.APR.2025 17:01:59

DH5_Ant1_2402_30~1000



Date: 22.APR.2025 17:02:03

DH5_Ant1_2402_1000~26500



DH5_Ant1_2441_0~Reference



DH5_Ant1_2441_30~1000



DH5_Ant1_2441_1000~26500



DH5_Ant1_2480_0~Reference



DH5_Ant1_2480_30~1000



DH5_Ant1_2480_1000~26500



2DH5_Ant1_2402_0~Reference



2DH5_Ant1_2402_30~1000



2DH5_Ant1_2402_1000~26500



2DH5_Ant1_2441_0~Reference



2DH5_Ant1_2441_30~1000



2DH5_Ant1_2441_1000~26500



Date: 22.APR.2025 17:24:53

2DH5_Ant1_2480_0~Reference



Date: 22.APR.2025 17:30:34

2DH5_Ant1_2480_30~1000



Date: 22.APR.2025 17:30:39

2DH5_Ant1_2480_1000~26500



Remark:

Pre test 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage
outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 2^9 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)
According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels. According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

5.11 Radiated Spurious Emission & Restricted bands

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Receiver Setup:	

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Peak	120 kHz	300kHz	Peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Setup:	



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. For below 1GHz part, through pre-scan, the worst case is the highest channel. Only the worst case is recorded in the report.
Test Results:	Pass

5.11.1 Radiated Emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg
1	39.30	8.86	11.83	20.69	40.00	-19.31	Peak	VERTICAL	100	21
2	62.00	9.23	12.29	21.52	40.00	-18.48	Peak	VERTICAL	100	51
3	109.03	8.54	12.77	21.31	43.50	-22.19	Peak	VERTICAL	100	130
4	408.95	8.73	19.38	28.11	46.00	-17.89	Peak	VERTICAL	100	119
5	530.10	9.52	22.12	31.64	46.00	-14.36	Peak	VERTICAL	100	16
6 pp	851.04	10.09	29.07	39.16	46.00	-6.84	Peak	VERTICAL	100	1

Remark:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Factor= Antenna Factor + Cable Factor – Preamplifier Factor,
Level = Read Level + Factor,
Over Limit=Level-Limit Line.

Test mode:	Transmitting	Horizontal



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg
1	54.64	9.60	13.82	23.42	40.00	-16.58	Peak	HORIZONTAL	100	77
2	110.96	10.88	12.60	23.48	43.50	-20.02	Peak	HORIZONTAL	100	33
3	225.31	9.49	14.23	23.72	46.00	-22.28	Peak	HORIZONTAL	100	76
4	429.52	10.11	19.83	29.94	46.00	-16.06	Peak	HORIZONTAL	100	320
5	651.94	9.91	23.39	33.30	46.00	-12.70	Peak	HORIZONTAL	100	210
6 pp	887.61	9.90	29.62	39.52	46.00	-6.48	Peak	HORIZONTAL	100	219

Remark:
The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Factor= Antenna Factor + Cable Factor – Preamplifier Factor,
Level = Read Level + Factor,
Over Limit=Level-Limit Line.

5.11.2 Transmitter Emission above 1GHz

Worse case mode:		GFSK(DH5)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390	55.54	-9.2	46.34	54	-7.66	Peak	H	1.5	304
2400	54.84	-9.39	45.45	54	-8.55	Peak	H	1.5	191
4804	52.90	-4.33	48.57	54	-5.43	Peak	H	1.5	263
7206	49.89	1.01	50.90	54	-3.10	Peak	H	1.5	15
2390	55.93	-9.2	46.73	54	-7.27	Peak	V	1.5	294
2400	54.83	-9.39	45.44	54	-8.56	Peak	V	1.5	119
4804	52.89	-4.33	48.56	54	-5.44	Peak	V	1.5	312
7206	49.69	1.01	50.70	54	-3.30	Peak	V	1.5	333

Worse case mode:		GFSK(DH5)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4882	52.05	-4.11	47.94	54	-6.06	peak	H	1.5	168
7323	50.45	1.51	51.96	54	-2.04	peak	H	1.5	332
4882	51.89	-4.11	47.78	54	-6.22	peak	V	1.5	347
7323	48.39	1.51	49.90	54	-4.10	peak	V	1.5	214

Worse case mode:		GFSK(DH5)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.5	56.54	-9.29	47.25	54	-6.75	Peak	H	1.5	126
4960	51.23	-4.04	47.19	54	-6.81	Peak	H	1.5	211
7440	50.51	1.57	52.08	54	-1.92	Peak	H	1.5	155
2483.5	56.05	-9.29	46.76	54	-7.24	Peak	V	1.5	85
4960	49.64	-4.04	45.60	54	-8.40	Peak	V	1.5	35
7440	50.40	1.57	51.97	54	-2.03	Peak	V	1.5	88

Worse case mode:		π /4DQPSK (2DH5)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2390	54.07	-9.2	44.87	74	-29.13	Peak	H	1.5	307
2400	55.07	-9.39	45.68	74	-28.32	Peak	H	1.5	139
4804	52.32	-4.33	47.99	74	-26.01	Peak	H	1.5	203
7206	49.38	1.01	50.39	74	-23.61	Peak	H	1.5	294
2390	53.45	-9.2	44.25	74	-29.75	Peak	V	1.5	337
2400	57.03	-9.39	47.64	74	-26.36	Peak	V	1.5	185
4804	53.34	-4.33	49.01	74	-24.99	Peak	V	1.5	271
7206	50.91	1.01	51.92	74	-22.08	Peak	V	1.5	154

Worse case mode:		π /4DQPSK (2DH5)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
4882	52.80	-4.11	48.69	74	-25.31	peak	H	1.5	159
7323	50.27	1.51	51.78	74	-22.22	peak	H	1.5	292
4882	52.39	-4.11	48.28	74	-25.72	peak	V	1.5	301
7323	48.34	1.51	49.85	74	-24.15	peak	V	1.5	20

Worse case mode:		π /4DQPSK (2DH5)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
2483.5	54.31	-9.29	45.02	74	-28.98	Peak	H	1.5	241
4960	52.25	-4.04	48.21	74	-25.79	Peak	H	1.5	221
7440	50.65	1.57	52.22	74	-21.78	Peak	H	1.5	126
2483.5	54.36	-9.29	45.07	74	-28.93	Peak	V	1.5	161
4960	51.21	-4.04	47.17	74	-26.83	Peak	V	1.5	323
7440	48.69	1.57	50.26	74	-23.74	Peak	V	1.5	292

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
   Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Emission

9KHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission

6.3 RF Conducted measurement



7 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details OF EUT for CQASZ20250400856E-01.

*** END OF REPORT ***