

TEST REPORT

Product Name : Haylou RS4 Plus
Brand Mark : HAYLOU
Model No. : Haylou-LS11-551
FCC ID : 2AMQ6-LS11-551
Report Number : BLA-EMC-202110-A4102
Date of Sample Receipt : 2021/10/21
Date of Test : 2021/10/22 to 2021/11/15
Date of Issue : 2021/11/15
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass


Prepared for:

Dongguan Liesheng Electronic Co., Ltd.
Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District,
Dongguan City, Guangdong, China.


Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:



Review by:



Approved by:



Date:

2021/11/15



REPORT REVISE RECORD

Version No.	Date	Description
00	2021/11/15	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY.....	5
2	GENERAL INFORMATION.....	6
3	GENERAL DESCRIPTION OF E.U.T.....	6
4	TEST ENVIRONMENT.....	7
5	TEST MODE.....	7
6	MEASUREMENT UNCERTAINTY.....	7
7	DESCRIPTION OF SUPPORT UNIT.....	8
8	LABORATORY LOCATION.....	8
9	TEST INSTRUMENTS LIST.....	9
10	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	13
10.1	LIMITS.....	13
10.2	BLOCK DIAGRAM OF TEST SETUP.....	13
10.3	PROCEDURE.....	13
10.4	TEST DATA.....	15
11	CONDUCTED BAND EDGES MEASUREMENT.....	17
11.1	LIMITS.....	17
11.2	BLOCK DIAGRAM OF TEST SETUP.....	17
11.3	TEST DATA.....	18
12	CONDUCTED SPURIOUS EMISSIONS.....	19
12.1	LIMITS.....	19
12.2	BLOCK DIAGRAM OF TEST SETUP.....	19
12.3	TEST DATA.....	20
13	POWER SPECTRUM DENSITY.....	21
13.1	LIMITS.....	21
13.2	BLOCK DIAGRAM OF TEST SETUP.....	21
13.3	TEST DATA.....	21
14	CONDUCTED PEAK OUTPUT POWER.....	22
14.1	LIMITS.....	22
14.2	BLOCK DIAGRAM OF TEST SETUP.....	22
14.3	TEST DATA.....	23

15 MINIMUM 6DB BANDWIDTH.....	24
15.1 LIMITS.....	24
15.2 BLOCK DIAGRAM OF TEST SETUP.....	24
15.3 TEST DATA.....	24
16 ANTENNA REQUIREMENT.....	25
16.1 CONCLUSION.....	25
17 RADIATED SPURIOUS EMISSIONS.....	26
17.1 LIMITS.....	26
17.2 BLOCK DIAGRAM OF TEST SETUP.....	27
17.3 PROCEDURE.....	27
17.4 TEST DATA.....	29
18 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	37
18.1 LIMITS.....	37
18.2 BLOCK DIAGRAM OF TEST SETUP.....	38
18.3 PROCEDURE.....	38
18.4 TEST DATA.....	40
19 APPENDIX.....	44
APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....	59
APPENDIX B: PHOTOGRAPHS OF EUT.....	61

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

2 GENERAL INFORMATION

Applicant	Dongguan Liesheng Electronic Co., Ltd.
Address	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China.
Manufacturer	Dongguan Liesheng Electronic Co., Ltd.
Address	Room 401-410, Building 1, No.86 Hongtu Road, Nancheng District, Dongguan City, Guangdong, China.
Factory	Dongguan Zhengrong Electronic Co., Ltd.
Address	No.4, Shugang Avenue, Hongmei Town, Dongguan City, Guangdong
Product Name	Haylou RS4 Plus
Test Model No.	Haylou-LS11-551

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.0
Software Version	V1.0
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Internal Antenna
Antenna Gain:	-0.92 dBi (provided by applicant)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.3V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode

Remark: Only the data of the worst mode would be recorded in this report.

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30MHz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter (UGREEN)	UGREEN	CD112	N/A	N/A
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021
Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2021	5/7/2022
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Receiver	R&S	ESR7	101199	5/7/2021	5/6/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2021	7/13/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2021	7/13/2022
Amplifier	SKET	LNPA-0118-45	N/A	7/14/2021	7/13/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2021	2/13/2022

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021

Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of Conducted Peak Output Power

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021
Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of Dwell Time

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021
Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of Hopping Channel Number

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021
Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of Carrier Frequencies Separation

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021
Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of 20dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Spectrum	Agilent	N9020A	MY49100060	12/18/2020	12/17/2021
Signal Generator	Agilent	N5182A	MY49060650	12/18/2020	12/17/2021
Signal Generator	Agilent	E8257D	MY44320250	5/7/2021	5/6/2022

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	6/10/2021	6/9/2022
Receiver	R&S	ESPI3	101082	5/7/2021	5/7/2022
LISN	R&S	ENV216	3560.6550.15	7/4/2021	7/3/2022
LISN	AT	AT166-2	AKK1806000003	12/18/2020	12/17/2021
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2021	5/7/2022

Spectrum	R&S	FSP40	100817	7/4/2021	7/3/2022
Receiver	R&S	ESR7	101199	5/7/2021	5/6/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2021	7/13/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2021	7/13/2022
Amplifier	SKET	LNPA-0118-45	N/A	7/4/2021	7/3/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2021	2/13/2022

BlueAsia

10 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

10.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.


- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

10.4 TEST DATA

[TestMode: TX]; [Line: Line] [Power:AC120V/60Hz]



Site: Limit: FCC Class B Conduction(QP) Phase: **L1** Temperature: (C)
EUT: Power: Humidity: %RH
M/N: Haylou-LS11-551
Mode: TX mode
Note:

No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		Level	Factor	ment		dB	Detector	Comment
1	0.1700	8.89	10.16	19.05	64.96	-45.91	QP	
2	0.1700	3.13	10.16	13.29	54.96	-41.67	AVG	
3	0.6380	14.38	9.87	24.25	56.00	-31.75	QP	
4 *	0.6380	5.87	9.87	15.74	46.00	-30.26	AVG	
5	1.5300	8.57	9.93	18.50	56.00	-37.50	QP	
6	1.5300	2.35	9.93	12.28	46.00	-33.72	AVG	
7	2.5540	6.53	9.96	16.49	56.00	-39.51	QP	
8	2.5540	-0.28	9.96	9.68	46.00	-36.32	AVG	
9	4.9980	3.91	10.02	13.93	56.00	-42.07	QP	
10	4.9980	-3.72	10.02	6.30	46.00	-39.70	AVG	
11	10.4980	4.67	10.21	14.88	60.00	-45.12	QP	
12	10.4980	-0.20	10.21	10.01	50.00	-39.99	AVG	


*:Maximum data x:Over limit !:over margin

〈Reference Only

Test Result: Pass

[TestMode: TX]; [Line: Nutral] [Power:AC120V/60Hz]

Conducted Emission Measurement


Site Phase: **N** Temperature: (C)

Limit: FCC Class B Conduction(QP) Power: Humidity: %RH

EUT:

M/N: Haylou-LS11-551

Mode: TX mode

Note:

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
			dBuV	dB	dBuV	dB			
1		0.2819	7.80	9.77	17.57	60.76	-43.19	QP	
2		0.2819	2.38	9.77	12.15	50.76	-38.61	AVG	
3		0.6380	14.65	9.80	24.45	56.00	-31.55	QP	
4 *		0.6380	7.15	9.80	16.95	46.00	-29.05	AVG	
5		1.6820	8.93	9.85	18.78	56.00	-37.22	QP	
6		1.6820	2.94	9.85	12.79	46.00	-33.21	AVG	
7		2.7500	6.85	9.89	16.74	56.00	-39.26	QP	
8		2.7500	-0.97	9.89	8.92	46.00	-37.08	AVG	
9		4.9340	2.66	9.95	12.61	56.00	-43.39	QP	
10		4.9340	-5.27	9.95	4.68	46.00	-41.32	AVG	
11		13.3740	-1.58	10.27	8.69	60.00	-51.31	QP	
12		13.3740	-3.27	10.27	7.00	50.00	-43.00	AVG	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass


11 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


12 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25 °C
Humidity	52%

12.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

12.2 BLOCK DIAGRAM OF TEST SETUP



12.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


13 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

13.1 LIMITS

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

13.2 BLOCK DIAGRAM OF TEST SETUP



13.3 TEST DATA

Pass: Please Refer To Appendix: For Details


14 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

14.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


15 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Sven
Temperature	25°C
Humidity	52%

15.1 LIMITS

Limit: ≥ 500 kHz

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 TEST DATA

Pass: Please Refer To Appendix: For Details

16 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

16.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.92dBi.



17 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX;TX Low channel;TX middle channel;TX high channel
Test Mode (Final Test)	TX;TX middle channel;TX Low channel;TX high channel
Tester	Sven
Temperature	25°C
Humidity	52%

17.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

17.4 TEST DATA

[TestMode: TX]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202110-A41
EUT:	Test Engineer: Charlie
M/N: Haylou-LS11-551	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2021-10-26 20:17:10




No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	40.913MHz	40.0	24.5	-15.5	0.4	24.1	QP	Hor	100.0	148.0
2*	67.951MHz	40.0	21.9	-18.1	0.1	21.8	QP	Hor	100.0	68.0
3*	140.338MHz	43.5	24.2	-19.3	0.5	23.7	QP	Hor	100.0	344.0
4*	238.429MHz	46.0	24.7	-21.3	2.0	22.7	QP	Hor	100.0	332.0
5*	347.675MHz	46.0	25.5	-20.5	-0.1	25.6	QP	Hor	100.0	19.0
6*	527.489MHz	46.0	30.2	-15.8	1.0	29.2	QP	Hor	100.0	294.0

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab (RE #1)	Project: BLA-EMC-202110-A41
EUT:	Test Engineer: Charlie
M/N: Haylou-LS11-551	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2021-10-26 20:19:17



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	36.063MHz	40.0	24.0	-16.0	0.3	23.7	QP	Ver	100.0	149.0
2*	56.554MHz	40.0	24.3	-15.7	0.7	23.6	QP	Ver	100.0	287.0
3*	148.340MHz	43.5	24.7	-18.8	1.2	23.5	QP	Ver	100.0	4.0
4*	236.004MHz	46.0	24.9	-21.1	2.3	22.6	QP	Ver	100.0	10.0
5*	292.870MHz	46.0	24.7	-21.3	0.8	23.9	QP	Ver	100.0	135.0
6*	594.176MHz	46.0	32.7	-13.3	1.6	31.1	QP	Ver	100.0	255.0

Test Result: Pass

[TestMethod: TX Low channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-L

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3831.750	43.09	7.25	50.34	74.00	-23.66	peak	
2		4804.000	43.23	3.71	46.94	74.00	-27.06	peak	
3		7206.000	39.80	5.96	45.76	74.00	-28.24	peak	
4		8261.500	41.54	8.23	49.77	74.00	-24.23	peak	
5		9608.000	37.82	9.29	47.11	74.00	-26.89	peak	
6	*	11410.500	39.81	11.78	51.59	74.00	-22.41	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data #5

2021/11/6

14:42:04



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-L

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		3643.750	42.53	7.76	50.29	74.00	-23.71	peak
2		4804.000	39.24	3.71	42.95	74.00	-31.05	peak
3		7206.000	40.32	5.96	46.28	74.00	-27.72	peak
4		8050.000	41.08	8.01	49.09	74.00	-24.91	peak
5		9608.000	38.17	9.29	47.46	74.00	-26.54	peak
6	*	11328.250	39.76	11.86	51.62	74.00	-22.38	peak

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Project No.: RE

Data #14

2021/11/6

15:29:13



Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-M

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
			MHz	dBuV	dB/m	dBuV/m	dB	
1		3843.500	42.69	7.12	49.81	74.00	-24.19	peak
2		4960.000	40.86	3.75	44.61	74.00	-29.39	peak
3		7440.000	38.58	6.86	45.44	74.00	-28.56	peak
4		8144.000	41.28	8.13	49.41	74.00	-24.59	peak
5		9920.000	37.12	10.16	47.28	74.00	-26.72	peak
6	*	11011.000	39.70	11.99	51.69	74.00	-22.31	peak

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMethod: TX middle channel]; [Polarity: Vertical]

Radiated Emission Measurement

Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-M

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		3643.750	42.28	7.76	50.04	74.00	-23.96	peak
2		4960.000	39.13	3.75	42.88	74.00	-31.12	peak
3		7440.000	39.24	6.86	46.10	74.00	-27.90	peak
4		8238.000	41.29	8.22	49.51	74.00	-24.49	peak
5		9920.000	36.91	10.16	47.07	74.00	-26.93	peak
6	*	11328.250	39.51	11.86	51.37	74.00	-22.63	peak

*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Test Result: Pass

[TestMethod: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement

Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		3690.750	42.06	7.72	49.78	74.00	-24.22	peak	
2		4960.000	40.21	3.75	43.96	74.00	-30.04	peak	
3		7440.000	39.25	6.86	46.11	74.00	-27.89	peak	
4		8226.250	40.43	8.22	48.65	74.00	-25.35	peak	
5		9920.000	38.03	10.16	48.19	74.00	-25.81	peak	
6	*	12409.250	39.75	11.80	51.55	74.00	-22.45	peak	

*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data #11

2021/11/6

15:09:56



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-H

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
1		3831.750	42.99	7.25	50.24	74.00	-23.76	peak
2		4960.000	40.10	3.75	43.85	74.00	-30.15	peak
3		7440.000	38.62	6.86	45.48	74.00	-28.52	peak
4		8285.000	40.81	8.24	49.05	74.00	-24.95	peak
5		9920.000	37.76	10.16	47.92	74.00	-26.08	peak
6	*	11293.000	39.60	11.91	51.51	74.00	-22.49	peak

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

18 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX;TX Low channel;TX high channel
Test Mode (Final Test)	TX;TX Low channel;TX high channel
Tester	Sven
Temperature	25°C
Humidity	52%

18.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

18.2 BLOCK DIAGRAM OF TEST SETUP



18.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

18.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]




Site: FCC Part15 (PK) Polarization: **Horizontal** Temperature: (C)
 Limit: FCC Part15 (PK) Power: Humidity: %RH
 EUT: shoubiao
 M/N: Haylou-LSII-551
 Mode: TX-L
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB/m	dBuV/m	dB			
1		2310.000	42.87	-4.61	38.26	74.00	-35.74	peak	
2	*	2384.765	58.08	-4.29	53.79	74.00	-20.21	peak	
3		2384.765	32.76	-4.29	28.47	54.00	-25.53	AVG	
4		2390.000	57.56	-4.27	53.29	74.00	-20.71	peak	
5		2390.000	33.52	-4.27	29.25	54.00	-24.75	AVG	

*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]
Radiated Emission Measurement

Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-L

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		2310.000	43.89	-4.61	39.28	74.00	-34.72	peak
2	*	2390.000	46.20	-4.27	41.93	74.00	-32.07	peak


*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site: Limit: FCC Part15 (PK) Polarization: **Horizontal** Temperature: (C)
EUT: shoubiao Power: Humidity: %RH
M/N: Haylou-LSII-551
Mode: TX-H
Note:

No.	Mk.	Reading		Correct Factor	Measure- ment	Limit	Over		Comment	
		Freq.	Level				dB/m	dBuV/m	dB	Detector
1	*	2483.500	59.16	-3.84	55.32	74.00	-18.68		peak	
2		2483.500	38.35	-3.84	34.51	54.00	-19.49		AVG	
3		2484.028	58.69	-3.84	54.85	74.00	-19.15		peak	
4		2484.028	35.14	-3.84	31.30	54.00	-22.70		AVG	
5		2500.000	47.35	-3.78	43.57	74.00	-30.43		peak	

*:Maximum data x:Over limit !:over margin

〈Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]


Radiated Emission Measurement

Project No.: RE

Data :#10

2021/11/6

15:06:17



Site

Polarization: *Vertical*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: shoubiao

M/N: Haylou-LSII-551

Mode: TX-H

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
1	*	2483.500	48.12	-3.84	44.28	74.00	-29.72	peak
2		2500.000	43.22	-3.78	39.44	74.00	-34.56	peak

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

19 APPENDIX


Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-2.126	-2.126	30	Pass
NVNT	BLE 1M	2442	Ant1	-1.95	-1.95	30	Pass
NVNT	BLE 1M	2480	Ant1	-2.119	-2.119	30	Pass

Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2442MHz Ant1




Power NVNT BLE 1M 2480MHz Ant1




-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.695	0.5	Pass
NVNT	BLE 1M	2442	Ant1	0.646	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.662	0.5	Pass

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1


-6dB Bandwidth NVNT BLE 1M 2442MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.025236498
NVNT	BLE 1M	2442	Ant1	1.040741531
NVNT	BLE 1M	2480	Ant1	1.027558396

OBW NVNT BLE 1M 2402MHz Ant1


OBW NVNT BLE 1M 2442MHz Ant1



OBW NVNT BLE 1M 2480MHz Ant1



Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-10.931	8	Pass
NVNT	BLE 1M	2442	Ant1	-10.894	8	Pass
NVNT	BLE 1M	2480	Ant1	-11.018	8	Pass

PSD NVNT BLE 1M 2402MHz Ant1


PSD NVNT BLE 1M 2442MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1




Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-48.9	-30	Pass
NVNT	BLE 1M	2480	Ant1	-51.95	-30	Pass


Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref




Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-43.13	-30	Pass
NVNT	BLE 1M	2442	Ant1	-42.95	-30	Pass
NVNT	BLE 1M	2480	Ant1	-42.06	-30	Pass

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2442MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Conducted Emissions at AC Power Line (150kHz-30MHz)



Bluex



APPENDIX B: PHOTOGRAPHS OF EUT

(Reference to the test report No. BLA-EMC-202110-A4101)

----END OF REPORT----

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia