

## RF Exposure Evaluation Statement

**Product Name:** Haylou Wireless Earbuds

**Model No.:** Haylou-T17

**FCC ID:** 2AMQ6-T17

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

## Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$

$[\sqrt{f}(\text{GHz})] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- ☐  $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- ☐ Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- ☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

| Operational Mode: BDR (GFSK worst case)                 |                                           |                        |                       |      |                  |                     |
|---------------------------------------------------------|-------------------------------------------|------------------------|-----------------------|------|------------------|---------------------|
| Channel                                                 | Maximum Peak Conducted Output Power (dBm) | Tune up tolerance (dB) | Maximum tune-up Power |      | Calculated value | Exclusion threshold |
|                                                         |                                           |                        | (dBm)                 | (mW) |                  |                     |
| 2402MHZ                                                 | 5.88                                      | ±1                     | 6.88                  | 4.88 | 1.51             | 3.0                 |
| 2441MHz                                                 | 5.42                                      | ±1                     | 6.42                  | 4.39 | 1.37             |                     |
| 2480MHz                                                 | 4.85                                      | ±1                     | 5.85                  | 3.85 | 1.21             |                     |
| Conclusion: the calculated value ≤3.0, SAR is exempted. |                                           |                        |                       |      |                  |                     |