

TEST REPORT

Product Name : Haylou-T19 True Wireless Earbuds
Brand Mark : N/A
Model No. : Haylou-T19, Haylou-T19(R)
FCC ID: 2AMQ6-T19R
Report Number : BLA-EMC-202004-A9703
Date of Sample Receipt : 2020/5/13
Date of Test : 2020/5/15 to 2020/5/22
Date of Issue : 2020/5/22
Test Standard : 47 CFR Part 1.1307, Part 2.1093, KDB
447498
Test Result : Pass

Prepared for:

Dongguan Liesheng Electronic Co., Ltd.
13/F, Project Phrase 2 of GaoshengTechTower, No.5, Longxi
Road, Nancheng, Dongguan, Guangdong, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
IOT Test Centre of BlueAsia

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China

TEL: +86-755-28682673

FAX: +86-755-28682673

Compiled by:

hason

Review by:

Sweet. Liang

Approved by:

Jmen Li

Date:

2020/5/22



REPORT REVISE RECORD

Version No.	Date	Description
00	2020/5/22	Original

1.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

1.2 EUT RF EXPOSURE EVALUATION

Operational Mode: WORSE CASE						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power(dBm)	Maximum tune-up Power(mW)	Calculated value	Exclusion threshold
2402MHz	1.39	± 1	2.39	1.73	0.54	3
2441MHz	0.01	± 1	1.01	1.26	0.40	3
2480MHz	-0.75	± 1	0.25	1.06	0.33	3

Conclusion: the calculated value ≤ 3.0 , SAR is exempted.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia