

# TEST REPORT

Applicant Name: United Automotive Electronic Systems Co., Ltd.  
Address: No.555 Rong Qiao Road, Pudong New Area, 201206 Shanghai,  
P.R. China  
Report Number: 2501V02116E-RF-00  
FCC ID: 2AMR2-F03H00M4AH

**Test Standard (s)**

FCC PART 15.247

**Sample Description**

Product Type: BNCM  
Model No.: PK-BLE-1.0  
Multiple Model(s) No.: N/A  
Trade Mark: UAES  
Date Received: 2025-07-16  
Issue Date: 2025-09-11

Test Result:	Pass <sup>▲</sup>
--------------	-------------------

▲ In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

Allen. Bai

Allen Bai  
RF Engineer

**Approved By:**

Nancy Wang

Nancy Wang  
RF Supervisor

Note: The information marked\* is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

**Bay Area Compliance Laboratories Corp. (Shenzhen)**

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China  
Tel: +86-755-33320018 Fax: +86-755-33320008 [www.baclcorp.com.cn](http://www.baclcorp.com.cn)

## TABLE OF CONTENTS

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>GENERAL INFORMATION .....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION .....</b>	<b>6</b>
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>9</b>
<b>REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>10</b>
AC LINE CONDUCTED EMISSIONS.....	10
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS .....	12
6 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH.....	15
PEAK OUTPUT POWER MEASUREMENT .....	17
POWER SPECTRAL DENSITY .....	18
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	19
CONDUCTED SPURIOUS EMISSION.....	20
DUTY CYCLE.....	21
<b>ANTENNA REQUIREMENT .....</b>	<b>22</b>
<b>TEST DATA AND RESULTS .....</b>	<b>23</b>
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS .....	23
6dB EMISSION BANDWIDTH.....	61
99% OCCUPIED BANDWIDTH .....	63
MAXIMUM CONDUCTED OUTPUT POWER .....	65
POWER SPECTRAL DENSITY .....	67
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	69
DUTY CYCLE.....	70
CONDUCTED SPURIOUS EMISSION.....	72
<b>RF EXPOSURE EVALUATION .....</b>	<b>74</b>
<b>EUT PHOTOGRAPHS .....</b>	<b>76</b>
<b>TEST SETUP PHOTOGRAPHS .....</b>	<b>77</b>

**DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501V02116E-RF-00	Original Report	2025-09-11

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>Frequency Range</b>	2402~2480MHz
<b>Maximum Conducted Output Peak Power</b>	BLE 1M:6.91dBm;BLE 2M:6.88dBm
<b>Modulation Technique</b>	GFSK
<b>Antenna Specification<sup>#</sup></b>	5.15dBi (provided by the applicant)
<b>Voltage Range</b>	DC 5V
<b>Sample serial number</b>	36RB-1 for Radiated Emissions Test 36RB-2 for RF Conducted Test (Assigned by BACL, Shenzhen)
<b>Sample/EUT Status</b>	Good condition
<b>Adapter Information</b>	N/A

### Objective

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209, 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Power Spectral Density		0.90dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.63dB(k=2, 95% level of confidence)
	150 kHz~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	<b>2402</b>	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
<b>19</b>	<b>2440</b>	<b>39</b>	<b>2480</b>

EUT was tested with Channel 0, 19 and 39.

### EUT Exercise Software

Exercise Software <sup>#</sup>	Btool.exe		
Power Level <sup>#</sup>			
Mode	Low Channel	Middle Channel	High Channel
BLE 1M	Default	Default	Default
BLE 2M	Default	Default	Default

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
insteck	DC Power	GPS-3030DD	EM832096

**External I/O Cable**


Cable Description	Length (m)	From Port	To
Unshielded Detachable DC cable	3.0	EUT	DC Power

**Block Diagram of Test Setup**

For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



## SUMMARY OF TEST RESULTS

Test Rules	Description of Test	Result
§1.1307 (b) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
C63.10 §11.6	Duty Cycle	/

Not Applicable: The EUT cannot connect directly to the public power network.

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2025/04/29	2026/04/28
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	XH500C	J-10M-A	2025/04/29	2026/04/28
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2025/03/26	2026/03/25
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D (1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Filter Switch Unit	DT7220FSU	DS79906	2024/09/09	2025/09/08
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2025/04/29	2026/04/28
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
<b>RF Conducted Test</b>					
Rohde&Schwarz	Spectrum Analyzer	FSV40-N	102259	2024/12/04	2025/12/03
R&S	Spectrum Analyzer	FSU26	200120	2024/12/04	2025/12/03
Unknown	10dB Attenuator	Unknown	F-03-EM190	2025/06/26	2026/06/25

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


## REQUIREMENTS AND TEST PROCEDURES

### AC Line Conducted Emissions

#### Applicable Standard

FCC§15.207

#### EUT Setup



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

#### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

## Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).


## Unwanted Emission Frequencies and Restricted Bands

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;


### EUT Setup

**9 kHz-30MHz:**



**30MHz-1GHz:**



**Above 1GHz:**

The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak

1-25GHz:  
Pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	1 kHz	Peak
	<98%	1MHz	≥1/Ton	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	≥1/Ton	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

### Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

## 6 dB Emission Bandwidth & 99% Occupied Bandwidth

### Standard Applicable

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.8.1 & Clause 6.9.3

The steps for the first option are as follows:


- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “–6 dB down amplitude”. If a marker is below this “–6 dB down amplitude” value, then it shall be as close as possible to this value.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.

g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



## Peak Output Power Measurement

### Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.9.1.1

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the  $RBW \geq DTS$  bandwidth.
- b) Set  $VBW \geq [3 \times RBW]$ .
- c) Set span  $\geq [3 \times RBW]$ .
- d) Sweep time = No faster than coupled (auto) time.
- e) Detector = peak.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

## Power Spectral Density

### Applicable Standard

According to FCC §15.247(e):


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span  $>1.5$  times the DTS bandwidth.
- c) Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- e) Detector = peak.
- f) Sweep time = No faster than coupled (auto) time.
- g) Trace mode = max-hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

## 100 kHz Bandwidth of Frequency Band Edge

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

### Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.11.3


Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution

- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



## Conducted Spurious Emission

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

Test Method: ANSI C63.10-2020 Clause 11.11.3


Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution

- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.




## Duty Cycle

### Test Procedure

According to ANSI C63.10-2020 Section 11.6

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
  - 1) Set the center frequency of the instrument to the center frequency of the transmission.
  - 2) Set  $RBW \geq OBW$  if possible; otherwise, set  $RBW$  to the largest available value.
  - 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
  - 4) The zero-span measurement method shall not be used unless both  $RBW$  and  $VBW$  are  $> 50/T$  and the number of sweep points across duration  $T$  exceeds 100. (For example, if  $VBW$  and/or  $RBW$  are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)



## **ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

### **Antenna Connector Construction**

The EUT has an internal antenna arrangement, which was permanently attached, the antenna gain<sup>#</sup> is 5.15dBi, fulfill the requirement of this section. Please refer to the EUT photos.

### **Result: Compliant**

## TEST DATA AND RESULTS


### Unwanted Emission Frequencies and Restricted Bands

#### Environmental Conditions

<b>Temperature (°C)</b>	24.6-25.1	<b>Relative Humidity (%)</b>	51-58
<b>ATM Pressure (kPa):</b>	100.6-101.2	<b>Test engineer:</b>	Anson Su&Leon Guo
<b>Test date:</b>	2025/08/15-2025/08/16		
<b>EUT operation mode:</b>	Below 1GHz: Transmitting(Maximum output power mode, BLE 1M Mode 2402MHz) Above 1GHz: Transmitting		
<b>Note:</b>	<ol style="list-style-type: none"><li>1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded.</li><li>2. For the radiated spurious emission below 1GHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.</li><li>3. After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.</li></ol>		

**Below 1GHz:**


9kHz-150kHz



Site : Chamber A  
Condition : 3m  
Project Number : 2501V02116E-RF  
Test Mode : BLE Transmitting  
Detector: Peak RBW/VBW: 0.3/1kHz  
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	0.010	32.36	24.69	57.05	127.85	-70.80	Peak
2	0.019	30.57	21.98	52.55	121.99	-69.44	Peak
3	0.034	28.04	21.48	49.52	116.88	-67.36	Peak
4	0.060	25.37	21.09	46.46	112.00	-65.54	Peak
5	0.087	22.91	21.81	44.72	108.81	-64.09	Peak
6	0.132	20.12	19.63	39.75	105.20	-65.45	Peak


150kHz-30MHz



Site : Chamber A  
Condition : 3m  
Project Number : 2501V02116E-RF  
Test Mode : BLE Transmitting  
Detector: Peak RBW/VBW: 10/30kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	0.415	8.02	34.27	42.29	95.25 -52.96 Peak
2	0.544	5.86	32.53	38.39	72.88 -34.49 Peak
3	0.718	3.71	34.21	37.92	70.41 -32.49 Peak
4	0.962	1.48	31.93	33.41	67.82 -34.41 Peak
5	1.355	0.21	31.47	31.68	64.78 -33.10 Peak
6	1.902	-1.32	31.15	29.83	69.54 -39.71 Peak


## 30MHz-1GHz\_Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501V02116E-RF  
Test Mode : BLE Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
		MHz	dB/m	dBuV	dBuV/m	dB
1	128.96	-11.21	29.44	18.23	43.50	-25.27 Peak
2	218.69	-14.19	40.63	26.44	46.00	-19.56 Peak
3	232.12	-13.73	39.47	25.74	46.00	-20.26 Peak
4	267.78	-12.03	42.55	30.52	46.00	-15.48 Peak
5	284.73	-11.23	49.44	38.21	46.00	-7.79 Peak
6	375.94	-9.26	31.77	22.51	46.00	-23.49 Peak

## 30MHz-1GHz\_Verical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501V02116E-RF  
Test Mode : BLE Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
		MHz	dB/m	dBuV	dBuV/m		
1		36.14	-9.59	33.31	23.72	40.00	-16.28 Peak
2		125.94	-11.12	28.58	17.46	43.50	-26.04 Peak
3		218.69	-14.19	34.83	20.64	46.00	-25.36 Peak
4		284.73	-11.23	44.79	33.56	46.00	-12.44 Peak
5		337.22	-10.48	33.15	22.67	46.00	-23.33 Peak
6		431.98	-7.78	32.07	24.29	46.00	-21.71 Peak

**Above 1GHz:**

Frequency (MHz)	Reading (dB $\mu$ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
<b>BLE 1M</b>							
Low Channel							
4804	66.31	PK	H	-7.79	58.52	74	-15.48
4804	59.36	AV	H	-7.79	51.57	54	-2.43
4804	60.01	PK	V	-7.79	52.22	74	-21.78
Middle Channel							
4880	64.80	PK	H	-7.59	57.21	74	-16.79
4880	57.80	AV	H	-7.59	50.21	54	-3.79
4880	57.63	PK	V	-7.59	50.04	74	-23.96
High Channel							
4960	66.42	PK	H	-7.56	58.86	74	-15.14
4960	60.53	AV	H	-7.56	52.97	54	-1.03
4960	60.13	PK	V	-7.56	52.57	74	-21.43
<b>BLE 2M</b>							
Low Channel							
4804	66.20	PK	H	-7.79	58.41	74	-15.59
4804	60.32	AV	H	-7.79	52.53	54	-1.47
4804	60.30	PK	V	-7.79	52.51	74	-21.49
Middle Channel							
4880	64.97	PK	H	-7.59	57.38	74	-16.62
4880	58.83	AV	H	-7.59	51.24	54	-2.76
4880	57.82	PK	V	-7.59	50.23	74	-23.77
High Channel							
4960	66.19	PK	H	-7.56	58.63	74	-15.37
4960	60.23	AV	H	-7.56	52.67	54	-1.33
4960	59.56	PK	V	-7.56	52.00	74	-22.00

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

The test result of peak was less than the limit of average, so just peak values were recorded.

**Test plots****Band Edge**


Left Band edge\_Horizontal\_Peak\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2402

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2389.797	-10.98	75.77	64.79	74.00	-9.21	Peak
2	2390.000	-10.98	74.24	63.26	74.00	-10.74	Peak


## Left Band edge\_Horizontal\_Average\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:10kHz Detector:Peak  
Note : BLE\_1M\_2402

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	2361.649	-10.91	50.39	39.48	54.00	-14.52	Average
2	2390.000	-10.98	49.47	38.49	54.00	-15.51	Average


## Left Band edge\_Vertical\_Peak\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2402

	Freq	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	2389.830	-10.98	73.92	62.94	74.00	-11.06 Peak
2	2390.000	-10.98	71.56	60.58	74.00	-13.42 Peak


## Left Band edge\_Vertical\_Average\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:10kHz Detector:Peak  
Note : BLE\_1M\_2402

	Freq	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	2389.017	-10.98	50.78	39.80	54.00	-14.20 Average
2	2390.000	-10.98	50.35	39.37	54.00	-14.63 Average


## Right Band edge\_Horizontal\_Peak\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2483.500	-10.97	76.09	65.12	74.00	-8.88	Peak
2	2483.551	-10.97	83.11	72.14	74.00	-1.86	Peak


## Right Band edge\_Horizontal\_Average\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:10kHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	2483.500	-10.97	51.51	40.54	54.00	-13.46	Average
2	2486.671	-10.97	51.94	40.97	54.00	-13.03	Average


## Right Band edge\_Vertical\_Peak\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

	Freq	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dB	
1	2483.500	-10.97	82.96	71.99	74.00	-2.01 Peak
2	2483.513	-10.97	84.28	73.31	74.00	-0.69 Peak

## Right Band edge\_Vertical\_Average\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF


Tester : Leon Guo

Spectrum setting: Average reading: RBW:1MHz VBW:10kHz Detector:Peak

Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	2483.500	-10.97	52.16	41.19	54.00	-12.81	Average
2	2483.573	-10.97	52.62	41.65	54.00	-12.35	Average


## Left Band edge\_Horizontal\_Peak\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2402

	Freq	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dB	
1	2389.863	-10.98	75.65	64.67	74.00	-9.33 Peak
2	2390.000	-10.98	75.34	64.36	74.00	-9.64 Peak


## Left Band edge\_Horizontal\_Average\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:20kHz Detector:Peak  
Note : BLE\_2M\_2402

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	2333.305	-10.85	50.46	39.61	54.00	-14.39	Average
2	2390.000	-10.98	49.96	38.98	54.00	-15.02	Average


## Left Band edge\_Vertical\_Peak\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2402

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	2389.927	-10.98	72.15	61.17	74.00	-12.83	Peak
2	2390.000	-10.98	71.50	60.52	74.00	-13.48	Peak


## Left Band edge\_Vertical\_Average\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:20kHz Detector:Peak  
Note : BLE\_2M\_2402

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2322.043	-10.81	50.35	39.54	54.00	-14.46	Average
2	2390.000	-10.98	50.26	39.28	54.00	-14.72	Average


## Right Band edge\_Horizontal\_Peak\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	2483.500	-10.97	79.84	68.87	74.00	-5.13	Peak
2	2483.640	-10.97	83.51	72.54	74.00	-1.46	Peak


## Right Band edge\_Horizontal\_Average\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:20kHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2483.500	-10.97	55.13	44.16	54.00	-9.84	Average
2	2483.625	-10.97	55.26	44.29	54.00	-9.71	Average


## Right Band edge\_Vertical\_Peak\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	2483.500	-10.97	81.52	70.55	74.00	-3.45	Peak
2	2483.551	-10.97	84.74	73.77	74.00	-0.23	Peak

## Right Band edge\_Vertical\_Average\_BLE 2M




Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:20kHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	2483.500	-10.97	56.10	45.13	54.00	-8.87	Average
2	2483.543	-10.97	57.39	46.42	54.00	-7.58	Average

**1-25GHz (Listed with the worst margin test plot)**


1-4GHz Horizontal BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dB <sub>uV</sub>	Line	dB <sub>uV/m</sub>
1		3913.739	-9.70	57.02	47.32	74.00	-26.68 Peak


## 1-4GHz\_Vertical\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq Factor	MHz	Read Level		Limit Level		Over Line	Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m			
1	3579.573	-10.00	57.63	47.63	74.00	-26.37	Peak	


## 4-18GHz\_Horizontal\_Peak\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4960.000	-7.56	66.42	58.86	74.00	-15.14	Peak
2	17838.980	11.57	49.21	60.78	74.00	-13.22	Peak


## 4-18GHz\_Horizontal\_Average\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:10kHz Detector:Peak  
Note : BLE\_1M\_2480

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB
1	4960.000	-7.56	60.53	52.97	54.00	-1.03	Average
2	17979.000	13.09	33.90	46.99	54.00	-7.01	Average


## 4-18GHz\_Vertical\_Peak\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4960.000	-7.56	60.13	52.57	74.00	-21.43	Peak
2	17868.730	12.12	48.75	60.87	74.00	-13.13	Peak


## 4-18GHz\_Vertical\_Average\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:10kHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1 17915.990	12.78	33.74	46.52	54.00	-7.48 Average


## 18-25GHz\_Horizontal\_BLE 1M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	
1	19405.680	15.45	36.98	52.43	74.00	-21.57	Peak


## 18-25GHz\_Vertical\_BLE 1M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_1M\_2480

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	19686.210	15.34	36.38	51.72	74.00 -22.28 Peak


## 1-4GHz\_Horizontal\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	3632.454	-9.92	56.96	47.04	74.00	-26.96	Peak


## 1-4GHz\_Vertical\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	3629.454	-9.93	56.76	46.83	74.00	-27.17	Peak


## 4-18GHz\_Horizontal\_Peak\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4960.000	-7.56	66.19	58.63	74.00	-15.37	Peak
2	17929.990	12.86	49.66	62.52	74.00	-11.48	Peak


## 4-18GHz\_Horizontal\_Average\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:20kHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Limit		
1	4960.000	-7.56	60.23	52.67	54.00	-1.33	Average
2	17957.990	13.00	33.11	46.11	54.00	-7.89	Average


## 4-18GHz\_Vertical\_Peak\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4960.000	-7.56	59.56	52.00	74.00	-22.00	Peak
2	17987.750	13.13	48.39	61.52	74.00	-12.48	Peak


## 4-18GHz\_Vertical\_Average\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Average reading: RBW:1MHz VBW:20kHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
17993.000	13.17	33.00	46.17	54.00	-7.83 Average


## 18-25GHz\_Horizontal\_BLE 2M



Condition : Horizontal  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	18648.080	14.75	36.40	51.15	74.00	-22.85	Peak

## 18-25GHz\_Vertical\_BLE 2M



Condition : Vertical  
Project No. : 2501V02116E-RF  
Tester : Leon Guo  
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak  
Note : BLE\_2M\_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	19413.180	15.45	37.88	53.33	74.00	-20.67	Peak

**RF Conducted data****6dB Emission Bandwidth****Test Information:**

<b>Sample No.:</b>	36RB-2	<b>Test Date:</b>	2025/08/07
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	24.8	<b>Relative Humidity:</b> (%)	52	<b>ATM Pressure:</b> (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------



**Test Data:****BLE 1M**

<b>Channel</b>	<b>Result (MHz)</b>	<b>Limit (MHz)</b>	<b>Verdict</b>
Low Channel	0.555	≥0.5	Pass
Middle Channel	<b>0.575</b>	≥0.5	Pass
High Channel	0.565	≥0.5	Pass

**BLE 2M**

<b>Channel</b>	<b>Result (MHz)</b>	<b>Limit (MHz)</b>	<b>Verdict</b>
Low Channel	<b>0.900</b>	≥0.5	Pass
Middle Channel	<b>0.900</b>	≥0.5	Pass
High Channel	<b>0.900</b>	≥0.5	Pass



## BLE 1M



ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:26:30

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:36:18



BLE 2M



ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:39:03

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:43:16

## BLE\_2M\_Middle\_Channel



ProjectNo.:2501v02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:49:19

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:51:27

**99% Occupied Bandwidth****Test Information:**

<b>Sample No.:</b>	36RB-2	<b>Test Date:</b>	2025/08/07
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	24.8	<b>Relative Humidity:</b> (%)	52	<b>ATM Pressure:</b> (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

**Test Data:****BLE 1M**


<b>Channel</b>	<b>99% OBW (MHz)</b>
Low Channel	1.150
Middle Channel	<b>1.155</b>
High Channel	1.050

**BLE 2M**


<b>Channel</b>	<b>99% OBW (MHz)</b>
Low Channel	<b>2.040</b>
Middle Channel	<b>2.040</b>
High Channel	2.033

## BLE 1M


## BLE\_1M\_Low\_Channel




## BLE\_1M\_Middle\_Channel




## BLE\_1M\_High\_Channel




## BLE\_2M\_Low\_Channel



## BLE\_2M\_Middle\_Channel



## BLE\_2M\_High\_Channel



**Maximum Conducted Output Power****Test Information:**

<b>Sample No.:</b>	36RB-2	<b>Test Date:</b>	2025/08/07
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	24.8	<b>Relative Humidity:</b> (%)	52	<b>ATM Pressure:</b> (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

**Test Data:****BLE 1M**


<b>Channel</b>	<b>Peak Output Power (dBm)</b>	<b>Limit (dBm)</b>	<b>Verdict</b>
Low Channel	<b>6.91</b>	30.00	Pass
Middle Channel	6.75	30.00	Pass
High Channel	6.57	30.00	Pass

**BLE 2M**

<b>Channel</b>	<b>Peak Output Power (dBm)</b>	<b>Limit (dBm)</b>	<b>Verdict</b>
Low Channel	<b>6.88</b>	30.00	Pass
Middle Channel	6.78	30.00	Pass
High Channel	6.56	30.00	Pass

## BLE 1M

## BLE\_1M\_Low\_Channel



## BLE\_1M\_Middle\_Channel




ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:27:07

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:36:46

## BLE 2M

## BLE\_1M\_High\_Channel




## BLE\_2M\_Low\_Channel



ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:39:32

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:44:01

## BLE\_2M\_Middle\_Channel



## BLE\_2M\_High\_Channel



ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:49:47

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:52:01

## Power Spectral Density

### Test Information:

<b>Sample No.:</b>	36RB-2	<b>Test Date:</b>	2025/08/07
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

### Environmental Conditions:

<b>Temperature:</b> (°C)	24.8	<b>Relative Humidity:</b> (%)	52	<b>ATM Pressure:</b> (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

### Test Data:

#### BLE 1M


<b>Channel</b>	<b>Result</b> (dBm/3kHz)	<b>Limit</b> (dBm/3kHz)	<b>Verdict</b>
Low Channel	-11.27	8	Pass
Middle Channel	-11.54	8	Pass
High Channel	<b>-10.72</b>	8	Pass

#### BLE 2M


<b>Channel</b>	<b>Result</b> (dBm/3kHz)	<b>Limit</b> (dBm/3kHz)	<b>Verdict</b>
Low Channel	-13.34	8	Pass
Middle Channel	-13.70	8	Pass
High Channel	<b>-13.12</b>	8	Pass

## BLE 1M


## BLE\_1M\_Low\_Channel




## BLE\_1M\_Middle\_Channel




## BLE\_1M\_High\_Channel




## BLE\_2M\_Low\_Channel



## BLE\_2M\_Middle\_Channel



## BLE\_2M\_High\_Channel



## 100 kHz Bandwidth of Frequency Band Edge

### Test Information:

Sample No.:	36RB-2	Test Date:	2025/08/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass


### Environmental Conditions:

Temperature: (°C)	24.8	Relative Humidity: (%)	52	ATM Pressure: (kPa)	100.5
-------------------	------	------------------------	----	---------------------	-------


### Test Data:

#### BLE 1M

##### BLE\_1M\_Low\_Channel



##### BLE\_1M\_High\_Channel




ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:27:51


ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:40:17

#### BLE 2M

##### BLE\_2M\_Low\_Channel



##### BLE\_2M\_High\_Channel



ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:44:45

ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 7.AUG.2025 21:52:45

**Duty Cycle****Test Information:**

<b>Sample No.:</b>	36RB-2	<b>Test Date:</b>	2025/08/16
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	24.5	<b>Relative Humidity:</b> (%)	49	<b>ATM Pressure:</b> (kPa)	101.1
-----------------------------	------	----------------------------------	----	-------------------------------	-------

**Test Data:****BLE 1M**


<b>Channel</b>	<b>Ton</b> (ms)	<b>Ton+Toff</b> (ms)	<b>Duty Cycle</b> (%)	<b>Duty Cycle Factor(dB)</b>	<b>1/Ton</b> (Hz)	<b>VBW Setting</b> (kHz)
Middle Channel	<b>0.110</b>	0.625	17.60	7.54	9091	10

**BLE 2M**

<b>Channel</b>	<b>Ton</b> (ms)	<b>Ton+Toff</b> (ms)	<b>Duty Cycle</b> (%)	<b>Duty Cycle Factor(dB)</b>	<b>1/Ton</b> (Hz)	<b>VBW Setting</b> (kHz)
Middle Channel	<b>0.072</b>	0.625	11.52	9.39	13889	20

## BLE 1M


## BLE\_1M\_Middle\_Channel



ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 16.AUG.2025 20:21:43

## BLE 2M

## BLE\_2M\_Middle\_Channel






ProjectNo.:2501V02116E-RF Tester:Cheeb Huang  
Date: 16.AUG.2025 20:23:17

**Conducted Spurious Emission****Test Information:**

<b>Sample No.:</b>	36RB-2	<b>Test Date:</b>	2025/08/07~2025/08/26
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	23.6-24.8	<b>Relative Humidity:</b> (%)	44-52	<b>ATM Pressure:</b> (kPa)	100.5-101.1
-----------------------------	-----------	--------------------------------------	-------	-------------------------------	-------------

**Test Data:****BLE 1M**

## RF EXPOSURE EVALUATION

### MPE-Based Exemption

#### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

#### MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2 R^2$ .

R is the minimum separation distance in meters

f = frequency in MHz

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

### Result

Mode	Frequency (MHz)	Tune up conducted power <sup>#</sup> (dBm)	Antenna Gain#		ERP		Evaluation Distance (m)	ERP Limit (W)
			(dBi)	(dBd)	(dBm)	(W)		
BLE 1M	2402-2480	7	5.15	3	10	0.01	0.2	0.768
BLE 2M	2402-2480	7	5.15	3	10	0.01	0.2	0.768

Note: The tune up conducted power and antenna gain was declared by the applicant.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant**

## **EUT PHOTOGRAPHS**

Please refer to the attachment 2501V02116E-RF External photo and 2501V02116E-RF Internal photo.

---

## TEST SETUP PHOTOGRAPHS

---

Please refer to the attachment 2501V02116E-RF-TSP Test Setup photo.

\*\*\*\*\* END OF REPORT \*\*\*\*\*