

## TEST REPORT

**Report No.: 20100064HKG-001R1**

Hopstech Industries Ltd.

Application For Certification  
(Original Grant)

**FCC ID: 2AMR420200929**

Transceiver

This report supersedes previous report with report number 20100064HKG-001 dated October 27, 2020. Please refer TY-S20-0180 Letter issued on November 19, 2020 for amendment/ supersede notification.

**Prepared and Checked by:**

**Approved by:**

Signed On File

Lee For Yiu, Florey  
Assistant Engineer

Wong Kwok Yeung, Kenneth  
Senior Lead Engineer  
Date: November 19, 2020

## TEST REPORT

### GENERAL INFORMATION

<b>Grantee:</b>	Hopstech Industries Ltd.
<b>Grantee Address:</b>	Room 1411, 14/F., Block A, Hoi Luen Industrial Ctentre, 55 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong
<b>Contact Person:</b>	Rita Chung
<b>Tel:</b>	27275457
<b>Fax:</b>	N/A
<b>e-mail:</b>	N/A
<b>Manufacturer:</b>	Hopstech Industries Ltd.
<b>Manufacturer Address:</b>	Room 1411, 14/F., Block A, Hoi Luen Industrial Ctentre, 55 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong
<b>Brand Name:</b>	Maggy BV
<b>Model:</b>	Maggy
<b>Type of EUT:</b>	Transceiver
<b>Description of EUT:</b>	Maggy
<b>Serial Number:</b>	N/A
<b>FCC ID:</b>	2AMR420200929
<b>Date of Sample Submitted:</b>	October 05, 2020
<b>Date of Test:</b>	October 05, 2020 to October 21, 2020
<b>Report No.:</b>	20100064HKG-001R1
<b>Report Date:</b>	November 19, 2020
<b>Environmental Conditions:</b>	Temperature: +10 to 40°C Humidity: 10 to 90%
<b>Conclusion:</b>	Test was conducted by client submitted sample. The submitted sample as received complied with the 47 CFR Part 15 Certification.

**TEST REPORT****SUMMARY OF TEST RESULT**

Test Specification	Reference	Results
Transmitter Power Line Conducted Emissions	15.207	Pass
Radiated Emission	15.249, 15.209	Pass
Radiated Emission on the Bandedge		
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2019 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.  
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

**TEST REPORT****AMENDMENT HISTORY**

<b>Report No.</b>	<b>Issued Date</b>	<b>Content</b>
20100064HKG-001	October 27, 2020	Original Report
20100064HKG-001R1	November 19, 2020	P.11: Revise data of lowest channel frequency from 2400MHz to 2402MHz

## TEST REPORT

### TABLE OF CONTENTS

<b>1.0</b>	<b>GENERAL DESCRIPTION .....</b>	<b>6</b>
1.1	Product Description .....	6
1.2	Related Submittal(s) Grants.....	6
1.3	Test Methodology .....	6
1.4	Test Facility .....	6
<b>2.0</b>	<b>SYSTEM TEST CONFIGURATION.....</b>	<b>7</b>
2.1	Justification .....	7
2.2	EUT Exercising Software.....	7
2.3	Special Accessories.....	7
2.4	Measurement Uncertainty .....	7
2.5	Support Equipment List and Description .....	7
<b>3.0</b>	<b>EMISSION RESULTS.....</b>	<b>8</b>
3.1	Field Strength Calculation.....	8
3.2	Radiated Emission Configuration Photograph.....	9
3.3	Radiated Emission Data.....	9
3.4	Conducted Emission Configuration Photograph .....	9
3.5	Conducted Emission Data.....	9
<b>4.0</b>	<b>EQUIPMENT PHOTOGRAPHS .....</b>	<b>14</b>
<b>5.0</b>	<b>PRODUCT LABELLING.....</b>	<b>14</b>
<b>6.0</b>	<b>TECHNICAL SPECIFICATIONS .....</b>	<b>14</b>
<b>7.0</b>	<b>INSTRUCTION MANUAL .....</b>	<b>14</b>
<b>8.0</b>	<b>MISCELLANEOUS INFORMATION .....</b>	<b>15</b>
8.1	Radiated Emission on the Bandedge.....	15
8.2	Emissions Test Procedures .....	18
<b>9.0</b>	<b>CONFIDENTIALITY REQUEST .....</b>	<b>22</b>
<b>10.0</b>	<b>EQUIPMENT LIST.....</b>	<b>22</b>

## TEST REPORT

### 1.0 GENERAL DESCRIPTION

#### 1.1 Product Description

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver for a Bluetooth device. The sample supplied operated on 40 channels, normally at 2402 - 2480MHz. The channels are separated with 2MHz spacing.

The EUT is powered by 1 x 3.7V Rechargeable battery. After switching on the EUT, it will be emitting sound based on the button pressed on the EUT.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **“Justification Section”** of this Application.

#### 1.4 Test Facility

The 3m Chamber and conducted measurement facility used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong SAR, China. This test facility and site measurement data have been placed on file with the FCC.

## TEST REPORT

### 2.0 SYSTEM TEST CONFIGURATION

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by new DC 3.7V (1 x 3.7V Rechargeable Battery).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

#### 2.5 Support Equipment List and Description

N/A.

## TEST REPORT

### 3.0 EMISSION RESULTS

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in dB $\mu$ V/m

RR = RA - AG - AV in dB $\mu$ V

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V}/\text{m})/20] = 22.4 \mu\text{V}/\text{m}$$

## TEST REPORT

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 2480 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 1.5 dB

### 3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 163.5 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

### 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 14.48 dB


## TEST REPORT

### CONDUCTED EMISSION

Model: Maggy

Date of Test: October 21, 2020

Worst-Case Operating Mode: PC Charging



EDIT PEAK LIST (Final Measurement Results)					
Trace1:	CF15MQP				
Trace2:	CF15MAV				
Trace3:	---				
TRACE FREQUENCY LEVEL dBμV DELTA LIMIT dB					
2 CISPR Average	154.5 kHz	37.42	N	-18.33	
1 Quasi Peak	163.5 kHz	50.80	N	-14.48	
1 Quasi Peak	217.5 kHz	42.16	L1	-20.75	
1 Quasi Peak	492 kHz	30.30	N	-25.82	
2 CISPR Average	514.5 kHz	30.37	L1	-15.63	
1 Quasi Peak	3.831 MHz	27.10	N	-28.89	
2 CISPR Average	3.831 MHz	26.06	L1	-19.93	
2 CISPR Average	4.3125 MHz	22.40	L1	-23.59	
2 CISPR Average	6.3465 MHz	23.42	L1	-26.57	

 Note: Measurement Uncertainty is  $\pm 4.2\text{dB}$  at a level of confidence 95%.

## TEST REPORT

### RADIATED EMISSIONS

Model: Maggy

Date of Test: October 21, 2020

Worst-Case Operating Mode: Transmitting

**Table 1**  
**Pursuant to FCC Part 15 Section 15.249 Requirement**

Lowest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	94.7	33	29.4	91.1	94.0	-2.9
<b>H</b>	<b>4804.000</b>	<b>44.6</b>	<b>33</b>	<b>34.9</b>	<b>46.5</b>	<b>54.0</b>	<b>-7.5</b>
<b>V</b>	<b>7206.000</b>	<b>25.6</b>	<b>33</b>	<b>37.9</b>	<b>30.5</b>	<b>54.0</b>	<b>-23.5</b>
H	9608.000	22.8	33	40.4	30.2	54.0	-23.8
<b>H</b>	<b>12010.000</b>	<b>23.2</b>	<b>33</b>	<b>40.5</b>	<b>30.7</b>	<b>54.0</b>	<b>-23.3</b>
H	14412.000	23.3	33	40.0	30.3	54.0	-23.7

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	95.9	33	29.4	92.3	114.0	-21.7
<b>H</b>	<b>4804.000</b>	<b>50.9</b>	<b>33</b>	<b>34.9</b>	<b>52.8</b>	<b>74.0</b>	<b>-21.2</b>
<b>V</b>	<b>7206.000</b>	<b>33.4</b>	<b>33</b>	<b>37.9</b>	<b>38.3</b>	<b>74.0</b>	<b>-35.7</b>
H	9608.000	31.2	33	40.4	38.6	74.0	-35.4
<b>H</b>	<b>12010.000</b>	<b>31.0</b>	<b>33</b>	<b>40.5</b>	<b>38.5</b>	<b>74.0</b>	<b>-35.5</b>
H	14412.000	31.2	33	40.0	38.2	74.0	-35.8

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: Maggy

Date of Test: October 21, 2020

Worst-Case Operating Mode: Transmitting

**Table 2**  
**Pursuant to FCC Part 15 Section 15.249 Requirement**

Middle Channel

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	92.7	33	29.4	89.1	94.0	-4.9
<b>H</b>	<b>4880.000</b>	<b>45.9</b>	<b>33</b>	<b>34.9</b>	<b>47.8</b>	<b>54.0</b>	<b>-6.2</b>
V	<b>7320.000</b>	<b>25.1</b>	<b>33</b>	<b>37.9</b>	<b>30.0</b>	<b>54.0</b>	<b>-24.0</b>
H	9760.000	23.3	33	40.4	30.7	54.0	-23.3
<b>H</b>	<b>12200.000</b>	<b>22.5</b>	<b>33</b>	<b>40.5</b>	<b>30.0</b>	<b>54.0</b>	<b>-24.0</b>
H	14640.000	24.2	33	38.4	29.6	54.0	-24.4

Polari-zation	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2440.000	94.1	33	29.4	90.5	114.0	-23.5
<b>H</b>	<b>4880.000</b>	<b>51.9</b>	<b>33</b>	<b>34.9</b>	<b>53.8</b>	<b>74.0</b>	<b>-20.2</b>
V	<b>7320.000</b>	<b>33.4</b>	<b>33</b>	<b>37.9</b>	<b>38.3</b>	<b>74.0</b>	<b>-35.7</b>
H	9760.000	31.3	33	40.4	38.7	74.0	-35.3
<b>H</b>	<b>12200.000</b>	<b>30.6</b>	<b>33</b>	<b>40.5</b>	<b>38.1</b>	<b>74.0</b>	<b>-35.9</b>
H	14640.000	33.0	33	38.4	38.4	74.0	-35.6

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

Model: Maggy

Date of Test: October 21, 2020

Worst-Case Operating Mode: Transmitting

Table 3  
**Pursuant to FCC Part 15 Section 15.249 Requirement**

Highest Channel

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
<i>H</i>	<b>2480.000</b>	<b>96.1</b>	<b>33</b>	<b>29.4</b>	<b>92.5</b>	<b>94.0</b>	<b>-1.5</b>
<i>H</i>	<b>4960.000</b>	<b>41.9</b>	<b>33</b>	<b>34.9</b>	<b>43.8</b>	<b>54.0</b>	<b>-10.2</b>
<i>V</i>	<b>7440.000</b>	<b>25.8</b>	<b>33</b>	<b>37.9</b>	<b>30.7</b>	<b>54.0</b>	<b>-23.3</b>
H	9920.000	22.8	33	40.4	30.2	54.0	-23.8
<i>H</i>	<b>12400.000</b>	<b>23.2</b>	<b>33</b>	<b>40.5</b>	<b>30.7</b>	<b>54.0</b>	<b>-23.3</b>
H	14880.000	24.6	33	38.4	30.0	54.0	-24.0

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
<i>H</i>	<b>2480.000</b>	<b>97.3</b>	<b>33</b>	<b>29.4</b>	<b>93.7</b>	<b>114.0</b>	<b>-20.3</b>
<i>H</i>	<b>4960.000</b>	<b>49.0</b>	<b>33</b>	<b>34.9</b>	<b>50.9</b>	<b>74.0</b>	<b>-23.1</b>
V	7440.000	33.6	33	37.9	38.5	74.0	-35.5
<i>H</i>	<b>9920.000</b>	<b>31.2</b>	<b>33</b>	<b>40.4</b>	<b>38.6</b>	<b>74.0</b>	<b>-35.4</b>
<i>H</i>	<b>12400.000</b>	<b>30.9</b>	<b>33</b>	<b>40.5</b>	<b>38.4</b>	<b>74.0</b>	<b>-35.6</b>
H	14880.000	32.9	33	38.4	38.3	74.0	-35.7

NOTES:

1. Peak Detector Data unless otherwise stated.
2. Average detector is applied according to ANSI C63.10.
3. All measurements were made at 3 meters.
4. Negative sign in the column shows value below limit.
5. Horn antenna is used for the emission over 1000MHz.
6. Emission (the row indicated by ***bold italic***) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
7. Measurement Uncertainty is  $\pm 5.3$ dB at a level of confidence of 95%.

## TEST REPORT

### 4.0 EQUIPMENT PHOTOGRAPHS

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 PRODUCT LABELLING

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 TECHNICAL SPECIFICATIONS

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 INSTRUCTION MANUAL

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## TEST REPORT

### 8.0 MISCELLANEOUS INFORMATION

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).



#### 8.1 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.10 (2013) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209 , whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

## TEST REPORT

### PEAK MEASUREMENT



## TEST REPORT

### PEAK MEASUREMENT

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=92.3 \text{ dB}\mu\text{V/m} - 43.0 \text{ dB}$$

$$=49.3 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=91.1 \text{ dB}\mu\text{V/m} - 43.0 \text{ dB}$$

$$=48.1 \text{ dB}\mu\text{V/m}$$

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

$$=93.7 \text{ dB}\mu\text{V/m} - 43.9 \text{ dB}$$

$$=49.8 \text{ dB}\mu\text{V/m}$$

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

$$=92.5 \text{ dB}\mu\text{V/m} - 43.9 \text{ dB}$$

$$=48.6 \text{ dB}\mu\text{V/m}$$

The resultant field strength meets the general radiated emission limit in Section 15.209, which does not exceed 74 dB $\mu$ V/m (Peak Limit) but exceeded 54 dB $\mu$ V/m (Average Limit).

## TEST REPORT

### 8.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

## TEST REPORT

### 8.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


## TEST REPORT

### 8.2.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz


## TEST REPORT

### 8.2.2 Conducted Emission Test Procedures

For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. For floor-standing equipment, the EUT and all cables were insulated, if required, from the ground plane by up to 12 mm of insulating material. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were moved to find the maximum emission.

### 8.2.3 Conducted Emission Test Setup



## TEST REPORT

### 9.0 CONFIDENTIALITY REQUEST

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

### 10.0 EQUIPMENT LIST

#### 1) Radiated Emissions Test

Equipment	Spectrum Analyzer	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-3281	EW-0571	EW-1042
Manufacturer	ROHDE SCHWARZ	EMCO	EMCO
Model No.	FSV40	3104C	3148
Calibration Date	March 04, 2020	July 23, 2019	November 23, 2019
Calibration Due Date	March 04, 2021	January 23, 2021	November 23, 2020

Equipment	Double Ridged Guide Antenna	14m Double Shield RF Cable (20MHz - 6GHz)	RF Cable 14m (1GHz to 26.5GHz)
Registration No.	EW-1015	EW-2505	EW-3151
Manufacturer	EMCO	RADIALL	GREATBILLION
Model No.	3115	Br5d	SMA m/SHF5MPU /SMA m ra14m,26G
Calibration Date	May 16, 2019	November 14, 2019	March 04, 2020
Calibration Due Date	November 16, 2020	November 14, 2020	March 04, 2021

Equipment	RF Pre-amplifier 3 pcs (9kHz to 40GHz)	Active Loop H-field (9kHz to 30MHz)
Registration No.	EW-3006	EW-2313
Manufacturer	SCHWARZBECK	ELECTROMETRI
Model No.	BBV 9718	EM-6876
Calibration Date	November 25, 2019	June 17, 2020
Calibration Due Date	November 25, 2020	June 17, 2021

#### 2) Conducted Emissions Test

Equipment	EMI Test Receiver	Artificial Mains Network	RF Cable 80cm (RG142) (9kHz to 30MHz)
Registration No.	EW-2251	EW-2874	EW-2451
Manufacturer	ROHDE SCHWARZ	ROHDE SCHWARZ	RADIALL
Model No.	ESCI	ENV-216	bnc m st / 142 / bnc m st 80cm
Calibration Date	December 21, 2019	December 05, 2019	December 08, 2019
Calibration Due Date	December 21, 2020	December 05, 2020	December 08, 2020

**TEST REPORT**

## 3) Bandwidth Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-3281
Manufacturer	ROHDESCHWARZ
Model No.	FSV40
Calibration Date	March 04, 2020
Calibration Due Date	March 04, 2021

**END OF TEST REPORT**