

# Analysis Report

The Equipment Under Test (EUT) is a 2.4GHz Transmitter (Remote). The EUT is powered by 2 x 1.5V AAA batteries. The 2.4GHz module is operating at the frequencies (2409 and 2430) MHz. After switching on the EUT and the corresponding Receiver (Engine), activating the control keys on the EUT can control the (Engine) moving.

**Antenna Type: Internal antenna**

**Antenna Gain: 0dBi**

**Nominal rated field strength: 95.6 dB $\mu$ V/m at 3m**

**Maximum allowed field strength of production tolerance: +/- 3dB**

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 98.6dB $\mu$ V/m at 3m in frequency 2.4GHz, thus;

The EIRP =  $[(FS \cdot D)^2 \cdot 1000 / 30] = 2.173\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain  
So;

Conducted Power =  $2.173\text{mW}$ .

The SAR Exclusion Threshold Level:

$$\begin{aligned} &= 3.0 * (\text{min. test separation distance, mm}) / \text{sqrt(freq. in GHz)} \\ &= 3.0 * 5 / \text{sqrt}(2.430) \text{ mW} \\ &= 9.62 \text{ mW} \end{aligned}$$

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.