

RF Exposure Report

Report No.: SA181109E05

FCC ID: 2AMRICR48NA

Test Model: CR48NA

Series Model: CXD2800

Received Date: Nov. 13, 2018

Test Date: Dec. 07, 2018

Issued Date: Feb. 20, 2019

Applicant: Connected IO

Address: 8304 Esters Boulevard, Suite 850, Irving, Texas United States 75063

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7
Appendix	8

Release Control Record

Issue No.	Description	Date Issued
SA181109E05	Original release.	Feb. 20, 2019

1 Certificate of Conformity

Product: Router

Brand: Connected IO, Netsurion

Test Model: CR48NA

Series Model: CXD2800

Sample Status: ENGINEERING SAMPLE

Applicant: Connected IO

Test Date: Dec. 07, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu, **Date:** Feb. 20, 2019
Wendy Wu / Specialist

Approved by : May Chen, **Date:** Feb. 20, 2019
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 23cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN							
Ant Set.	Chain No.	Brand	Model	Antenna Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
1	Chain 0	JOYMAX	TWX-1513RSXX-711	5	2.4~2.4835	Collinear	R-SMA
				5	5.15~5.85		
	Chain 1	JOYMAX	TWX-1513RSXX-711	5	2.4~2.4835	Collinear	R-SMA
				5	5.15~5.85		
2	Chain 0	JOYMAX	TWX-6141RSXX-711	3	2.4~2.4835	Microstrip	R-SMA
				5	5.15~5.85		
	Chain 1	JOYMAX	TWX-6141RSXX-711	3	2.4~2.4835	Microstrip	R-SMA
				5	5.15~5.85		
WWAN – 3G / LTE							
Ant Set	Transmitter Circuit	Brand	Model	Antenna Gain (dBi)	Frequency Range (MHz)	Antenna Type	Connector Type
1	Main	JOYMAX	YWX-6252SAXX-711	3	698~960	Microstrip	SMA
					1710~2710		
					2300~2700		
	Aux	JOYMAX	YWX-6252SAXX-711	3	698~960	Microstrip	SMA
					1710~2710		
					2300~2700		

Note:

1. For WLAN: Ant set 1 was selected for the final test.

2.5 Calculation Result of Maximum Conducted Power

For WLAN

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	683.343	8.01	23	0.65009	1
WLAN UNII-1	5230	59.941	8.01	23	0.05702	1
WLAN UNII-3	5745	139.597	8.01	23	0.13280	1

NOTE:

2.4GHz: Directional gain = 5dBi + 10log(2) = 8.01dBi

5GHz: Directional gain = 5dBi + 10log(2) = 8.01dBi

For 3G/LTE <Worst case> (FCC ID: RI7LE910NAV2)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
UMTS Band V	826.4	229	3.00	23	0.06873	0.55093*

Note: *Limit of Power Density = F/1500

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz + 3G/LTE = 0.65009 / 1 + 0.13280 / 1 + 0.06873 / 0.55093 = 0.90764

Therefore the maximum calculations of above situations are less than the “1” limit.

Appendix

3G/LTE module

MPE Evaluation for FCC ID: RI7LE910NAV2 Module

Mode	Equipment Category	Transmitter Range (MHz)		Maximum Power		Antenna Gain (dBi)	Power Density (mW/cm ²)		Ratio
		Start	Stop	(dBm)	(W)		Vaule	Limit	
UMTS	Band II	1852.4	1907.6	23.655	0.232	3	0.06963	1	0.06963
	Band V	826.4	846.6	23.598	0.229	3	0.06873	0.55093	0.12475
LTE	Band 2	1850.7	1909.3	23.424	0.22	3	0.06603	1	0.06603
	Band 4	1710.7	1754.3	23.117	0.205	3	0.06153	1	0.06153
	Band 5	824.7	848.3	22.9	0.195	3	0.05853	0.5498	0.10646
	Band 12	699.7	715.3	22.856	0.193	3	0.05793	0.46646	0.12419
	Band 13	779.5	784.5	22.878	0.194	3	0.05823	0.51966	0.11205

--- END ---