


## FCC RADIO TEST REPORT

Applicant..... : Summit Electronics LLC  
Address..... : 1 Rewe Street, Brooklyn, New York, 11211 United States  
Manufacturer..... : Summit Electronics LLC  
Address..... : 1 Rewe Street, Brooklyn, New York, 11211 United States  
Factory..... : Summit Electronics LLC  
Address..... : 1 Rewe Street, Brooklyn, New York, 11211 United States  
Product Name..... : Wireless Speaker  
Brand Name..... : COBY, COOLBUDS, CHARGEWORX, CAR AND DRIVER, GO TOUGH  
Model No. .... : CSTW530 (For model difference refer to section 1.1)  
FCC ID..... : 2AMSOSTW001  
Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.247)  
Receipt Date of Samples..... : October 15, 2021  
Date of Tested..... : October 15, 2021 to November 19, 2021  
Date of Report..... : November 29, 2021

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Jenny Liu / Project Engineer



Approved by

Iori Fan / Authorized Signatory

## Table of Contents

|  |    |
|--|----|
| 1. Summary of Test Result .....  | 4  |
| 2. General Description of EUT .....                                    | 5  |
| 3. Test Channels and Modes Detail.....                                 | 8  |
| 4. Configuration of EUT .....  | 8  |
| 5. Modification of EUT.....  | 8  |
| 6. Description of Support Device .....                                 | 9  |
| 7. Test Facility and Location .....                                    | 10 |
| 8. Applicable Standards and References.....                            | 11 |
| 9. Deviations and Abnormalities from Standard Conditions.....          | 11 |
| 10. Test Conditions .....  | 12 |
| 11. Measurement Uncertainty.....                                       | 13 |
| 12. Sample Calculations .....  | 14 |
| 13. Test Items and Results .....                                       | 15 |
| 13.1 Conducted Emissions Measurement .....                             | 15 |
| 13.2 Radiated Spurious Emissions and Restricted Bands Measurement..... | 19 |
| 13.3 Channel Separation test .....                                     | 26 |
| 13.4 20dB Bandwidth.....   | 30 |
| 13.5 Hopping Channel Number .....                                      | 34 |
| 13.6 Time of Occupancy (Dwell Time).....                               | 36 |
| 13.7 Maximum Peak Output Power .....                                   | 40 |
| 13.8 Band Edge Conducted Spurious Emission Measurement.....            | 44 |
| 13.9 Antenna Requirement.....  | 49 |
| 14. Test Equipment List .....  | 50 |

---

**REVISION HISTORY**

| Report Number  | Description   | Issued Date |
|----------------|---------------|-------------|
| NTC2110030FV00 | Initial Issue | 2021-11-29  |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |
|                |               |             |

## 1. Summary of Test Result

| FCC Rules                       | Description of Test               | Result | Remarks |
|---------------------------------|-----------------------------------|--------|---------|
| §15.247(a)(1)                   | Channel Separation test           | PASS   | ---     |
| §15.247(a)(1)                   | 20dB Bandwidth                    | PASS   | ---     |
| §15.247(a)(1)(iii)              | Hopping Channel Number            | PASS   | ---     |
| §15.247(a)(1)(iii)              | Time of Occupancy<br>(Dwell Time) | PASS   | ---     |
| §15.247(b)                      | Max Peak output Power test        | PASS   | ---     |
| §15.247(d)                      | Band edge test                    | PASS   | ---     |
| §15.207 (a)                     | AC Power Conducted Emission       | PASS   | ---     |
| §15.247(d), §15.209,<br>§15.205 | Radiated Emission                 | PASS   | ---     |
| §15.203                         | Antenna Requirement               | PASS   | ---     |
| §15.247(d)                      | Conducted Spurious Emission       | PASS   | ---     |

## 2. General Description of EUT

| Product Information     |  |
|-------------------------|--|
| Product name:           | Wireless Speaker   |
| Main Model Name:        | CSTW530  |
| Additional Model Name:  | CPA440, CPA510, CPA540, CPA541, CPA640, CPA545, CPA537, CPA547, CPA800, CPA910, CPA901, CPA905, CSTW444, CSTW455, CSTW502, CSTW509, CSTW535, CSTW561, CSTW630, CPSTW310, CSTV130, CPSTW510, CAD-FMX500, CX9029, GT7085, GT7015 |
| Model Difference:       | These models have the same circuit schematic, construction, PCB Layout and critical components. Their difference are model number to trading purpose.  |
| S/N:                    | N/A  |
| Brand Name              | COBY, COOLBUDS, CHARGEWORX, CAR AND DRIVER, GO TOUGH   |
| Hardware version:       | Not Stated   |
| Software version:       | Not Stated   |
| Rating:                 | DC3.7V from Battery or DC5V from USB Host Unit   |
| Classification:         | Class B  |
| Typical arrangement:    | Table-top  |
| I/O Port:               | Refer to the user manual   |
| Accessories Information |  |
| Adapter:                | N/A  |
| Cable:                  | USB Cable: 0.46m, unshielded   |
| Other:                  | N/A  |
| Additional information  |  |
| Note:                   | According to the model difference, all tests were performed on model CSTW530.  |
| Remark:                 | All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.   |

| Technical Specification |  |
|-------------------------|--|
| Bluetooth Version:      | V5.0   |
| Frequency Range:        | 2402-2480MHz                                     |
| Modulation Type:        | GFSK, $\pi/4$ -DQPSK, 8DPSK                      |
| Number of Channel:      | 79 (refer to following channel list for details) |
| Channel Space:          | 1MHz   |
| Antenna Type:           | PCB antenna*1                                    |
| Antenna Gain:           | -0.58dBi   |


| Channel List |                 |         |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 0            | 2402            | 20      | 2422            | 40      | 2442            | 60      | 2462            |
| 1            | 2403            | 21      | 2423            | 41      | 2443            | 61      | 2463            |
| 2            | 2404            | 22      | 2424            | 42      | 2444            | 62      | 2464            |
| 3            | 2405            | 23      | 2425            | 43      | 2445            | 63      | 2465            |
| 4            | 2406            | 24      | 2426            | 44      | 2446            | 64      | 2466            |
| 5            | 2407            | 25      | 2427            | 45      | 2447            | 65      | 2467            |
| 6            | 2408            | 26      | 2428            | 46      | 2448            | 66      | 2468            |
| 7            | 2409            | 27      | 2429            | 47      | 2449            | 67      | 2469            |
| 8            | 2410            | 28      | 2430            | 48      | 2450            | 68      | 2470            |
| 9            | 2411            | 29      | 2431            | 49      | 2451            | 69      | 24721           |
| 10           | 2412            | 30      | 2432            | 50      | 2452            | 70      | 2472            |
| 11           | 2413            | 31      | 2433            | 51      | 2453            | 71      | 2473            |
| 12           | 2414            | 32      | 2434            | 52      | 2454            | 72      | 2474            |
| 13           | 2415            | 33      | 2435            | 53      | 2455            | 73      | 2475            |
| 14           | 2416            | 34      | 2436            | 54      | 2456            | 74      | 2476            |
| 15           | 2417            | 35      | 2437            | 55      | 2457            | 75      | 2477            |
| 16           | 2418            | 36      | 2438            | 56      | 2458            | 76      | 2478            |
| 17           | 2419            | 37      | 2439            | 57      | 2459            | 77      | 2479            |
| 18           | 2420            | 38      | 2440            | 58      | 2460            | 78      | 2480            |
| 19           | 2421            | 39      | 2441            | 59      | 2461            | ----    | ----            |

### 3. Test Channels and Modes Detail

| No. | Mode        | Channel | Frequency (MHz) | Modulation                  |
|-----|-------------|---------|-----------------|-----------------------------|
| 1   | TX          | Hopping | 2402-2480       | GFSK/ $\pi$ /4-DQPSK /8DPSK |
| 2   | TX          | Low     | 2402            | GFSK/ $\pi$ /4-DQPSK /8DPSK |
| 3   | TX          | Mid     | 2441            | GFSK/ $\pi$ /4-DQPSK /8DPSK |
| 4   | TX          | High    | 2480            | GFSK/ $\pi$ /4-DQPSK /8DPSK |
| 5.  | Normal Mode | ---     | ---             | ---                         |

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

### 4. Configuration of EUT



### 5. Modification of EUT

No modifications are made to the EUT during all test items.



## 6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| No. | Equipment   | Brand  | M/N             | S/N      | Cable Specification  | Remarks                     |
|-----|-------------|--------|-----------------|----------|--|-----------------------------|
| 1.  | Notebook PC | Lenovo | R720-151K<br>BN | PF0Z35FH | AC Line: 1.10m unshielded,<br>DC Line: 1.15m unshielded<br>with a core | Provided by<br>manufacturer |

| No. | Test Software                          | Modulation     | Power Setting |
|-----|--|----------------|---------------|
| 1.  | Engineering Mode (No need<br>software) | GFSK           | Default       |
| 2.  |  | $\pi/4$ -DQPSK | Default       |
| 3.  |  | 8DPSK          | Default       |

## 7. Test Facility and Location

|                                   |   |   |
|-----------------------------------|---|---|
| Test Site                         | : | Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)   |
| Accreditations and Authorizations | : | <p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01<br/>Listed by CNAS, August 13, 2018<br/>The Certificate Registration Number is L5795.<br/>The Certificate is valid until August 13, 2024</p> <p>The Laboratory has been assessed and proved to be in compliance with ISO17025<br/>Listed by A2LA, November 01, 2017<br/>The Certificate Registration Number is 4429.01<br/>The Certificate is valid until December 31, 2021</p> <p>Listed by FCC, November 06, 2017<br/>Test Firm Registration Number: 907417</p> <p>Listed by Industry Canada, June 08, 2017<br/>The Certificate Registration Number. Is 46405-9743A</p> |
| Test Site Location                | : | Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China  |

## **8. Applicable Standards and References**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

### **Test Standards:**

47 CFR Part 15, Subpart C, 15.247

ANSI C63.10-2013

### **References Test Guidance:**

DTS KDB 558074 D01 15.247 Meas Guidance v05r02

### **Remark:**

The EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## **9. Deviations and Abnormalities from Standard Conditions**

No additions, deviations and exclusions from the standard.

## 10. Test Conditions

| No. | Test Item                         | Test Mode | Test Voltage | Tested by | Remarks               |
|-----|-----------------------------------|-----------|--------------|-----------|-----------------------|
| 1.  | Channel Separation test           | 1         | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 2.  | 20dB Bandwidth                    | 2-4       | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 3.  | Hopping Channel Number            | 1         | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 4.  | Time of Occupancy<br>(Dwell Time) | 1         | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 5.  | Max Peak output Power test        | 2-4       | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 6.  | Band edge test                    | 1-4       | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 7.  | AC Power Conducted Emission       | 5         | AC120V 60Hz  | Ray       | See note <sup>1</sup> |
| 8.  | Radiated Emission                 | 1-4       | DC 3.7V      | Ray       | See note <sup>1</sup> |
| 9.  | Antenna Requirement               | ---       | ---          | ---       | See note <sup>1</sup> |
| 10. | Conducted Spurious Emission       | 1-4       | DC 3.7V      | Ray       | See note <sup>1</sup> |

**Note:**

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35°C, 30~70%, 86~106kPa
2. As the EUT can be operated multiple positions, all X,Y,Z axis were considered during the test and only the worst case X was recorded.
3. This product will not be connected to the AC mains during normal use, therefore the AC Power Conducted Emission test is not applicable.

## 11. Measurement Uncertainty

| No. | Test Item              | Frequency      | Uncertainty | Remarks |
|-----|------------------------|----------------|-------------|---------|
| 1.  | Conducted Emission     | 150KHz ~ 30MHz | ±2.52 dB    | ---     |
| 2.  | Radiated Emission Test | 9kHz ~ 30MHz   | ±2.60 dB    | ---     |
|     |                        | 30MHz ~ 1GHz   | ±4.68 dB    | ---     |
|     |                        | 1GHz ~ 18GHz   | ±5.14 dB    | ---     |
|     |                        | 18GHz ~ 40GHz  | ±5.14 dB    | ---     |
| 3.  | RF Conducted Test      | 10Hz ~ 40GHz   | ±1.06 dB    | ---     |

**Note:**

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

## 12. Sample Calculations

| Conducted Emission |                      |                     |                    |              |           |          |
|--------------------|----------------------|---------------------|--------------------|--------------|-----------|----------|
| Freq. (MHz)        | Reading Level (dBuV) | Correct Factor (dB) | Measurement (dBuV) | Limit (dBuV) | Over (dB) | Detector |
| 4.1900             | 30.10                | 10.60               | 40.70              | 56.00        | -15.30    | QP       |

Where,

Freq. = Emission frequency in MHz  
 Reading Level = Uncorrected Analyzer/Receiver reading  
 Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation  
 Measurement = Reading + Corrector Factor  
 Limit = Limit stated in standard  
 Margin = Measurement - Limit  
 Detector = Reading for Quasi-Peak / Average / Peak

| Radiated Spurious Emissions and Restricted Bands |                      |                       |                      |                |           |          |
|--|----------------------|-----------------------|----------------------|----------------|-----------|----------|
| Freq. (MHz)                                      | Reading Level (dBuV) | Correct Factor (dB/m) | Measurement (dBuV/m) | Limit (dBuV/m) | Over (dB) | Detector |
| 233.0700   | 45.88                | -18.38                | 27.50                | 46.00          | -18.50    | QP       |

Where,

Freq. = Emission frequency in MHz  
 Reading Level = Uncorrected Analyzer/Receiver reading  
 Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier  
 Measurement = Reading + Corrector Factor  
 Limit = Limit stated in standard  
 Over = Margin, which calculated by Measurement - Limit  
 Detector = Reading for Quasi-Peak / Average / Peak

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

### 13. Test Items and Results

#### 13.1 Conducted Emissions Measurement


##### LIMIT

According to the requirements of FCC PART 15.207, the limits are as follows:

| Frequency (MHz) | Quasi-peak | Average  |
|-----------------|------------|----------|
| 0.15 to 0.5     | 66 to 56   | 56 to 46 |
| 0.5 to 5        | 56         | 46       |
| 5 to 30         | 60         | 50       |

- Note:
1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
  2. The lower limit shall apply at the transition frequencies.
  3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

##### BLOCK DIAGRAM OF TEST SETUP



## **TEST PROCEDURES**

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

## **TEST RESULTS**

PASS

Please refer to the following pages of the worst case.




|              |                               |
|--------------|-------------------------------|
| M/N: CSTW530 | Testing Voltage: AC 120V 60Hz |
| Phase: L1    | Detector: QP & AVG            |
| Test Mode: 5 |                               |

### Conducted Emission Measurement

Date: 2021/10/21

Time: 17:12:19




| No. Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit | Over   | Detector | Comment |
|---------|--------|---------------|----------------|-------------|-------|--------|----------|---------|
|         | MHz    | dBuV          | dB             | dBuV        | dBuV  | dB     |          |         |
| 1       | 0.1660 | 25.53         | 10.60          | 36.13       | 65.16 | -29.03 | QP       |         |
| 2       | 0.1660 | 7.47          | 10.60          | 18.07       | 55.16 | -37.09 | AVG      |         |
| 3 *     | 0.4900 | 27.82         | 10.63          | 38.45       | 56.17 | -17.72 | QP       |         |
| 4       | 0.4900 | 14.45         | 10.63          | 25.08       | 46.17 | -21.09 | AVG      |         |
| 5       | 0.5940 | 19.99         | 10.64          | 30.63       | 56.00 | -25.37 | QP       |         |
| 6       | 0.5940 | 5.33          | 10.64          | 15.97       | 46.00 | -30.03 | AVG      |         |
| 7       | 1.0260 | 19.46         | 10.70          | 30.16       | 56.00 | -25.84 | QP       |         |
| 8       | 1.0260 | 5.19          | 10.70          | 15.89       | 46.00 | -30.11 | AVG      |         |
| 9       | 1.4260 | 18.69         | 10.70          | 29.39       | 56.00 | -26.61 | QP       |         |
| 10      | 1.4260 | 3.90          | 10.70          | 14.60       | 46.00 | -31.40 | AVG      |         |
| 11      | 1.8140 | 19.00         | 10.70          | 29.70       | 56.00 | -26.30 | QP       |         |
| 12      | 1.8140 | 2.40          | 10.70          | 13.10       | 46.00 | -32.90 | AVG      |         |

|              |                               |
|--------------|-------------------------------|
| M/N: CSTW530 | Testing Voltage: AC 120V 60Hz |
| Phase: N     | Detector: QP & AVG            |
| Test Mode: 5 |                               |

### Conducted Emission Measurement

Date: 2021/10/21

Time: 17:18:03



| No. Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit | Over   | Detector | Comment |
|---------|--------|---------------|----------------|-------------|-------|--------|----------|---------|
|         | MHz    | dBuV          | dB             | dBuV        | dBuV  | dB     |          |         |
| 1       | 0.1500 | 27.21         | 10.60          | 37.81       | 66.00 | -28.19 | QP       |         |
| 2       | 0.1500 | 8.91          | 10.60          | 19.51       | 56.00 | -36.49 | AVG      |         |
| 3       | 0.4940 | 27.41         | 10.63          | 38.04       | 56.10 | -18.06 | QP       |         |
| 4 *     | 0.4940 | 20.63         | 10.63          | 31.26       | 46.10 | -14.84 | AVG      |         |
| 5       | 0.6020 | 19.36         | 10.64          | 30.00       | 56.00 | -26.00 | QP       |         |
| 6       | 0.6020 | 5.54          | 10.64          | 16.18       | 46.00 | -29.82 | AVG      |         |
| 7       | 1.0300 | 18.60         | 10.70          | 29.30       | 56.00 | -26.70 | QP       |         |
| 8       | 1.0300 | 4.69          | 10.70          | 15.39       | 46.00 | -30.61 | AVG      |         |
| 9       | 1.4220 | 18.44         | 10.70          | 29.14       | 56.00 | -26.86 | QP       |         |
| 10      | 1.4220 | 2.96          | 10.70          | 13.66       | 46.00 | -32.34 | AVG      |         |
| 11      | 2.0140 | 16.21         | 10.70          | 26.91       | 56.00 | -29.09 | QP       |         |
| 12      | 2.0140 | 4.17          | 10.70          | 14.87       | 46.00 | -31.13 | AVG      |         |

## 13.2 Radiated Spurious Emissions and Restricted Bands Measurement


### LIMIT

| Frequency range<br>MHz | Distance Meters | Field Strengths Limit (15.209) |
|------------------------|-----------------|--------------------------------|
|                        |                 | $\mu\text{V/m}$                |
| 0.009 ~ 0.490          | 300             | 2400/F(kHz)                    |
| 0.490 ~ 1.705          | 30              | 24000/F(kHz)                   |
| 1.705 ~ 30             | 30              | 30                             |
| 30 ~ 88                | 3               | 100                            |
| 88 ~ 216               | 3               | 150                            |
| 216 ~ 960              | 3               | 200                            |
| Above 960              | 3               | 500                            |


- Remark:
- (1) Emission level (dB) $\mu\text{V}$  = 20 log Emission level  $\mu\text{V/m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
  - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
  - (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

**BLOCK DIAGRAM OF TEST SETUP**


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



## TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:
 

The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum

value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.
- g. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type.  
The worst case was found when the EUT was positioned on X axis for radiated emission.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

| Frequency Band (MHz) | Detector | Resolution Bandwidth | Video Bandwidth |
|----------------------|----------|----------------------|-----------------|
| 30 to 1000           | QP       | 120 kHz              | 300 kHz         |
| Above 1000           | Peak     | 1 MHz                | 3 MHz           |
|                      | Average  | 1 MHz                | 10 Hz           |

## TEST RESULTS

PASS


Please refer to the following pages.

|                               |                          |
|-------------------------------|--------------------------|
| M/N: CSTW530                  | Testing Voltage: DC 3.7V |
| Polarization: Horizontal      | Detector: QP             |
| Test Mode: 5 (the worst case) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2021/10/19

Time: 8:24:23



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB/m | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 50.3700      | 27.53                    | -6.94                     | 20.59                      | 40.00           | -19.41     | QP       |         |
| 2   |     | 191.9900     | 33.65                    | -8.12                     | 25.53                      | 43.50           | -17.97     | QP       |         |
| 3   | *   | 275.4100     | 42.39                    | -5.93                     | 36.46                      | 46.00           | -9.54      | QP       |         |
| 4   |     | 739.0700     | 25.41                    | 2.86                      | 28.27                      | 46.00           | -17.73     | QP       |         |
| 5   |     | 836.0700     | 26.38                    | 4.57                      | 30.95                      | 46.00           | -15.05     | QP       |         |
| 6   |     | 887.4800     | 25.61                    | 5.40                      | 31.01                      | 46.00           | -14.99     | QP       |         |


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

|                               |                          |
|-------------------------------|--------------------------|
| M/N: CSTW530                  | Testing Voltage: DC 3.7V |
| Polarization: Vertical        | Detector: QP             |
| Test Mode: 5 (the worst case) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2021/10/19

Time: 8:30:41



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB/m | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 34.8500      | 33.10                    | -9.16                     | 23.94                      | 40.00           | -16.06     | QP       |         |
| 2   |     | 191.9900     | 30.92                    | -9.03                     | 21.89                      | 43.50           | -21.61     | QP       |         |
| 3   |     | 282.2000     | 35.81                    | -6.84                     | 28.97                      | 46.00           | -17.03     | QP       |         |
| 4   |     | 468.4400     | 28.75                    | -3.25                     | 25.50                      | 46.00           | -20.50     | QP       |         |
| 5   |     | 576.1100     | 25.34                    | -0.91                     | 24.43                      | 46.00           | -21.57     | QP       |         |
| 6   | *   | 854.5000     | 25.46                    | 4.83                      | 30.29                      | 46.00           | -15.71     | QP       |         |

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.



| Modulation: 8DPSK(the worst case)           |                 |                     |       | Test Result: PASS |                         |       | Test frequency range: 1-25GHz |       |             |        |
|---|-----------------|---------------------|-------|-------------------|-------------------------|-------|-------------------------------|-------|-------------|--------|
| Freq. (MHz)                                 | Ant. Pol. (H/V) | Reading Level(dBuV) |       | Factor (dB/m)     | Emission Level (dBuV/m) |       | Limit 3m (dBuV/m)             |       | Margin (dB) |        |
|   |                 | PK                  | AV    |                   | PK                      | AV    | PK                            | AV    | PK          | AV     |
| <b>Operation Mode: TX Mode (Low)</b>        |                 |                     |       |                   |                         |       |                               |       |             |        |
| 4804  | H               | 53.11               | 38.39 | 6.30              | 59.41                   | 44.69 | 74.00                         | 54.00 | -14.59      | -9.31  |
| 7206  | H               | 49.30               | 36.08 | 10.44             | 59.74                   | 46.52 | 74.00                         | 54.00 | -14.26      | -7.48  |
| ---   |                 |                     |       |                   |                         |       |                               |       |             |        |
| 4804  | V               | 52.59               | 36.25 | 6.30              | 58.89                   | 42.55 | 74.00                         | 54.00 | -15.11      | -11.45 |
| 7206  | V               | 48.70               | 35.64 | 10.44             | 59.14                   | 46.08 | 74.00                         | 54.00 | -14.86      | -7.92  |
| ---   |                 |                     |       |                   |                         |       |                               |       |             |        |
| <b>Operation Mode: TX Mode (Mid)</b>        |                 |                     |       |                   |                         |       |                               |       |             |        |
| 4882  | H               | 52.36               | 37.21 | 6.60              | 58.96                   | 43.81 | 74.00                         | 54.00 | -15.04      | -10.19 |
| 7323  | H               | 49.07               | 35.98 | 10.55             | 59.62                   | 46.53 | 74.00                         | 54.00 | -14.38      | -7.47  |
| ---   |                 |                     |       |                   |                         |       |                               |       |             |        |
| 4882  | V               | 51.01               | 36.45 | 6.60              | 57.61                   | 43.05 | 74.00                         | 54.00 | -16.39      | -10.95 |
| 7323  | V               | 47.89               | 35.61 | 10.55             | 58.44                   | 46.16 | 74.00                         | 54.00 | -15.56      | -7.84  |
| ---   |                 |                     |       |                   |                         |       |                               |       |             |        |
| <b>Operation Mode: TX Mode (High)</b>       |                 |                     |       |                   |                         |       |                               |       |             |        |
| 4960  | H               | 52.12               | 37.00 | 6.89              | 59.01                   | 43.89 | 74.00                         | 54.00 | -14.99      | -10.11 |
| 7440  | H               | 49.11               | 35.68 | 10.60             | 59.71                   | 46.28 | 74.00                         | 54.00 | -14.29      | -7.72  |
| ---   |                 |                     |       |                   |                         |       |                               |       |             |        |
| 4960  | V               | 51.82               | 36.20 | 6.89              | 58.71                   | 43.09 | 74.00                         | 54.00 | -15.29      | -10.91 |
| 7440  | V               | 48.41               | 35.40 | 10.60             | 59.01                   | 46.00 | 74.00                         | 54.00 | -14.99      | -8.00  |
| ---   |                 |                     |       |                   |                         |       |                               |       |             |        |
| <b>Spurious Emission in restricted band</b> |                 |                     |       |                   |                         |       |                               |       |             |        |
| 2390.000                                    | H               | 51.15               | 36.76 | 0.09              | 51.24                   | 36.85 | 74.00                         | 54.00 | -22.76      | -17.15 |
| 2390.000                                    | V               | 50.52               | 35.93 | 0.09              | 50.61                   | 36.02 | 74.00                         | 54.00 | -23.39      | -17.98 |
| 2483.500                                    | H               | 53.30               | 37.71 | 0.35              | 53.65                   | 38.06 | 74.00                         | 54.00 | -20.35      | -15.94 |
| 2483.500                                    | V               | 53.57               | 36.21 | 0.35              | 53.92                   | 36.56 | 74.00                         | 54.00 | -20.08      | -17.44 |


Remark: Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits.

### 13.3 Channel Separation test

#### LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

- a. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- b. Set to the maximum power setting and enable the EUT transmit continuously.
- c. Enable the EUT hopping function.
- d. Set spectrum analyzer and perform testing according to ANSI C63.10-2013 clause 7.8.2.


#### TEST RESULTS

PASS

Please refer to the following table.

| Modulation     | Channel | Frequency (MHz) | Hopping Separation Measurement (MHz) | Hopping Separation Limit (MHz) | Test Result |
|----------------|---------|-----------------|--------------------------------------|--------------------------------|-------------|
| GFSK           | Low     | 2402            | 0.999                                | >0.638                         | Pass        |
|                | Mid     | 2441            | 1.002                                | >0.636                         | Pass        |
|                | High    | 2480            | 1.002                                | >0.637                         | Pass        |
| $\pi/4$ -DQPSK | Low     | 2402            | 0.999                                | >0.855                         | Pass        |
|                | Mid     | 2441            | 0.999                                | >0.856                         | Pass        |
|                | High    | 2480            | 0.999                                | >0.857                         | Pass        |
| 8DPSK          | Low     | 2402            | 1.005                                | >0.866                         | Pass        |
|                | Mid     | 2441            | 0.999                                | >0.866                         | Pass        |
|                | High    | 2480            | 1.005                                | >0.867                         | Pass        |






### 13.4 20dB Bandwidth

#### LIMIT

N/A

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

- a. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- b. Set to the maximum power setting and enable the EUT transmit continuously.
- c. Set spectrum analyzer and perform testing according to ANSI C63.10-2013 clause 6.9.2.

#### TEST RESULTS

PASS

Please refer to the following table.