

Date: **May 10<sup>th</sup> 2018**

to:	from:
<b>Regulatory Certification Body</b> DEKRA Testing and Certification, S.A.U. Parque Tecnológico de Andalucía C/ Severo Ochoa 2 & 6 29590 Campanillas Málaga, España	<b>RADE TECNOLOGÍAS S.L.,</b> Avenida Diagonal Plaza, 14, Nave 61, 50197, Zaragoza, Spain

**Related to product:**

<b>Type of equipment:</b>	Electronic device for the remote control of a light weapon locking system.
<b>Brand name:</b>	Radetec
<b>Model:</b>	Lock Remote Control (LRC)
<b>FCC ID:</b>	2AMSYLRCP0141

**To whom it may concern,**

This is an RF exposure evaluation for the aforementioned equipment.

As you will see below, the product can be used in portable conditions and certified without the need of submitting a SAR test report or an MPE calculation to show compliance with FCC or ISED regulation.

**1. Introduction**

The device Lock Remote Control (LRC) is a radio frequency transmitter-receiver. It is an RF transceiver working in the 915 MHz band and is designed to be used in portable exposure conditions.

**2. FCC SAR limits**

According to § 2.1093 (d) (2) the limits for General Population/Uncontrolled exposure are:

- 0.08 W/kg as averaged over the whole-body  
And
- peak spatial-average SAR limit is 1.6 W/kg, averaged over any 1 gram of tissue over the whole body.

**3. Compliance criteria:**

For FCC,

Individual transmitters are deemed to comply with § 2.1093 requirements if the output power of the transmitter meets the conditions specified in section 4.3.1 (Standalone SAR test exclusion) considerations of the document “KDB 447498 D01 Clause 4.3.1 General RF Exposure Guidance v05r02”.

**4. Compliance calculations:**

**Evaluation distance per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 (mm)**

Frequency (GHz)	Peak field strength (dB $\mu$ V/m)	Peak output power (dBm)	Peak output power (mW)	Evaluation distance per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 (mm)	$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$	SAR Test Exclusion Thresholds per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 - 1)	
0,915	N/A	10,62	11,534 5326	5	2,206686015	≤ 3	COMPLIANT

Sincerely,

**By:** Jose Cuesta  
**Title:** R&D Director  
**Company:** RADE TECNOLOGÍAS, S.L.  
**Telephone:** +34 976 756 113  
**e-mail:** jcuesta@radetec.com

P.A

