



## Test Report

Test Report No.:	KTI17EF07001		
Registration No.:	KR0023		
Applicant:	KingStone		
Applicant Address:	68-10, Godeok-ro 355 beon-gil, Yangju-si, Gyeonggi-do, 11480 SOUTH KOREA		
Product:	Bluetooth		
FCC ID:	2AMTE-POWER-SUPPLY	Model No.	HEXKO DC POWER SUPPLY
Receipt No.:	KTI17EK07001	Date of Incoming:	Jun 26, 2017
Date of Issue:	Jul 03, 2017		
Testing location	Korea Technology Institute Co., Ltd. 58-10, Sagiso-gil, Docheok-myeon, Gwangju-si, Gyeonggi-do, Korea		
Test Standards:	FCC PART 15 SUBPART C Section 15.247		
Method of Measurement	FCC Public Notice DA 00-705		
Test Result:	The above-mentioned product has been tested with compliance.		

Tested by: W. J. Yun.  
/ Engineer

Signature Date Jul 03, 2017

Approved by: S. H. Song  
/Technical Manager

Signature Date Jul 03, 2017

Other Aspects:			
Abbreviations:	* OK, Pass=passed * Fail=failed * N/A=not applicable		

- This test report is not permitted to copy partly without our permission.

- This test result is dependent on only equipment to be used.

- This test result is based on a single evaluation of one sample of the above mentioned.

- We certify this test report has been based on the measurement standards that is traceable to the national or international standards.

**>>> Contents <<<**

<b>1. Verification of compliance</b>	<b>3</b>
<b>2. General Information</b>	<b>4</b>
<b>3. EUT MODIFICATIONS</b>	<b>4</b>
<b>4. MAXIMUM PERMISSIBLE EXPOSURE</b>	<b>5</b>



## 1. Verification of compliance

Applicant : KingStone

Address : 68-10, Godeok-ro 355beon-gil,

Yangju-si, Gyeonggi-do, 11480 SOUTH KOREA

FCC ID : 2AMTE-POWER-SUPPLY

Model Name : HEXKO DC POWER SUPPLY

Brand Name : 

Serial Number : N/A

Test Date Jun 26, 2017

Equipment Class	DTS – DIGITAL TRNSMISSION SYSTEM
Kind of Equipment	Bluetooth
Measurement Procedures	ANSI C63.10: 2014
Type of Equipment Tested	Pre-Production
Kind of Equipment Authorization Requested	Certification
Equipment Will Be Operated Under FCC Rules Part(s)	FCC PART 15 SUBPART C Section 15.247
Modifications On The Equipment To Achieve Compliance	None
Final Test was Conducted On	10m Open area test site

- The above equipment was tested by Korea Technology Institute Co., Ltd. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanation from equipment are within the compliance requirements.



## 2. General Information

### 2.1 Product Description

BPAY-CAG-01 (referred to in this report as EUT) is used as a Power Supply.

The product specification described herein was obtained from product data sheet or user's manual.

Equipment Name	HEXKO DC POWER SUPPLY
Operating Frequency	2402 MHz ~ 2480 MHz
RF Output Power	-1.81 dBm
Number of Channel	40 Channels
Modulation Type	GFSK
Antenna Type / Gain	Dielectric Chip Antenna / -2.68 dBi (Max)
List of Each OSC. Or Crystal. Freq.	180 MHz
Rated Supply Voltage	DC 19.0 V

**Alternative type(s)/model(s); also covered by this test report.**

- None

## 3. EUT MODIFICATIONS

- None



## 4. MAXIMUM PERMISSIBLE EXPOSURE

### RF Exposure Calculation

According to the FCC rule §1.1310, the limit for General Population/Uncontrolled exposure is 1 mW/cm<sup>2</sup> for the device operating 1 500 ~ 100 000 MHz.

### EUT Description

Kind of EUT	HEXKO DC POWER SUPPLY
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz <input type="checkbox"/> and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 240 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Bluetooth BLE: 2 402 MHz ~ 2 480 MHz
MAX. RF OUTPUT	-1.81 dBm
Antenna Gain	-2.68 dBi
Exposure Evaluation Applied	<input type="checkbox"/> MPE <input type="checkbox"/> SAR <input checked="" type="checkbox"/> N/A

### Test Result

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is  

$$[(\text{Max. Power of channel, including tune-up tolerance, mW}) / (\text{Mim. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$$

$$= (0.65/5) \times \sqrt{2.402} = 0.2$$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and excluded SAR Test.

	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
BLE (GFSK)	2 402	1.0 ± 1.0	0.8	1.2	5	0.2