



Appendix B

RF Test Data for BLE (Conducted Measurement)

Product Name: Legends Ultimate Mini Home Arcade

Test Model: HA8811

Environmental Conditions

Temperature:	23.5° C
Relative Humidity:	52.2%
ATM Pressure:	100.0 kPa
Test Engineer:	Monkey Li
Supervised by:	Li huan



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



B.1 6dB Bandwidth


Test Result


TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant	2402	0.704	2401.644	2402.348	0.5	PASS
		2440	0.704	2439.644	2440.348	0.5	PASS
		2480	0.720	2479.636	2480.356	0.5	PASS





Test Graphs







B.2 Maximum conducted output power


Test Result


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant	2402	0.50	≤30	PASS
		2440	0.24	≤30	PASS
		2480	0.14	≤30	PASS





Test Graphs







B.3 Maximum power spectral density


Test Result


TestMode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant	2402	-15.28	≤8.00	PASS
		2440	-15.46	≤8.00	PASS
		2480	-15.69	≤8.00	PASS





Test Graphs







B.4 Band edge measurements


Test Result

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant	Low	2402	0.47	-47.65	≤-19.53	PASS
		High	2480	0.18	-47.99	≤-19.82	PASS





Test Graphs





B.5 Conducted Spurious Emission


Test Result


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant	2402	Reference	0.39	0.39	---	PASS
			30~1000	0.39	-60.37	≤-19.61	PASS
			1000~26500	0.39	-46.33	≤-19.61	PASS
		2440	Reference	0.07	0.07	---	PASS
			30~1000	0.07	-60.44	≤-19.93	PASS
			1000~26500	0.07	-46.09	≤-19.93	PASS
		2480	Reference	0.04	0.04	---	PASS
			30~1000	0.04	-60.44	≤-19.96	PASS
			1000~26500	0.04	-44.62	≤-19.96	PASS






Test Graphs






BLE_Ant_2440_0~Reference




BLE_Ant_2440_30~1000








BLE_Ant_2440_1000~26500



BLE_Ant_2480_0~Reference









B.6 Duty Cycle


Test Result


TestMode	Antenna	Channel	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
BLE	Ant	2402	2.14	2.50	0.8560	85.60	0.68	---	---
		2440	2.14	2.50	0.8560	85.60	0.68	---	---
		2480	2.14	2.50	0.8560	85.60	0.68	---	---





Test Graphs







B.7 Emissions in Restricted Bands

Test Result

TestMode	Antenna	ChName	Channel	Detector	Freq. [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE	Ant	Low	2402	AV	2310.000	-48.27	≤-41.20	46.93	≤54	PASS
				AV	2389.250	-47.66	≤-41.20	47.54	≤54	PASS
				AV	2390.000	-47.82	≤-41.20	47.38	≤54	PASS
				Peak	2310.000	-39.99	≤-21.20	55.21	≤74	PASS
				Peak	2345.045	-36.53	≤-21.20	58.67	≤74	PASS
				Peak	2390.000	-38.75	≤-21.20	56.45	≤74	PASS
		High	2480	AV	2483.500	-46.83	≤-41.20	48.37	≤54	PASS
				AV	2483.520	-46.83	≤-41.20	48.37	≤54	PASS
				AV	2500.000	-47.34	≤-41.20	47.86	≤54	PASS
				Peak	2483.500	-36	≤-21.20	59.20	≤74	PASS
				Peak	2483.520	-36	≤-21.20	59.20	≤74	PASS
				Peak	2500.000	-38.51	≤-21.20	56.69	≤74	PASS

Note:

1. The Antenna Gain is compensated in the graph.
2. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Test Graphs

