

TEST REPORT

Applicant Name : Changsha Qisi Technology Co., Ltd.
Address : #10039, BLD 2, B1E1, NO. 68 Qinglan Rd Kaifu District, Changsha, Hunan Province, PRC
Report Number : RA230113-02333E-RF-00A
FCC ID: 2AMUA-AV1

Test Standard (s)
FCC PART 15.247


Sample Description

Product Type: AURGA Viewer
Model No.: AVW1
Trade Name: AURGA
Date Received: 2023-01-13
Date of Test: 2023-02-06 to 2023-02-15
Report Date: 2023-02-15

Test Result:	Pass*
--------------	-------


* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Roger.Ling
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “★”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	11
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	13
TEST EQUIPMENT LIST	14
FCC §1.1307(b)&§2.1093 - RF EXPOSURE.....	15
FCC §15.203 – ANTENNA REQUIREMENT	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	18
FACTOR & MARGIN CALCULATION	18
TEST DATA	18
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
FACTOR & MARGIN CALCULATION	22
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	37
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41

FCC §15.247(e) - POWER SPECTRAL DENSITY	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	44

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230113-02333E-RF-00A	Original Report	2023-02-15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	AURGA Viewer
Tested Model	AVW1
Frequency Range	BLE 1M/2M: 2402~2480MHz
Maximum conducted Peak output power	4.52dBm
Modulation Technique	GFSK
Antenna Specification*	Internal Antenna:3dBi (provided by the applicant)
Voltage Range	DC 5V from USB port
Sample number	RA230113-02333E-RF-S1 (RF Radiated Test) RA230113-02333E-RF-S2 (RF Conducted Test) (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF Frequency	0.082×10^{-7}	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
AC Power Lines Conducted Emissions	2.72dB	
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
Temperature	1°C	
Humidity	6%	
Supply voltages	0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
...
...
...
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

EUT Exercise Software

Software “Putty”* was used during testing and the power level was default*.

Special Accessories



No special accessory.



Equipment Modifications



No modification was made to the EUT tested.

Duty Cycle

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T minimum VBW setting[kHz]
BLE_1M	Ant1	2402	2.11	2.47	85.42	0.474
		2440	2.11	2.47	85.42	0.474
		2480	2.11	2.47	85.42	0.474
BLE_2M	Ant1	2402	1.07	1.86	57.53	0.935
		2440	1.07	1.87	57.23	0.935
		2480	1.07	1.86	57.53	0.935







Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Giec	DVD	Bdp-G4308	546372048691125
HUAWEI	Adapter	HW-050100C01	H779KBK6V19398

External I/O Cable


Cable Description	Length (m)	From/Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 & §2.1093	RF Exposure(SAR)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2022/11/30	2025/11/29
Schwarzbeck	Horn Antenna	BBHA9170	9170-359	2022/12/26	2025/12/25
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24
Radiated Emission Test Software: e3 19821b (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2022/11/25	2023/11/24
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2022/11/25	2023/11/24
WEINSCHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.33	RF-03	Each time	

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(B)&§2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RA230113-02333E-SA.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 3dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Test Data


Environmental Conditions

Temperature:	23°C
Relative Humidity:	53%
ATM Pressure:	101.0kPa

The testing was performed by Lipa Wu on 2023-02-15.

EUT operation mode: BLE Transmitting


AC 120V/60 Hz, Line



Site : Shielding Room
Condition: Line
Job No. : RA230113-02333E-RF
Mode : BLE Transmitting

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	0.189	9.90	32.71	42.61	54.07 -11.46 Average
2	0.189	9.90	47.18	57.08	64.07 -6.99 QP
3	0.240	9.88	24.91	34.79	52.11 -17.32 Average
4	0.240	9.88	40.60	50.48	62.11 -11.63 QP
5	0.244	9.88	23.00	32.88	51.95 -19.07 Average
6	0.244	9.88	39.46	49.34	61.95 -12.61 QP
7	0.305	9.85	19.42	29.27	50.10 -20.83 Average
8	0.305	9.85	35.16	45.01	60.10 -15.09 QP
9	1.850	9.91	20.15	30.06	46.00 -15.94 Average
10	1.850	9.91	30.24	40.15	56.00 -15.85 QP
11	5.805	9.96	22.06	32.02	50.00 -17.98 Average
12	5.805	9.96	29.20	39.16	60.00 -20.84 QP

AC 120V/60 Hz, Neutral





Site : Shielding Room
Condition: Neutral
Job No. : RA230113-02333E-RF
Mode : BLE Transmitting

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	0.187	9.80	32.59	42.39	54.18 -11.79 Average
2	0.187	9.80	46.78	56.58	64.18 -7.60 QP
3	0.196	9.80	31.29	41.09	53.78 -12.69 Average
4	0.196	9.80	44.86	54.66	63.78 -9.12 QP
5	0.209	9.80	11.87	21.67	53.24 -31.57 Average
6	0.209	9.80	36.22	46.02	63.24 -17.22 QP
7	0.252	9.83	28.19	38.02	51.69 -13.67 Average
8	0.252	9.83	39.77	49.60	61.69 -12.09 QP
9	3.623	9.84	21.22	31.06	46.00 -14.94 Average
10	3.623	9.84	29.94	39.78	56.00 -16.22 QP
11	5.440	9.96	21.38	31.34	50.00 -18.66 Average
12	5.440	9.96	28.20	38.16	60.00 -21.84 QP

FCC §15.205, §15.209 & §15.247(D) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10Hz*	/	Ave.
	1 MHz	1/T**	/	Ave.

Note: * for duty cycle \geq 98%

**for duty cycle $<$ 98%, and T is maximum transmission duration.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$


Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	59%
ATM Pressure:	101.0kPa


The testing was performed by Jimi Zheng on 2023-02-10.

EUT operation mode: Transmitting (Scan with BLE 1M mode at X axis, Y axis, Z axis, the worst case is at X axis)

Below 1GHz: (worst case for BLE 1M, High Channel)**Horizontal**

Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA230113-02333E-RF
Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	150.011	-15.27	52.21	36.94	43.50	-6.56	Peak
2	241.465	-10.81	51.31	40.50	46.00	-5.50	QP
3	325.168	-8.26	46.03	37.77	46.00	-8.23	Peak
4	378.087	-7.20	45.74	38.54	46.00	-7.46	Peak
5	434.255	-5.72	42.05	36.33	46.00	-9.67	Peak
6	741.934	-0.82	40.81	39.99	46.00	-6.01	QP

Vertical

Site : chamber
Condition: 3m VERTICAL
Job No. : RA230113-02333E-RF
Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	53.953	-10.34	38.99	28.65	40.00	-11.35	Peak
2	154.617	-14.97	48.51	33.54	43.50	-9.96	Peak
3	239.987	-10.91	46.40	35.49	46.00	-10.51	Peak
4	409.664	-6.36	42.73	36.37	46.00	-9.63	Peak
5	549.983	-4.03	40.13	36.10	46.00	-9.90	Peak
6	750.108	-0.87	40.02	39.15	46.00	-6.85	Peak

Note: For below 1GHz, when the test result of peak was below to the limit of QP more than 6dB, just peak value was recorded.

Above 1GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
BLE 1M, Low Channel									
2310	47.45	PK	97	1.6	H	-7.23	40.22	74	-33.78
2310	51.34	PK	45	2.1	V	-7.23	44.11	74	-29.89
2390	49.39	PK	338	1.0	H	-7.21	42.18	74	-31.82
2390	55.87	PK	224	1.5	V	-7.21	48.66	74	-25.34
4804	49.68	PK	38	1.4	H	-3.52	46.16	74	-27.84
4804	49.33	PK	210	1.0	V	-3.52	45.81	74	-28.19
BLE 1M, Middle Channel									
4880	49.03	PK	184	1.3	H	-3.38	45.65	74	-28.35
4880	49.02	PK	291	1.8	V	-3.38	45.64	74	-28.36
BLE 1M, High Channel									
2483.5	47.15	PK	27	1.0	H	-7.2	39.95	74	-34.05
2483.5	47.62	PK	266	1.3	V	-7.2	40.42	74	-33.58
2500	46.82	PK	27	2.0	H	-7.18	39.64	74	-34.36
2500	48.04	PK	226	1.2	V	-7.18	40.86	74	-33.14
4960	49.27	PK	57	1.4	H	-3.01	46.26	74	-27.74
4960	47.86	PK	292	1.2	V	-3.01	44.85	74	-29.15

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
BLE 2M, Low Channel									
2310	46.48	PK	97	1.6	H	-7.23	39.25	74	-34.75
2310	47.58	PK	45	2.1	V	-7.23	40.35	74	-33.65
2390	47.64	PK	338	1.0	H	-7.21	40.43	74	-33.57
2390	52.14	PK	224	1.5	V	-7.21	44.93	74	-29.07
4804	49.28	PK	38	1.4	H	-3.52	45.76	74	-28.24
4804	48.62	PK	210	1.0	V	-3.52	45.1	74	-28.9
BLE 2M, Middle Channel									
4880	48.24	PK	184	1.3	H	-3.38	44.86	74	-29.14
4880	48.64	PK	291	1.8	V	-3.38	45.26	74	-28.74
BLE 2M, High Channel									
2483.5	50.18	PK	27	1.0	H	-7.2	42.98	74	-31.02
2483.5	48.22	PK	266	1.3	V	-7.2	41.02	74	-32.98
2500	47.63	PK	27	2.0	H	-7.18	40.45	74	-33.55
2500	47.55	PK	226	1.2	V	-7.18	40.37	74	-33.63
4960	49.18	PK	57	1.4	H	-3.01	46.17	74	-27.83
4960	48.46	PK	292	1.2	V	-3.01	45.45	74	-28.55

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected Amplitude - Limit


The other spurious emission which is in the noise floor level was not recorded.

For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.


1 GHz - 18 GHz: (Pre-Scan plots)

Worst for BLE 1M, High Channel

Horizontal




Vertical




18-25GHz: (Pre-Scan plots)

Worst for BLE 1M, High Channel

Horizontal



Vertical



FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10 section 11.8.1 and section 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Use the 99% power bandwidth function of the instrument and report the measured occupied bandwidth
5. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	48%
ATM Pressure:	101.0 kPa


The testing was performed by Glenn Jiang on 2023-02-06.

EUT operation mode: Transmitting


Test Result: PASS. Please refer to the tables and plots.

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.692	2401.608	2402.300	0.5	PASS
		2440	0.692	2439.612	2440.308	0.5	PASS
		2480	0.684	2479.624	2480.212	0.5	PASS
BLE_2M	Ant1	2402	1.178	2401.334	2402.512	0.5	PASS
		2440	1.182	2439.334	2440.516	0.5	PASS
		2480	1.169	2479.351	2479.520	0.5	PASS

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.055	2401.433	2402.488	---	PASS
		2440	1.055	2439.437	2440.492	---	PASS
		2480	1.055	2479.441	2480.496	---	PASS
BLE_2M	Ant1	2402	2.082	2400.925	2403.007	---	PASS
		2440	2.082	2438.929	2441.011	---	PASS
		2480	2.082	2478.933	2481.015	---	PASS


6 dB EMISSION BANDWIDTH:

Date: 6.FEB.2023 13:59:00




Date: 6.FEB.2023 14:07:14

BLE_1M_Ant1_2480





Date: 6.FEB.2023 14:09:15



BLE_2M_Ant1_2402







Date: 6.FEB.2023 14:24:39



Date: 6.FEB.2023 14:34:23

99% OCCUPIED BANDWIDTH:





FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10 section 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	48%
ATM Pressure:	101.0 kPa


The testing was performed by Glenn Jiang on 2023-02-06.

EUT operation mode: Transmitting

Test Result: PASS. Please refer to the table and plots.


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	3.77	<=30	PASS
		2440	4.23	<=30	PASS
		2480	4.45	<=30	PASS
BLE_2M	Ant1	2402	3.80	<=30	PASS
		2440	4.29	<=30	PASS
		2480	4.52	<=30	PASS

BLE_1M_Ant1_2402




Date: 6.FEB.2023 13:59:30

BLE_1M_Ant1_2440




Date: 6.FEB.2023 14:07:43

BLE_1M_Ant1_2480




Date: 6.FEB.2023 14:09:44

BLE_2M_Ant1_2402




Date: 6.FEB.2023 14:25:09

BLE_2M_Ant1_2440



Date: 6.FEB.2023 14:28:51

BLE_2M_Ant1_2480



Date: 6.FEB.2023 14:34:53

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10 section 11.11.2

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data



Environmental Conditions



Temperature:	24°C
Relative Humidity:	48%
ATM Pressure:	101.0 kPa

The testing was performed by Glenn Jiang on 2023-02-06.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the table and plots.





FCC §15.247(E) - POWER SPECTRAL DENSITY


Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10 section 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	48%
ATM Pressure:	101.0 kPa


The testing was performed by Glenn Jiang on 2023-02-06.

EUT operation mode: Transmitting


Test Result: PASS. Please refer to the table and plots.

Test Mode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-11.96	<=8	PASS
		2440	-11.61	<=8	PASS
		2480	-11.35	<=8	PASS
BLE_2M	Ant1	2402	-12.94	<=8	PASS
		2440	-12.46	<=8	PASS
		2480	-12.26	<=8	PASS


BLE_1M_Ant1_2402



BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




Date: 6.FEB.2023 14:09:56


BLE_2M_Ant1_2402



Date: 6.FEB.2023 14:25:20



Date: 6.FEB.2023 14:29:03



Date: 6.FEB.2023 14:35:05

******* END OF REPORT *******