

TEST REPORT

Product Name: Five-pass amphibious small shark stunt car
FCC ID: 2AMVB-989-313
Trademark: N/A
Model Number: 989-313, See next page for other models
Prepared For: XIONGQI TOYS FACTORY
Address: NO.8, 1 ROAD, LIANDONG WEST,LIANXIA TOWN OF XIACUN INDUSTRIAL ZONE, CHENGHAI DISTRICT, SHANTOU, China
Manufacturer: XIONGQI TOYS FACTORY
Address: NO.8, 1 ROAD, LIANDONG WEST,LIANXIA TOWN OF XIACUN INDUSTRIAL ZONE, CHENGHAI DISTRICT, SHANTOU, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd,
Address: Floor 1&2, Building A, No, 26 of Xinhe Road, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China,
Sample Received Date: Jul. 20, 2022
Sample tested Date: Jul. 20, 2022 to Jul. 26, 2022
Issue Date: Jul. 26, 2022
Report No. : CTB220726031RF
Test Standards FCC Part15, 249
ANSI C63, 10:2013
Test Results PASS
Remark: This is 2.4GHz radio test report,

Compiled by:

Chen Zheng

Reviewed by:

Arron Liu

Approved by:



Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report, The test report is effective only with both signature and specialized stamp, This result(s) shown in this report refer only to the sample(s) tested, Without written approval of Shenzhen CTB Testing Technology Co., Ltd, this report can't be reproduced except in full, The tested sample(s) and the sample information are provided by the client, “*” indicates the testing items were fulfilled by subcontracted lab, “#” indicates the items are not in CNAS accreditation scope,

Other models are as follows:

989-01, 989-02, 989-03, 989-04, 989-05, 989-06, 989-07, 989-08, 989-09, 989-10, 989-01A, 989-02A, 989-03A, 989-04A, 989-11, 989-12, 989-13, 989-14, 989-15, 989-16, 989-17, 989-18, 989-19, 989-20, 989-11B, 989-12B, 989-13B, 989-14B, 989-15B, 989-16B, 989-17B, 989-18B, 989-19B, 989-20B, 989-21, 989-22, 989-23, 989-24, 989-25, 989-26, 989-27, 989-28, 989-29, 989-30, 989-31, 989-32, 989-33, 989-34, 989-35, 989-36, 989-37, 989-38, 989-39, 989-40, 989-31B, 989-32B, 989-33B, 989-34B, 989-35B, 989-36B, 989-37B, 989-38B, 989-39B, 989-40B, 989-111, 989-222, 989-333, 989-555, 989-666, 989-777, 989-888, 989-999, 989-323, 989-353, 989-363, 989-373, 989-383, 989-393, 989-393A, 989-51, 989-52, 989-53, 989-54, 989-55, 989-56, 989-57, 989-58, 989-59, 989-60, 989-61, 989-62, 989-63, 989-64, 989-65, 989-66, 989-67, 989-68, 989-69, 989-70, 989-71, 989-72, 989-73, 989-74, 989-75, 989-76, 989-77, 989-78, 989-79, 989-80, 989-81, 989-82, 989-83, 989-84, 989-85, 989-86, 989-87, 989-88, 989-89, 989-90, 989-91, 989-92, 989-93, 989-94, 989-95, 989-96, 989-97, 989-98, 989-99, 989-303

TABLE OF CONTENT

Test Report Declaration	Page
1, VERSION	4
2, TEST SUMMARY	5
3, MEASUREMENT UNCERTAINTY	6
4, PRODUCT INFORMATION AND TEST SETUP	7
4, 1 Product Information	7
4, 2 Test Setup Configuration	8
4, 3 Support Equipment	8
4, 4 Channel List	9
4, 5 Test Mode	9
4, 6 Test Environment	9
5, TEST FACILITY AND TEST INSTRUMENT USED	10
5, 1 Test Facility	10
5, 2 Test Instrument Used	10
6, AC POWER LINE CONDUCTED EMISSION	13
6, 1 Block Diagram Of Test Setup	13
6, 2 Limit	13
6, 3 Test procedure	13
6, 4 Test Result	15
7, RADIATED SPURIOUS EMISSION	16
7, 1 Block Diagram Of Test Setup	16
7, 2 Limit	16
7, 3 Test procedure	17
7, 4 Test Result	18
8, BAND EDGE AND RF CONDUCTED SPURIOUS EMISSIONS	23
8, 1 Block Diagram Of Test Setup	23
8, 2 Limit	23
8, 3 Test procedure	24
8, 4 Test Result	25
9, BANDWIDTH TEST	26
9, 1 Block Diagram Of Test Setup	26
9, 2 Limit	26
9, 3 Test procedure	26
9, 4 Test Result	26
10, ANTENNA REQUIREMENT	28
11, EUT TEST SETUP PHOTOGRAPHS	29

(Note: N/A means not applicable)

1. VERSION

Report No,	Issue Date	Description	Approved
CTB220726031RF	Jul. 26, 2022	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Standard Section	Test Item	Judgment	Remark
15, 207	Conducted Emission	PASS	
15, 215	20dB Bandwidth	PASS	
15, 249	Fundamental & Radiated Spurious Emission Measurement	PASS	
15, 205	Band Edge Emission	PASS	
15, 203	Antenna Requirement	PASS	

Remark:

Test according to ANSI C63, 4-2014 & ANSI C63, 10-2013,

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2,

Item	Uncertainty
Occupancy bandwidth	54, 3kHz
Conducted output power Above 1G	0, 9dB
Conducted output power below 1G	0, 9dB
Power Spectral Density , Conduction	0, 9dB
Conduction spurious emissions	2, 0dB
Out of band emission	2, 0dB
3m chamber Radiated spurious emission(9KHz-30MHz)	4, 8dB
3m chamber Radiated spurious emission(30MHz-1GHz)	4, 6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5, 1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3, 4dB
humidity uncertainty	5, 5%
Temperature uncertainty	0, 63°C
frequency	1×10 ⁻⁷
Conducted Emission (150KHz-30MHz)	3, 2 dB
Radiated Emission(30MHz ~ 1000MHz)	4, 8 dB
Radiated Emission(1GHz ~6GHz)	4, 9 dB

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):

989-313, 989-01, 989-02, 989-03, 989-04, 989-05, 989-06, 989-07, 989-08, 989-09, 989-10, 989-01A, 989-02A, 989-03A, 989-04A, 989-11, 989-12, 989-13, 989-14, 989-15, 989-16, 989-17, 989-18, 989-19, 989-20, 989-11B, 989-12B, 989-13B, 989-14B, 989-15B, 989-16B, 989-17B, 989-18B, 989-19B, 989-20B, 989-21, 989-22, 989-23, 989-24, 989-25, 989-26, 989-27, 989-28, 989-29, 989-30, 989-31, 989-32, 989-33, 989-34, 989-35, 989-36, 989-37, 989-38, 989-39, 989-40, 989-31B, 989-32B, 989-33B, 989-34B, 989-35B, 989-36B, 989-37B, 989-38B, 989-39B, 989-40B, 989-111, 989-222, 989-333, 989-555, 989-666, 989-777, 989-888, 989-999, 989-323, 989-353, 989-363, 989-373, 989-383, 989-393, 989-393A, 989-51, 989-52, 989-53, 989-54, 989-55, 989-56, 989-57, 989-58, 989-59, 989-60, 989-61, 989-62, 989-63, 989-64, 989-65, 989-66, 989-67, 989-68, 989-69, 989-70, 989-71, 989-72, 989-73, 989-74, 989-75, 989-76, 989-77, 989-78, 989-79, 989-80, 989-81, 989-82, 989-83, 989-84, 989-85, 989-86, 989-87, 989-88, 989-89, 989-90, 989-91, 989-92, 989-93, 989-94, 989-95, 989-96, 989-97, 989-98, 989-99, 989-303

Model Description:

All the model are the same circuit and RF module, only for model name, Test sample model: 989-313

Hardware Version:

V1.0

Software Version:

V1.0

Operation Frequency: 2410-2473MHz

Type of Modulation: GFSK

Antenna installation: Interna Antenna

Antenna Gain: 1dBi

Ratings: DC 3V by battery

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment,

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series	Note

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test,
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use,

4, 4 Channel List

Channel	Frequency (MHz)	Channe l	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410	11	2429	21	2450	31	2469
2	2414	12	2430	22	2452	32	2473
3	2415	13	2431	23	2454		
4	2416	14	2433	24	2456		
5	2417	15	2434	25	2458		
6	2418	16	2439	26	2462		
7	2419	17	2441	27	2464		
8	2421	18	2442	28	2465		
9	2426	19	2444	29	2466		
10	2428	20	2446	30	2467		

4, 5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported,

Test mode	Low channel	Middle channel	High channel
Transmitting GFSK	2410MHz	2439MHz	2473MHz

4, 6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):	3V
Normal Temperature(°C)	23
Low Temperature(°C)	0
High Temperature(°C)	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5, 1 Test Facility

All measurement facilities used to collect the measurement data are located at Floor 1&2, Building A, No, 26 of Xinhe Road, Xinqiao Street, Baoan District, Shenzhen China, The site and apparatus are constructed in conformance with the requirements of ANSI C63, 4 and CISPR 16-1-1 other equivalent standards,

5, 2 Test Instrument Used

No,	Equipment	Manufacturer	Model No,	Serial No,	Calibrated date	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	2021, 09, 27	2022, 08, 05
2	Power Sensor	Agilent	U2021XA	MY56120032	2021, 09, 27	2022, 08, 05
3	Power Sensor	Agilent	U2021XA	MY56120034	2021, 09, 27	2022, 08, 05
4	Communication test set	R&S	CMW500	108058	2021, 09, 27	2022, 08, 05
5	Spectrum Analyzer	R&S	FSP40	100550	2021, 09, 27	2022, 08, 05
6	Signal Generator	Agilent	N5181A	MY49060920	2021, 09, 27	2022, 08, 16
7	Signal Generator	Agilent	N5182A	MY47420195	2021, 09, 27	2022, 08, 05
8	Communication test set	Agilent	E5515C	MY50102567	2021, 09, 27	2022, 08, 16
9	band rejection filter	Shenxiang	MSF2400-2483, 5MS-1154	20181015001	2021, 09, 27	2022, 08, 05
10	band rejection filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	2021, 09, 27	2022, 08, 05
11	band rejection filter	Xingbo	XBLBQ-DZA120	190821-1-1	2021, 09, 27	2022, 08, 05
12	BT&WI-FI Automatic test software	Microwave	MTS8310	Ver, 2, 0, 0, 0	2021, 09, 27	2022, 08, 05
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	2021, 09, 27	2022, 08, 05
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	2021, 09, 27	2022, 08, 05
15	234G Automatic test software	Microwave	MTS8200	Ver, 2, 0, 0, 0	2021, 09, 27	2022, 08, 05
16	966 chamber	C, R, T,	966 Room	966	2021, 09, 27	2024, 08, 11
17	Receiver	R&S	ESPI	100362	2021, 09, 27	2022, 08, 05
18	Amplifier	HP	8447E	2945A02747	2021, 09, 27	2022, 08, 05
19	Amplifier	Agilent	8449B	3008A01838	2021, 09, 27	2022, 08, 05
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	869	2021, 09, 27	2022, 08, 07
21	Horn Antenna	Schwarzbeck	BBHA9120D	1911	2021, 09, 27	2022, 08, 08
22	Software	Fala	EZ-EMC	FA-03A2 RE	2021, 09, 27	2022, 08, 05




23	3-Loop Antenna	Daze	ZN30401	17014	2021, 09, 27	2022, 08, 05
24	loop antenna	ZHINAN	ZN30900A	/	2021, 09, 27	2022, 08, 05
25	Horn antenna	A/H/System	SAS-574	588	2021, 09, 27	2022, 08, 05
26	Amplifier	AEROFLEX	/	S/N/ 097	2021, 09, 27	2022, 08, 05

Radiated emission						
No,	Equipment	Manufacturer	Model No,	Serial No,	Calibrated date	Calibrated until
1	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	1911	2021, 09, 27	2022, 08, 08
2	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	869	2021, 09, 27	2022, 08, 05
3	Amplifier	Agilent	8449B	3008A01838	2021, 09, 27	2022, 08, 05
4	Amplifier	HP	8447E	2945A02747	2021, 09, 27	2022, 08, 05
5	EMI TEST RECEIVER	ROHDE&SCHW ARZ	ESPI7	100362	2021, 09, 27	2022, 08, 05
6	Coaxial cable	ETS	RFC-SNS-100-NMS-80 NI	/	2021, 09, 27	2022, 08, 05
7	Coaxial cable	ETS	RFC-SNS-100-NMS-20 NI	/	2021, 09, 27	2022, 08, 05
8	Coaxial cable	ETS	RFC-SNS-100-SMS-20 NI	/	2021, 09, 27	2022, 08, 05
9	Coaxial cable	ETS	RFC-NNS-100-NMS-30 0 NI	/	2021, 09, 27	2022, 08, 05
10	Communication test set	Agilent	E5515C	MY50102567	2021, 09, 27	2022, 08, 16
11	Communication test set	R&S	CMW500	108058	2021, 09, 27	2022, 08, 05
12	EZ-EMC	Frad	EMC-con3A1, 1	/	/	/

6, AC POWER LINE CONDUCTED EMISSION

6, 1 Block Diagram Of Test Setup



6, 2 Limit

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

* Decreasing linearly with the logarithm of the frequency

6, 3 Test procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room,
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded,
- 3) The tabletop EUT was placed upon a non-metallic table 0,8m above the ground reference plane, And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane, The rear of the EUT shall be 0,4 m from the vertical ground reference plane, The vertical ground reference plane was bonded to the horizontal ground reference plane, The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference

plane, This distance was between the closest points of the LISN 1 and the EUT, All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2,

- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63, 10 on conducted measurement,
- 6) All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported,
- 7) If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane,

6, 4 Test Result

N/A

NOTE: This EUT is powered by DC power only, this test item is not applicable,

7. RADIATED SPURIOUS EMISSION

7, 1 Block Diagram Of Test Setup




Figure 1, Below 30MHz





Figure 2, 30MHz to 1GHz



7, 2 Limit

Spurious Emissions:

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0, 009MHz-0, 490MHz	2400/F(kHz)	-	-	300
0, 490MHz-1, 705MHz	24000/F(kHz)	-	-	30
1, 705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40, 0	Quasi-peak	3
88MHz-216MHz	150	43, 5	Quasi-peak	3
216MHz-960MHz	200	46, 0	Quasi-peak	3
960MHz-1GHz	500	54, 0	Quasi-peak	3
Above 1GHz	500	54, 0	Average	3

Note: 15, 35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device,

7.3 Test procedure

Below 1GHz test procedure as below:

- a, The EUT was placed on the top of a rotating table 0, 8 meters above the ground at a 3 meter semi-anechoic camber, The table was rotated 360 degrees to determine the position of the highest radiation,
- b, The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower,
- c, The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength, Both horizontal and vertical polarizations of the antenna are set to make the measurement,
- d, For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading,
- e, The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode,
- f, If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported, Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet,

Above 1GHz test procedure as below:

- g, Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0, 8 meter to 1, 5 meter(Above 18GHz the distance is 1 meter and table is 1, 5 meter),
- h, Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- j, Repeat above procedures until all frequencies measured was complete,
- j, Full battery is used during test

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0, 009MHz-0, 090MHz	Peak	10kHz	30KHz	Peak
0, 009MHz-0, 090MHz	Average	10kHz	30KHz	Average
0, 090MHz-0, 110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0, 110MHz-0, 490MHz	Peak	10kHz	30KHz	Peak
0, 110MHz-0, 490MHz	Average	10kHz	30KHz	Average
0, 490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

7.4 Test Result

Below 1GHz Test Results:

Antenna polarity: H



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB/m	dB
1		44.9004	33.61	-5.45	28.16	40.00	-11.84
2		85.1486	35.22	-9.75	25.47	40.00	-14.53
3		164.3301	41.06	-5.82	35.24	43.50	-8.26
4		231.3119	42.13	-5.88	36.25	46.00	-9.75
5	!	377.9211	43.11	-2.46	40.65	46.00	-5.35
6	*	685.9469	37.01	3.77	40.78	46.00	-5.22

Remark: Factor = Cable loss + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

Antenna polarity: V



No.	Mk.	Freq.	Reading	Correct Factor	Measure-	Limit	Over	Detector
			Level		ment			
1		61.5617	39.46	-6.44	33.02	40.00	-6.98	QP
2		131.9889	43.06	-6.01	37.05	43.50	-6.45	QP
3		231.3119	43.72	-5.88	37.84	46.00	-8.16	QP
4	!	295.6648	46.24	-5.26	40.98	46.00	-5.02	QP
5	!	565.6295	38.63	1.93	40.56	46.00	-5.44	QP
6	*	698.0795	37.10	3.94	41.04	46.00	-4.96	QP

Remark: Factor = Cable loss + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

CH Low (2410MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
2410	106.66	-5.71	100.95	114	-13.05	peak
2410	92.08	-5.71	86.37	94	-7.63	AVG
4820	54.74	-3.51	51.23	74	-22.77	peak
4820	46.45	-3.51	42.94	54	-11.06	AVG
7230	56.08	-0.82	55.26	74	-18.74	peak
7230	46.51	-0.82	45.69	54	-8.31	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
2410	111.08	-5.84	105.24	114	-8.76	peak
2410	94.10	-5.84	88.26	94	-5.74	AVG
4820	56.96	-3.64	53.32	74	-20.68	peak
4820	49.91	-3.64	46.27	54	-7.73	AVG
7230	59.19	-0.95	58.24	74	-15.76	peak
7230	48.49	-0.95	47.54	54	-6.46	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

CH Middle (2439MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
2439	106.38	-5.71	100.67	114	-13.33	peak
2439	93.10	-5.71	87.39	94	-6.61	AVG
4878	54.55	-3.51	51.04	74	-22.96	peak
4878	46.30	-3.51	42.79	54	-11.21	AVG
7317	56.63	-0.82	55.81	74	-18.19	peak
7317	47.55	-0.82	46.73	54	-7.27	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
2439	106.37	-5.71	100.66	114	-13.34	peak
2439	91.96	-5.71	86.25	94	-7.75	AVG
4878	54.74	-3.51	51.23	74	-22.77	peak
4878	45.12	-3.51	41.61	54	-12.39	AVG
7317	57.10	-0.82	56.28	74	-17.72	peak
7317	46.75	-0.82	45.93	54	-8.07	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

CH High (2473MHz)

Horizontal:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
2473	107.55	-5.65	101.90	114	-12.10	peak
2473	92.45	-5.65	86.80	94	-7.20	AVG
4946	55.98	-3.43	52.55	74	-21.45	peak
4946	46.11	-3.43	42.68	54	-11.32	AVG
7419	56.59	-0.75	55.84	74	-18.16	peak
7419	46.86	-0.75	46.11	54	-7.89	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type
2473	106.32	-5.65	100.67	114	-13.33	peak
2473	92.17	-5.65	86.52	94	-7.48	AVG
4946	54.54	-3.43	51.11	74	-22.89	peak
4946	46.38	-3.43	42.95	54	-11.05	AVG
7419	56.42	-0.75	55.67	74	-18.33	peak
7419	46.40	-0.75	45.65	54	-8.35	AVG

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 9KHz to the 25 GHz,
- (2), All modes of GFSK were test at Low, Middle, and High channel, only the worst result of GFSK Low Channel was reported for below 1GHz test,
- (3), For BT above 1GHz test all modes of GFSK were test at Low, Middle, and High channel, only the worst result of GFSK Low Channel was reported,
- (4), By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report,
- (5), Radiated emission test from 9kHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9kHz to 30MHz and not recorded in this report,

8. BAND EDGE AND RF CONDUCTED SPURIOUS EMISSIONS

8, 1 Block Diagram Of Test Setup




Figure 1, Below 30MHz





Figure 2, 30MHz to 1GHz



8, 2 Limit

Spurious Emissions:

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0, 009MHz-0, 490MHz	2400/F(kHz)	-	-	300
0, 490MHz-1, 705MHz	24000/F(kHz)	-	-	30
1, 705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40, 0	Quasi-peak	3
88MHz-216MHz	150	43, 5	Quasi-peak	3
216MHz-960MHz	200	46, 0	Quasi-peak	3
960MHz-1GHz	500	54, 0	Quasi-peak	3
Above 1GHz	500	54, 0	Average	3

Note: 15, 35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device,

8. 3 Test procedure

- a, The EUT was placed on the top of a rotating table 0, 8 meters above the ground at a 3 meter semi-anechoic chamber, The table was rotated 360 degrees to determine the position of the highest radiation,
- b, The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower,
- c, The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength, Both horizontal and vertical polarizations of the antenna are set to make the measurement,
- d, For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading,
- e, The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode,
- f, If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported, Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet,

Frequency	Detector	RBW	VBW	Remark
2310MHz-2400MHz	peak	1MHz	3MHz	peak
2483, 5MHz-2500MHz	peak	1MHz	3MHz	peak

8, 4 Test Result

CH Low:
Horizontal:

No,	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.231	29.71	-4.30	25.41	54	-28.59	peak
2	2343.698	29.70	-4.28	25.42	54	-28.58	peak
3	2378.28	30.80	-4.49	26.31	54	-27.69	peak
4	2389.999	26.18	-4.88	21.31	54	-32.69	peak
5	2440.125	29.97	-3.98	25.99	54	-28.01	peak

Vertical:

No,	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.234	26.40	-4.34	22.07	54	-31.93	peak
2	2343.998	30.77	-4.26	26.51	54	-27.49	peak
3	2378.117	28.22	-4.46	23.77	54	-30.23	peak
4	2390.053	26.80	-4.87	21.93	54	-32.07	peak
5	2440.139	26.36	-3.97	22.39	54	-31.61	peak

CH High:
Horizontal:


No,	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.737	28.90	-4.29	24.62	54	-29.38	peak
2	2488.822	29.91	-4.33	25.58	54	-28.42	peak
3	2490.231	31.51	-4.41	27.10	54	-26.90	peak
4	2493.185	33.55	-4.97	28.58	54	-25.42	peak
5	2496.066	28.44	-3.92	24.52	54	-29.48	peak

Vertical:

No,	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.72	31.19	-4.33	26.86	54	-27.14	peak
2	2488.993	32.61	-4.28	28.32	54	-25.68	peak
3	2490.294	33.16	-4.47	28.70	54	-25.30	peak
4	2493.171	29.41	-4.91	24.50	54	-29.50	peak
5	2496.029	27.37	-3.93	23.44	54	-30.56	peak

9. BANDWIDTH TEST

9, 1 Block Diagram Of Test Setup



FCC Part15 (15, 249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15, 249	Bandwidth	2402-2483, 5	PASS

9, 3 Test procedure



- 1, Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz,
- 2, Set the video bandwidth (VBW) $\geq 3 \times$ RBW,
- 3, Detector = Peak,
- 4, Trace mode = max hold,
- 5, Sweep = auto couple,
- 6, Allow the trace to stabilize,
- 7, Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission,

9, 4 Test Result

Test Mode	Frequency (MHz)	20dB Bandwidth (MHz)	Result
GFSK	Low channel	1.099	PASS
	Mid channel	1.108	PASS
	High channel	1.101	PASS

Note: All modes of operation were Pre-scan and the worst-case emissions are reported,

Test Graph:

GFSK Low channel	 <p>Agilent Spectrum Analyzer - Occupied BW Center Freq 2.410000000 GHz Ref Offset 6.92 dB Ref 26.92 dBm Mkr3 2.410542 GHz -17.378 dBm 10 dB/div Log Span 3 MHz Sweep 1 ms Center 2.41 GHz #Res BW 100 kHz #VBW 300 kHz Occupied Bandwidth 941.99 kHz Total Power 7.44 dBm Transmit Freq Error -7.707 kHz OBW Power 99.00 % x dB Bandwidth 1.099 MHz x dB -20.00 dB</p>
GFSK Mid channel	 <p>Agilent Spectrum Analyzer - Occupied BW Center Freq 2.439000000 GHz Ref Offset 6.96 dB Ref 26.96 dBm Mkr3 2.43955 GHz -16.895 dBm 10 dB/div Log Span 3 MHz Sweep 1 ms Center 2.439 GHz #Res BW 100 kHz #VBW 300 kHz Occupied Bandwidth 961.43 kHz Total Power 7.41 dBm Transmit Freq Error -3.576 kHz OBW Power 99.00 % x dB Bandwidth 1.108 MHz x dB -20.00 dB</p>
GFSK High channel	 <p>Agilent Spectrum Analyzer - Occupied BW Center Freq 2.473000000 GHz Ref Offset 6.97 dB Ref 26.97 dBm Mkr3 2.473552 GHz -17.751 dBm 10 dB/div Log Span 3 MHz Sweep 1 ms Center 2.473 GHz #Res BW 100 kHz #VBW 300 kHz Occupied Bandwidth 953.28 kHz Total Power 7.18 dBm Transmit Freq Error 2.037 kHz OBW Power 99.00 % x dB Bandwidth 1.101 MHz x dB -20.00 dB</p>

10. ANTENNA REQUIREMENT

15, 203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited,

15, 247(b) (4) requirement:



The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi,

EUT Antenna:

The antenna is Interna Antenna, The best case gain of the antenna is 1dBi,

11. EUT TEST SETUP PHOTOGRAPHS

Radiated Emissions

******* END OF REPORT *******