

RF Exposure Evaluation

FCC ID: 2AMWV-SL10

1. Client Information

Applicant : Fring Electronics(Shenzhen) Co., Ltd
Address : Room 1701, Huiyi Fortune Center, Dalang Street, Longhua New District, ShenZhen, China
Manufacturer : Fring Electronics(Shenzhen) Co., Ltd
Address : Room 1701, Huiyi Fortune Center, Dalang Street, Longhua New District, ShenZhen, China

2. General Description of EUT

EUT Name	:	Speaker Lantern	
Models No.	:	SL10, C2	
Model Difference	:	All these models are identical in the same PCB layout and electrical circuit, the only difference is model name for commercial.	
Product Description	:	Operation Frequency:	Bluetooth V4.2: 2402~2480 MHz
		RF Output Power:	Bluetooth: -1.473dBm(π /4-DQPSK) BLE: -4.170dBm
		Antenna Gain:	0dBi PCB Antenna
Power Supply	:	DC Voltage supplied by USB Cable DC Voltage supplied by Li-ion battery	
Power Rating	:	DC 5V by USB Cable DC 3.7V by 2600mAh Li-ion battery	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR}$$

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2. Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-3.012	-3±1	-2	0.631	0.196	3.0
2.441	-2.747	-3±1	-2	0.631	0.197	3.0
2.480	-2.404	-3±1	-2	0.631	0.199	3.0
Bluetooth Mode (π/4-DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-2.076	-2±1	-1	0.794	0.246	3.0
2.441	-1.838	-2±1	-1	0.794	0.248	3.0
2.480	-1.473	-2±1	-1	0.794	0.250	3.0
BLE Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-4.737	-4±1	-3	0.501	0.155	3.0
2.442	-4.170	-4±1	-3	0.501	0.157	3.0
2.480	-4.453	-4±1	-3	0.501	0.158	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----