

# RF Exposure Evaluation

## FCC ID: 2AMWY-ANC-02PRO

### 1. Client Information

<b>Applicant</b>	:	Shenzhen Pincun Digital Technology Co., LTD.
<b>Address</b>	:	5C038, Exchange Square, 2 South China City, Pinghu Street, Longgang District, Shenzhen, Guangdong, China. 518111
<b>Manufacturer</b>	:	Shenzhen Shenzhen Electronics CO., LTD.
<b>Address</b>	:	Building 6, No.1 Xuri East Road, Shanxia community, Pinghu, Longgang, Shenzhen, Guangdong, China, 518111

### 2. General Description of EUT

<b>EUT Name</b>	:	Wireless Headphone
<b>Model(s) No.</b>	:	ANC-02Pro, ANC-05
<b>Model Different</b>	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name.
<b>Product Description</b>	Operation Frequency:	Bluetooth 5.0: 2402MHz~2480MHz
	Number of Channel:	Bluetooth 5.0: 79 channels
	Antenna Gain:	0.5 dBi PCB Antenna
	Modulation Type:	GFSK, Pi/4-DQPSK, 8-DPSK
	Bit Rate of Transmitter:	Bluetooth :1/2/3Mbps
<b>Power Supply</b>	:	Input: DC 5V DC 3.7V by 800mAh Rechargeable Li-ion battery
<b>Software Version</b>	:	V1.0
<b>Hardware Version</b>	:	V1.0

**Remark:** The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

**Note:** More test information about the EUT please refer the RF Test Report.

## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{GHz}}}] \leq 3.0$  for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{\text{GHz}}}] \leq 7.5.0$  for 10-g SAR

**2. Calculation:**

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.05	1±1	2	1.585	0.491	3.0
2.441	1.26	1±1	2	1.585	0.495	3.0
2.480	0.68	0±1	1	1.259	0.397	3.0
Bluetooth Mode (Pi/4-DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	5.20	5±1	6	3.981	1.234	3.0
2.441	5.75	5±1	6	3.981	1.244	3.0
2.480	5.31	5±1	6	3.981	1.254	3.0
Bluetooth Mode (8-DPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	5.83	5±1	6	3.981	1.234	3.0
2.441	6.42	6±1	7	5.012	1.566	3.0
2.480	5.98	5±1	6	3.981	1.254	3.0

**Conclusion:**

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----