



RF Conducted Spurious Emission



Antenna 0

IEEE 802.11n HT40





2392 MHz – 2452 MHz

9 KHz – 26.5 GHz




2407 MHz – 2467 MHz

9 KHz – 26.5 GHz



2422 MHz – 2482 MHz


9 KHz = 26.5 GHz




Band-edge measurements for conducted emissions

IEEE 802.11b

Antenna 0




2397 MHz – 2427 MHz




2447 MHz – 2477 MHz

Antenna 1




2397 MHz – 2427 MHz

Channel 1 / 2412 MHz



Channel 11 / 2462 MHz




Channel 1 / 2412 MHz

Band-edge measurements for conducted emissions

IEEE 802.11b


Antenna 1




Band-edge measurements for conducted emissions

IEEE 802.11g

Antenna 0



2397 MHz – 2427 MHz





This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd.



Band-edge measurements for conducted emissions

IEEE 802.11g

Antenna 1



2397 MHz – 2427 MHz





2447 MHz – 2477 MHz

Band-edge measurements for conducted emissions


IEEE 802.11n HT20


Antenna 0




2397 MHz – 2427 MHz

Channel 1 / 2412 MHz







5.7. Power line conducted emissions


5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dB μ V) | |
|-----------------------|---------------------|-----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56* | 56 to 46* |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

5.7.2 Block Diagram of Test Setup




5.7.3 Test Results

PASS.


The test data please refer to following page.

AC Conducted Emission @ AC 120V/60Hz @ IEEE 802.11b



| | Freq | Reading | LISN | Fac | Cab | Los | Aux | 2Fac | Measured | Limit | Over | Remark |
|----|-------|---------|------|------|-------|-------|-------|--------|----------|-------|------|--------|
| | MHz | dBuV | dB | dB | dB | dB | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.19 | 20.69 | 9.62 | 0.02 | 10.00 | 40.33 | 64.02 | -23.69 | Q.P | | | |
| 2 | 0.19 | 8.05 | 9.62 | 0.02 | 10.00 | 27.69 | 54.02 | -26.33 | Average | | | |
| 3 | 0.49 | 14.94 | 9.62 | 0.04 | 10.00 | 34.60 | 56.23 | -21.63 | Q.P | | | |
| 4 | 0.49 | 2.19 | 9.62 | 0.04 | 10.00 | 21.85 | 46.23 | -24.38 | Average | | | |
| 5 | 1.08 | 11.58 | 9.63 | 0.05 | 10.00 | 31.26 | 56.00 | -24.74 | Q.P | | | |
| 6 | 1.08 | 0.52 | 9.63 | 0.05 | 10.00 | 20.20 | 46.00 | -25.80 | Average | | | |
| 7 | 1.58 | 13.53 | 9.64 | 0.05 | 10.00 | 33.22 | 56.00 | -22.78 | Q.P | | | |
| 8 | 1.58 | -0.68 | 9.64 | 0.05 | 10.00 | 19.01 | 46.00 | -26.99 | Average | | | |
| 9 | 3.96 | 8.35 | 9.65 | 0.06 | 10.00 | 28.06 | 56.00 | -27.94 | Q.P | | | |
| 10 | 3.96 | -7.38 | 9.65 | 0.06 | 10.00 | 12.33 | 46.00 | -33.67 | Average | | | |
| 11 | 20.38 | 17.33 | 9.75 | 0.12 | 10.00 | 37.20 | 60.00 | -22.80 | Q.P | | | |
| 12 | 20.38 | 9.67 | 9.75 | 0.12 | 10.00 | 29.54 | 50.00 | -20.46 | Average | | | |


Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.



| | Freq | Reading | LISN | Fac | Cab | Los | Aux | 2Fac | Measured | Limit | Over | Remark |
|----|-------|---------|------|------|-------|-------|-------|--------|----------|-------|------|--------|
| | MHz | dBuV | dB | dB | dB | dB | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.15 | 29.31 | 9.70 | 0.02 | 10.00 | 49.03 | 65.91 | -16.88 | Q.P | | | |
| 2 | 0.15 | 16.18 | 9.70 | 0.02 | 10.00 | 35.90 | 55.91 | -20.01 | Average | | | |
| 3 | 0.50 | 14.52 | 9.62 | 0.04 | 10.00 | 34.18 | 56.00 | -21.82 | Q.P | | | |
| 4 | 0.50 | 3.03 | 9.62 | 0.04 | 10.00 | 22.69 | 46.00 | -23.31 | Average | | | |
| 5 | 1.60 | 11.76 | 9.63 | 0.05 | 10.00 | 31.44 | 56.00 | -24.56 | Q.P | | | |
| 6 | 1.60 | -1.17 | 9.63 | 0.05 | 10.00 | 18.51 | 46.00 | -27.49 | Average | | | |
| 7 | 3.96 | 7.44 | 9.65 | 0.06 | 10.00 | 27.15 | 56.00 | -28.85 | Q.P | | | |
| 8 | 3.96 | -8.14 | 9.65 | 0.06 | 10.00 | 11.57 | 46.00 | -34.43 | Average | | | |
| 9 | 10.51 | 9.55 | 9.72 | 0.08 | 10.00 | 29.35 | 60.00 | -30.65 | Q.P | | | |
| 10 | 10.51 | -4.83 | 9.72 | 0.08 | 10.00 | 14.97 | 50.00 | -35.03 | Average | | | |
| 11 | 20.38 | 17.60 | 9.87 | 0.12 | 10.00 | 37.59 | 60.00 | -22.41 | Q.P | | | |
| 12 | 20.38 | 9.20 | 9.87 | 0.12 | 10.00 | 29.19 | 50.00 | -20.81 | Average | | | |


Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.

AC Conducted Emission @ AC 240V/60Hz @ IEEE 802.11b



| Freq | Reading | LISN | Fac | Cab | Loss | Aux2 | Fac | Measured | Limit | Over | Remark |
|------|---------|-------|------|------|-------|-------|-------|----------|---------|------|--------|
| MHz | dBuV | dB | dB | dB | dB | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.16 | 27.78 | 9.58 | 0.02 | 10.00 | 47.38 | 65.56 | -18.18 | QP | | |
| 2 | 0.16 | 14.74 | 9.58 | 0.02 | 10.00 | 34.34 | 55.55 | -21.21 | Average | | |
| 3 | 0.49 | 17.42 | 9.62 | 0.04 | 10.00 | 37.08 | 56.19 | -19.11 | QP | | |
| 4 | 0.49 | 4.06 | 9.62 | 0.04 | 10.00 | 23.72 | 46.17 | -22.45 | Average | | |
| 5 | 1.58 | 13.00 | 9.64 | 0.05 | 10.00 | 32.69 | 56.00 | -23.31 | QP | | |
| 6 | 1.58 | 1.39 | 9.64 | 0.05 | 10.00 | 21.08 | 46.00 | -24.92 | Average | | |
| 7 | 3.99 | 9.85 | 9.65 | 0.06 | 10.00 | 29.56 | 56.00 | -26.44 | QP | | |
| 8 | 3.99 | -3.40 | 9.65 | 0.06 | 10.00 | 16.31 | 46.00 | -29.69 | Average | | |
| 9 | 14.29 | 8.44 | 9.71 | 0.10 | 10.00 | 28.25 | 60.00 | -31.75 | QP | | |
| 10 | 14.29 | -1.68 | 9.71 | 0.10 | 10.00 | 18.13 | 50.00 | -31.87 | Average | | |
| 11 | 22.54 | 15.47 | 9.71 | 0.12 | 10.00 | 35.30 | 60.00 | -24.70 | QP | | |
| 12 | 22.54 | 4.39 | 9.71 | 0.12 | 10.00 | 24.22 | 50.00 | -25.78 | Average | | |

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.



| Freq | Reading | LISN | Fac | Cab | Loss | Aux2 | Fac | Measured | Limit | Over | Remark |
|------|---------|-------|------|------|-------|-------|-------|----------|---------|------|--------|
| MHz | dBuV | dB | dB | dB | dB | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.16 | 27.48 | 9.67 | 0.02 | 10.00 | 47.17 | 65.34 | -18.17 | QP | | |
| 2 | 0.16 | 15.43 | 9.67 | 0.02 | 10.00 | 35.12 | 55.33 | -20.21 | Average | | |
| 3 | 0.19 | 19.15 | 9.60 | 0.02 | 10.00 | 38.77 | 63.84 | -25.07 | QP | | |
| 4 | 0.19 | 10.17 | 9.60 | 0.02 | 10.00 | 29.79 | 53.84 | -24.05 | Average | | |
| 5 | 0.51 | 18.71 | 9.62 | 0.04 | 10.00 | 38.37 | 56.00 | -17.63 | QP | | |
| 6 | 0.51 | 6.16 | 9.62 | 0.04 | 10.00 | 25.82 | 46.00 | -20.18 | Average | | |
| 7 | 1.67 | 10.71 | 9.63 | 0.05 | 10.00 | 30.39 | 56.00 | -25.61 | QP | | |
| 8 | 1.67 | -0.19 | 9.63 | 0.05 | 10.00 | 19.49 | 46.00 | -26.51 | Average | | |
| 9 | 10.62 | 9.45 | 9.72 | 0.08 | 10.00 | 29.25 | 60.00 | -30.75 | QP | | |
| 10 | 10.62 | -4.79 | 9.72 | 0.08 | 10.00 | 15.01 | 50.00 | -34.99 | Average | | |
| 11 | 20.38 | 15.79 | 9.87 | 0.12 | 10.00 | 35.78 | 60.00 | -24.22 | QP | | |
| 12 | 20.38 | 7.14 | 9.87 | 0.12 | 10.00 | 27.13 | 50.00 | -22.87 | Average | | |

Remarks: 1. Measured = Reading +Cable Loss +Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.


***Note: Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11b).

5.8 Band-edge measurements for radiated emissions

5.8.1. Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2. Test Setup Layout



5.8.3. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.8.4. Test Procedures

According to KDB 558074 D01 V03 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/B for Peak detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies \leq 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies $>$ 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:
$$E = EIRP - 20\log D + 104.8$$

Where:

E = electric field strength in $\text{dB}\mu\text{V}/\text{m}$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

12. Compare the resultant electric field strength level to the applicable regulatory limit.

13. Perform radiated spurious emission test duress until all measured frequencies were complete.

5.8.5 Test Results

For Antenna Chain 0

| IEEE 802.11b | | | | | | | |
|-----------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Verdict |
| 2310.000 | -54.963 | 2.0 | 0.00 | 41.437 | Peak | 74.00 | PASS |
| 2310.000 | -65.711 | 2.0 | 0.00 | 30.689 | AV | 54.00 | PASS |
| 2390.000 | -50.560 | 2.0 | 0.00 | 45.840 | Peak | 74.00 | PASS |
| 2390.000 | -61.638 | 2.0 | 0.00 | 34.762 | AV | 54.00 | PASS |
| 2483.500 | -49.265 | 2.0 | 0.00 | 47.135 | Peak | 74.00 | PASS |
| 2483.500 | -59.152 | 2.0 | 0.00 | 37.248 | AV | 54.00 | PASS |
| 2500.000 | -49.480 | 2.0 | 0.00 | 46.920 | Peak | 74.00 | PASS |
| 2500.000 | -60.865 | 2.0 | 0.00 | 35.535 | AV | 54.00 | PASS |

| IEEE 802.11g | | | | | | | |
|-----------------|-----------------------|--------------------|--------------------------------|--|----------|----------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflectio n Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Verdict |
| 2310.000 | -48.489 | 2.0 | 0.00 | 47.911 | Peak | 74.00 | PASS |
| 2310.000 | -65.665 | 2.0 | 0.00 | 30.735 | AV | 54.00 | PASS |
| 2390.000 | -54.484 | 2.0 | 0.00 | 41.916 | Peak | 74.00 | PASS |
| 2390.000 | -59.786 | 2.0 | 0.00 | 36.614 | AV | 54.00 | PASS |
| 2483.500 | -49.985 | 2.0 | 0.00 | 46.415 | Peak | 74.00 | PASS |
| 2483.500 | -59.085 | 2.0 | 0.00 | 37.315 | AV | 54.00 | PASS |
| 2500.000 | -50.197 | 2.0 | 0.00 | 46.203 | Peak | 74.00 | PASS |
| 2500.000 | -60.797 | 2.0 | 0.00 | 35.603 | AV | 54.00 | PASS |

| IEEE 802.11n HT20 | | | | | | | |
|-------------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Verdict |
| 2310.000 | -55.430 | 2.0 | 0.00 | 40.970 | Peak | 74.00 | PASS |
| 2310.000 | -66.171 | 2.0 | 0.00 | 30.229 | AV | 54.00 | PASS |
| 2390.000 | -48.269 | 2.0 | 0.00 | 48.131 | Peak | 74.00 | PASS |
| 2390.000 | -60.939 | 2.0 | 0.00 | 35.461 | AV | 54.00 | PASS |
| 2483.500 | -50.416 | 2.0 | 0.00 | 45.984 | Peak | 74.00 | PASS |
| 2483.500 | -60.700 | 2.0 | 0.00 | 35.700 | AV | 54.00 | PASS |
| 2500.000 | -52.072 | 2.0 | 0.00 | 44.328 | Peak | 74.00 | PASS |
| 2500.000 | -60.209 | 2.0 | 0.00 | 36.191 | AV | 54.00 | PASS |

| IEEE 802.11n HT40 | | | | | | | |
|-------------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Verdict |
| 2310.000 | -55.865 | 2.0 | 0.00 | 40.535 | Peak | 74.00 | PASS |
| 2310.000 | -66.363 | 2.0 | 0.00 | 30.037 | AV | 54.00 | PASS |
| 2390.000 | -49.304 | 2.0 | 0.00 | 47.096 | Peak | 74.00 | PASS |
| 2390.000 | -60.701 | 2.0 | 0.00 | 35.699 | AV | 54.00 | PASS |
| 2483.500 | -49.008 | 2.0 | 0.00 | 47.392 | Peak | 74.00 | PASS |
| 2483.500 | -60.292 | 2.0 | 0.00 | 36.108 | AV | 54.00 | PASS |
| 2500.000 | -50.626 | 2.0 | 0.00 | 45.774 | Peak | 74.00 | PASS |
| 2500.000 | -62.492 | 2.0 | 0.00 | 33.908 | AV | 54.00 | PASS |

For Antenna Chain 1

| IEEE 802.11b | | | | | | | | |
|-----------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Over limit dB | Verdict |
| 2310.000 | -49.784 | 2.0 | 0.000 | 46.616 | Peak | 74.00 | -27.384 | PASS |
| 2310.000 | -57.559 | 2.0 | 0.000 | 38.841 | AV | 54.00 | -15.159 | PASS |
| 2390.000 | -46.282 | 2.0 | 0.000 | 50.118 | Peak | 74.00 | -23.882 | PASS |
| 2390.000 | -57.559 | 2.0 | 0.000 | 38.841 | AV | 54.00 | -15.159 | PASS |
| 2483.500 | -46.560 | 2.0 | 0.000 | 49.840 | Peak | 74.00 | -24.160 | PASS |
| 2483.500 | -58.060 | 2.0 | 0.000 | 38.340 | AV | 54.00 | -15.660 | PASS |
| 2500.000 | -45.833 | 2.0 | 0.000 | 50.567 | Peak | 74.00 | -23.433 | PASS |
| 2500.000 | -58.960 | 2.0 | 0.000 | 37.440 | AV | 54.00 | -16.560 | PASS |

| IEEE 802.11g | | | | | | | | |
|-----------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Over limit dB | Verdict |
| 2310.000 | -49.539 | 2.0 | 0.000 | 46.861 | Peak | 74.00 | -27.139 | PASS |
| 2310.000 | -61.434 | 2.0 | 0.000 | 34.966 | AV | 54.00 | -19.034 | PASS |
| 2390.000 | -44.479 | 2.0 | 0.000 | 51.921 | Peak | 74.00 | -22.079 | PASS |
| 2390.000 | -57.959 | 2.0 | 0.000 | 38.441 | AV | 54.00 | -15.559 | PASS |
| 2483.500 | -46.025 | 2.0 | 0.000 | 50.375 | Peak | 74.00 | -23.625 | PASS |
| 2483.500 | -58.137 | 2.0 | 0.000 | 38.263 | AV | 54.00 | -15.737 | PASS |
| 2500.000 | -46.334 | 2.0 | 0.000 | 50.066 | Peak | 74.00 | -23.934 | PASS |
| 2500.000 | -59.044 | 2.0 | 0.000 | 37.356 | AV | 54.00 | -16.644 | PASS |

| IEEE 802.11 n HT20 | | | | | | | | |
|--------------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Over limit dB | Verdict |
| 2310.000 | -48.150 | 2.0 | 0.000 | 48.250 | Peak | 74.00 | -25.750 | PASS |
| 2310.000 | -61.450 | 2.0 | 0.000 | 34.950 | AV | 54.00 | -19.050 | PASS |
| 2390.000 | -42.529 | 2.0 | 0.000 | 53.871 | Peak | 74.00 | -20.129 | PASS |
| 2390.000 | -57.837 | 2.0 | 0.000 | 38.563 | AV | 54.00 | -15.437 | PASS |
| 2483.500 | -46.058 | 2.0 | 0.000 | 50.342 | Peak | 74.00 | -23.658 | PASS |
| 2483.500 | -58.137 | 2.0 | 0.000 | 38.263 | AV | 54.00 | -15.737 | PASS |
| 2500.000 | -46.975 | 2.0 | 0.000 | 49.425 | Peak | 74.00 | -24.575 | PASS |
| 2500.000 | -59.044 | 2.0 | 0.000 | 37.356 | AV | 54.00 | -16.644 | PASS |

| IEEE 802.11 n HT40 | | | | | | | | |
|--------------------|-----------------------|--------------------|-------------------------------|--|----------|----------------|---------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Over limit dB | Verdict |
| 2310.000 | -50.288 | 2.0 | 0.000 | 46.112 | Peak | 74.00 | -27.888 | PASS |
| 2310.000 | -61.668 | 2.0 | 0.000 | 34.732 | AV | 54.00 | -19.268 | PASS |
| 2390.000 | -40.456 | 2.0 | 0.000 | 55.944 | Peak | 74.00 | -18.056 | PASS |
| 2390.000 | -58.665 | 2.0 | 0.000 | 37.735 | AV | 54.00 | -16.265 | PASS |
| 2483.500 | -37.602 | 2.0 | 0.000 | 58.798 | Peak | 74.00 | -15.202 | PASS |
| 2483.500 | -58.909 | 2.0 | 0.000 | 37.491 | AV | 54.00 | -16.509 | PASS |
| 2500.000 | -47.384 | 2.0 | 0.000 | 49.016 | Peak | 74.00 | -24.984 | PASS |
| 2500.000 | -59.759 | 2.0 | 0.000 | 36.641 | AV | 54.00 | -17.359 | PASS |

For Combined Antenna Chain 0, Antenna Chain 1

| IEEE 802.11n HT20 | | | | | | | | | | |
|-------------------|-----------------------|-----------|--------|-----------------------|-------------------------------|--|----------|----------------|---------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | | | Directional Gain (dB) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Over limit dB | Verdict |
| | Antenna 0 | Antenna 1 | Sum | | | | | | | |
| 2310.000* | -55.430 | -48.150 | -47.41 | 5.010* | 0.000 | 56.35 | Peak | 74.00 | -28.190 | PASS |
| 2310.000 | -66.171 | -61.450 | -60.19 | 5.010* | 0.000 | 43.57 | AV | 54.00 | -20.086 | PASS |
| 2390.000 | -48.269 | -42.529 | -41.50 | 5.010* | 0.000 | 62.26 | Peak | 74.00 | -27.098 | PASS |
| 2390.000 | -60.939 | -57.837 | -56.11 | 5.010* | 0.000 | 47.65 | AV | 54.00 | -18.512 | PASS |
| 2483.500* | -50.416 | -46.058 | -44.70 | 5.010* | 0.000 | 59.06 | Peak | 74.00 | -26.556 | PASS |
| 2483.500 | -60.700 | -58.137 | -56.22 | 5.010* | 0.000 | 47.54 | AV | 54.00 | -18.184 | PASS |
| 2500.000 | -52.072 | -46.975 | -45.80 | 5.010* | 0.000 | 57.96 | Peak | 74.00 | -27.152 | PASS |
| 2500.000 | -60.209 | -59.044 | -56.58 | 5.010* | 0.000 | 47.18 | AV | 54.00 | -18.605 | PASS |


| IEEE 802.11n HT40 | | | | | | | | | | |
|-------------------|-----------------------|-----------|---------|-----------------------|-------------------------------|--|----------|----------------|---------------|---------|
| Frequency (MHz) | Conducted Power (dBm) | | | Directional Gain (dB) | Ground Reflection Factor (dB) | Covert Radiated E Level At 3m (dBuV/m) | Detector | Limit (dBuV/m) | Over limit dB | Verdict |
| | Antenna 0 | Antenna 1 | Sum | | | | | | | |
| 2310.000* | -55.865 | -50.288 | -49.226 | 5.010* | 0.000 | 54.53 | Peak | 74.00 | -27.399 | PASS |
| 2310.000 | -66.363 | -61.668 | -60.399 | 5.010* | 0.000 | 43.36 | AV | 54.00 | -20.134 | PASS |
| 2390.000 | -49.304 | -40.456 | -39.924 | 5.010* | 0.000 | 63.84 | Peak | 74.00 | -26.899 | PASS |
| 2390.000 | -60.701 | -58.665 | -56.554 | 5.010* | 0.000 | 47.21 | AV | 54.00 | -18.655 | PASS |
| 2483.500* | -49.008 | -37.602 | -37.299 | 5.010* | 0.000 | 66.46 | Peak | 74.00 | -19.975 | PASS |
| 2483.500 | -60.292 | -58.909 | -56.535 | 5.010* | 0.000 | 47.22 | AV | 54.00 | -18.249 | PASS |
| 2500.000 | -50.626 | -47.384 | -45.699 | 5.010* | 0.000 | 58.06 | Peak | 74.00 | -26.159 | PASS |
| 2500.000 | -62.492 | -59.759 | -57.904 | 5.010* | 0.000 | 45.86 | AV | 54.00 | -18.775 | PASS |

Remark:

1. Measured Band-edge measurements for radiated emissions at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
4. --- means that the fundamental frequency not for 15.209 limits requirement.
5. No need measure Average values if Peak values meets Average limits;
6. * means maximum values of frequency band 2310 – 2390 MHz, 2483.5 – 2500 MHz;
7. For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;

Array gain = 10 log (N_{ant}), where N_{ant} is the number of transmit antennas.


8. *5.010=2.000+10*log(2).
9. Covert Radiated E Level At 3m = Conducted average power + Directional Gain + 104.77-20*log(2);
10. Please refer to following plots;




Band-edge measurements for radiated emissions

Antenna 0

IEEE 802.11b




IEEE 802.11g




Channel 11 / 2462 MHz – Average

IEEE 802.11n HT20




Channel 11 / 2462 MHz – Average


IEEE 802.11n HT40



Channel 1 / 2412 MHz – Peak





Channel 3 / 2422 MHz – Peak



Channel 1 / 2412 MHz – Average

Channel 3 / 2422 MHz – Average







Band-edge measurements for radiated emissions

Antenna 1

IEEE 802.11b




IEEE 802.11g




Channel 11 / 2462 MHz – Average

IEEE 802.11n HT20




Channel 11 / 2462 MHz – Average


IEEE 802.11n HT40



Channel 1 / 2412 MHz – Peak




Channel 3 / 2422 MHz – Peak



Channel 1 / 2412 MHz – Average

Channel 3 / 2422 MHz – Average



5.9. Antenna Requirements

5.9.1. Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

5.9.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 3.78 which is an R-SMA antenna and no consideration of replacement. Please see EUT photo for details.

5.9.3. Results: Compliance.

Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refers ANSI C63.10:2013 Output power test procedure for DTS devices.

Radiated power refers to ANSI C63.10:2013 Radiated emissions tests.

Measurement parameters

| Measurement parameter | |
|-----------------------|----------|
| Detector: | Peak |
| Sweep Time: | Auto |
| Resolution bandwidth: | 1MHz |
| Video bandwidth: | 3MHz |
| Trace-Mode: | Max hold |

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the IEEE 802.11b mode is used.

Limits

| FCC | ISED |
|--------------|------|
| Antenna Gain | |
| 6 dBi | |

Antenna Chain 0

| T _{nom} | V _{nom} | Lowest Channel 2412 MHz | Middle Channel 2437 MHz | Highest Channel 2462 MHz |
|---|------------------|------------------------------------|----------------------------|-----------------------------|
| Conducted power [dBm] Measured with DSSS modulation | | 15.28 | 15.44 | 15.39 |
| Radiated power [dBm] Measured with DSSS modulation | | 16.38 | 16.55 | 16.51 |
| Gain [dBi] Calculated | | 1.103 | 1.113 | 1.118 |
| Measurement uncertainty | | ± 1.6 dB (cond.) / ± 3.8 dB (rad.) | | |

Antenna Chain 1

| T _{nom} | V _{nom} | Lowest Channel 2412 MHz | Middle Channel 2437 MHz | Highest Channel 2462 MHz |
|---|------------------|------------------------------------|----------------------------|-----------------------------|
| Conducted power [dBm] Measured with DSSS modulation | | 15.02 | 15.21 | 15.43 |
| Radiated power [dBm] Measured with DSSS modulation | | 16.209 | 16.366 | 16.542 |
| Gain [dBi] Calculated | | 1.189 | 1.156 | 1.112 |
| Measurement uncertainty | | ± 1.6 dB (cond.) / ± 3.8 dB (rad.) | | |

6. LIST OF MEASURING EQUIPMENTS

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Cal Date | Due Date |
|----------------------------|----------------|----------------------------------|-------------|-----------------|------------------|------------------|
| EMC Receiver | R&S | ESCS 30 | 100174 | 9kHz - 2.75GHz | June 18, 2017 | June 17, 2018 |
| Signal analyzer | Agilent | E4448A(External mixers to 40GHz) | US44300469 | 9kHz~40GHz | July 16, 2017 | July 15, 2018 |
| Signal analyzer | Agilent | N9020A | MY50510140 | 9kHz~26.5GHz | October 27, 2016 | October 27, 2017 |
| LISN | MESS Tec | NNB-2/16Z | 99079 | 9KHz-30MHz | June 18, 2017 | June 17, 2018 |
| LISN (Support Unit) | EMCO | 3819/2NM | 9703-1839 | 9KHz-30MHz | June 18, 2017 | June 17, 2018 |
| RF Cable-CON | UTIFLEX | 3102-26886-4 | CB049 | 9KHz-30MHz | June 18, 2017 | June 17, 2018 |
| ISN | SCHAFFNER | ISN ST08 | 21653 | 9KHz-30MHz | June 18, 2017 | June 17, 2018 |
| 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 30M-18GHz 3m | June 18, 2017 | June 17, 2018 |
| Amplifier | SCHAFFNER | COA9231A | 18667 | 9kHz-2GHz | June 18, 2017 | June 17, 2018 |
| Amplifier | Agilent | 8449B | 3008A02120 | 1GHz-26.5GHz | July 16, 2017 | July 15, 2018 |
| Amplifier | MITEQ | AMF-6F-260400 | 9121372 | 26.5GHz-40GHz | July 16, 2017 | July 15, 2018 |
| Loop Antenna | R&S | HFH2-Z2 | 860004/001 | 9k-30MHz | June 18, 2017 | June 17, 2018 |
| By-log Antenna | SCHWARZBEC | VULB9163 | 9163-470 | 30MHz-1GHz | June 10, 2017 | June 09, 2018 |
| Horn Antenna | EMCO | 3115 | 6741 | 1GHz-18GHz | June 10, 2017 | June 09, 2018 |
| Horn Antenna | SCHWARZBEC | BBHA9170 | BBHA9170154 | 15GHz-40GHz | June 10, 2017 | June 09, 2018 |
| RF Cable-R03m | Jye Bao | RG142 | CB021 | 30MHz-1GHz | June 18, 2017 | June 17, 2018 |
| RF Cable-HIGH | SUHNER | SUCOFLEX 106 | 03CH03-HY | 1GHz-40GHz | June 18, 2017 | June 17, 2018 |
| Power Meter | R&S | NRVS | 100444 | DC-40GHz | June 18, 2017 | June 17, 2018 |
| Power Sensor | R&S | NRV-Z51 | 100458 | DC-30GHz | June 18, 2017 | June 17, 2018 |
| Power Sensor | R&S | NRV-Z32 | 10057 | 30MHz-6GHz | June 18, 2017 | June 17, 2018 |
| AC Power Source | HPC | HPA-500E | HPA-9100024 | AC 0-300V | June 18, 2017 | June 17, 2018 |
| DC power source | GW | GPC-6030D | C671845 | DC 1V-60V | June 18, 2017 | June 17, 2018 |
| Temp. and Humidify Chamber | Giant Force | GTH-225-20-S | MAB0103-00 | N/A | June 18, 2017 | June 17, 2018 |
| RF CABLE-1m | JYE Bao | RG142 | CB034-1m | 20MHz-7GHz | June 18, 2017 | June 17, 2018 |
| RF CABLE-2m | JYE Bao | RG142 | CB)35-2m | 20MHz-1GHz | June 18, 2017 | June 17, 2018 |
| EMC Test software | Audix | E3 | N/A | N/A | N/A | N/A |

Note: All equipment through GRRG EST calibration

-----THE END OF REPORT-----