

FCC RF EXPOSURE REPORT

FCC ID: 2AMXW-S0012B30GGU1H

Project No. : 1707C056
Equipment : Bluetooth and ANC headphone
Model : GID6B
Applicant : CHONGQING GUANZHUO TECHNOLOGY CO.,LTD
Address : tere floor,4th floor,Xiyong Software Park of Shapingba,Chongqing city

According: : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PCB	N/A	1.83

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
3.98	2.5003	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 2.5003mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold