



TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	Bluetooth module
Trademark	TRIDONIC
Model and /or type reference	TR003BNANO
FCC ID	2AMXZ-TR003BNANO
Features	3.3 Vdc
Applicant's name / address	Tridonic GmbH & Co KG. Faerbergasse 15 6851 Dornbirn, Austria
Test method requested, standard	KDB 447498 D01V06 FCC Part 1.1310
Verdict Summary	COMPLIANCE
Tested by (name & signature)	Jazz Liang 
Approved by (name & signature)	Tim Yan 
Date of issue	2024-03-15
Report template No	TRF_EMC 2017-06- FCC_Exposure

INDEX

	page
General conditions.....	3
Uncertainty.....	3
Environmental conditions.....	3
Possible test case verdicts	3
Definition of symbols used in this test report.....	4
Abbreviations	4
Document History	4
Remarks and Comments	4
1 General Information.....	5
1.1 General Description of the Item(s)	5
1.2 Test data	6
1.3 The environment(s) in which the EUT is intended to be used	6
2 Description of Test Setup	7
2.1 Operating mode(s) used for tests.....	7
2.2 Support / Auxiliary equipment / unit / software for the EUT	7
2.3 Test Configuration / Block diagram used for tests	7
2.4 Measurement procedure	7
3 RF Exposure Evaluation.....	8
3.1 Limits	8
3.2 Test Procedure.....	9
3.3 Test Result	9

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not tested	N/T

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

☒ Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
☐ Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	☒	Comma (,)	☐ Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	Bluetooth module
Trademark.....	TRIDONIC
Model / Type number.....	TR003BNANO
FCC ID	2AMXZ-TR003BNANO
Hardware	Version 1.2
Software.....	N/A
Firmware	Version 1.0
Ratings.....	3.3 Vdc
Manufacturer.....	Tridonic GmbH & Co KG. Faerbergasse 15 6851 Dornbirn, Austria
Factory	Shenzhen FangPeng Technology Co.,Ltd. B4 Building, Haosan No.1 Industry Park, Shajing Town, Baoan District, Shenzhen, Guangdong, China.

Operating frequency range(s).....	2402 MHz – 2480 MHz
Type of Modulation	GFSK
Maximum RF output power.....	7.5 dBm
Antenna type.....	External Antenna
Operating Temperature Range.....	-40 – 105 °C
BT version.....	Bluetooth 5.1BLE
Antenna gain.....	2.5 dBi

Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 3.3V					
	☐	Battery:					
Mounting position.....	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☐	Hand-held equipment					
	☒	Other: Installed on the circuit board					

Intended use of the Equipment Under Test (EUT)
The apparatus as supplied for the test is Bluetooth module which designed to integrated into LED driver, different lighting control applications sensors etc. According to customer description, the EUT is Wireless modules designed to be integrated into LED drivers, different lighting control applications, sensors etc. Hence,model TR003BNANO were chosen for full test.
Copy of marking plate:
No provide.

1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324;
Date of receipt of test item	2024-02-02
Date (s) of performance of tests	2024-02-02 to 2024-03-08
Test sample	Normal sample: TR003BNANO(Lab no.4398538-1), RF conducted sample: TR003BNANO(Lab no.4398538-2), RF radiated sample: TR003BNANO(Lab no.4398538-1)

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

☒	Residential (domestic) environment.
☒	Commercial and light-industrial environment.
☐	Industrial environment.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methos	
		Conducted	Radiated
1	Transmitting at 1 Mbit/s,	☒	☐
2		☐	☐
3		☐	☐
Supplemental information: ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
Laptop	Latitude 5488	DELL	DEKRA
TELINK BDT(Burning and Debugging tool)	-	-	Client
nRFgo Studio (soft ware)	V1.21.2.10	-	Client
Supplemental information: ---			

2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

2.4 Measurement procedure

The EUT was controlled by a serial PCB(TELINK BDT) which provided by manufacturer which connected to laptop through the com port. After connected, run the software “nRFgo Studio” supplied by manufacturer to control the EUT work in required test mode as below table.

RF Mode	Set_channel(MHz)	Set_power in software
BLE_1M	2402	0
	2440	19
	2480	39

3 RF EXPOSURE EVALUATION

3.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Power Density: $P_d (W/m^2) = E^2 / 377$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

E = Electric Field (V/m)

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

3.3 Test Result

Test Mode	Frequency Band (MHz)	Conducted RF Power Output (dBm)	Conducted Maximum Power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit of Power Density S(mW/cm ²)	Verdict
BLE	2400 ~ 2480	5.0	3.16	0.00063	1	PASS

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

For example,: EIRP= $P_{out} \cdot G = 3.16$ mW

$E = 3.16 / (4 \cdot \pi \cdot 20^2) = 0.00063$ mW/cm²

--- END ---