

FCC PART 15.247

TEST REPORT

For

HUIZHOU HUAZHU INDUSTRIAL CO.,LTD

3rd floor, NO.18 District, Zhongkai High-tech Zone, Huizhou.China

FCC ID: 2AN2LYXA01

Report Type: Original Report	Product Name: BAMBOOBALL SOUND
Report Number: RDG171009001-00	
Report Date: 2017-10-27	
Jerry Zhang	
Reviewed By:	EMC Manager <i>Jerry Zhang</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
SUPPORT CABLE LIST AND DETAILS	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE.....	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
TEST EQUIPMENT LIST AND DETAILS.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	58
APPLICABLE STANDARD	58
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST PROCEDURE	58
TEST DATA	58
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64

TEST EQUIPMENT LIST AND DETAILS.....	64
TEST DATA	64
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	70
APPLICABLE STANDARD	70
TEST PROCEDURE	70
TEST EQUIPMENT LIST AND DETAILS.....	70
TEST DATA	70
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	74
APPLICABLE STANDARD	74
TEST PROCEDURE	74
TEST EQUIPMENT LIST AND DETAILS.....	74
TEST DATA	74
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	90
APPLICABLE STANDARD	90
TEST PROCEDURE	90
TEST EQUIPMENT LIST AND DETAILS.....	90
TEST DATA	90
FCC §15.247(d) - BAND EDGES TESTING	92
APPLICABLE STANDARD	92
TEST PROCEDURE	92
TEST EQUIPMENT LIST AND DETAILS.....	92
TEST DATA	93

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **HUIZHOU HUAZHU INDUSTRIAL CO.,LTD**'s product, model number: **ZDYX-A01 (FCC ID: 2AN2LYXA01)** (the "EUT") in this report was a **BAMBOOBALL SOUND**, which was measured approximately: 113 mm (L) x 105mm (W) x 55 mm (H), rated power: DC3.7V from Battery or DC 5V from USB system.

Note: The series product, model ZDYX-A01, ZDYX-A02, ZDYX-A03, ZDYX-A04, ZDYX-A05, ZDYX-A06, ZDYX-A07 are electrically identical, the difference them is the model name and appearance, we selected ZDYX-A01 for fully testing, the details was explained in the declaration letter.

**All measurement and test data in this report was gathered from production sample serial number: 171009001 (Assigned by BACL,Dongguan). The EUT was received on 2017-10-09.*

Objective

This report is prepared on behalf of **HUIZHOU HUAZHU INDUSTRIAL CO.,LTD** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal(s)/granat(s).

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~26.5GHz: 5.23 dB
Unwanted Emissions , conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China

Bay Area Compliance Laboratories Corp. (Dongguan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L5662). And accredited to ISO/IEC 17025 by NVLAP(Test Laboratory Accreditation Certificate Number 500069-0), the FCC Designation No. CN5002 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Dongguan) was registered with ISED Canada under ISED Canada Registration Number 3062D.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

The test software: 'FCCAssist_1.5' configured the maximum power level as below setting:

Test Software Version	FCCAssist_1.5		
Test Frequency	2402MHz	2441MHz	2480MHz
GFSK	10	10	10
π /4-DQPSK	10	10	10
8-DPSK	10	10	10

Equipment Modifications

No modification was made to the EUT.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HUAWEI	Adaptor	HW-050200C01	N/A

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
USB Cable	Yes	No	1	Adaptor	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The max conducted power including tune-up tolerance is -3.0 dBm (0.5 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.5/5 \cdot (\sqrt{2.480}) = 0.2 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement for BT, and the antenna gain is -3.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF : voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2016-12-08	2017-12-08
R&S	L.I.S.N	ESH2-Z5	892107/021	2017-09-25	2018-09-25
R&S	Two-line V-network	ENV 216	3560.6550.12	2017-09-25	2018-09-25
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
Unknown	Coaxial Cable	2m	Con-1	2017-09-25	2018-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.1 °C
Relative Humidity:	43 %
ATM Pressure:	100.6 kPa

The testing was performed by Alex You on 2017-10-13.


Test Mode: Transmitting

AC120V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.201433	41.8	9.000	L1	10.6	21.8	63.6	Compliance
0.214692	41.2	9.000	L1	10.5	21.8	63.0	Compliance
0.590613	37.6	9.000	L1	9.8	18.4	56.0	Compliance
0.845331	34.9	9.000	L1	9.8	21.1	56.0	Compliance
1.407671	33.0	9.000	L1	9.7	23.0	56.0	Compliance
1.802095	29.7	9.000	L1	9.7	26.3	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.283749	31.5	9.000	L1	10.2	19.2	50.7	Compliance
0.590613	29.7	9.000	L1	9.8	16.3	46.0	Compliance
0.845331	29.9	9.000	L1	9.8	16.1	46.0	Compliance
0.999305	26.7	9.000	L1	9.8	19.3	46.0	Compliance
1.407671	26.0	9.000	L1	9.7	20.0	46.0	Compliance
4.802010	27.7	9.000	L1	9.8	18.3	46.0	Compliance

AC120V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.519918	34.4	9.000	N	9.9	21.6	56.0	Compliance
0.581275	36.1	9.000	N	9.8	19.9	56.0	Compliance
0.845331	38.5	9.000	N	9.8	17.5	56.0	Compliance
1.239175	33.2	9.000	N	9.8	22.8	56.0	Compliance
1.982914	35.9	9.000	N	9.7	20.1	56.0	Compliance
5.368716	37.3	9.000	N	9.8	22.7	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.281497	32.9	9.000	N	10.2	17.9	50.8	Compliance
0.590613	25.6	9.000	N	9.8	20.4	46.0	Compliance
0.845331	32.4	9.000	N	9.8	13.6	46.0	Compliance
1.239175	26.4	9.000	N	9.8	19.6	46.0	Compliance
1.418932	23.6	9.000	N	9.7	22.4	46.0	Compliance
4.802010	29.5	9.000	N	9.8	16.5	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 10 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	10 Hz	/	AVG

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2016-07-28	2018-07-28
Sunol Sciences	Antenna	JB3	A060611-3	2017-07-21	2019-07-21
HP	Amplifier	8447F	2443A01912	2017-09-05	2018-09-05
unknown	Coaxial Cable	4m	C0400/01	2017-09-05	2018-09-05
unknown	Coaxial Cable	0.75m	C0075/02	2017-09-05	2018-09-05
unknown	Coaxial Cable	22m	C2200/01	2017-09-05	2018-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2016-12-08	2017-12-08
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-05
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2017-09-05	2018-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017-06-27	2018-06-27
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2017-06-16	2020-06-15
unknown	Coaxial Cable	8m	C0800/01	2017-09-05	2018-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions


Temperature:	27.1 °C
Relative Humidity:	43 %
ATM Pressure:	100.6 kPa

The testing was performed by Steve Zuo on 2017-10-13.


Test Mode: Transmitting

1) 30MHz-1GHz(8DPSK Low channel was the worst)**Horizontal:**


Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
32.9100	29.97	QP	-9.17	20.80	40.00	19.20
141.5500	30.03	QP	-12.53	17.50	43.50	26.00
239.5200	38.07	QP	-13.27	24.80	46.00	21.20
299.6600	40.41	QP	-10.61	29.80	46.00	16.20
358.8300	33.83	QP	-9.23	24.60	46.00	21.40
660.5000	28.94	QP	-1.84	27.10	46.00	18.90

Vertical:



Frequency (MHz)	Receiver Reading (dBμV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
60.0700	49.01	QP	-19.81	29.20	40.00	10.80
142.5200	31.74	QP	-12.54	19.20	43.50	24.30
239.5200	38.17	QP	-13.27	24.90	46.00	21.10
299.6600	33.81	QP	-10.61	23.20	46.00	22.80
359.8000	36.69	QP	-9.19	27.50	46.00	18.50
540.2200	31.53	QP	-4.63	26.90	46.00	19.10

1GHz-25GHz:*BDR Mode (GFSK):**Low Channel, Horizontal:*

Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2390.000	24.02	peak	29.87	53.89	74.00	168	152	20.11	
*	2	2390.000	13.85	AVG	29.87	43.72	54.00	168	152	10.28	
	3	2402.015	55.53	peak	29.90	85.43	125.20	168	152	39.77	Fundamental
	4	2402.015	45.67	AVG	29.90	75.57	125.20	168	152	49.63	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	53.87	peak	-1.14	52.73	74.00	136	225	21.27	
*	2	4802.500	40.59	AVG	-1.14	39.45	54.00	136	225	14.55	




Note: No emission was detected in the range 10-25GHz.



Vertical:




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2390.000	25.31	peak	29.88	55.19	74.00	157	69	18.81	
*	2	2390.000	14.67	AVG	29.88	44.55	54.00	157	69	9.45	
	3	2402.070	49.11	peak	29.90	79.01	125.20	157	69	46.19	Fundamental
	4	2402.070	40.65	AVG	29.90	70.55	125.20	157	69	54.65	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	6143.500	46.54	peak	1.10	47.64	74.00	152	338	26.36	
*	2	6143.500	37.49	AVG	1.10	38.59	54.00	152	338	15.41	




*Middle Channel**Horizontal*

Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1	2441.115	56.10	peak	30.00	86.10	125.20	157	142	39.10	Fundamental
	2	2441.115	46.35	AVG	30.00	76.35	125.20	157	142	48.85	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	50.85	peak	-1.14	49.71	74.00	146	57	24.29	
*	2	4802.500	37.97	AVG	-1.14	36.83	54.00	146	57	17.17	


Note: No emission was detected in the range 10-25GHz.

Vertical


Mk.	No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1	2441.185	49.09	peak	30.00	79.09	125.20	154	227	46.11	Fundamental
	2	2441.185	40.15	AVG	30.00	70.15	125.20	154	227	55.05	Fundamental



Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	5999.500	47.04	peak	0.80	47.84	74.00	149	228	26.16	
*	2	5999.500	38.46	AVG	0.80	39.26	54.00	149	228	14.74	


*High Channel**Horizontal*

Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2480.195	58.30	peak	30.10	88.40	125.20	145	224	36.80	Fundamental
	2	2480.195	49.58	AVG	30.10	79.68	125.20	145	224	45.52	Fundamental
	3	2483.500	25.79	peak	30.11	55.90	74.00	145	224	18.10	
*	4	2483.500	16.35	AVG	30.11	46.46	54.00	145	224	7.54	




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4960.000	53.28	peak	-0.80	52.48	74.00	138	97	21.52	
*	2	4960.000	40.62	AVG	-0.80	39.82	54.00	138	97	14.18	

Note: No emission was detected in the range 10-25GHz.

Vertical


Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2480.060	52.04	peak	30.10	82.14	125.20	154	25	43.06	Fundamental
	2	2480.060	42.53	AVG	30.10	72.63	125.20	154	25	52.57	Fundamental
	3	2483.500	26.35	peak	30.11	56.46	74.00	154	25	17.54	
*	4	2483.500	16.24	AVG	30.11	46.35	54.00	154	25	7.65	




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	6040.000	46.30	peak	0.88	47.18	74.00	135	226	26.82	
*	2	6040.000	37.32	AVG	0.88	38.20	54.00	135	226	15.80	

EDR Mode ($\pi/4$ -DQPSK):

Low Channel, Horizontal




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2390.000	23.52	peak	29.87	53.39	74.00	155	248	20.61	
*	2	2390.000	14.13	AVG	29.87	44.00	54.00	155	248	10.00	
	3	2402.015	56.53	peak	29.90	86.43	125.20	155	248	38.77	Fundamental
	4	2402.015	47.58	AVG	29.90	77.48	125.20	155	248	47.72	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	54.87	peak	-1.14	53.73	74.00	152	336	20.27	
*	2	4802.500	41.67	AVG	-1.14	40.53	54.00	152	336	13.47	

Note: No emission was detected in the range 10-25GHz.

Vertical




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2390.000	24.52	peak	29.87	54.39	74.00	158	34	19.61	
*	2	2390.000	14.63	AVG	29.87	44.50	54.00	158	34	9.50	
	3	2402.015	51.03	peak	29.90	80.93	125.20	158	34	44.27	Fundamental
	4	2402.015	42.35	AVG	29.90	72.25	125.20	158	34	52.95	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	6067.000	47.24	peak	0.94	48.18	74.00	162	223	25.82	
*	2	6067.000	38.49	AVG	0.94	39.43	54.00	162	223	14.57	

Middle Channel

Horizontal




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1	2441.115	55.10	peak	30.00	85.10	125.20	152	223	40.10	Fundamental
	2	2441.115	45.67	AVG	30.00	75.67	125.20	152	223	49.53	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	49.85	peak	-1.14	48.71	74.00	159	46	25.29	
*	2	4802.500	37.25	AVG	-1.14	36.11	54.00	159	46	17.89	

Note: No emission was detected in the range 10-25GHz.

Vertical




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1	2440.800	49.98	peak	30.00	79.98	125.20	142	224	45.22	Fundamental
	2	2440.800	40.75	AVG	30.00	70.75	125.20	142	224	54.45	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	6098.500	46.81	peak	1.01	47.82	74.00	156	223	26.18	
*	2	6098.500	37.49	AVG	1.01	38.50	54.00	156	223	15.50	

High Channel

Horizontal




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2480.420	56.34	peak	30.10	86.44	125.20	159	43	38.76	Fundamental
	2	2480.420	47.53	AVG	30.10	77.63	125.20	159	43	47.57	Fundamental
	3	2483.500	26.85	peak	30.11	56.96	74.00	159	43	17.04	
*	4	2483.500	15.43	AVG	30.11	45.54	54.00	159	43	8.46	




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	50.85	peak	-1.14	49.71	74.00	154	226	24.29	
*	2	4802.500	37.59	AVG	-1.14	36.45	54.00	154	226	17.55	

Note: No emission was detected in the range 10-25GHz.

Vertical




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2480.060	50.04	peak	30.10	80.14	125.20	153	224	45.06	Fundamental
	2	2480.060	40.83	AVG	30.10	70.93	125.20	153	224	54.27	Fundamental
	3	2483.500	24.85	peak	30.11	54.96	74.00	153	224	19.04	
*	4	2483.500	14.67	AVG	30.11	44.78	54.00	153	224	9.22	




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4960.000	48.62	peak	-0.80	47.82	74.00	143	225	26.18	
	2	4960.000	39.48	AVG	-0.80	38.68	54.00	143	225	15.32	
	3	7358.500	45.54	peak	3.27	48.81	74.00	143	225	25.19	
*	4	7358.500	36.52	AVG	3.27	39.79	54.00	143	225	14.21	

EDR Mode (8-DPSK):

Low Channel, Horizontal




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2390.000	23.52	peak	29.87	53.39	74.00	135	27	20.61	
*	2	2390.000	13.54	AVG	29.87	43.41	54.00	135	27	10.59	
	3	2402.015	58.03	peak	29.90	87.93	125.20	135	27	37.27	Fundamental
	4	2402.015	49.57	AVG	29.90	79.47	125.20	135	27	45.73	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	53.87	peak	-1.14	52.73	74.00	151	224	21.27	
*	2	4802.500	40.38	AVG	-1.14	39.24	54.00	151	224	14.76	

Note: No emission was detected in the range 10-25GHz.

Vertical




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2390.000	24.52	peak	29.87	54.39	74.00	157	24	19.61	
*	2	2390.000	14.65	AVG	29.87	44.52	54.00	157	24	9.48	
	3	2402.015	52.03	peak	29.90	81.93	125.20	157	24	43.27	Fundamental
	4	2402.015	43.38	AVG	29.90	73.28	125.20	157	24	51.92	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	5990.500	47.05	peak	0.81	47.86	74.00	152	36	26.14	
*	2	5990.500	38.46	AVG	0.81	39.27	54.00	152	36	14.73	

Middle Channel

Horizontal




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1	2441.115	58.10	peak	30.00	88.10	125.20	178	46	37.10	Fundamental
	2	2441.115	49.36	AVG	30.00	79.36	125.20	178	46	45.84	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4802.500	50.85	peak	-1.14	49.71	74.00	154	226	24.29	
*	2	4802.500	37.59	AVG	-1.14	36.45	54.00	154	226	17.55	

Note: No emission was detected in the range 10-25GHz.

Vertical


Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1	2441.115	51.60	peak	30.00	81.60	125.20	148	55	43.60	Fundamental
	2	2441.115	42.57	AVG	30.00	72.57	125.20	148	55	52.63	Fundamental




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	6103.000	46.40	peak	1.02	47.42	74.00	136	58	26.58	
*	2	6103.000	37.46	AVG	1.02	38.48	54.00	136	58	15.52	

High Channel

Horizontal




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2480.060	57.54	peak	30.10	87.64	125.20	157	64	37.56	Fundamental
	2	2480.060	48.36	AVG	30.10	78.46	125.20	157	64	46.74	Fundamental
	3	2483.500	25.35	peak	30.11	55.46	74.00	157	64	18.54	
*	4	2483.500	14.68	AVG	30.11	44.79	54.00	157	64	9.21	




Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	4960.000	51.78	peak	-0.80	50.98	74.00	151	224	23.02	
*	2	4960.000	38.68	AVG	-0.80	37.88	54.00	151	224	16.12	

Note: No emission was detected in the range 10-25GHz.

Vertical



Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	2480.060	50.54	peak	30.10	80.64	125.20	156	224	44.56	Fundamental
	2	2480.060	40.98	AVG	30.10	71.08	125.20	156	224	54.12	Fundamental
	3	2483.500	25.35	peak	30.11	55.46	74.00	156	224	18.54	
*	4	2483.500	14.26	AVG	30.11	44.37	54.00	156	224	9.63	



Mk.	No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1	6103.000	46.40	peak	1.02	47.42	74.00	153	226	26.58	
*	2	6103.000	37.52	AVG	1.02	38.54	54.00	153	226	15.46	

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2016-12-08	2017-12-08
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

* The testing was performed by Nami Zhou on 2017-10-24.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
<i>BDR</i> (<i>GFSK</i>)	Low	2402	1.004	0.59
	Middle	2441	1.004	0.59
	High	2480	1.000	0.59
EDR ($\pi/4$ -DQPSK)	Low	2402	1.000	0.83
	Middle	2441	1.000	0.84
	High	2480	1.000	0.83
<i>EDR</i> (8DPSK)	Low	2402	1.000	0.83
	Middle	2441	1.000	0.84
	High	2480	1.004	0.83

Note: Limit= $(2/3) \times 20\text{dB bandwidth}$

BDR Mode (GFSK):


Date: 24.OCT.2017 09:33:34

Middle Channel




Date: 24.OCT.2017 09:34:38

High Channel




Date: 24.OCT.2017 09:35:25

Low Channel



Date: 24.OCT.2017 09:37:08


High Channel



Date: 24.OCT.2017 09:36:17


EDR Mode (8-DPSK):

Low Channel




Date: 24.OCT.2017 09:38:55

Middle Channel



Date: 24.OCT.2017 09:39:47

High Channel



Date: 24.OCT.2017 09:40:37

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2016-12-08	2017-12-08
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

* The testing was performed by Nami Zhou on 2017-10-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.88
	Middle	2441	0.88
	High	2480	0.88
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	1.24
	Middle	2441	1.26
	High	2480	1.24
EDR Mode (8-DPSK)	Low	2402	1.25
	Middle	2441	1.26
	High	2480	1.24


BDR Mode (GFSK):

Low Channel




Date: 24.OCT.2017 09:16:21

Middle Channel




Date: 24.OCT.2017 09:17:57


High Channel




Date: 24.OCT.2017 09:20:09

*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**


Date: 24.OCT.2017 09:25:08

Middle Channel

Date: 24.OCT.2017 09:24:11


High Channel

Date: 24.OCT.2017 09:22:10

*EDR Mode (8-DPSK):***Low Channel**


Date: 24.OCT.2017 09:26:43

Middle Channel



Date: 24.OCT.2017 09:28:00

High Channel



Date: 24.OCT.2017 09:30:23

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2016-12-08	2017-12-08
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

* The testing was performed by Nami Zhou on 2017-10-24.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



Date: 24.OCT.2017 09:43:28

EDR Mode ($\pi/4$ -DQPSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 24.OCT.2017 09:47:00

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



Date: 24.OCT.2017 09:51:36

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; the time of single pulses was tested.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2016-12-08	2017-12-08
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.8°C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

* The testing was performed by Nami Zhou on 2017-10-24.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.389	0.124	0.4	Compliance
	Middle	0.391	0.125	0.4	Compliance
	High	0.389	0.124	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
DH3	Low	1.665	0.266	0.4	Compliance
	Middle	1.665	0.266	0.4	Compliance
	High	1.665	0.266	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
DH5	Low	2.926	0.312	0.4	Compliance
	Middle	2.916	0.311	0.4	Compliance
	High	2.916	0.311	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

DH1: Low Channel




Date: 24.OCT.2017 10:03:08

DH1: Middle Channel




Date: 24.OCT.2017 10:03:16

DH1: High Channel




Date: 24.OCT.2017 10:03:25

DH3: Low Channel




Date: 24.OCT.2017 10:03:49


DH3: Middle Channel



Date: 24.OCT.2017 10:03:58


DH3: High Channel

Date: 24.OCT.2017 10:04:07

DH5: Low Channel


Date: 24.OCT.2017 10:05:51

DH5: Middle Channel



Date: 24.OCT.2017 10:06:01

DH5: High Channel




Date: 24.OCT.2017 10:06:10

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.403	0.129	0.4	Compliance
	Middle	0.401	0.128	0.4	Compliance
	High	0.403	0.129	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
2DH3	Low	1.668	0.267	0.4	Compliance
	Middle	1.678	0.268	0.4	Compliance
	High	1.673	0.268	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
2DH5	Low	2.933	0.313	0.4	Compliance
	Middle	2.933	0.313	0.4	Compliance
	High	2.933	0.313	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

2DH1: Low Channel




Date: 24.OCT.2017 10:28:28

2DH1: Middle Channel




Date: 24.OCT.2017 10:27:50

2DH1: High Channel




Date: 24.OCT.2017 10:27:33

2DH3: Low Channel




Date: 24.OCT.2017 10:22:48

2DH3: Middle Channel




Date: 24.OCT.2017 10:22:07

2DH3: High Channel




Date: 24.OCT.2017 10:19:58

2DH5: Low Channel




Date: 24.OCT.2017 10:16:34

2DH5: Middle Channel



Date: 24.OCT.2017 10:15:20


2DH5: High Channel




Date: 24.OCT.2017 10:13:34

EDR Mode (8-DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.404	0.129	0.4	Compliance
	Middle	0.403	0.129	0.4	Compliance
	High	0.401	0.128	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
3DH3	Low	1.663	0.266	0.4	Compliance
	Middle	1.668	0.267	0.4	Compliance
	High	1.673	0.268	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
3DH5	Low	2.933	0.313	0.4	Compliance
	Middle	2.917	0.311	0.4	Compliance
	High	2.917	0.311	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				

3DH1: Low Channel

Date: 24.OCT.2017 10:28:45


3DH1: Middle Channel

Date: 24.OCT.2017 10:29:02

3DH1: High Channel


Date: 24.OCT.2017 10:29:32

3DH3: Low Channel




Date: 24.OCT.2017 10:23:25


3DH3: Middle Channel




Date: 24.OCT.2017 10:23:42

3DH3: High Channel


Date: 24.OCT.2017 10:24:00

3DH5: Low Channel

Date: 24.OCT.2017 10:17:11

3DH5: Middle Channel

Date: 24.OCT.2017 10:17:29

3DH5: High Channel

Date: 24.OCT.2017 10:18:10

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY54170006	2016-12-21	2017-12-21
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

* The testing was performed by Nami Zhou on 2017-10-24.

Test Result: Compliance.

Test Mode: Transmitting

Mode	Frequency (MHz)	Peak Conducted Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	2402	-6.73	30
	2441	-5.66	30
	2480	-4.02	30
EDR Mode ($\pi/4$ -DQPSK)	2402	-5.65	30
	2441	-4.61	30
	2480	-4.02	30
EDR Mode (8-DPSK)	2402	-5.64	30
	2441	-4.59	30
	2480	-3.94	30

Note: The data above was tested in conducted mode.

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW/ VBW of spectrum analyzer to 100/300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2016-12-08	2017-12-08
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	26.8 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

** The testing was performed by Nami Zhou on 2017-10-24.*

Test Result: Compliance


BDR Mode (GFSK):

Band Edge, Left Side



Date: 24.OCT.2017 09:17:03


Band Edge, Right Side



Date: 24.OCT.2017 09:21:04


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side



Date: 24.OCT.2017 09:25:52


Band Edge, Right Side



Date: 24.OCT.2017 09:23:15

*EDR Mode (8-DPSK):***Band Edge, Left Side**

Date: 24.OCT.2017 09:27:28

Band Edge, Right Side

Date: 24.OCT.2017 09:31:12

******* END OF REPORT *******