



**Solutions**

**FCC 47 CFR PART 15 SUBPART C  
ISED RSS-247 ISSUE 3**

**TEST REPORT**

*For*

**Robotic Vacuum Cleaner**

**MODEL NUMBER: RRE0VSP**

**PROJECT NUMBER: 4791759006**

**REPORT NUMBER: 4791759006-2**

**FCC ID: 2AN2O-RRE0VSP01**

**IC: 23317-RRE0VSP01**

**HVIN: RRE0VSP-BLM8**

**ISSUE DATE: JUN. 20, 2025**

*Prepared for*

**Beijing Roborock Technology Co., Ltd.**

*Prepared by*

**UL-CCIC COMPANY LIMITED**

**No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China**

**Tel: +86 512-6808 6400**

**Fax: +86 512-6808 4099**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	06/20/2025	Initial Issue	

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>6</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>6</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>7</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	7
4.2. <i>MEASUREMENT UNCERTAINTY .....</i>	7
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>8</b>
5.1. <i>DESCRIPTION OF EUT.....</i>	8
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	9
5.3. <i>CHANNEL LIST.....</i>	9
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	9
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	9
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	10
5.7. <i>THE WORSE CASE CONFIGURATIONS.....</i>	10
5.8. <i>TEST ENVIRONMENT .....</i>	10
5.9. <i>DESCRIPTION OF TEST SETUP .....</i>	11
5.10. <i>MEASURING INSTRUMENT AND SOFTWARE USED .....</i>	13
<b>6. MEASUREMENT METHODS.....</b>	<b>14</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>15</b>
7.1. <i>ON TIME AND DUTY CYCLE .....</i>	15
7.2. <i>6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>	17
7.3. <i>CONDUCTED OUTPUT POWER .....</i>	23
7.4. <i>POWER SPECTRAL DENSITY .....</i>	25
7.5. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS .....</i>	28
<b>8. RADIATED TEST RESULTS .....</b>	<b>37</b>
8.1. <i>LIMITS AND PROCEDURE .....</i>	37
8.2. <i>TEST ENVIRONMENT .....</i>	44
8.3. <i>RESTRICTED BANDEDGE .....</i>	44
8.4. <i>SPURIOUS EMISSIONS.....</i>	49
<b>9. AC POWER LINE CONDUCTED EMISSIONS.....</b>	<b>69</b>
<b>10. ANTENNA REQUIREMENTS .....</b>	<b>72</b>

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Beijing Roborock Technology Co., Ltd.  
Address: Room 1001, Floor 10, Building 3, Yard 17, Anju Road, Changping District, Beijing, P.R. China

### Manufacturer Information

Company Name: Beijing Roborock Technology Co., Ltd.  
Address: Room 1001, Floor 10, Building 3, Yard 17, Anju Road, Changping District, Beijing, P.R. China

### EUT Description

Product Name: Robotic Vacuum Cleaner  
Model Name: RRE0VSP  
Series Model Name: /  
Model Difference: /  
Sample Number: 8522767-S001  
Data of Receipt Sample: May. 30, 2025  
Test Date: May. 30, 2025~ Jue. 20, 2025

### APPLICABLE STANDARDS

#### STANDARD

#### TEST RESULTS

CFR 47 Part 15 Subpart C  
ISED RSS-247 Issue 3  
ISED RSS-GEN Issue 5

PASS

Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6 dB Bandwidth and 99% Occupied Bandwidth	FCC 15.247 (a) (2) RSS-247 Clause 5.2 (a) RSS-Gen Clause 6.7	PASS
2	Conducted Power	FCC 15.247 (b) (3) RSS-247 Clause 5.4 (d) RSS-Gen Clause 6.12	PASS
3	Power Spectral Density	FCC 15.247 (e) RSS-247 Clause 5.2 (b)	PASS
4	Conducted Band edge And Spurious emission	FCC 15.247 (d) RSS-247 Clause 5.5 RSS-GEN Clause 6.13	PASS
5	Radiated Band edges and Spurious emission	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 6.13 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	PASS
6	Conducted Emission Test for AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	PASS
7	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	PASS

**Note:**  
The measurement result for the sample received is < Pass > according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15C > when < Simple Acceptance > decision rule is applied.

Prepared By:

*Tom Tang*

Tom Tang

Reviewed By:

*Emily Wang*

Emily Wang

Authorized By:

*Kevin Shen*

Kevin Shen

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, FCC 47 CFR Part 2, FCC 47 CFR Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 3 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4829.01)</b> <b>UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA.</b></p> <p><b>FCC (FCC Designation No.: CN1247)</b> <b>UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</b></p> <p><b>IC (IC Designation No.: 25056; CAB No.: CN0073)</b> <b>UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</b></p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.1dB
DTS Bandwidth	1.9%
Maximum Conducted Output Power	1.3dB
Maximum Power Spectral Density Level	1.5dB
Band-edge Compliance	1.9%
Unwanted Emissions in Non-restricted Freq Bands	9kHz-30MHz: $\pm 0.90$ dB 30MHz-1GHz: $\pm 1.5$ dB 1GHz-12.75GHz: $\pm 1.9$ dB 12.75GHz-26.5GHz: $\pm 2.1$ dB
Radiation Emission test (include Fundamental emission) (9kHz-30MHz)	3.4dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	3.4dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	3.5dB (1GHz-18GHz) 3.9dB (18GHz-26.5GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

Equipment:	Robotic Vacuum Cleaner	
Model Name:	RRE0VSP	
Technology:	Bluetooth - Low Energy	
Transmit Frequency Range:	2402 MHz ~ 2480 MHz	
Modulation:	GFSK	
Data Rate:	LE 1M	1 Mbps
Test Software of EUT:	ADB (manufacturer declare)	
Antenna Type:	PCB Antenna	
Antenna Gain:	2.29 dBi Note: This data is provided by customer and our lab isn't responsible for this data.	

## 5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max Output Power(dBm)
BLE 1M	2402-2480	0-39[40]	5.87

## 5.3. CHANNEL LIST

Channel	Frequency (MHz)						
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

## 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel		Frequency
GFSK	Low Channel	CH 0	2402MHz
	Middle Channel	CH 19	2440MHz
	High Channel	CH 39	2480MHz

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		ADB		
Modulation Type	Transmit Antenna Number	Test Channel		
		LCH	MCH	HCH
GFSK	1	default	default	default

## 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2400-2483.5	PCB Antenna	2.29 dBi

Note: This data is provided by customer and our lab isn't responsible for this data.

Test Mode	Transmit and Receive Mode	Description
BLE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.

## 5.7. THE WORSE CASE CONFIGURATIONS

For BLE module, the product only supports 1 Mbps, only the test result of 1 Mbps was recorded in this report.

## 5.8. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	101kPa	
Temperature	TN	23 ~ 28°C
	VL	N/A
Voltage:	VN	AC 120V
	VH	N/A

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage

VH= Upper Extreme Test Voltage

TN= Normal Temperature

## 5.9. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Description
1	Laptop	ThinkPad	E590	/

### I/O PORT

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	USB-TTL	USB	100cm Length	/

### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	Empty Wash Fill Dock	roborock	EWFD49LRR	Rated Input: 120V~ 60Hz Rated Output: 20V= 1.5A


Note: The docker with two alternative main PCBs of power part will be collocated to the EUT, of them have been test, only the worse case is recorded in this test report.

## **TEST SETUP**


The EUT can work in an engineer mode with a software through a laptop.

### **SETUP DIAGRAM FOR TESTS**

For Antenna Port Test and Radiated Test:



For Conducted Emission Test and Radiated Test:



Note: The EUT can transmit independently and be charged with a docker. The docker is just a charger, not an intentional transmitter.

## 5.10. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	126700	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	126701	2023-11-25	2024-11-02	2025-11-01
Conducted Emissions Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Conducted Emissions Test		R&S	EMC32		9.25.00	
Radiated Emissions Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR7	222993	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR26	126703	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Spectrum Analyzer	R&S	FSV3044	222992	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	155456	2021-06-03	2024-05-27	2027-05-26
<input checked="" type="checkbox"/>	Receiver Antenna (30MHz-1GHz)	Schwarzbeck	VULB 9168	171952	2021-07-05	2024-07-04	2027-07-03
<input checked="" type="checkbox"/>	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2022-02-28	2025-02-17	2028-02-16
<input checked="" type="checkbox"/>	Receiver Antenna (18GHz-26.5GHz)	Schwarzbeck	BBHA9170	126706	2022-02-28	2025-02-17	2028-02-16
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	Tonscned	TAP01018050	224539	2023-10-10	2024-10-10	2025-10-09
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	R&S	SCU-18D	134667	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	135391	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCGV12-2375-2400-2485-2510-40SS	1	2023-12-18	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	High Pass Filter	COM-MW	ZBF13-3-18G-01	2	2023-12-18	2024-11-02	2025-11-01
Radiated Emissions Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Radiated Emissions Test		Tonscend	JS32-RE		5.0.0.2	
Antenna Port Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	155368	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Power Meter	MWT	MW100-RFCB	221694	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Power Meter	Anritsu	MA24406A	12896	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Attenuator	PASTERNACK	PE7087-6	1624	/	2024-11-04	2025-11-03
Antenna Port Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Antenna Port Test		Tonscend	JS1120-3 Test System		V3.2.22	

## 6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6 dB Bandwidth and 99% Occupied Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.2.3 (11.9.1.3 Method PKPM of ANSI C63.10)
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4 (11.10.2 Method PKPSD of ANSI C63.10)
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test for AC Power Port	ANSI C63.10-2013	6.2

## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

FCC KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V


#### TEST RESULTS TABLE

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)	Final VBW (kHz)
BLE 1M	0.39	0.62	0.6290	62.90%	2.01	2.6	3

Note: 1) Duty Cycle Correction Factor=10log(1/x).

2) Where: x is Duty Cycle (Linear)

3) Where: T is On Time (transmit duration)

TEST GRAPHS


## 7.2. 6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(a)(2) ISED RSS-247 5.2 (a)	6dB Bandwidth	$\geq 500\text{kHz}$	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	For reporting purposes only	2400-2483.5

### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Frequency Span	Peak
Detector	For 6 dB Bandwidth: 100 kHz For 99% Occupied Bandwidth: 1% to 5% of the occupied bandwidth
RBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 99% Occupied Bandwidth: $\geq 3 \times \text{RBW}$
VBW	Max hold
Trace	Max hold
Sweep	Auto couple

- Use the 99% power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

### TEST RESULTS TABLE

Test Mode	Test Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Result
BLE 1M	LCH	0.728	1.0293	Pass
	MCH	0.732	1.0295	Pass
	HCH	0.728	1.0290	Pass

## TEST GRAPHS


### 6dB Bandwidth


Test Mode	Test Channel	Verdict																																																						
BLE 1M	LCH	PASS																																																						
 <p><b>Spectrum Analyzer 1</b>  <b>KEYSIGHT</b> Input: RF  R.L. → Coupling: DC  Align: Auto</p> <p>Input Z: 50 Ω  Corrections: Off  Freq Ref. Int (S)</p> <p>#Atten: 30 dB  Preamp: Off  PNO: Best Wide  IF Gain: Off  Sig Track: Off</p> <p>#Avg Type: Power (RMS)  Avg/Hold: 200/200  Trig: Free Run</p> <p>Frequency: 2.40200000 GHz  Span: 4.000000 MHz  Center Frequency: 2.40200000 GHz  Start Freq: 2.40000000 GHz  Stop Freq: 2.40400000 GHz  Auto Tune  CF Step: 400.000 kHz  Freq Offset: 0 Hz  X-Axis Scale: Log  Signal Track: (Span Zoom)</p> <p>1 Spectrum  Ref Lvl Offset 8.15 dB  Ref Level 20.00 dBm  Scale/Div 10 dB  Log  10.0  0.00  -10.0  -20.0  -30.0  -40.0  -50.0  -60.0  -70.0  Center 2.402000 GHz #Video BW 300 KHz Span 4.000 MHz Sweep 1.00 ms (1001 pts)  #Res BW 100 kHz</p> <p>ΔMr3 728 kHz -0.05 dB</p> <p>Marker Table</p> <table border="1"> <thead> <tr> <th>Mode</th> <th>Trace</th> <th>Scale</th> <th>X</th> <th>Y</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.401 632 GHz</td> <td>-2.374 dBm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.401 996 GHz</td> <td>3.534 dBm</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>Δ1</td> <td>1</td> <td>f (Δ)</td> <td>728 kHz (Δ)</td> <td>-0.04881 dB</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>Jun 05, 2025 5:18:26 PM</p>	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.401 632 GHz	-2.374 dBm			2	N	1	f	2.401 996 GHz	3.534 dBm			3	Δ1	1	f (Δ)	728 kHz (Δ)	-0.04881 dB			4								5								6							
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																																																	
1	N	1	f	2.401 632 GHz	-2.374 dBm																																																			
2	N	1	f	2.401 996 GHz	3.534 dBm																																																			
3	Δ1	1	f (Δ)	728 kHz (Δ)	-0.04881 dB																																																			
4																																																								
5																																																								
6																																																								


Test Mode	Test Channel	Verdict																																																						
BLE 1M	MCH	PASS																																																						
 <p><b>Spectrum Analyzer 1</b>  <b>KEYSIGHT</b> Input: RF  R.L. → Coupling: DC  Align: Auto</p> <p>Input Z: 50 Ω  Corrections: Off  Freq Ref. Int (S)</p> <p>#Atten: 30 dB  Preamp: Off  PNO: Best Wide  IF Gain: Off  Sig Track: Off</p> <p>#Avg Type: Power (RMS)  Avg/Hold: 200/200  Trig: Free Run</p> <p>Frequency: 2.44000000 GHz  Span: 4.000000 MHz  Center Frequency: 2.44000000 GHz  Start Freq: 2.43800000 GHz  Stop Freq: 2.44200000 GHz  Auto Tune  CF Step: 400.000 kHz  Freq Offset: 0 Hz  X-Axis Scale: Log  Signal Track: (Span Zoom)</p> <p>1 Spectrum  Ref Lvl Offset 8.23 dB  Ref Level 20.00 dBm  Scale/Div 10 dB  Log  10.0  0.00  -10.0  -20.0  -30.0  -40.0  -50.0  -60.0  -70.0  Center 2.440000 GHz #Video BW 300 KHz Span 4.000 MHz Sweep 1.00 ms (1001 pts)  #Res BW 100 kHz</p> <p>ΔMr3 732 kHz -0.04 dB</p> <p>Marker Table</p> <table border="1"> <thead> <tr> <th>Mode</th> <th>Trace</th> <th>Scale</th> <th>X</th> <th>Y</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.439 620 GHz</td> <td>-1.324 dBm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.439 988 GHz</td> <td>4.614 dBm</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>Δ1</td> <td>1</td> <td>f (Δ)</td> <td>732 kHz (Δ)</td> <td>-0.03679 dB</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>Jun 05, 2025 5:21:09 PM</p>	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.439 620 GHz	-1.324 dBm			2	N	1	f	2.439 988 GHz	4.614 dBm			3	Δ1	1	f (Δ)	732 kHz (Δ)	-0.03679 dB			4								5								6							
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																																																	
1	N	1	f	2.439 620 GHz	-1.324 dBm																																																			
2	N	1	f	2.439 988 GHz	4.614 dBm																																																			
3	Δ1	1	f (Δ)	732 kHz (Δ)	-0.03679 dB																																																			
4																																																								
5																																																								
6																																																								

Test Mode	Test Channel	Verdict																																																								
BLE 1M	HCH	PASS																																																								
 <p><b>Marker Table</b></p> <table border="1"> <thead> <tr> <th>Mode</th> <th>Trace</th> <th>Scale</th> <th>X</th> <th>Y</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.479 612 GHz</td> <td>-0.9126 dBm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.479 980 GHz</td> <td>5.048 dBm</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>Δ1</td> <td>1</td> <td>f</td> <td>(Δ) 728 kHz</td> <td>(Δ) 0.05112 dB</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>			Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.479 612 GHz	-0.9126 dBm			2	N	1	f	2.479 980 GHz	5.048 dBm			3	Δ1	1	f	(Δ) 728 kHz	(Δ) 0.05112 dB			4								5								6							
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																																																			
1	N	1	f	2.479 612 GHz	-0.9126 dBm																																																					
2	N	1	f	2.479 980 GHz	5.048 dBm																																																					
3	Δ1	1	f	(Δ) 728 kHz	(Δ) 0.05112 dB																																																					
4																																																										
5																																																										
6																																																										

**99% Bandwidth**

Test Mode	Test Channel	Verdict
BLE 1M	LCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	HCH	PASS
		

### 7.3. CONDUCTED OUTPUT POWER

#### LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(b)(3) ISED RSS-247 5.4 (d) RSS-Gen Clause 6.12	Output Power	1 watt or 30dBm	2400-2483.5


#### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.  
 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.  
 Measure the power of each channel.  
 PK Detector used for PK result.

#### TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

#### TEST SETUP



**TEST RESULTS TABLE**

<b>Test Mode</b>	<b>Test Channel</b>	<b>Maximum Conducted Output Power (PK)</b>		<b>LIMIT</b>
		<b>dBm</b>	<b>dBm</b>	
BLE 1M	LCH	4.47		30
	MCH	5.48		30
	HCH	5.87		30

## 7.4. POWER SPECTRAL DENSITY

### LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

### TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST ENVIRONMENT


Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

### TEST SETUP



TEST RESULTS TABLE

Test Mode	Test Channel	Maximum Peak power spectral density (dBm/30kHz)	Result
BLE 1M	LCH	1.35	Pass
	MCH	2.28	Pass
	HCH	2.84	Pass

TEST GRAPHS


Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	HCH	PASS
		

## 7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

### LIMITS

FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
FCC §15.247 (d) RSS-247 Clause 5.5 RSS-GEN Clause 6.13	Conducted Bandedge and Spurious Emissions	20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:


Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
measurement points	$\geq$ span/RBW
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

### TEST SETUP



## TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V


## PART 1: REFERENCE LEVEL MEASUREMENT

### TEST RESULTS TABLE

Test Mode	Test Channel	Result[dBm]
BLE 1M	LCH	3.66
	MCH	4.71
	HCH	5.11



### TEST GRAPHS





**PART 2: CONDUCTED BANDEDGE****TEST RESULTS TABLE**

Test Mode	Test Channel	Result	Verdict
BLE 1M	LCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS


**TEST GRAPHS**


**PART 3: CONDUCTED SPURIOUS EMISSION****TEST RESULTS TABLE**


Test Mode	Test Channel	Result	Verdict
BLE 1M	LCH	Refer to the Test Graph	PASS
	MCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS

## TEST GRAPHS


Test Mode	Channel	Verdict
BLE 1M	LCH	PASS



Test Mode	Channel	Verdict
BLE 1M	MCH	PASS



Test Mode	Channel	Verdict
BLE 1M	HCH	PASS



## 8. RADIATED TEST RESULTS

### 8.1. LIMITS AND PROCEDURE

#### LIMITS

Please refer to FCC §15.205 and §15.209, ISED RSS-247 Clause 5.5, ISED RSS-GEN Clause 8.9&6.13 (Transmitter)

#### Radiation Disturbance Test Limit for ISED (9kHz-1GHz)

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

**Table 5 – General field strength limits at frequencies above 30 MHz**

Frequency (MHz)	Field strength ( $\mu$ V/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

**Table 6 – General field strength limits at frequencies below 30 MHz**

Frequency	Magnetic field strength (H-Field) ( $\mu$ A/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Please refer to FCC KDB 558074

Radiation Disturbance Test Limit for FCC (Class B) (9kHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

## Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

## Restricted bands of operation


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

 Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
VBW	200 Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report  
(Photographs of the Test Configuration)
8. The limits in FCC 47 CFR, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377 \Omega$ . For example, the measurement frequency  $X$  kHz resulted in a level of  $Y$  dBuV/m, which is equivalent to  $Y - 51.5 = Z$  dBuA/m, which has the same margin,  $W$  dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1G




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Above 1G




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK:3 MHz AVG: See note6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements; and 1 MHz resolution bandwidth with video bandwidth  $\geq 1/T$  but not less than the setting list in section 7.1 when use peak detector, max hold to be run for at least  $[50 * (1/\text{Duty Cycle})]$  traces for average measurements. For the Duty Cycle need to refer the results in section 7.1.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in one orthogonal axis (X axis) emissions had been tested and recorded in the report.

Note 2: The EUT can transmit with/without the dock, both the two conditions have been tested, the condition without dock was the worse case and recorded in this test report.

## 8.2. TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V


## 8.3. RESTRICTED BANDEDGE

### TEST RESULT TABLE

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	LCH	<Limit	PASS
	HCH	<Limit	PASS

### TEST GRAPHS

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS




#### PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dB $\mu$ V/m]	[dB]	[dB $\mu$ V/m]	[dB $\mu$ V/m]	[dB]	
1	2346.4683	40.10	13.49	53.59	74.00	-20.41	Horizontal
2	2390.0000	36.96	13.72	50.68	74.00	-23.32	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.  
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).  
3. Measurement = Reading Level + Correct Factor.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2374.3530	39.30	13.72	53.02	74.00	-20.98	Vertical
2	2390.0000	37.31	13.72	51.03	74.00	-22.97	Vertical

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.  
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).  
3. Measurement = Reading Level + Correct Factor.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	37.33	14.12	51.45	74.00	-22.55	Horizontal
2	2537.4422	39.95	14.57	54.52	74.00	-19.48	Horizontal


**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2537.4422	30.47	14.57	45.04	54.00	-8.96	Horizontal

Note:

1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Vertical	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	38.19	14.12	52.31	74.00	-21.69	Vertical
2	2550.8314	40.13	14.73	54.86	74.00	-19.14	Vertical

**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2550.8314	30.27	14.73	45.00	54.00	-9.00	Vertical

Note:

1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 8.4. SPURIOUS EMISSIONS

### TEST RESULTS TABLE

#### 1) For 1GHz~18GHz

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

#### 2) For 9kHz~30MHz

Test Mode	Channel	Puw(dBm)	Verdict
BLE	MCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

#### 3) For 30MHz~1GHz

Test Mode	Channel	Puw(dBm)	Verdict
BLE	MCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

#### 4) For 18GHz~26.5GHz


Test Mode	Channel	Puw(dBm)	Verdict
BLE	MCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

Part 1: 1GHz~6.5GHz
**HARMONICS AND SPURIOUS EMISSIONS**

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS



**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1255.0944	44.04	-1.98	42.06	74.00	-31.94	Horizontal
2	3081.3227	36.26	9.99	46.25	74.00	-27.75	Horizontal
3	4124.3905	35.91	13.71	49.62	74.00	-24.38	Horizontal
4	5181.2102	36.12	15.54	51.66	74.00	-22.34	Horizontal
5	5740.9051	35.17	18.03	53.20	74.00	-20.80	Horizontal
6	6083.3229	35.20	18.29	53.49	74.00	-20.51	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS



**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1185.6482	42.52	-1.95	40.57	74.00	-33.43	Vertical
2	1255.0944	45.36	-1.98	43.38	74.00	-30.62	Vertical
3	3457.4322	36.72	11.15	47.87	74.00	-26.13	Vertical
4	4688.8986	35.28	15.85	51.13	74.00	-22.87	Vertical
5	5713.4017	35.20	17.73	52.93	74.00	-21.07	Vertical
6	5938.2423	34.66	18.49	53.15	74.00	-20.85	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS



**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1255.0944	42.89	-1.98	40.91	74.00	-33.09	Horizontal
2	3590.8239	36.91	11.13	48.04	74.00	-25.96	Horizontal
3	4158.7698	36.78	13.33	50.11	74.00	-23.89	Horizontal
4	5431.4914	35.30	17.54	52.84	74.00	-21.16	Horizontal
5	5992.5616	35.21	18.38	53.59	74.00	-20.41	Horizontal
6	6293.0366	34.72	18.83	53.55	74.00	-20.45	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS



**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1185.6482	42.13	-1.95	40.18	74.00	-33.82	Vertical
2	1255.0944	47.34	-1.98	45.36	74.00	-28.64	Vertical
3	1394.6743	41.00	-1.45	39.55	74.00	-34.45	Vertical
4	3688.4611	36.96	11.68	48.64	74.00	-25.36	Vertical
5	5744.3430	35.14	17.97	53.11	74.00	-20.89	Vertical
6	6306.1008	34.16	19.01	53.17	74.00	-20.83	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS



**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1255.0944	42.86	-1.98	40.88	74.00	-33.12	Horizontal
2	1618.1398	38.83	0.40	39.23	74.00	-34.77	Horizontal
3	2045.1306	38.94	4.42	43.36	74.00	-30.64	Horizontal
4	4694.3993	35.45	15.51	50.96	74.00	-23.04	Horizontal
5	5726.4658	35.22	17.64	52.86	74.00	-21.14	Horizontal
6	6058.5698	34.69	18.22	52.91	74.00	-21.09	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Vertical	PASS


**PK Result:**


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1185.6482	42.23	-1.95	40.28	74.00	-33.72	Vertical
2	1255.0944	45.95	-1.98	43.97	74.00	-30.03	Vertical
3	3081.3227	37.18	9.99	47.17	74.00	-26.83	Vertical
4	4136.0795	36.39	13.35	49.74	74.00	-24.26	Vertical
5	4979.7475	36.75	15.26	52.01	74.00	-21.99	Vertical
6	6023.5029	35.22	18.14	53.36	74.00	-20.64	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Part 2: 6.5GHz~18GHz
**HARMONICS AND SPURIOUS EMISSIONS**

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS


**PK Result:**


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7601.2627	44.49	5.05	49.54	74.00	-24.46	Horizontal
2	8811.7890	43.63	6.38	50.01	74.00	-23.99	Horizontal
3	12125.6407	41.67	8.34	50.01	74.00	-23.99	Horizontal
4	15002.4378	40.58	12.96	53.54	74.00	-20.46	Horizontal
5	15597.6372	40.34	13.47	53.81	74.00	-20.19	Horizontal
6	16487.5609	38.48	16.67	55.15	74.00	-18.85	Horizontal
7	17706.7133	36.61	19.33	55.94	74.00	-18.06	Horizontal

**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16487.5609	28.91	16.67	45.58	54.00	-8.42	Horizontal
2	17706.7133	26.82	19.33	46.15	54.00	-7.85	Horizontal

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.  
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).  
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.  
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7602.7003	44.35	5.03	49.38	74.00	-24.62	Vertical
2	8255.4069	43.29	6.19	49.48	74.00	-24.52	Vertical
3	8806.0383	45.07	6.36	51.43	74.00	-22.57	Vertical
4	15612.0140	39.90	13.52	53.42	74.00	-20.58	Vertical
5	16519.1899	38.97	16.66	55.63	74.00	-18.37	Vertical
6	16842.6678	38.19	16.92	55.11	74.00	-18.89	Vertical
7	17715.3394	37.34	19.42	56.76	74.00	-17.24	Vertical


**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16519.1899	28.74	16.66	45.40	54.00	-8.60	Vertical
2	16842.6678	27.06	16.92	43.98	54.00	-10.02	Vertical
3	17715.3394	26.87	19.42	46.29	54.00	-7.71	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7309.4137	45.59	4.03	49.62	74.00	-24.38	Horizontal
2	8794.5368	44.22	6.31	50.53	74.00	-23.47	Horizontal
3	14860.1075	40.97	12.75	53.72	74.00	-20.28	Horizontal
4	15584.6981	40.71	13.51	54.22	74.00	-19.78	Horizontal
5	16532.1290	40.03	16.42	56.45	74.00	-17.55	Horizontal
6	17722.5278	37.64	19.50	57.14	74.00	-16.86	Horizontal
7	17976.9971	35.26	20.62	55.88	74.00	-18.12	Horizontal


**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	15584.6981	29.95	13.51	43.46	54.00	-10.54	Horizontal
2	16532.1290	28.42	16.42	44.84	54.00	-9.16	Horizontal
3	17722.5278	27.26	19.50	46.76	54.00	-7.24	Horizontal
4	17976.9971	25.06	20.62	45.68	54.00	-8.32	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7614.2018	44.37	5.12	49.49	74.00	-24.51	Vertical
2	8449.4937	43.67	6.09	49.76	74.00	-24.24	Vertical
3	9683.0229	43.21	6.47	49.68	74.00	-24.32	Vertical
4	15094.4493	40.23	13.19	53.42	74.00	-20.58	Vertical
5	15627.8285	40.27	13.67	53.94	74.00	-20.06	Vertical
6	16517.7522	38.61	16.67	55.28	74.00	-18.72	Vertical
7	17721.0901	36.44	19.48	55.92	74.00	-18.08	Vertical


**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16517.7522	29.65	16.67	46.32	54.00	-7.68	Vertical
2	17721.0901	27.35	19.48	46.83	54.00	-7.17	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	8518.5023	43.94	6.70	50.64	74.00	-23.36	Horizontal
2	9670.0838	43.94	6.43	50.37	74.00	-23.63	Horizontal
3	14881.6727	40.46	12.71	53.17	74.00	-20.83	Horizontal
4	15751.4689	39.67	14.40	54.07	74.00	-19.93	Horizontal
5	16478.9349	38.75	16.58	55.33	74.00	-18.67	Horizontal
6	16928.9286	37.36	16.78	54.14	74.00	-19.86	Horizontal
7	17690.8989	37.39	19.15	56.54	74.00	-17.46	Horizontal


**AV Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	15751.4689	28.72	14.40	43.12	54.00	-10.88	Horizontal
2	16478.9349	28.76	16.58	45.34	54.00	-8.66	Horizontal
3	16928.9286	27.32	16.78	44.10	54.00	-9.90	Horizontal
4	17690.8989	28.03	19.15	47.18	54.00	-6.82	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Vertical	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	8808.9136	43.57	6.38	49.95	74.00	-24.05	Vertical
2	12158.7073	41.87	8.46	50.33	74.00	-23.67	Vertical
3	15078.6348	40.53	13.09	53.62	74.00	-20.38	Vertical
4	15596.1995	40.83	13.48	54.31	74.00	-19.69	Vertical
5	16591.0739	38.85	16.73	55.58	74.00	-18.42	Vertical
6	17700.9626	37.57	19.28	56.85	74.00	-17.15	Vertical
7	17953.9942	35.58	20.48	56.06	74.00	-17.94	Vertical

**AV Result:**


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	15596.1995	30.29	13.48	43.77	54.00	-10.23	Vertical
2	16591.0739	27.76	16.73	44.49	54.00	-9.51	Vertical
3	17700.9626	27.08	19.28	46.36	54.00	-7.64	Vertical
4	17953.9942	25.13	20.48	45.61	54.00	-8.39	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Part 3: 18GHz~26.5GHz
**SPURIOUS EMISSIONS 18GHz ~ 26.5GHz (WORST-CASE CONFIGURATION)**


Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS


**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	18738.7239	49.71	-6.23	43.48	74.00	-30.52	Horizontal
2	20311.3811	48.84	-5.45	43.39	74.00	-30.61	Horizontal
3	21290.6791	48.54	-5.90	42.64	74.00	-31.36	Horizontal
4	23160.8661	48.03	-3.43	44.60	74.00	-29.40	Horizontal
5	23956.5457	48.39	-2.68	45.71	74.00	-28.29	Horizontal
6	25164.5165	49.29	-3.44	45.85	74.00	-28.15	Horizontal

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. Measurement = Reading Level + Correct Factor.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS



**PK Result:**

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	18590.8091	49.72	-6.44	43.28	74.00	-30.72	Vertical
2	20121.8122	48.29	-5.19	43.10	74.00	-30.90	Vertical
3	21039.0539	48.56	-6.00	42.56	74.00	-31.44	Vertical
4	23435.4435	48.18	-3.20	44.98	74.00	-29.02	Vertical
5	24788.7789	49.08	-3.31	45.77	74.00	-28.23	Vertical
6	25287.7788	49.82	-3.33	46.49	74.00	-27.51	Vertical

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. Measurement = Reading Level + Correct Factor.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Part 4: 30MHz~1GHz
**SPURIOUS EMISSIONS 30MHz ~ 1GHz (WORST-CASE CONFIGURATION)**


Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	45.6186	8.24	20.20	28.44	40.00	-11.56	Peak
2	187.2527	19.09	17.94	37.03	43.50	-6.47	Peak
3	229.2579	10.61	17.60	28.21	46.00	-17.79	Peak
4	279.0239	5.89	20.56	26.45	46.00	-19.55	Peak
5	372.2502	5.54	22.90	28.44	46.00	-17.56	Peak
6	437.7318	7.43	24.85	32.28	46.00	-13.72	Peak

Note: 1. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.  
3. Measurement = Reading Level + Correct Factor.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	45.6186	7.21	20.20	27.41	40.00	-12.59	Peak
2	69.7740	3.38	18.00	21.38	40.00	-18.62	Peak
3	188.7079	13.97	17.81	31.78	43.50	-11.72	Peak
4	279.0239	7.66	20.56	28.22	46.00	-17.78	Peak
5	454.3204	6.88	25.14	32.02	46.00	-13.98	Peak
6	600.0290	4.46	28.24	32.70	46.00	-13.30	Peak

Note: 1. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.  
3. Measurement = Reading Level + Correct Factor.

Part 5: 9kHz~30MHz
**SPURIOUS EMISSIONS 9kHz ~ 30MHz (WORST CASE CONFIGURATION-FACE ON)**

Test Mode	Channel	Frequency Range	Verdict
BLE 1M	MCH	9kHz~150kHz	PASS




No.	Frequency	Reading Level	Correct Factor	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dBuA/m]	[dBuA/m]	[dB]	
1	0.0205	18.87	-61.74	-42.87	41.38	-94.37	-10.12	-84.25	Peak
2	0.0559	15.87	-61.60	-45.73	32.65	-97.23	-18.85	-78.38	Peak
3	0.0665	10.02	-61.61	-51.59	31.14	-103.09	-20.36	-82.73	Peak
4	0.1077	11.56	-61.71	-50.15	26.96	-101.65	-24.54	-77.11	Peak
5	0.1330	10.75	-61.73	-50.98	25.13	-102.48	-26.37	-76.11	Peak
6	0.1480	12.32	-61.73	-49.41	24.19	-100.91	-27.31	-73.60	Peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Test Mode	Channel	Frequency Range	Verdict
BLE 1M	MCH	150kHz~490kHz	PASS




No.	Frequency	Reading Level	Correct Factor	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dBuA/m]	[dBuA/m]	[dB]	
1	0.1531	28.27	-61.74	-33.47	23.90	-84.97	-27.60	-57.37	Peak
2	0.1698	28.17	-61.75	-33.58	23.01	-85.08	-28.49	-56.59	Peak
3	0.2376	28.77	-61.79	-33.02	20.08	-84.52	-31.42	-53.10	Peak
4	0.3116	26.80	-61.82	-35.02	17.73	-86.52	-33.77	-52.75	Peak
5	0.3639	30.59	-61.83	-31.24	16.38	-82.74	-35.12	-47.62	Peak
6	0.4304	25.80	-61.85	-36.05	14.67	-87.55	-36.83	-50.72	Peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Test Mode	Channel	Frequency Range	Verdict
BLE 1M	MCH	490kHz~30MHz	PASS



No.	Frequency	Reading Level	Correct Factor	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dBuA/m]	[dBuA/m]	[dB]	
1	0.5136	19.05	-21.89	-2.84	33.39	-54.34	-18.11	-36.23	Peak
2	0.6346	20.14	-21.88	-1.74	31.55	-53.24	-19.95	-33.29	Peak
3	0.6966	19.79	-21.87	-2.08	30.74	-53.58	-20.76	-32.82	Peak
4	0.8471	16.30	-21.87	-5.57	29.04	-57.07	-22.46	-34.61	Peak
5	1.0832	15.76	-21.86	-6.10	26.91	-57.60	-24.59	-33.01	Peak
6	1.4374	16.86	-21.84	-4.98	24.45	-56.48	-27.05	-29.43	Peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

## 9. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS


Please refer to FCC §15.207 (a)

FREQUENCY (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST ENVIRONMENT


Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

### TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 12 mm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

LINE L RESULTS (WORST-CASE CONFIGURATION)

**Final Result**

Frequency [MHz]	QuasiPeak [dB $\mu$ V]	Average [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Meas. Time [ms]	Bandwidth [kHz]	Line	Filter	Corr. [dB]
0.408700	---	39.40	47.68	8.27	1500.0	9.000	L1	OFF	9.6
0.408700	42.24	---	57.68	15.44	1500.0	9.000	L1	OFF	9.6
0.438550	---	43.11	47.09	3.98	1500.0	9.000	L1	OFF	9.6
0.438550	43.99	---	57.09	13.10	1500.0	9.000	L1	OFF	9.6
0.465913	---	45.04	46.59	1.55	1500.0	9.000	L1	OFF	9.6
0.465913	51.16	---	56.59	5.43	1500.0	9.000	L1	OFF	9.6
0.480838	---	45.73	46.33	0.59	1500.0	9.000	L1	OFF	9.6
0.480838	50.67	---	56.33	5.66	1500.0	9.000	L1	OFF	9.6
0.801725	---	39.90	46.00	6.10	1500.0	9.000	L1	OFF	9.6
0.801725	43.02	---	56.00	12.98	1500.0	9.000	L1	OFF	9.6
1.602700	---	31.44	46.00	14.56	1500.0	9.000	L1	OFF	9.6
1.602700	36.69	---	56.00	19.31	1500.0	9.000	L1	OFF	9.6

Note:

1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.
5. Pre-testing all test modes and channels and find the MCH of BLE 1M which is the worst case, so only the worst case is included in this test report.

LINE N RESULTS (WORST-CASE CONFIGURATION)

**Final Result**

Frequency [MHz]	QuasiPeak [dB $\mu$ V]	Average [dB $\mu$ V]	Limit [dB $\mu$ V]	Margin [dB]	Meas. Time [ms]	Bandwidth [kHz]	Line	Filter	Corr. [dB]
0.388800	---	39.26	48.09	8.83	1500.0	9.000	N	OFF	9.6
0.388800	40.95	---	58.09	17.14	1500.0	9.000	N	OFF	9.6
0.411188	---	41.64	47.62	5.98	1500.0	9.000	N	OFF	9.6
0.411188	43.45	---	57.62	14.17	1500.0	9.000	N	OFF	9.6
0.438550	---	42.08	47.09	5.01	1500.0	9.000	N	OFF	9.6
0.438550	44.00	---	57.09	13.09	1500.0	9.000	N	OFF	9.6
0.465913	---	45.61	46.59	0.97	1500.0	9.000	N	OFF	9.6
0.465913	51.30	---	56.59	5.29	1500.0	9.000	N	OFF	9.6
0.804213	---	42.36	46.00	3.64	1500.0	9.000	N	OFF	9.6
0.804213	44.53	---	56.00	11.47	1500.0	9.000	N	OFF	9.6
1.610163	---	35.67	46.00	10.33	1500.0	9.000	N	OFF	9.6
1.610163	38.43	---	56.00	17.57	1500.0	9.000	N	OFF	9.6

Note:

1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.
5. Pre-testing all test modes and channels and find the MCH of BLE 1M which is the worst case, so only the worst case is included in this test report.

## 10. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### ANTENNA GAIN

The antenna gain of EUT is less than 6 dBi

## END OF REPORT