

RF Exposure Evaluation Declaration

FCC ID: 2AN2O-RSW02

APPLICANT: Beijing Roborock Technology Co., Ltd.

Application Type: Certification

Product: WIFI Module

Model No.: BL-R8189ME1 V1.2

FCC Classification: Digital Transmission System (DTS)

Test Procedure(s): KDB 447498 D01v06


Test Date: January 13, 2020

Reviewed By:



(Kevin Guo)

Approved By:



(Robin Wu)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
1909WSU021-U2	Rev. 01	Initial report	01-13-2020	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	WIFI Module
Model No.:	BL-R8189ME1 V1.2
Wi-Fi Specification	802.11b/g/n
Power Type:	DC 3.3V

1.2. Product Specification Subjective to this Report

Frequency Range:	802.11b/g/n-HT20: 2412 ~ 2462 MHz
Channel Number:	802.11b/g/n-HT20: 11
Type of Modulation:	802.11b: DSSS 802.11g/n: OFDM
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 150Mbps
Antenna Type:	Internal PCB antenna
Antenna Gain:	3.87dBi

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	WIFI Module			
Test Item	RF Exposure Evaluation			

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11b/g/n	2412 ~ 2462	22.54	0.057	1

CONCULISON:

The max Power Density at R (20 cm) = 0.0357mW/cm² < 1 mW/cm² for 2.4G WLAN.

Therefore, the Min Safety Distance is 20cm.

The End

Appendix A – EUT Photograph

Refer to "1909WSU021-UE" file.