

TEST REPORT

Applicant Name : M5Stack Technology Co.,Ltd
Address : Block A10, Expo Bay South Coast, Fuhai Street, Bao'an District,
Shenzhen, Guangdong, China
Report Number : 2504S32884E-RF-00B
FCC ID: 2AN3WM5SWITCHC6

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: M5SwitchC6
Model No.: SwitchC6
Trade Mark:



Date Received: 2025-04-21
Date of Test: 2025-04-29 to 2025-05-22
Report Date: 2025-05-28


Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:



Matt Liang
EMC Engineer

Approved By:



Bob Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY..... 4

GENERAL INFORMATION..... 5

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 5

 OBJECTIVE 5

 TEST METHODOLOGY 5

 TEST FACILITY 6

 MEASUREMENT UNCERTAINTY 6

SYSTEM TEST CONFIGURATION 7

 SUPPORT EQUIPMENT LIST AND DETAILS 7

 EXTERNAL I/O CABLE..... 7

 BLOCK DIAGRAM OF TEST SETUP 8

SUMMARY OF TEST RESULTS 10

TEST EQUIPMENT LIST 11

FCC §15.203-ANTENNA REQUIREMENT 13

 APPLICABLE STANDARD..... 13

 ANTENNA CONNECTOR CONSTRUCTION 13

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS 14

 APPLICABLE STANDARD..... 14

 EUT SETUP 14

 EMI TEST RECEIVER SETUP 14

 TEST PROCEDURE 14

 CALCULATION 15

 TEST DATA 15

FCC §15.209, §15.205 &§15.247(d) - SPURIOUS EMISSIONS..... 18

 APPLICABLE STANDARD..... 18

 EUT SETUP 18

 EMI TEST RECEIVER& SPECTRUM ANALYZER SETUP 20

 TEST PROCEDURE 20

 CALCULATION 21

 TEST DATA 21

FCC §15.247(a) (2)-6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH 109

 APPLICABLE STANDARD..... 109

 TEST PROCEDURE 109

 TEST DATA 109

FCC §15.247(b) (3)-MAXIMUM CONDUCTED OUTPUT POWER..... 110

 APPLICABLE STANDARD..... 110

 TEST PROCEDURE 110

 TEST DATA 110

FCC §15.247(d)-100 kHz BANDWIDTH OF FREQUENCY BAND EDGE 111

 APPLICABLE STANDARD..... 111

 TEST PROCEDURE 111

 TEST DATA 111

FCC §15.247(e)-POWER SPECTRAL DENSITY 112

 APPLICABLE STANDARD..... 112

 TEST PROCEDURE 112

 TEST DATA 113

APPENDIX (RF TEST RESULTS) 114

 6dB EMISSION BANDWIDTH 114

99% OCCUPIED BANDWIDTH 119

MAXIMUM CONDUCTED OUTPUT POWER 124

POWER SPECTRAL DENSITY 126

100 KHz BANDWIDTH OF FREQUENCY BAND EDGE 131

DUTY CYCLE..... 135

EXHIBIT A - EUT PHOTOGRAPHS 140

EXHIBIT B - TEST SETUP PHOTOGRAPHS 141

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504S32884E-RF-00B	Original Report	2025-05-28

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	M5SwitchC6
Tested Model	SwitchC6
Frequency Range	2.4G Wi-Fi: 2412-2462MHz, 2422-2452MHz
Mode	802.11b/g/n20/n40/ax20
Maximum Conducted Peak Output Power	23.62dBm
Modulation Technique	DSSS, OFDM, OFDMA
Antenna Specification [#]	3.96dBi(It is provided by the applicant.)
Voltage Range [#]	AC 100-230V
Sample Serial Number	31OL-1 (For CE&RE Test), 31OM-1 (For RF Conducted Test) (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, and KDB 558074 D01 15.247 Meas Guidance v05r02.

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.064×10^{-7}
RF output power, conducted		0.3 dB
Unwanted Emission, conducted		1.2 dB
AC Power Lines Conducted Emissions		2.7 dB
Emissions, Radiated	9kHz - 30MHz	2.1 dB
	30MHz - 1GHz	4.3 dB
	1GHz - 18GHz	4.9 dB
	18GHz - 26.5GHz	5.2 dB
Temperature		1°C
Humidity		7%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4G Wi-Fi, total 11channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

802.11b, 802.11g, 802.11n20, 802.11ax20 mode was tested with Channel 1, 6 and 11.

802.11n40 mode was tested with Channel 3, 6 and 9.

EUT Exercise Software and Power Level#

Exercise Software:		EspRFTestTool_v3.6		
Mode	Data Rate	Power Level		
		Low Channel	Middle Channel	High Channel
802.11 b	1Mbps	27	27	27
802.11 g	6Mbps	27	27	27
802.11 n20	MCS0	27	27	27
802.11 n40	MCS0	27	27	27
802.11 ax20	MCS0	27	27	27

Note 1: The information in the above table is provided by the applicant.

Note 2: The worse-case data rates are determined to be as above for each mode based upon investigations by measuring the output power and PSD across all data rates, bandwidths and modulations.

Note 3: The 802.11 AX mode only support full RU configuration. (It is provided by the applicant.)

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Kodect	LED lamp [#]	Unknown	Unknown
OPPLE	Lamp socket [#]	8602	Unknown

External I/O Cable


Cable Description	Shielding Type	Length (m)	From Port	To
AC Cable	No	1	AC Mains	Receptacle
AC Cable	No	1.37	EUT	Receptacle
AC Cable	No	0.20	EUT	Lamp socket

Block Diagram of Test Setup


For Conducted Emission:



For Radiated Emission Below 1GHz:



For Radiated Emission Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliance
§15.247(a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

- Note 1: For AC line conducted emissions, the maximum output power mode and channel was tested.
- Note 2: For Radiated Spurious Emissions 9kHz~1GHz/18GHz~25GHz, the maximum output power mode and channel was tested.
- Note 3: For Radiated Spurious Emissions, after pre-scan in the X, Y and Z axes of orientation, the worst case as setup photos was recorded.
- Note 4: The cable loss is 0.5 dB, which was added into the all RF test results.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2024/11/08	2025/11/07
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2024/11/08	2025/11/07
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2024/10/08	2025/10/07
Rohde & Schwarz	Pulse Limiter	ESH3-Z2	100312	2024/10/08	2025/10/07
Unknown	RF Coaxial Cable	No.17	N0350	2024/10/08	2025/10/07
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Below 1GHz)					
Rohde & Schwarz	Test Receiver	ESR	102725	2024/11/08	2025/11/07
SONOMA INSTRUMENT	Amplifier	310N	186131	2025/03/26	2026/03/25
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2024/08/08	2027/08/07
Unknown	RF Coaxial Cable	No.12	N040	2024/10/08	2025/10/07
Unknown	RF Coaxial Cable	No.13	N300	2024/10/08	2025/10/07
Unknown	RF Coaxial Cable	No.14	N800	2024/10/08	2025/10/07
BACL	LOOP ANTENNA	1313-1A	3110711	2024/01/16	2027/01/15
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Above 1GHz)					
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2024/10/08	2025/10/07
Decentest	Filter Switch Unit	DT7220FSU	DQ77927	2024/10/08	2025/10/07
Decentest	Multiplex Switch Test Control Set	DT7220CSU	DQ77924	2024/10/08	2025/10/07
A.H. Systems, inc.	Preamplifier	PAM-0118	226	2025/03/20	2026/03/19
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Unknown	RF Coaxial Cable	No.10	N050	2024/10/08	2025/10/07
Unknown	RF Coaxial Cable	No.11	N1000	2024/10/08	2025/10/07
Unknown	RF Coaxial Cable	No.19	N500	2024/10/08	2025/10/07
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2023/12/12	2026/12/11
BACL	Amplifier	BACL-1313-A1840	4012521	2024/07/05	2025/07/04
Unknown	RF Coaxial Cable	No.15	N600	2024/10/08	2025/10/07
Unknown	RF Coaxial Cable	No.16	N650	2024/10/08	2025/10/07
Test Software: e3 191218 (V9)					

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101590	2024/10/08	2025/10/07
Anritsu	Microwave Peak Power Sensor	MA24418A	12619	2025/03/26	2026/03/25
WEINSCHEL	10dB Attenuator	5324	AU 3842	2024/10/08	2025/10/07
Test Software: JDAutoTestSystem V1.0.0					

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.203-ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which were permanently attached to the EUT, fulfill the requirement of this section. Please refer to the EUT photos.

Frequency Range	Antenna gain
2412-2462MHz	3.96dBi


Result: Compliance.

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a).

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Limiter Attenuation. The basic equation is as follows:

Factor = LISN VDF + Cable Loss+ 10dB Attenuation(Limiter)

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

Over Limit = Level - Limit

Level = Read Level + Factor

Test Data


Environmental Conditions

Temperature:	24.6 °C
Relative Humidity:	56 %
ATM Pressure:	100.2 kPa
Test Engineer:	Jason Fan
Test Date:	2025-05-22
EUT Operation Mode:	2.4G WIFI Transmitting

Test Result: Compliance, please refer to the below data.

Note: The maximum output power mode and channel: 2.4G WIFI 802.11ax20 Middle channel was tested.


AC 120V/60Hz, Line:



Site : Shielding Room
 Condition : Line
 Project No. : 2504S32884E-RF Tester: Jason Fan
 Test Mode : 2.4G WIFI Transmitting
 Receiver Setting: IF B/W 9kHz PK/AV

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.203	20.22	10.70	30.92	53.47	-22.55	Average
2	0.203	20.22	16.53	36.75	63.47	-26.72	QP
3	0.285	20.14	-0.02	20.12	50.67	-30.55	Average
4	0.285	20.14	11.10	31.24	60.67	-29.43	QP
5	0.397	20.07	-2.50	17.57	47.91	-30.34	Average
6	0.397	20.07	9.04	29.11	57.91	-28.80	QP
7	0.802	20.25	-7.13	13.12	46.00	-32.88	Average
8	0.802	20.25	7.79	28.04	56.00	-27.96	QP
9	1.620	20.38	-10.91	9.47	46.00	-36.53	Average
10	1.620	20.38	3.57	23.95	56.00	-32.05	QP
11	7.825	20.35	-13.96	6.39	50.00	-43.61	Average
12	7.825	20.35	-9.15	11.20	60.00	-48.80	QP

AC 120V/60Hz, Neutral:



Site : Shielding Room
 Condition : neutral
 Project No. : 2504S32884E-RF Tester: Jason Fan
 Test Mode : 2.4G WIFI Transmitting
 Receiver Setting: IF B/W 9kHz PK/AV


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.186	19.85	5.74	25.59	54.21	-28.62	Average
2	0.186	19.85	17.71	37.56	64.21	-26.65	QP
3	0.323	19.82	-0.31	19.51	49.63	-30.12	Average
4	0.323	19.82	9.65	29.47	59.63	-30.16	QP
5	0.451	19.82	-3.33	16.49	46.87	-30.38	Average
6	0.451	19.82	6.88	26.70	56.87	-30.17	QP
7	0.870	20.37	-8.48	11.89	46.00	-34.11	Average
8	0.870	20.37	0.28	20.65	56.00	-35.35	QP
9	2.032	20.21	-12.42	7.79	46.00	-38.21	Average
10	2.032	20.21	-4.98	15.23	56.00	-40.77	QP
11	2.698	20.21	-13.64	6.57	46.00	-39.43	Average
12	2.698	20.21	-7.10	13.11	56.00	-42.89	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.205; §15.209; §15.247(d)


EUT Setup

9kHz - 30MHz:



30MHz - 1GHz:



Above 1GHz:

Boundary of the EUT, local AE and associated cabling and measurement distance for radiated emissions measurements:

The central point of the arrangement shall be positioned at the centre of the turntable. The measurement distance is the shortest horizontal distance between an imaginary circular periphery just encompassing this arrangement and the calibration point of the antenna. See as below Figure C.1 and C.2.




Figure C.1 – Measurement distance




Figure C.2 –Boundary of EUT, Local AE and associated cabling

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver& Spectrum Analyzer Setup

The system was investigated from 9kHz to 25GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz -1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9kHz - 150kHz	PK	0.3kHz	1kHz	/	PK
	QP/AV	/	/	200Hz	QP/AV
150kHz - 30MHz	PK	10kHz	30kHz	/	PK
	QP/AV	/	/	9kHz	QP/AV
30MHz - 1000MHz	PK	100kHz	300kHz	/	PK
	QP	/	/	120kHz	QP

1GHz-25GHz:

Pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	3kHz
		<98%	1MHz	≥1/T, no less than 5 kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	3kHz
		<98%	1MHz	≥1/T

Note 1: T is minimum transmission duration

Note 2: The 1GHz-4GHz testing use the notch filter and the 4GHz-18GHz testing use high-pass filter.

Note 3: The band edge testing use 10dB attenuator.

Note 4: The filters and attenuators are all integrated within the filter switch unit.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

According to ANSI C63.10-2020,9.2: For field strength measurements made at other than the distance specified by the limit, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance).

$$E_{SpecLimit} = E_{Meas} + 20 \log \left(\frac{D_{Meas}}{D_{SpecLimit}} \right)$$

where

$E_{SpecLimit}$	is the field strength of the emission at the distance specified by the limit, in dBuV/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dBuV/m
D_{Meas}	is the measurement distance, in m
$D_{SpecLimit}$	is the distance specified by the limit, in m

Note 1: If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Note 2: For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit/Margin} = \text{Level} / \text{Corrected Amplitude} - \text{Limit}$$

$$\text{Level} / \text{Corrected Amplitude} = \text{Read Level} + \text{Factor}$$

Test Data

9kHz-1GHz

Environmental Conditions


Temperature:	23.2 °C
Relative Humidity:	55 %
ATM Pressure:	101.3 kPa
Test Engineer:	Roger Ling
Test Date:	2025-04-29
EUT Operation Mode:	2.4G WIFI Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: The Loop Antenna were tested in parallel, perpendicular and ground-parallel. The worst orientation was parallel and the data was recorded in report.


Note 2: The maximum output power mode and channel: 2.4G WiFi 802.11ax20 Middle channel was tested.

9kHz~30MHz:



Site : Chamber
 Condition : 3m
 Project No. : 2504S32884E-RF
 Polarization : Parallel Tester: Roger Ling
 Test Mode : 2.4G WIFI Transmitting
 Receiver Setting: RBW:300Hz VBW:1kHz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.009	36.23	27.06	63.29	128.06	-64.77	Peak
2	0.019	31.70	27.71	59.41	121.90	-62.49	Peak
3	0.027	28.22	27.43	55.65	118.94	-63.29	Peak
4	0.084	18.15	22.08	40.23	109.14	-68.91	Peak
5	0.108	16.10	23.20	39.30	106.97	-67.67	Peak
6	0.141	14.56	27.87	42.43	104.62	-62.19	Peak



Site : Chamber
Condition : 3m
Project No. : 2504S32884E-RF
Polarization : Parallel Tester: Roger Ling
Test Mode : 2.4G WIFI Transmitting
Receiver Setting: RBW:10kHz VBW:30kHz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.280	8.18	43.55	51.73	98.65	-46.92	Peak
2	0.567	2.48	47.71	50.19	72.50	-22.31	Peak
3	1.197	-2.57	52.55	49.98	65.88	-15.90	Peak
4	2.664	-5.73	66.29	60.56	69.54	-8.98	Peak
5	4.269	-6.32	52.42	46.10	69.54	-23.44	Peak
6	10.676	-5.27	42.74	37.47	69.54	-32.07	Peak

30MHz~1GHz:



Site : Chamber
 Condition : 3m HORIZONTAL
 Project No. : 2504S32884E-RF Tester: Roger Ling
 Test Mode : 2.4G WIFI Transmitting
 Receiver Setting: RBW:100kHz VBW:300kHz

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.557	-11.96	28.23	16.27	40.00	-23.73	Peak
2	57.217	-10.74	26.93	16.19	40.00	-23.81	Peak
3	94.015	-13.00	31.67	18.67	43.50	-24.83	Peak
4	107.746	-11.77	27.49	15.72	43.50	-27.78	Peak
5	197.806	-10.73	27.28	16.55	43.50	-26.95	Peak
6	626.450	-2.43	28.32	25.89	46.00	-20.11	Peak



Site : Chamber

Condition : 3m VERTICAL

Project No. : 2504S32884E-RFTester: Roger Ling

Test Mode : 2.4G WIFI Transmitting

Receiver Setting: RBW:100kHz VBW:300kHz

	Freq Factor		Read Level	Limit Level	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	34.037	-12.38	28.13	15.75	40.00	-24.25 Peak
2	42.432	-10.71	29.12	18.41	40.00	-21.59 Peak
3	107.275	-11.68	27.11	15.43	43.50	-28.07 Peak
4	188.992	-11.11	27.65	16.54	43.50	-26.96 Peak
5	370.865	-7.58	28.67	21.09	46.00	-24.91 Peak
6	672.845	-1.82	28.81	26.99	46.00	-19.01 Peak

1GHz-25GHz

Environmental Conditions


Temperature:	23.6 to 24.9 °C
Relative Humidity:	53 to 56 %
ATM Pressure:	100.2 kPa
Test Engineer:	Roger Ling
Test Date:	2025-05-10 to 2025-05-19
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: For 1GHz-4GHz, the fundamental test with filter switch unit.

Note 2: For 18GHz-25GHz, the maximum output power mode and channel: 2.4G WiFi 802.11ax20 Middle channel was tested.


2.4G WIFI 802.11b Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1284.250	-13.78	63.93	50.15	74.00	-23.85 Peak


2.4G WIFI 802.11b Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1236.250	-14.02	64.85	50.83	74.00	-23.17 Peak

2.4G WIFI 802.11b Low Channel_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester: Roger Ling

Note : 2.4G WIFI 802.11b Low Channel 2412MHz 4GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	43.19	36.58	54.00	-17.42	Average
2	4824.000	-6.61	51.73	45.12	74.00	-28.88	peak
3	7236.000	-1.31	53.78	52.47	74.00	-21.53	peak
4	9647.250	1.63	43.34	44.97	54.00	-9.03	Average
5	9647.250	1.63	50.99	52.62	74.00	-21.38	Peak
6	14533.250	8.77	38.96	47.73	54.00	-6.27	Average
7	14533.250	8.77	51.71	60.48	74.00	-13.52	Peak


2.4G WIFI 802.11b Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	41.80	35.19	54.00	-18.81 Average
2	4824.000	-6.61	51.23	44.62	74.00	-29.38 peak
3	7236.000	-1.31	52.02	50.71	74.00	-23.29 peak
4	9647.250	1.63	42.95	44.58	54.00	-9.42 Average
5	9647.250	1.63	50.95	52.58	74.00	-21.42 Peak
6	14619.000	8.27	39.00	47.27	54.00	-6.73 Average
7	14619.000	8.27	51.87	60.14	74.00	-13.86 Peak


2.4G WIFI 802.11b Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	57.68	47.44	74.00	-26.56	Peak


2.4G WIFI 802.11b Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.24	60.57	50.33	74.00	-23.67 peak


2.4G WIFI 802.11b Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2494.000	-10.23	63.00	52.77	74.00	-21.23 Peak


2.4G WIFI 802.11b Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1271.875	-13.81	64.82	51.01	74.00	-22.99 Peak


2.4G WIFI 802.11b Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Mid Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	48.77	42.14	54.00	-11.86 Average
2	4874.000	-6.63	51.78	45.15	74.00	-28.85 peak
3	7311.000	-1.21	51.85	50.64	74.00	-23.36 peak
4	14769.500	7.90	39.73	47.63	54.00	-6.37 Average
5	14769.500	7.90	52.01	59.91	74.00	-14.09 Peak


2.4G WIFI 802.11b Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b Mid Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 4874.000	-6.63	46.15	39.52	54.00	-14.48	Average
2 4874.000	-6.63	52.59	45.96	74.00	-28.04	peak
3 7311.000	-1.21	51.52	50.31	74.00	-23.69	peak
4 14545.500	8.97	38.86	47.83	54.00	-6.17	Average
5 14545.500	8.97	51.29	60.26	74.00	-13.74	Peak


2.4G WIFI 802.11b High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1272.250	-13.81	64.10	50.29	74.00	-23.71 Peak


2.4G WIFI 802.11b High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1224.250	-14.16	64.98	50.82	74.00	-23.18 Peak

2.4G WIFI 802.11b High Channel_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester: Roger Ling

Note : 2.4G WIFI 802.11b High Channel 2462MHz 4GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	47.54	40.94	54.00	-13.06	Average
2	4924.000	-6.60	53.98	47.38	74.00	-26.62	peak
3	7386.000	-1.38	51.88	50.50	74.00	-23.50	peak
4	14708.250	8.07	39.51	47.58	54.00	-6.42	Average
5	14708.250	8.07	52.51	60.58	74.00	-13.42	Peak


2.4G WIFI 802.11b High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b High Channel 2462MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	46.19	39.59	54.00	-14.41 Average
2	4924.000	-6.60	52.16	45.56	74.00	-28.44 peak
3	7386.000	-1.38	52.27	50.89	74.00	-23.11 peak
4	14657.500	8.50	39.26	47.76	54.00	-6.24 Average
5	14657.500	8.50	52.08	60.58	74.00	-13.42 Peak


2.4G WIFI 802.11b High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	55.16	44.94	54.00	-9.06 Average
2	2483.500	-10.22	61.28	51.06	74.00	-22.94 Peak


2.4G WIFI 802.11b High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11b High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500 -10.22	49.80	39.58	54.00	-14.42	Average
2	2483.500 -10.22	58.17	47.95	74.00	-26.05	Peak


2.4G WIFI 802.11g Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1284.250	-13.78	63.78	50.00	74.00	-24.00 Peak

2.4G WIFI 802.11g Low Channel_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester:Roger Ling

Note : 2.4G WIFI 802.11g Low Channel 2412MHz 1GHz-4GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1260.250	-13.84	64.75	50.91	74.00	-23.09 Peak


2.4G WIFI 802.11g Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	50.11	43.50	74.00	-30.50 peak
2	7236.000	-1.31	51.99	50.68	74.00	-23.32 peak
3	14547.250	9.00	38.79	47.79	54.00	-6.21 Average
4	14547.250	9.00	51.47	60.47	74.00	-13.53 Peak


2.4G WIFI 802.11g Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	50.38	43.77	74.00	-30.23 peak
2	7236.000	-1.31	52.75	51.44	74.00	-22.56 peak
3	14769.500	7.90	39.90	47.80	54.00	-6.20 Average
4	14769.500	7.90	52.37	60.27	74.00	-13.73 Peak


2.4G WIFI 802.11g Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	60.96	50.72	74.00	-23.28	peak


2.4G WIFI 802.11g Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.24	60.37	50.13	74.00	-23.87 peak


2.4G WIFI 802.11g Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1283.875	-13.78	64.22	50.44	74.00	-23.56 Peak


2.4G WIFI 802.11g Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1271.875	-13.81	64.09	50.28	74.00	-23.72 Peak

2.4G WIFI 802.11g Middle Channel_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester: Roger Ling

Note : 2.4G WIFI 802.11g Middle Channel 2437MHz 4GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	49.90	43.27	74.00	-30.73	peak
2	7311.000	-1.21	52.70	51.49	74.00	-22.51	peak
3	14538.500	8.87	38.79	47.66	54.00	-6.34	Average
4	14538.500	8.87	52.18	61.05	74.00	-12.95	Peak

2.4G WIFI 802.11g Middle Channel_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester: Roger Ling

Note : 2.4G WIFI 802.11g Middle Channel 2437MHz 4GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	49.64	43.01	74.00	-30.99	peak
2	7311.000	-1.21	51.74	50.53	74.00	-23.47	peak
3	17195.000	6.78	39.89	46.67	54.00	-7.33	Average
4	17195.000	6.78	53.31	60.09	74.00	-13.91	Peak


2.4G WIFI 802.11g High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1271.875	-13.81	64.04	50.23	74.00	-23.77 Peak


2.4G WIFI 802.11g High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1260.250	-13.84	65.07	51.23	74.00	-22.77 Peak


2.4G WIFI 802.11g High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g High Channel 2462MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	48.09	41.49	74.00	-32.51 peak
2	7386.000	-1.38	50.97	49.59	74.00	-24.41 peak
3	14743.250	7.97	39.77	47.74	54.00	-6.26 Average
4	14743.250	7.97	51.60	59.57	74.00	-14.43 Peak


2.4G WIFI 802.11g High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g High Channel 2462MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	49.19	42.59	74.00	-31.41 peak
2	7386.000	-1.38	50.89	49.51	74.00	-24.49 peak
3	14753.750	7.95	39.72	47.67	54.00	-6.33 Average
4	14753.750	7.95	51.68	59.63	74.00	-14.37 Peak


2.4G WIFI 802.11g High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	54.10	43.88	54.00	-10.12 average
2	2483.500	-10.22	69.02	58.80	74.00	-15.20 peak


2.4G WIFI 802.11g High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11g High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	50.72	40.50	54.00	-13.50 average
2	2483.500	-10.22	63.38	53.16	74.00	-20.84 peak


2.4G WIFI 802.11n20 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2541.250	-10.16	61.90	51.74	74.00	-22.26 Peak


2.4G WIFI 802.11n20 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1223.875	-14.16	64.91	50.75	74.00	-23.25 Peak


2.4G WIFI 802.11n20 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	48.89	42.28	74.00	-31.72 peak
2	7236.000	-1.31	51.59	50.28	74.00	-23.72 peak
3	14592.750	8.22	39.40	47.62	54.00	-6.38 Average
4	14592.750	8.22	52.05	60.27	74.00	-13.73 Peak


2.4G WIFI 802.11n20 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	49.61	43.00	74.00	-31.00 peak
2	7236.000	-1.31	52.04	50.73	74.00	-23.27 peak
3	14400.250	8.45	39.11	47.56	54.00	-6.44 Average
4	14400.250	8.45	51.15	59.60	74.00	-14.40 Peak


2.4G WIFI 802.11n20 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	60.59	50.35	74.00	-23.65	peak


2.4G WIFI 802.11n20 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	60.61	50.37	74.00	-23.63	peak


2.4G WIFI 802.11n20 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2590.375	-9.92	60.42	50.50	74.00	-23.50 Peak


2.4G WIFI 802.11n20 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1272.250	-13.81	64.71	50.90	74.00	-23.10 Peak


2.4G WIFI 802.11n20 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Middle Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	49.77	43.14	74.00	-30.86 peak
2	7311.000	-1.21	50.93	49.72	74.00	-24.28 peak
3	14440.500	8.47	39.10	47.57	54.00	-6.43 Average
4	14440.500	8.47	51.25	59.72	74.00	-14.28 Peak


2.4G WIFI 802.11n20 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 Middle Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	48.91	42.28	74.00	-31.72 peak
2	7311.000	-1.21	51.47	50.26	74.00	-23.74 peak
3	14753.750	7.95	39.92	47.87	54.00	-6.13 Average
4	14753.750	7.95	51.91	59.86	74.00	-14.14 Peak


2.4G WIFI 802.11n20 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2545.000	-10.15	42.19	32.04	54.00	-21.96 Average
2	2545.000	-10.15	64.65	54.50	74.00	-19.50 Peak


2.4G WIFI 802.11n20 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1259.875	-13.84	65.06	51.22	74.00	-22.78 Peak


2.4G WIFI 802.11n20 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 High Channel 2462MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	49.26	42.66	74.00	-31.34 peak
2	7386.000	-1.38	50.65	49.27	74.00	-24.73 peak
3	14545.500	8.97	38.56	47.53	54.00	-6.47 Average
4	14545.500	8.97	50.73	59.70	74.00	-14.30 Peak


2.4G WIFI 802.11n20 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 High Channel 2462MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	49.13	42.53	74.00	-31.47 peak
2	7386.000	-1.38	51.37	49.99	74.00	-24.01 peak
3	14773.000	7.89	39.79	47.68	54.00	-6.32 Average
4	14773.000	7.89	52.74	60.63	74.00	-13.37 Peak


2.4G WIFI 802.11n20 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	51.87	41.65	54.00	-12.35 average
2	2483.500	-10.22	66.89	56.67	74.00	-17.33 peak


2.4G WIFI 802.11n20 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n20 High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	49.31	39.09	54.00	-14.91 average
2	2483.500	-10.22	61.50	51.28	74.00	-22.72 peak


2.4G WIFI 802.11n40 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1260.250	-13.84	63.68	49.84	74.00	-24.16 Peak


2.4G WIFI 802.11n40 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1271.875	-13.81	64.77	50.96	74.00	-23.04 Peak


2.4G WIFI 802.11n40 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-6.62	49.91	43.29	74.00	-30.71 peak
2	7266.000	-1.26	52.22	50.96	74.00	-23.04 peak
3	14538.500	8.87	39.02	47.89	54.00	-6.11 Average
4	14538.500	8.87	51.62	60.49	74.00	-13.51 Peak


2.4G WIFI 802.11n40 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4844.000	-6.62	48.87	42.25	74.00	-31.75 peak
2	7266.000	-1.26	51.31	50.05	74.00	-23.95 peak
3	14486.000	8.29	39.41	47.70	54.00	-6.30 Average
4	14486.000	8.29	52.61	60.90	74.00	-13.10 Peak


2.4G WIFI 802.11n40 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	60.35	50.11	74.00	-23.89	peak


2.4G WIFI 802.11n40 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Low Channel 2422MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	60.02	49.78	74.00	-24.22	peak


2.4G WIFI 802.11n40 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2564.500	-10.06	60.28	50.22	74.00	-23.78 Peak


2.4G WIFI 802.11n40 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2492.875	-10.23	62.15	51.92	74.00	-22.08 Peak


2.4G WIFI 802.11n40 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Middle Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	50.65	44.02	74.00	-29.98 peak
2	7311.000	-1.21	51.26	50.05	74.00	-23.95 peak
3	14554.250	8.97	38.84	47.81	54.00	-6.19 Average
4	14554.250	8.97	51.92	60.89	74.00	-13.11 Peak


2.4G WIFI 802.11n40 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 Middle Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	50.47	43.84	74.00	-30.16 peak
2	7311.000	-1.21	51.97	50.76	74.00	-23.24 peak
3	14354.750	8.77	39.08	47.85	54.00	-6.15 Average
4	14354.750	8.77	51.17	59.94	74.00	-14.06 Peak


2.4G WFT 802.11n40 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WFI 802.11n40 High Channel 2452MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2518.750	-10.20	42.84	32.64	54.00	-21.36 Average
2	2518.750	-10.20	63.58	53.38	74.00	-20.62 Peak


2.4G WIFI 802.11n40 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 High Channel 2452MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1259.875	-13.84	64.94	51.10	74.00	-22.90 Peak


2.4G WIFI 802.11n40 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 High Channel 2452MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4904.000	-6.63	50.28	43.65	74.00	-30.35 peak
2	7356.000	-1.31	51.66	50.35	74.00	-23.65 peak
3	9808.250	1.86	43.63	45.49	54.00	-8.51 Average
4	9808.250	1.86	49.45	51.31	74.00	-22.69 Peak
5	14466.750	8.39	39.36	47.75	54.00	-6.25 Average
6	14466.750	8.39	51.37	59.76	74.00	-14.24 Peak

2.4G WIFI 802.11n40 High Channel_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester: Roger Ling

Note : 2.4G WIFI 802.11n40 High Channel 2452MHz 4GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4904.000	-6.63	48.94	42.31	74.00	-31.69	peak
2	7356.000	-1.31	50.95	49.64	74.00	-24.36	peak
3	14668.000	8.40	39.31	47.71	54.00	-6.29	Average
4	14668.000	8.40	51.59	59.99	74.00	-14.01	Peak


2.4G WIFI 802.11n40 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 High Channel 2452MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	54.98	44.76	54.00	-9.24 average
2	2483.500	-10.22	64.56	54.34	74.00	-19.66 peak


2.4G WIFI 802.11n40 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11n40 High Channel 2452MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	55.21	44.99	54.00	-9.01 average
2	2483.500	-10.22	62.99	52.77	74.00	-21.23 peak


2.4G WIFI 802.11ax20 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1272.250	-13.81	63.95	50.14	74.00	-23.86 Peak


2.4G WIFI 802.11ax20 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level		Limit	Over	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1260.250	-13.84	64.70	50.86	74.00	-23.14 Peak


2.4G WIFI 802.11ax20 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	48.48	41.87	74.00	-32.13 peak
2	7236.000	-1.31	51.74	50.43	74.00	-23.57 peak
3	14598.000	8.12	39.44	47.56	54.00	-6.44 Average
4	14598.000	8.12	52.75	60.87	74.00	-13.13 Peak


2.4G WIFI 802.11ax20 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4824.000	-6.61	48.86	42.25	74.00	-31.75 peak
2	7236.000	-1.31	51.09	49.78	74.00	-24.22 peak
3	14426.500	8.46	39.25	47.71	54.00	-6.29 Average
4	14426.500	8.46	51.52	59.98	74.00	-14.02 Peak


2.4G WIFI 802.11ax20 Low Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 2390.000	-10.24	61.00	50.76	74.00	-23.24	peak


2.4G WIFI 802.11ax20 Low Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Low Channel 2412MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	-10.24	60.72	50.48	74.00	-23.52 peak


2.4G WIFI 802.11ax20 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2526.625	-10.18	60.99	50.81	74.00	-23.19 Peak


2.4G WIFI 802.11ax20 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1260.250	-13.84	65.07	51.23	74.00	-22.77 Peak


2.40 WIFI 802.11ax20 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	50.23	43.60	74.00	-30.40 peak
2	7311.000	-1.21	50.93	49.72	74.00	-24.28 peak
3	14556.000	8.94	38.48	47.42	54.00	-6.58 Average
4	14556.000	8.94	52.12	61.06	74.00	-12.94 Peak


2.40 WIFI 802.11ax20 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4874.000	-6.63	49.36	42.73	74.00	-31.27 peak
2	7311.000	-1.21	51.76	50.55	74.00	-23.45 peak
3	14984.750	6.64	40.68	47.32	54.00	-6.68 Average
4	14984.750	6.64	53.62	60.26	74.00	-13.74 Peak


2.4G WIFI 802.11ax20 Middle Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 18GHz-25GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 18843.500	-9.29	56.49	47.20	74.00	-26.80	Peak


2.4G WIFI 802.11ax20 Middle Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 Middle Channel 2437MHz 18GHz-25GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 18370.130	-9.56	56.61	47.05	74.00	-26.95	Peak


2.4G WIFI 802.11ax20 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2486.875	-10.24	61.44	51.20	74.00	-22.80 Peak


2.4G WIFI 802.11ax20 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz 1GHz-4GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1260.250	-13.84	64.43	50.59	74.00	-23.41 Peak


2.4G WIFI 802.11ax20 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz 4GHz-18GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	48.79	42.19	74.00	-31.81 peak
2	7386.000	-1.38	51.56	50.18	74.00	-23.82 peak
3	17732.250	7.67	39.66	47.33	54.00	-6.67 Average
4	17732.250	7.67	52.63	60.30	74.00	-13.70 Peak

2.4G WIFI 802.11ax20 High Channel_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2504S32884E-RF


Test Mode : Transmitting Tester: Roger Ling

Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz 4GHz-18GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4924.000	-6.60	50.00	43.40	74.00	-30.60	peak
2	7386.000	-1.38	51.40	50.02	74.00	-23.98	peak
3	16733.000	7.49	40.37	47.86	54.00	-6.14	Average
4	16733.000	7.49	52.68	60.17	74.00	-13.83	Peak


2.4G WIFI 802.11ax20 High Channel_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	54.02	43.80	54.00	-10.20 average
2	2483.500	-10.22	68.08	57.86	74.00	-16.14 peak

2.4G WIFI 802.11ax20 High Channel_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2504S32884E-RF
Test Mode : Transmitting Tester:Roger Ling
Note : 2.4G WIFI 802.11ax20 High Channel 2462MHz Bandedge
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.22	50.34	40.12	54.00	-13.88 average
2	2483.500	-10.22	63.68	53.46	74.00	-20.54 peak

FCC §15.247(a) (2)-6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard


Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020, section 11.8 and section 6.9

The steps for the first option are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.



Test Data

Please refer to the Appendix.

FCC §15.247(b) (3)-MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.


Test Procedure

According to ANSI C63.10-2020, section 11.9.1.2

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

According to ANSI C63.10-2020, section 11.9.2.3

- Measurement using a power meter (PM)(Method AVGPM)
 - a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent, if all of the conditions listed below are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
 - b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.
 - c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
 - d) Correct the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.



Test Data

Please refer to the Appendix.

FCC §15.247(d)-100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020, section 11.11

a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.

NOTE—the number of points can also be increased for large spans to retain frequency resolution

b) Set the RBW = 100 kHz.

c) Set the VBW $\geq [3 \times \text{RBW}]$.

d) Detector = peak.


e) Sweep time = No faster than coupled (auto) time.

f) Trace mode = max-hold.

g) Allow trace to fully stabilize.

h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



Test Data

Please refer to the Appendix.

FCC §15.247(e)-POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2020, section 11.10.2

- Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span > 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

According to ANSI C63.10-2020, section 11.10.3

- Method AVGPSSD-1: (for duty cycle $\geq 98\%$)

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to help ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):


- Set instrument center frequency to DTS channel center frequency.
- Set span to > 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = power averaging (rms) or sample detector (when rms not available).
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- Sweep time = auto couple.
- Employ trace averaging (rms) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

According to ANSI C63.10-2020, section 11.10.5

- Method AVGPSD-2: (for duty cycle < 98% and constant duty cycle)

The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e., $D < 98\%$), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is constant (i.e., duty cycle variations are less than $\pm 2\%$):

- Measure the duty cycle (D) of the transmitter output signal as described in 11.6.
- Set instrument center frequency to DTS channel center frequency.
- Set span to > 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = power averaging (rms) or sample detector (when rms not available).
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- Sweep time = auto couple.
- Do not use sweep triggering; allow sweep to "free run."
- Employ trace averaging (rms) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
- If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



Test Data

Please refer to the Appendix.

APPENDIX (RF TEST RESULTS)

6dB Emission Bandwidth

Test Information:

Sample No.:	31OM-1	Test Date:	2025/05/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11b	2412	9.289	≥0.5	Pass
	2437	9.249	≥0.5	Pass
	2462	9.249	≥0.5	Pass
802.11g	2412	16.336	≥0.5	Pass
	2437	16.376	≥0.5	Pass
	2462	16.056	≥0.5	Pass
802.11n20	2412	17.337	≥0.5	Pass
	2437	17.578	≥0.5	Pass
	2462	15.295	≥0.5	Pass
802.11n40	2422	36.116	≥0.5	Pass
	2437	36.196	≥0.5	Pass
	2452	36.276	≥0.5	Pass
802.11ax20_RU_Full	2412	19.019	≥0.5	Pass
	2437	19.019	≥0.5	Pass
	2462	19.019	≥0.5	Pass

802.11b_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:21:34

802.11b_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:23:39

802.11b_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:24:47

802.11g_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:26:07

802.11g_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:27:35

802.11g_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:29:01

802.11n20_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:30:40

802.11n20_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:32:15

802.11n20_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:33:46

802.11n40_2422MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:35:12

802.11n40_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:37:19

802.11n40_2452MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:39:18

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:41:46

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:43:24

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:45:06

99% Occupied Bandwidth

Test Information:

Sample No.:	31OM-1	Test Date:	2025/05/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	/


Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Test Frequency (MHz)	99% OBW (MHz)
802.11b	2412	13.040
	2437	13.040
	2462	13
802.11g	2412	16.480
	2437	16.480
	2462	16.480
802.11n20	2412	17.600
	2437	17.600
	2462	17.600
802.11n40	2422	36.320
	2437	36.320
	2452	36.240
802.11ax20_RU_Full	2412	19
	2437	18.960
	2462	19

802.11b_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:16:40

802.11b_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:16:58

802.11b_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:17:10

802.11g_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:17:27

802.11g_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:17:40

802.11g_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:17:57


802.11n20_2412MHz




802.11n20_2437MHz




802.11n20_2462MHz




802.11n40_2422MHz




802.11n40_2437MHz



802.11n40_2452MHz




802.11ax20_2412MHz_RU_Full




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:20:09

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:20:27

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:20:44

Maximum Conducted Output Power

Test Information:

Sample No.:	31OM-1	Test Date:	2025/05/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Data:

Mode	Test Frequency (MHz)	Peak Output Power(dBm)	Average Output Power(dBm)	Limit (dBm)	Verdict
802.11b	2412	18.13	15.17	30	Pass
	2437	18.60	15.66	30	Pass
	2462	18.55	15.45	30	Pass
802.11g	2412	22.76	13.83	30	Pass
	2437	23.22	14.31	30	Pass
	2462	22.88	14.22	30	Pass
802.11n20	2412	21.38	12.55	30	Pass
	2437	21.63	12.89	30	Pass
	2462	21.59	12.65	30	Pass
802.11n40	2422	21.66	12.02	30	Pass
	2437	21.80	12.26	30	Pass
	2452	22.13	12.52	30	Pass
802.11ax20_RU_Full	2412	22.64	12.45	30	Pass
	2437	23.62	12.76	30	Pass
	2462	23.38	13.11	30	Pass

Power Spectral Density

Test Information:

Sample No.:	31OM-1	Test Date:	2025/05/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	2412	-9.38	8	Pass
	2437	-9.12	8	Pass
	2462	-9.25	8	Pass
802.11g	2412	-13.38	8	Pass
	2437	-10.31	8	Pass
	2462	-13.08	8	Pass
802.11n20	2412	-15.11	8	Pass
	2437	-14.77	8	Pass
	2462	-14.82	8	Pass
802.11n40	2422	-18.10	8	Pass
	2437	-17.90	8	Pass
	2452	-17.66	8	Pass
802.11ax20_RU_Full	2412	-14.65	8	Pass
	2437	-14.30	8	Pass
	2462	-14.44	8	Pass

802.11b_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:22:35

802.11b_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:24:12

802.11b_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:25:31

802.11g_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:27:08

802.11g_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:28:27

802.11g_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:30:02

802.11n20_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:31:43

802.11n20_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:33:10

802.11n20_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:49:41

802.11n40_2422MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:37:04

802.11n40_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:39:02

802.11n40_2452MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:41:11

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:42:55

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:44:36

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:46:16

100 kHz Bandwidth of Frequency Band Edge

Test Information:

Sample No.:	31OM-1	Test Date:	2025/05/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Data:


Mode	Test Frequency (MHz)	Result (dB)	Limit (dB)	Verdict
802.11b	2412	48.16	20	Pass
	2462	50.09	20	Pass
802.11g	2412	37.24	20	Pass
	2462	42.89	20	Pass
802.11n20	2412	35.83	20	Pass
	2462	44.62	20	Pass
802.11n40	2422	34.83	20	Pass
	2452	40.76	20	Pass
802.11ax20_RU_Full	2412	31.16	20	Pass
	2462	42.97	20	Pass

802.11b_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:22:07

802.11b_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:25:03

802.11g_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:26:22

802.11g_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:29:16

802.11n20_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:30:55

802.11n20_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:34:01

802.11n40_2422MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:35:27

802.11n40_2452MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:39:33

802.11ax20_2412MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:42:02

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:45:22

Duty Cycle

Test Information:

Sample No.:	31OM-1	Test Date:	2025/05/07
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.6	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Data:

Mode	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	2412	0.585	1.150	50.87	2.94	1709	2
	2437	0.585	1.150	50.87	2.94	1709	2
	2462	0.585	1.150	50.87	2.94	1709	2
802.11g	2412	0.204	0.373	54.69	2.62	4902	5
	2437	0.204	0.373	54.69	2.62	4902	5
	2462	0.204	0.373	54.69	2.62	4902	5
802.11n20	2412	0.200	0.369	54.20	2.66	5000	5
	2437	0.200	0.370	54.05	2.67	5000	5
	2462	0.200	0.370	54.05	2.67	5000	5
802.11n40	2422	0.200	0.370	54.05	2.67	5000	5
	2437	0.200	0.370	54.05	2.67	5000	5
	2452	0.200	0.370	54.05	2.67	5000	5
802.11ax20_RU_Full	2412	0.260	0.429	60.61	2.17	3846	5
	2437	0.260	0.429	60.61	2.17	3846	5
	2462	0.260	0.429	60.61	2.17	3846	5


Duty Cycle = Ton/(Ton+Toff)*100%

802.11b_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:09:43

802.11b_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:10:30

802.11b_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:10:50

802.11g_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:11:10

802.11g_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:11:25

802.11g_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:12:05

802.11n20_2412MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:12:41

802.11n20_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:12:55

802.11n20_2462MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:13:12

802.11n40_2422MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:13:29

802.11n40_2437MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:13:46

802.11n40_2452MHz




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:14:03

802.11ax20_2412MHz_RU_Full




ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:14:43

802.11ax20_2437MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:15:24

802.11ax20_2462MHz_RU_Full



ProjectNo.:2504S32884E-RF Tester:Cayde Hou
Date: 7.MAY.2025 10:15:39

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the Attachment: 2504S32884E-RF EUT EXTERNAL PHOTOGRAPHS and 2504S32884E-RF EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the Attachment: 2504S32884E-RF-00B TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******