



**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**CERTIFICATION TEST REPORT**

*For*

**Headphones**

**MODEL NUMBER: YH-E700A**

**FCC ID: 2AN4C-HPE700A**

**IC: 10276A-HPE700A**

**REPORT NUMBER: 4789430238-6**

**ISSUE DATE: April 09, 2020**

*Prepared for*

**Shenzhen Grandsun Electronics Co.,Ltd.  
Gaoqiao Industry Zone,Pingdi Town,Longgang District,Shenzhen,China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road,  
Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China**

**Tel: +86 769-22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	04/09/2020	Initial Issue	

Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d)	Pass
3	Power Spectral Density	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d) RSS-247 Clause 5.5	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
6	Conducted Emission Test For AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
7	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 6.8	Pass
This test report is only published to and used by the applicant, and it is not for evidence purpose in China			

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>6</b>
<b>2. TEST METHODOLOGY .....</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY .....</i>	<i>8</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>9</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>9</i>
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	<i>9</i>
5.3. <i>CHANNEL LIST.....</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>10</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>10</i>
5.7. <i>WORST-CASE CONFIGURATIONS.....</i>	<i>10</i>
5.8. <i>TEST ENVIRONMENT.....</i>	<i>11</i>
5.9. <i>DESCRIPTION OF TEST SETUP.....</i>	<i>12</i>
<b>6. MEASURING INSTRUMENT AND SOFTWARE USED .....</b>	<b>13</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>15</b>
7.1. <i>ON TIME AND DUTY CYCLE .....</i>	<i>15</i>
7.2. <i>6 dB DTS BANDWIDTH AND 99% BANDWIDTH.....</i>	<i>17</i>
7.2.1. <i>GFSK(1Mbps) MODE.....</i>	<i>18</i>
7.2.2. <i>GFSK(2Mbps) MODE.....</i>	<i>22</i>
7.3. <i>PEAK CONDUCTED OUTPUT POWER.....</i>	<i>26</i>
7.3.1. <i>GFSK(1Mbps) MODE.....</i>	<i>27</i>
7.3.2. <i>GFSK(2Mbps) MODE.....</i>	<i>27</i>
7.4. <i>POWER SPECTRAL DENSITY .....</i>	<i>28</i>
7.4.1. <i>GFSK(1Mbps) MODE.....</i>	<i>29</i>
7.4.2. <i>GFSK(2Mbps) MODE.....</i>	<i>31</i>
7.5. <i>CONDUCTED BANDEdge AND SPURIOUS EMISSIONS .....</i>	<i>33</i>
7.5.1. <i>GFSK(1Mbps) MODE.....</i>	<i>34</i>
7.5.2. <i>GFSK(2Mbps) MODE.....</i>	<i>38</i>
<b>8. RADIATED TEST RESULTS .....</b>	<b>41</b>
8.1. <i>RESTRICTED BANDEdge .....</i>	<i>47</i>
8.1.1. <i>GFSK(1Mbps) MODE.....</i>	<i>47</i>
8.1.2. <i>GFSK(2Mbps) MODE.....</i>	<i>51</i>



---

8.2. SPURIOUS EMISSIONS (1~3GHz) .....	57
8.2.1. GFSK(1Mbps) MODE.....	57
8.2.2. GFSK(2Mbps) MODE.....	63
8.3. SPURIOUS EMISSIONS (3~18GHz) .....	69
8.3.1. GFSK(1Mbps) MODE.....	69
8.3.2. GFSK(2Mbps) MODE.....	75
8.4. SPURIOUS EMISSIONS 18G ~ 26GHz.....	81
8.4.1. GFSK(1Mbps) MODE.....	81
8.5. SPURIOUS EMISSIONS 30M ~ 1 GHz.....	83
8.5.1. GFSK(1Mbps) MODE.....	83
8.6. SPURIOUS EMISSIONS BELOW 30M.....	85
8.6.1. GFSK(1Mbps) MODE.....	85
<b>9. AC POWER LINE CONDUCTED EMISSIONS .....</b>	<b>88</b>
9.1. GFSK(1Mbps) MODE.....	89
<b>10. ANTENNA REQUIREMENTS.....</b>	<b>91</b>

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Shenzhen Grandsun Electronics Co.,Ltd.  
Address: Gaoqiao Industry Zone,Pingdi Town,Longgang District,Shenzhen,China

### Manufacturer Information


Company Name: Shenzhen Grandsun Electronics Co.,Ltd.  
Address: Gaoqiao Industry Zone,Pingdi Town,Longgang District,Shenzhen,China

### EUT Description

Product Name Headphones  
Model Name YH-E700A  
Brand YAMAHA  
Sample Status Normal  
Sample ID 2980798  
Sample Received date March 27, 2020  
Date Tested March 30~ April 10, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:



Kebo Zhang  
Project Engineer

Checked By:



Shawn Wen  
Laboratory Leader

Approved By:



Stephen Guo  
Laboratory Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED(Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</p> <p>Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9kHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)( include Fundamental emission)	5.78dB (1GHz-18GHz) 5.23dB (18GHz-26GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	Headphones		
Model	YH-E700A		
Product Description	Operation Frequency		2402 MHz ~ 2480 MHz
	Modulation Type		Data Rate
	GFSK	1Mbps	
	GFSK	2Mbps	
Bluetooth Version	5.0LE		
Highest operating frequency	2480MHz		
Input Rating:	5V dc max: 200mA		
Battery	DC 3.7V		

### 5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max Output Power (dBm)	EIRP (dBm)
GFSK(1Mbps)	2402-2480	0-39[40]	0.26	4.20
GFSK(2Mbps)	2402-2480	0-39[40]	0.33	4.27

### 5.3. CHANNEL LIST

Channel	Frequency (MHz)						
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460		
8	2418	19	2440	30	2462		
9	2420	20	2442	31	2464		
10	2422	21	2444	32	2468		

#### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel Number	Test Channel
GFSK(1Mbps)	CH 0, CH 19, CH 39	Low, Middle, High
GFSK(2Mbps)	CH 0, CH 19, CH 39	Low, Middle, High

#### 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		Blue Test3		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	1	default	default	default
GFSK(2Mbps)	1	default	default	default

#### 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	inverted-F antenna	3.94

Test Mode	Transmit and Receive Mode	Description
GFSK(1Mbps)	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.
GFSK(2Mbps)	1TX, 1RX	Chain 1 can be used as transmitting/receiving antenna.

#### 5.7. WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BLE	DTS	GFSK(1Mbps)	1Mbit/s
		GFSK(2Mbps)	2Mbit/s

## 5.8. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	45 ~ 70%	
Atmospheric Pressure:	101kPa	
Temperature	TN	22 ~ 28 °C
Voltage:	VL	N/A
	VN	DC 3.7V
	VH	N/A

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage.

VH= Upper Extreme Test Voltage

TN= Normal Temperature

## 5.9. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	PC	Dell	Vostro 3902	8KNDB2
2	Mobile Phone	Meizu	m2 note	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	TYPE C	/	1.0	/
2	Audio Cable	/	/	1.0	/


### ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

### TEST SETUP

The EUT can work in engineering mode with a software.

### SETUP DIAGRAM FOR TEST





## 6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions								
Instrument								
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.		
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	101961	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	101983	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Dec.05,2019	Dec.05,2020		
Software								
Used	Description		Manufacturer	Name	Version			
<input checked="" type="checkbox"/>	Test Software for Conducted disturbance		Farad	EZ-EMC	Ver. UL-3A1			
Radiated Emissions								
Instrument								
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.		
<input checked="" type="checkbox"/>	MXE EMI Receiver	KESIGHT	N9038A	MY56400 036	Dec.06,2019	Dec.06,2020		
<input checked="" type="checkbox"/>	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021		
<input checked="" type="checkbox"/>	Preamplifier	HP	8447D	2944A090 99	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	EMI Measurement Receiver	R&S	ESR26	101377	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021		
<input checked="" type="checkbox"/>	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021		
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	Loop antenna	Schwarzbeck	1519B	00008	Jan.07, 2019	Jan.07, 2022		
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.05,2019	Dec.05,2020		
<input checked="" type="checkbox"/>	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.05,2019	Dec.05,2020		
Software								
Used	Description		Manufacturer	Name	Version			
<input checked="" type="checkbox"/>	Test Software for Radiated disturbance		Farad	EZ-EMC	Ver. UL-3A1			
Other instruments								



Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Power Meter	Keysight	N1911A	MY55416024	Dec.06,2019	Dec.06,2020
<input checked="" type="checkbox"/>	Power Sensor	Keysight	U2021XA	MY5100022	Dec.06,2019	Dec.06,2020

## 7. ANTENNA PORT TEST RESULTS

### 7.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	23.3°C	Relative Humidity	57%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

#### RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
GFSK(1Mbps)	2.130	2.500	0.852	85.2	0.696	0.469	1
GFSK(2Mbps)	1.075	1.875	0.573	57.3	2.418	0.930	1

Note:


Duty Cycle Correction Factor=10log(1/x).

Where: x is Duty Cycle(Linear)

Where: T is On Time (transmit duration)

If that calculated VBW is not available on the analyzer then the next higher value should be used.

## GFSK(1Mbps) ON TIME AND DUTY CYCLE MID CH



## GFSK(2Mbps) ON TIME AND DUTY CYCLE MID CH



## 7.2. 6 dB DTS BANDWIDTH AND 99% BANDWIDTH

### LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6dB Bandwidth	$\geq 500\text{kHz}$	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	For reporting purposes only	2400-2483.5


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Bandwidth :100kHz For 99% Occupied Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$ For 99% Occupied Bandwidth : $\geq 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP



## TEST ENVIRONMENT


Temperature	26.3°C	Relative Humidity	63%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V



## RESULTS



### 7.2.1. GFSK(1Mbps) MODE


Channel	Frequency (MHz)	6dB Occupied bandwidth (MHz)	99% Occupied bandwidth (MHz)	Result
Low	2402	0.705	1.0451	PASS
Middle	2441	0.741	1.0435	PASS
High	2480	0.759	1.0409	PASS

### Test Graph














### 7.2.2. GFSK(2Mbps) MODE


Channel	Frequency (MHz)	6dB Occupied bandwidth (MHz)	99% Occupied bandwidth (MHz)	Result
Low	2402	1.254	2.0758	PASS
Middle	2441	1.323	2.0736	PASS
High	2480	1.269	2.0710	PASS

#### Test Graph









### 7.3. PEAK CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Output Power	1 watt or 30dBm	2400-2483.5


#### TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.

Measure peak power each channel.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	26.3°C	Relative Humidity	63%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

**RESULTS****7.3.1. GFSK(1Mbps) MODE**

Test Channel	Maximum Conducted Output Power(PK)	EIRP	LIMIT
	(dBm)	(dBm)	dBm
Low	0.26	4.20	30
Middle	0.11	4.05	30
High	0.00	3.94	30

**7.3.2. GFSK(2Mbps) MODE**

Test Channel	Maximum Conducted Output Power(PK)	EIRP	LIMIT
	(dBm)	(dBm)	dBm
Low	0.33	4.27	30
Middle	0.19	4.13	30
High	0.02	3.96	30

Note: EIRP=Maximum Conducted Output Power(PK) + Antenna Gain

## 7.4. POWER SPECTRAL DENSITY

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST SETUP






**TEST ENVIRONMENT**

Temperature	26.3°C	Relative Humidity	63%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

**RESULTS****7.4.1. GFSK(1Mbps) MODE**


Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-15.77	8	PASS
Middle	-15.84	8	PASS
High	-16.09	8	PASS







## 7.4.2. GFSK(2Mbps) MODE

Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-16.95	8	PASS
Middle	-16.97	8	PASS
High	-17.19	8	PASS





## 7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100kHz
VBW	$\geq 3 \times$ RBW
measurement points	$\geq$ span/RBW
Trace	Max hold
Sweep time	Auto couple.


Use the peak marker function to determine the maximum amplitude level.

TEST SETUPTEST ENVIRONMENT


Temperature	26.3°C	Relative Humidity	63%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

RESULTS**7.5.1. GFSK(1Mbps) MODE****LOW CH BANDEDAGE**


## LOW CH SPURIOUS EMISSIONS 30M-26G




## MID CH REFERENCE LEVER




## MID CH SPURIOUS EMISSIONS 30M-26G



## HIGH CH BANDEDAGE




## HIGH CH SPURIOUS EMISSIONS 30M-26G




## 7.5.2. GFSK(2Mbps) MODE

### LOW CH BANDEDAGE




### LOW CH SPURIOUS EMISSIONS 30M-26G




## MID CH REFERENCE LEVER




## MID CH SPURIOUS EMISSIONS 30M-26G



## HIGH CH BANDEDAGE



## HIGH CH SPURIOUS EMISSIONS 30M-26G



## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9kHz-1GHz)

Emissions radiated outside of the specified frequency bands above 30MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) ( $\mu$ A/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch FORM No.: 10-SL-F0087  
This report shall not be reproduced except in full, without the written approval of UL Verification Services  
(Guangzhou) Co., Ltd, Song Shan Lake Branch.

Table 7 – Restricted frequency bands<sup>Note 1</sup>

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.8	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

### FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9kHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1G and above 30MHz




The setting of the spectrum analyser

RBW	120kHz
VBW	300kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G




The setting of the spectrum analyser

RBW	1MHz
VBW	PEAK: 3MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

Note 3: The EUT does not support simultaneous transmission.

#### TEST ENVIRONMENT

Temperature	22.1°C	Relative Humidity	63%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V


#### RESULTS

## 8.1. RESTRICTED BANDEDGE

### 8.1.1. GFSK(1Mbps) MODE


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

##### PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2380.840	16.50	32.92	49.42	74.00	-24.58	peak
2	2390.000	14.92	32.94	47.86	74.00	-26.14	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)PEAK


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2383.025	16.20	32.92	49.12	74.00	-24.88	peak
2	2390.000	14.41	32.94	47.35	74.00	-26.65	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.70	33.58	51.28	74.00	-22.72	peak
2	2488.275	19.09	33.62	52.71	74.00	-21.29	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)PEAK

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	16.25	33.58	49.83	74.00	-24.17	peak
2	2483.750	18.18	33.58	51.76	74.00	-22.24	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


### 8.1.2. GFSK(2Mbps) MODE

#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL) peak




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.695	15.96	32.94	48.90	74.00	-25.10	peak
2	2390.000	14.74	32.94	47.68	74.00	-26.32	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)Peak

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2362.440	16.45	32.85	49.30	74.00	-24.70	peak
2	2390.000	14.36	32.94	47.30	74.00	-26.70	peak


Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)  
peak

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.86	33.58	60.44	74.00	-13.56	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	12.55	33.58	46.13	54.00	-7.87	AVG

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
4. For transmit duration, please refer to clause 7.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEdge (HIGH CHANNEL, VERTICAL)**  
**peak**



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.51	33.58	54.09	74.00	-19.91	peak

Note: 1. Measurement = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	8.09	33.58	41.67	54.00	-12.33	AVG


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: VBW=1/Ton where: ton is transmit duration.
4. For transmit duration, please refer to clause 7.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 8.2. SPURIOUS EMISSIONS (1~3GHz)


### 8.2.1. GFSK(1Mbps) MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1080.000	47.44	-13.53	33.91	74.00	-40.09	peak
2	1496.000	46.31	-12.22	34.09	74.00	-39.91	peak
3	1622.000	48.21	-11.29	36.92	74.00	-37.08	peak
4	1882.000	45.56	-9.95	35.61	74.00	-38.39	peak
5	2218.000	44.11	-8.58	35.53	74.00	-38.47	peak
6	2402.000	53.52	-7.85	45.67	/	/	fundamental

Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1330.000	53.85	-12.36	41.49	74.00	-32.51	peak
2	1380.000	49.40	-12.38	37.02	74.00	-36.98	peak
3	1620.000	48.72	-11.29	37.43	74.00	-36.57	peak
4	1994.000	45.25	-9.83	35.42	74.00	-38.58	peak
5	2402.000	47.31	-7.85	39.46	/	/	fundamental
6	2700.000	47.02	-7.13	39.89	74.00	-34.11	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1254.000	45.72	-12.50	33.22	74.00	-40.78	peak
2	1620.000	48.90	-11.29	37.61	74.00	-36.39	peak
3	1914.000	44.87	-9.93	34.94	74.00	-39.06	peak
4	2322.000	47.58	-8.12	39.46	74.00	-34.54	peak
5	2440.000	49.20	-7.59	41.61	/	/	fundamental
6	2780.000	43.62	-6.27	37.35	74.00	-36.65	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1332.000	51.72	-12.35	39.37	74.00	-34.63	peak
2	1622.000	48.63	-11.29	37.34	74.00	-36.66	peak
3	1994.000	45.91	-9.83	36.08	74.00	-37.92	peak
4	2132.000	47.57	-9.00	38.57	74.00	-35.43	peak
5	2326.000	48.00	-8.10	39.90	74.00	-34.10	peak
6	2700.000	46.37	-7.13	39.24	74.00	-34.76	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1324.000	46.26	-12.36	33.90	74.00	-40.10	peak
2	1620.000	48.49	-11.29	37.20	74.00	-36.80	peak
3	1994.000	46.71	-9.83	36.88	74.00	-37.12	peak
4	2480.000	60.31	-7.31	53.00	/	/	fundamental
5	2696.000	43.95	-7.15	36.80	74.00	-37.20	peak
6	2876.000	43.17	-5.66	37.51	74.00	-36.49	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1328.000	52.15	-12.36	39.79	74.00	-34.21	peak
2	1618.000	48.29	-11.31	36.98	74.00	-37.02	peak
3	1992.000	46.30	-9.83	36.47	74.00	-37.53	peak
4	2330.000	47.42	-8.10	39.32	74.00	-34.68	peak
5	2480.000	54.57	-7.31	47.26	/	/	fundamental
6	2700.000	46.73	-7.13	39.60	74.00	-34.40	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### 8.2.2. GFSK(2Mbps) MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1254.000	46.22	-12.50	33.72	74.00	-40.28	peak
2	1620.000	47.87	-11.29	36.58	74.00	-37.42	peak
3	1916.000	44.72	-9.93	34.79	74.00	-39.21	peak
4	2134.000	47.89	-8.99	38.90	74.00	-35.10	peak
5	2402.000	53.55	-7.85	45.70	/	/	fundamental
6	2780.000	43.80	-6.27	37.53	74.00	-36.47	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Peak: Peak detector.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1330.000	51.91	-12.36	39.55	74.00	-34.45	peak
2	1618.000	48.84	-11.31	37.53	74.00	-36.47	peak
3	1994.000	45.97	-9.83	36.14	74.00	-37.86	peak
4	2134.000	48.35	-8.99	39.36	74.00	-34.64	peak
5	2326.000	49.80	-8.10	41.70	74.00	-32.30	peak
6	2660.000	46.83	-7.35	39.48	74.00	-34.52	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1342.000	46.05	-12.35	33.70	74.00	-40.30	peak
2	1620.000	48.49	-11.29	37.20	74.00	-36.80	peak
3	1912.000	45.18	-9.93	35.25	74.00	-38.75	peak
4	2134.000	52.32	-8.99	43.33	74.00	-30.67	peak
5	2330.000	51.79	-8.10	43.69	74.00	-30.31	peak
6	2440.000	49.16	-7.59	41.57	/	/	fundamental

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1328.000	51.95	-12.36	39.59	74.00	-34.41	peak
2	1618.000	47.90	-11.31	36.59	74.00	-37.41	peak
3	1890.000	45.16	-9.95	35.21	74.00	-38.79	peak
4	2328.000	50.20	-8.10	42.10	74.00	-31.90	peak
5	2568.000	44.44	-7.54	36.90	74.00	-37.10	peak
6	2700.000	49.04	-7.13	41.91	74.00	-32.09	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1330.000	45.46	-12.36	33.10	74.00	-40.90	peak
2	1620.000	47.15	-11.29	35.86	74.00	-38.14	peak
3	1994.000	45.84	-9.83	36.01	74.00	-37.99	peak
4	2350.000	44.32	-8.02	36.30	74.00	-37.70	peak
5	2480.000	57.15	-7.28	49.87	/	/	fundamental
6	2782.000	44.47	-6.25	38.22	74.00	-35.78	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1326.000	52.01	-12.35	39.66	74.00	-34.34	peak
2	1620.000	49.30	-11.29	38.01	74.00	-35.99	peak
3	1996.000	45.37	-9.83	35.54	74.00	-38.46	peak
4	2480.000	54.81	-7.28	47.53	/	/	fundamental
5	2700.000	45.55	-7.13	38.42	74.00	-35.58	peak
6	2848.000	43.51	-5.80	37.71	74.00	-36.29	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### 8.3. SPURIOUS EMISSIONS (3~18GHz)

#### 8.3.1. GFSK(1Mbps) MODE


##### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	52.10	-2.89	49.21	74.00	-24.79	peak
2	5895.000	40.00	4.86	44.86	74.00	-29.14	peak
3	7200.000	46.34	5.82	52.16	74.00	-21.84	peak
4	10500.000	38.95	11.38	50.33	74.00	-23.67	peak
5	13830.000	34.26	16.84	51.10	74.00	-22.90	peak
6	17415.000	31.20	21.39	52.59	74.00	-21.41	peak

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	50.68	-2.90	47.78	74.00	-26.22	peak
2	4980.000	52.46	1.29	53.75	74.00	-20.25	peak
3	7200.000	46.40	5.82	52.22	74.00	-21.78	peak
4	7965.000	42.48	7.00	49.48	74.00	-24.52	peak
5	12986.390	39.58	14.92	54.50	74.00	-19.50	peak
6	12986.390	21.06	14.92	35.98	54.00	-18.02	AVG
7	17790.000	29.86	23.22	53.08	74.00	-20.92	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$  where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	48.70	-2.89	45.81	74.00	-28.19	peak
2	4965.000	45.31	1.21	46.52	74.00	-27.48	peak
3	7320.000	45.88	6.14	52.02	74.00	-21.98	peak
4	10245.000	39.53	10.56	50.09	74.00	-23.91	peak
5	13635.000	35.06	15.97	51.03	74.00	-22.97	peak
6	17715.000	30.23	22.56	52.79	74.00	-21.21	peak


Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	48.10	-2.89	45.21	74.00	-28.79	peak
2	4980.000	44.81	1.29	46.10	74.00	-27.90	peak
3	7320.000	45.34	6.14	51.48	74.00	-22.52	peak
4	7965.000	43.28	7.00	50.28	74.00	-23.72	peak
5	13140.000	36.28	15.15	51.43	74.00	-22.57	peak
6	17700.000	30.66	22.43	53.09	74.00	-20.91	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	49.84	-2.90	46.94	74.00	-27.06	peak
2	7440.000	45.85	6.32	52.17	74.00	-21.83	peak
3	10620.000	37.70	11.88	49.58	74.00	-24.42	peak
4	13590.000	34.81	16.00	50.81	74.00	-23.19	peak
5	14445.000	34.41	16.36	50.77	74.00	-23.23	peak
6	17715.000	30.77	22.56	53.33	74.00	-20.67	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3315.000	48.39	-4.26	44.13	74.00	-29.87	peak
2	3990.000	52.41	-2.89	49.52	74.00	-24.48	peak
3	5925.000	40.25	4.54	44.79	74.00	-29.21	peak
4	7440.000	45.53	6.32	51.85	74.00	-22.15	peak
5	14955.000	35.34	15.99	51.33	74.00	-22.67	peak
6	17760.000	29.73	22.95	52.68	74.00	-21.32	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### 8.3.2. GFSK(2Mbps) MODE

#### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	49.88	-2.89	46.99	74.00	-27.01	peak
2	4980.000	44.10	1.29	45.39	74.00	-28.61	peak
3	7200.000	46.27	5.82	52.09	74.00	-21.91	peak
4	10275.000	37.53	10.85	48.38	74.00	-25.62	peak
5	13620.000	34.93	15.99	50.92	74.00	-23.08	peak
6	17715.000	30.14	22.56	52.70	74.00	-21.30	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	50.44	-2.89	47.55	74.00	-26.45	peak
2	4980.000	44.40	1.29	45.69	74.00	-28.31	peak
3	7200.000	45.01	5.82	50.83	74.00	-23.17	peak
4	7965.000	42.23	7.00	49.23	74.00	-24.77	peak
5	13965.000	34.95	16.09	51.04	74.00	-22.96	peak
6	17700.000	30.66	22.43	53.09	74.00	-20.91	peak


Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	50.53	-2.89	47.64	74.00	-26.36	peak
2	7320.000	45.41	6.14	51.55	74.00	-22.45	peak
3	11010.000	36.76	12.63	49.39	74.00	-24.61	peak
4	12735.000	35.85	14.77	50.62	74.00	-23.38	peak
5	14205.000	34.20	16.36	50.56	74.00	-23.44	peak
6	17715.000	29.91	22.56	52.47	74.00	-21.53	peak

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3990.000	51.07	-2.89	48.18	74.00	-25.82	peak
2	4991.925	54.30	1.36	55.66	74.00	-18.34	peak
3	4991.925	27.30	1.36	28.66	54.00	-25.34	AVG
4	7320.000	44.72	6.14	50.86	74.00	-23.14	peak
5	7965.000	42.40	7.00	49.40	74.00	-24.60	peak
6	12960.000	36.80	14.92	51.72	74.00	-22.28	peak
7	17775.000	29.87	23.09	52.96	74.00	-21.04	peak


Note:

1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	52.61	-2.90	49.71	74.00	-24.29	peak
2	5865.000	41.04	4.30	45.34	74.00	-28.66	peak
3	7440.000	46.74	6.32	53.06	74.00	-20.94	peak
4	11745.000	37.11	13.05	50.16	74.00	-23.84	peak
5	13800.000	34.16	17.10	51.26	74.00	-22.74	peak
6	17760.000	29.69	22.95	52.64	74.00	-21.36	peak

Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.  
4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3975.000	48.36	-2.90	45.46	74.00	-28.54	peak
2	4995.000	46.32	1.37	47.69	74.00	-26.31	peak
3	7440.000	45.71	6.32	52.03	74.00	-21.97	peak
4	7965.000	43.42	7.00	50.42	74.00	-23.58	peak
5	12705.000	36.37	14.35	50.72	74.00	-23.28	peak
6	17805.000	29.21	23.31	52.52	74.00	-21.48	peak


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton where: ton is transmit duration.
5. For transmit duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

## 8.4. SPURIOUS EMISSIONS 18G ~ 26GHz

### 8.4.1. GFSK(1Mbps) MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18688.000	50.62	-4.72	45.90	74.00	-28.10	peak
2	19952.000	49.46	-4.36	45.10	74.00	-28.90	peak
3	21560.000	51.06	-5.77	45.29	74.00	-28.71	peak
4	22544.000	51.98	-5.79	46.19	74.00	-27.81	peak
5	23992.000	52.16	-4.03	48.13	74.00	-25.87	peak
6	25400.000	49.49	-1.57	47.92	74.00	-26.08	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

SPURIOUS EMISSIONS (LOW CHANNEL , WORST-CASE CONFIGURATION, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18808.000	52.05	-4.85	47.20	74.00	-26.80	peak
2	19968.000	51.23	-4.36	46.87	74.00	-27.13	peak
3	21136.000	51.86	-5.41	46.45	74.00	-27.55	peak
4	22784.000	52.02	-5.71	46.31	74.00	-27.69	peak
5	23992.000	51.72	-4.03	47.69	74.00	-26.31	peak
6	25704.000	49.47	-1.42	48.05	74.00	-25.95	peak


Note: 1. Peak Result = Reading Level + Correct Factor.  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Peak: Peak detector.

Note: All the test modes have been tested, only the worst data record in the report.


## 8.5. SPURIOUS EMISSIONS 30M ~ 1 GHz

### 8.5.1. GFSK(1Mbps) MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



Note: 1. Result Level = Read Level + Correct Factor.  
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (LOW CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	50.3700	51.62	-18.30	33.32	40.00	-6.68	QP
2	180.3500	41.64	-16.93	24.71	43.50	-18.79	QP
3	261.8299	43.43	-15.90	27.53	46.00	-18.47	QP
4	600.3600	40.91	-8.90	32.01	46.00	-13.99	QP
5	663.4099	39.69	-7.68	32.01	46.00	-13.99	QP
6	995.1500	38.82	-2.95	35.87	54.00	-18.13	QP

Note: 1. Result Level = Read Level + Correct Factor.  
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.


Note: All the test modes have been tested, only the worst data record in the report

## 8.6. SPURIOUS EMISSIONS BELOW 30M

### 8.6.1. GFSK(1Mbps) MODE

#### SPURIOUS EMISSIONS (LOW CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9kHz~ 150kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0126	69.93	-101.38	-31.45	45.59	-82.95	-5.91	-77.04	peak
2	0.0206	66.42	-101.35	-34.93	41.32	-86.43	-10.18	-76.25	peak
3	0.0279	64.17	-101.38	-37.21	38.69	-88.71	-12.81	-75.90	peak
4	0.0427	61.14	-101.45	-40.31	34.99	-91.81	-16.51	-75.30	peak
5	0.0589	58.31	-101.52	-43.21	32.20	-94.71	-19.30	-75.41	peak
6	0.1073	53.80	-101.77	-47.97	26.99	-99.47	-24.51	-74.96	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m-  $20\log_{10}[120\pi]$  = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.


150kHz ~ 490kHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1669	68.65	-101.66	-33.01	23.16	-84.51	-28.34	-56.17	peak
2	0.1917	66.04	-101.70	-35.66	21.95	-87.16	-29.55	-57.61	peak
3	0.2298	63.55	-101.77	-38.22	20.37	-89.72	-31.13	-58.59	peak
4	0.2782	61.29	-101.83	-40.54	18.71	-92.04	-32.79	-59.25	peak
5	0.3286	58.71	-101.88	-43.17	17.27	-94.67	-34.23	-60.44	peak
6	0.4132	56.05	-101.98	-45.93	15.28	-97.43	-36.22	-61.21	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m = dBuV/m -  $20\log_{10}[120\pi]$  = dBuV/m - 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490kHz ~ 30MHz


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.6270	59.65	-62.09	-2.44	31.66	-53.94	-19.84	-34.10	peak
2	1.3750	55.64	-62.10	-6.46	24.84	-57.96	-26.66	-31.30	peak
3	1.8205	53.95	-61.90	-7.95	29.54	-59.45	-21.96	-37.49	peak
4	5.2705	49.54	-61.45	-11.91	29.54	-63.41	-21.96	-41.45	peak
5	10.9365	49.00	-60.84	-11.84	29.54	-63.34	-21.96	-41.38	peak
6	23.4783	49.24	-60.56	-11.32	29.54	-62.82	-21.96	-40.86	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m = dBuV/m -  $20\log_{10}[120\pi]$  = dBuV/m - 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the test modes have been tested, only the worst data record in the report.


## 9. AC POWER LINE CONDUCTED EMISSIONS

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	64%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V


## 9.1. GFSK(1Mbps) MODE

### LINE N RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1587	36.28	9.60	45.88	65.53	-19.65	QP
2	0.1587	18.89	9.60	28.49	55.53	-27.04	AVG
3	0.4606	22.01	9.60	31.61	56.68	-25.07	QP
4	0.4606	10.26	9.60	19.86	46.68	-26.82	AVG
5	4.0313	28.60	9.66	38.26	56.00	-17.74	QP
6	4.0313	19.85	9.66	29.51	46.00	-16.49	AVG
7	5.9111	21.25	9.70	30.95	60.00	-29.05	QP
8	5.9111	11.98	9.70	21.68	50.00	-28.32	AVG
9	7.1017	21.75	9.71	31.46	60.00	-28.54	QP
10	7.1017	13.80	9.71	23.51	50.00	-26.49	AVG
11	8.5960	28.13	9.74	37.87	60.00	-22.13	QP
12	8.5960	21.85	9.74	31.59	50.00	-18.41	AVG

Note: 1. Result = Reading +Correct Factor.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

LINE L RESULTS (LOW CHANNEL, WORST-CASE CONFIGURATION)

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1636	35.17	9.61	44.78	65.28	-20.50	QP
2	0.1636	18.38	9.61	27.99	55.28	-27.29	AVG
3	0.4498	18.93	9.60	28.53	56.88	-28.35	QP
4	0.4498	11.68	9.60	21.28	46.88	-25.60	AVG
5	2.0285	17.63	9.62	27.25	56.00	-28.75	QP
6	2.0285	10.49	9.62	20.11	46.00	-25.89	AVG
7	4.2899	28.50	9.66	38.16	56.00	-17.84	QP
8	4.2899	17.47	9.66	27.13	46.00	-18.87	AVG
9	5.8457	22.14	9.70	31.84	60.00	-28.16	QP
10	5.8457	13.65	9.70	23.35	50.00	-26.65	AVG
11	8.6937	28.27	9.73	38.00	60.00	-22.00	QP
12	8.6937	21.80	9.73	31.53	50.00	-18.47	AVG

Note: 1. Result = Reading +Correct Factor.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

Note: All the test modes have been tested, only the worst data record in the report.

## 10. ANTENNA REQUIREMENTS

### Applicable requirements

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

**END OF REPORT**