FCC Test Report

Report No.: AGC05559250801FE01

FCC ID		2AN62-GS10B
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Two Way Radio
BRAND NAME	:	Radioddity
MODEL NAME	:	GS-10B, GS-10B PRO
APPLICANT	:	SAIN3 LLC
DATE OF ISSUE	:	Sep. 05, 2025
STANDARD(S)	:	FCC Part 15 Subpart B
REPORT VERSION	:	V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 05, 2025	Valid	Initial Release

Table of Contents

1. General Information

Applicant	SAIN3 LLC
Address	36 Berkley Drive Newark, DE 19702 United States
Manufacturer	SAIN3 LLC
Address	36 Berkley Drive Newark, DE 19702 United States
Factory	SAIN3 LLC
Address	36 Berkley Drive Newark, DE 19702 United States
Product Designation	Two Way Radio
Brand Name	Radioddity
Test Model	GS-10B
Series Model(s)	GS-10B PRO
Difference Description	Only the model name is different; everything else is the same.
Date of receipt of test item	Aug. 15, 2025
Date of Test	Aug. 15, 2025~Sep. 04, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCTR-ER-FCC-CSR-V1.0

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo Zhang (Project Engineer)	Sep. 05, 2025
Reviewed By	Jack Gui (Reviewer)	Sep. 05, 2025
Approved By	Angela Li (Authorized Officer)	Sep. 05, 2025

2. Product Information

2.1 Product Technical Description

Housing Type	Plastic and metal
Receive Frequency Range	108-136MHz/136-174MHz/220-260/350-390MHz/400-520MHz (Scanning Receiver)
Highest Operating Frequency	☒Greater than 108MHz ☐Less than 108MHz
Equipment Type	Table-Top
Hardware Version	Ver 1.0
Software Version	Ver 1.0
Power Supply	DC 7.4V 2500mAh by battery or DC 5V from adapter

I/O Port Information (☒Applicable ☐Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
Antenna Port	1	0	1
Earphone Port	1	0	1

2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During the Measurement:

☒ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Adapter	N/A	GFBA005500100WA	Input: AC100-240V 50/60, 0.15A Output: DC 5V 1A	1.0m unshielded

☒ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Battery	SAIN3 LLC	BL-10b	DC 7.4V 2500mAh	--
2	Charger	N/A	C-51	Input: DC 5V 1A Output: DC 8.4V 0.5A	0.5m unshielded
3	Back Clip	N/A	N/A	N/A	N/A
4	USB Cable	N/A	N/A	N/A	1.0m unshielded

2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 15	Radio Frequency Devices
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

2.3 Description of Test Modes

No.	Test Mode	Remark
1	Scanning mode	Worst
2	Scanning stopped/Receiving at low channel of 108 MHz to 136 MHz	--
3	Scanning stopped/Receiving at middle channel of 108 MHz to 136 MHz	--
4	Scanning stopped/Receiving at high channel of 108 MHz to 136 MHz	--
5	Scanning stopped/Receiving at low channel of 136 MHz to 174 MHz	--
6	Scanning stopped/Receiving at middle channel of 136 MHz to 174 MHz	--
7	Scanning stopped/Receiving at high channel of 136 MHz to 174 MHz	--
8	Scanning stopped/Receiving at low channel of 220 MHz to 260 MHz	--
9	Scanning stopped/Receiving at middle channel of 220 MHz to 260 MHz	--
10	Scanning stopped/Receiving at high channel of 220 MHz to 260 MHz	--
11	Scanning stopped/Receiving at low channel of 350 MHz to 390 MHz	--
12	Scanning stopped/Receiving at middle channel of 350 MHz to 390 MHz	--
13	Scanning stopped/Receiving at high channel of 350 MHz to 390 MHz	--
14	Scanning stopped/Receiving at low channel of 400 MHz to 520 MHz	--
15	Scanning stopped/Receiving at middle channel of 400 MHz to 520 MHz	--
16	Scanning stopped/Receiving at high channel of 400 MHz to 520 MHz	--

Note: Only the result of the worst case was recorded in the report.

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

3.3 Environmental Conditions

	Normal Conditions
Temperature range (℃)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission	U_c = ±2.9 dB
Uncertainty of Radiated Emission below 1GHz	U_c = ±3.9 dB
Uncertainty of Radiated Emission above 1GHz	U_c = ±4.9 dB

3.5 List of Equipment Used

● RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-ER-E086	Spectrum Analyzer	KEYSIGHT	N9020A	MY53300860	2025-05-08	2026-05-07
☒	AGC-EM-E002	Wireless Connectivity Tester	HP	8920B	US35010161	2025-05-08	2026-05-07
☒	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2024-07-24	2026-07-23
☒	AGC-EM-A007	30dB Attenuator	Weinachel	58-30-33	ML030	2025-05-31	2027-05-30
☒	--	RF Connection Cable	N/A	1#	N/A	Each time	N/A
☒	--	RF Connection Cable	N/A	2#	N/A	Each time	N/A
☒	AGC-ER-A004	Power Splitter	Agilent	11667B	N/A	2024-05-23	2025-05-22

● Radiated Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-EM-E116	Test Receiver	R&S	ESCI	100034	2025-05-08	2026-05-07
☒	AGC-EM-A139	Attenuator	East sheep	LM-XX-6-5W	N/A	2025-05-16	2027-05-15
☒	AGC-ER-E005	Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2025-05-08	2026-05-07

● AC Power Line Conducted Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-EM-A171	Attenuator	Mini-Circuits	UNAT-10A+	100034	2024-02-01	2026-01-31
☒	AGC-EM-E023	Artificial Mains Network	R&S	ESH2-Z5	DC-6GZ	2025-05-08	2026-05-07
☒	AGC-EM-E116	Test Receiver	R&S	ESCI	ESH2-Z5	2025-05-08	2026-05-07

● Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
☒	AGC-EM-S004	RE Test System	Tonscend	TS$^+$ Ver2.1(JS32-RE)	4.0.0.0
☐	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A
☒	AGC-EM-S011	RSE Test System	Tonscend	TS$^+$ Ver2.1(JS36-RSE)	4.0.0.0
☒	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71

4. Summary of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.109	Radiated Emission	Class B	Pass
2	Section 15.107	Conducted Emission	Class B	Pass
3	§15.111	Antenna Conducted Power for Receivers	/	Pass
4	§15.121(b)	Scanning receivers and frequency converters used with scanning receivers	/	Pass

5. Radiated Emission Measurements

5.1 Provisions Applicable

FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	50.00	Quasi-peak
88MHz-216MHz	43.50	53.50	Quasi-peak
216MHz-960MHz	46.00	56.00	Quasi-peak
960MHz-1GHz	54.00	64.00	Quasi-peak
Above 1GHz	54.00	60.00	Average
	74.00	80.00	Peak

5.2 Measurement Setup



Radiated Emission Measurements Test Setup for 30MHz to 1GHz



Radiated Emission Measurements Test Setup for above 1GHz

5.3 Measurement Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. The EUT received power by AC 120V/60Hz.
5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
7. The test mode(s) were scanned during the test:
8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.
14. The test data of the worst case condition (mode 1) was reported on the following Data page.

EMI Test Receiver Setup:

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

5.4 Measurement Resul

Radiated Emission 30MHz-1GHz Test Result			
Test Mode	Mode 1	Polarity:	Horizontal



Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.49	32.86	14.41	40.00	7.14	100	122	Horizontal
2	110.51	29.72	12.73	43.50	13.78	100	343	Horizontal
3	208.48	35.86	12.33	43.50	7.64	100	263	Horizontal
4	325.85	34.56	16.90	46.00	11.44	100	84	Horizontal
5	420.91	26.04	19.32	46.00	19.96	100	97	Horizontal
6	931.13	35.19	28.94	46.00	10.81	100	205	Horizontal

Radiated Emission 30MHz-1GHz Test Result			
Test Mode	Mode 1	Polarity:	Vertical



Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	34.85	34.18	14.23	40.00	5.82	100	222	Vertical
2	69.77	33.01	11.96	40.00	6.99	100	155	Vertical
3	92.08	35.30	11.03	43.50	8.20	100	160	Vertical
4	141.55	26.72	15.11	43.50	16.78	100	280	Vertical
5	306.45	25.33	16.30	46.00	20.67	100	2	Vertical
6	848.68	33.25	27.63	46.00	12.75	100	6	Vertical

RESULT: PASS

Radiated Emission Above1GHz Test Result			
Test Mode	Mode 1	Polarity:	Horizontal



Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1187.037408	32.64	-18.12	74.00	41.36	100	250	Horizontal
2	1923.184637	37.87	-14.76	74.00	36.13	100	150	Horizontal
3	2652.330466	37.49	-12.43	74.00	36.51	100	320	Horizontal
4	3349.469894	38.66	-11.40	74.00	35.34	100	70	Horizontal
5	4784.756951	39.82	-9.26	74.00	34.18	100	260	Horizontal
6	5949.989998	42.73	-5.84	74.00	31.27	100	100	Horizontal

RESULT: PASS

Radiated Emission Above1GHz Test Result			
Test Mode	Mode 1	Polarity:	Vertical



Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1190.038008	33.08	-18.12	74.00	40.92	100	340	Vertical
2	1647.129426	33.09	-16.77	74.00	40.91	100	240	Vertical
3	2450.290058	37.46	-12.75	74.00	36.54	100	330	Vertical
4	3373.474695	38.89	-11.35	74.00	35.11	100	340	Vertical
5	4327.665533	37.64	-10.05	74.00	36.36	100	330	Vertical
6	5617.923585	42.21	-7.29	74.00	31.79	100	340	Vertical

RESULT: PASS

Note:

1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin= Limit-Measurement.
2. The “Factor” value can be calculated automatically by software of measurement system.

6. Conducted Emission Measurements

6.1 Provisions Applicable

FCC CFR Title 47 Part 15 Subpart B Section 15.107:
For Class B Limits:

Frequency	Maximum RF Line Voltage	
	Q.P. (dBμV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

For Class A Limits:

Frequency	Maximum RF Line Voltage	
	Q.P. (dBμV)	Average (dBμV)
150kHz~500kHz	79	66
500kHz~30MHz	73	60

6.2 Measurement Setup



6.3 Measurement Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipment received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test data of the worst case condition (Mode 1) was reported on the following Data page.

6.4 Measurement Result

Ac Power Line Conducted Emission Test			
Test Mode	Mode 1	LISN Line	Hot Side



MEASUREMENT RESULT: "agc_fin"

2025/8/27 21:23

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.742000	29.20	9.9	56	26.8	QP	L1
1.298000	30.20	9.9	56	25.8	QP	L1
1.346000	30.80	9.9	56	25.2	QP	L1
1.582000	28.50	9.9	56	27.5	QP	L1
1.642000	28.20	9.9	56	27.8	QP	L1
1.750000	27.30	9.9	56	28.7	QP	L1

MEASUREMENT RESULT: "agc_fin2"

2025/8/27 21:23

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.346000	20.80	9.9	49	28.3	AV	L1
0.774000	23.00	9.9	46	23.0	AV	L1
1.194000	20.00	9.9	46	26.0	AV	L1
1.558000	18.70	9.9	46	27.3	AV	L1
2.126000	15.20	9.9	46	30.8	AV	L1
5.630000	7.80	10.0	50	42.2	AV	L1

RESULT: PASS

Ac Power Line Conducted Emission Test			
Test Mode	Mode 1	LISN Line	Neutral Side



MEASUREMENT RESULT: "agc_fin"

2025/8/27 21:26

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.590000	30.90	9.9	56	25.1	QP	N
1.014000	30.50	9.9	56	25.5	QP	N
1.298000	30.70	9.9	56	25.3	QP	N
1.322000	31.10	9.9	56	24.9	QP	N
1.350000	30.10	9.9	56	25.9	QP	N
1.594000	28.60	9.9	56	27.4	QP	N

MEASUREMENT RESULT: "agc_fin2"

2025/8/27 21:26

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.350000	21.00	9.9	49	28.0	AV	N
0.554000	20.00	9.9	46	26.0	AV	N
1.014000	19.60	9.9	46	26.4	AV	N
2.146000	15.20	9.9	46	30.8	AV	N
6.426000	7.70	10.0	50	42.3	AV	N
29.142000	7.30	11.2	50	42.7	AV	N

RESULT: PASS

7. Antenna Conducted Power for Receivers

7.1 Provisions Applicable

The antenna conducted power of the receiver as defined in §15.111 shall not exceed the values given in the following tables

Frequency Range	9 KHz to 2GHz
Limit	2.0 nW (-57 dBm)

7.2 Measurement Setup



7.3 Measurement Procedure

1. The receiver antenna terminal connected to a spectrum analyzer.
2. Receiver set as follow:

Frequency range	RBW (kHz)	VBW (kHz)
9 kHz ~ 150 kHz	1	3
150 kHz ~ 30 MHz	10	30
30 MHz ~ 1000 MHz	100	300
1000 MHz ~ 3000 MHz	1000	3000

3. The test data of the worst case condition (mode 1) was reported on the following Data page.

7.4 Measurement Result

Test Graphs of Antenna Conducted Power for Receivers



Test_Graph_RX_FrequencyRange_9kHz-150kHz



Test_Graph_RX_FrequencyRange_150kHz-30MHz



Test_Graph_RX_FrequencyRange_30MHz-1GHz



Test_Graph_RX_FrequencyRange_1GHz-2GHz

RESULT: PASS

8. Scanning Receivers and Frequency Converters Used with Scanning Receivers

8.1 Provisions Applicable

Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

8.2 Measurement Setup



8.3 Measurement Procedure

1) Connected the EUT as shown in the above block diagram.
2) Apply a RF signal to the receiver input port at lowest, middle and highest channel frequencies of receiver operation band.
3) Adjust the audio output level of the receiver to it's rated value with the distortion less than 10%.
4) Adjust the RF Signal Generator Output Power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB.This output level of the RF SG at each channel frequency is the sensitivity of the receiver.
5) Select the lowest or worse-case sensitivity level for all of the bands as the reference sensitivity.
6) Adjust the RF Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5) and its frequency to the frequency points in the cellular band.
7) Set the Receiver squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level.
8) Set the receiver in a scanning mode and allow it to scan through it's complete receiving range.
9) If the receiver unsquelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38dB.
10) Repeat above procedure at the frequencies 824.5, 836.0, and 848.5 MHz for the mobile band, and 869.1, 881.5, and 893.5MHz for the cellular base band.

8.4 Measurement Result

Scanning Frequency Band (MHz)	Test Frequency of Cellular Band (MHz)	Spurious Value of Cellular Frequency (dBm)	Reference Sensitivity (dBm)	Measurement Result (dB)	Limit (dB)
108-136	824.5/836.0/848.5	>-46	-107	<-61	<-38
108-136	869.1/881.5/893.5	>-46	-107	<-61	<-38
136-174	824.5/836.0/848.5	>-45	-107	<-62	<-38
136-174	869.1/881.5/893.5	>-45	-107	<-62	<-38
220-260	824.5/836.0/848.5	>-46	-107	<-61	<-38
220-260	869.1/881.5/893.5	>-46	-107	<-61	<-38
350-390	824.5/836.0/848.5	>-44	-107	<-63	<-38
350-390	869.1/881.5/893.5	>-44	-107	<-63	<-38
400-520	824.5/836.0/848.5	>-45	-107	<-62	<-38
400-520	869.1/881.5/893.5	>-45	-107	<-62	<-38

Note:

1. Measurement Result = Rejection Ratio
2. Reference Sensitivity is the recorded value when the signal-to-noise ratio is 12dB.
3. Measurement Result = Reference Sensitivity- Spurious Value.

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC05559250801AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC05559250801AP02

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

-----End of Report-----