

FCC ID: 2AN7Y-BSBA-02

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

BT:

BT:2402-2480MHz

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna

BT antenna gain: 1dBi;

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(1/10)}=1.26$

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna Gain Numeric	Evaluation result at 20cm Power density(mW/cm	Power density Limits (mW/cm ²)
				tune-up power (dBm)	(mW)			
2402	GFSK	-1.45	-1±1	0	1	1.26	0.00025	1
2441		-0.75	-1±1	0	1	1.26	0.00025	1
2480		-0.67	-1±1	0	1	1.26	0.00025	1
2402	π/4-DQPSK	-0.58	-0.6±1	0.4	1.096478	1.26	0.00027	1
2441		0.11	-0.6±1	0.4	1.096478	1.26	0.00027	1
2480		0.18	-0.6±1	0.4	1.096478	1.26	0.00027	1

Conclusion:

For the max result : $0.00027 \leq 1.0$ for Max Power Density, compliance RF exposure..

Zefan Xia

Signature:

Date: 2019-06-27

NAME AND TITLE (Please print or type): Zefan Xia&Project Supervisor

COMPANY (Please print or type): Shenzhen Times Innovation Technology Co.,Ltd / 6/F, Building 3, WINLEAD, Fada Road, Bantian Street, Longgang District, Shenzhen, China.