

FCC ID : 2AN89-SMB001

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Tune up power

Mode	Ant. A	Ant.B
80.22b	18.5±1	18.5±1
802.11g	20±1	20±1
802.11n (ht20)	20±1	20±1
802.11n (ht40)	20±1	20±1

Antenna 0: 3.0 dBi

Antenna 1: 3.0 dBi

Antenna 0

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
802.11b	2412	18.21	18.5±1	19.5	1.995	0.0354	1
	2437	17.56	18.5±1	19.5	1.995	0.0354	1
	2462	17.85	18.5±1	19.5	1.995	0.0354	1
80.11g	2412	19.85	20±1	21	1.995	0.0500	1
	2437	19.44	20±1	21	1.995	0.0500	1
	2462	20.05	20±1	21	1.995	0.0500	1
802.11n (ht20)	2412	20.22	20±1	21	1.995	0.0500	1
	2437	19.27	20±1	21	1.995	0.0500	1
	2462	19.81	20±1	21	1.995	0.0500	1
802.11n (ht40)	2422	20.16	20±1	21	1.995	0.0500	1
	2437	19.27	20±1	21	1.995	0.0500	1
	2452	19.73	20±1	21	1.995	0.0500	1

Antenna 1

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
802.11b	2412	18.54	18.5±1	19.5	1.995	0.0354	1
	2437	19.31	18.5±1	19.5	1.995	0.0354	1
	2462	18.31	18.5±1	19.5	1.995	0.0354	1
80.11g	2412	20.55	20±1	21	1.995	0.0500	1
	2437	19.65	20±1	21	1.995	0.0500	1
	2462	19.27	20±1	21	1.995	0.0500	1
802.11n (ht20)	2412	20.33	20±1	21	1.995	0.0500	1
	2437	19.52	20±1	21	1.995	0.0500	1
	2462	19.16	20±1	21	1.995	0.0500	1
802.11n (ht40)	2422	19.64	20±1	21	1.995	0.0500	1
	2437	19.16	20±1	21	1.995	0.0500	1
	2452	19.06	20±1	21	1.995	0.0500	1

802.11n HT20: Antenna 0+1

Evaluation result (mW/cm ²) Ant A	Evaluation result (mW/cm ²) Ant B	Evaluation result (mW/cm ²) Ant A+B	Power density Limits (mW/cm ²)
0.0500	0.0500	0.1000	1

802.11n HT40: Antenna 0+1

Evaluation result (mW/cm ²) Ant A	Evaluation result (mW/cm ²) Ant B	Evaluation result (mW/cm ²) Ant A+B	Power density Limits (mW/cm ²)
0.0500	0.0500	0.1000	1