



## FCC SAR TEST REPORT

**Applicant:** Quanzhou Feijie Electron Co., Ltd

**Address:** No.6, Zi Hua Road, Jiangnan High-tech Park, Quanzhou, Fujian, China

**Product Name:** Network Digital Trunking Radio

**FCC ID:** 2AN96PO25701

**Standard(s):** 47 CFR Part 2(2.1093)

**Report Number:** 2502P03369E-20

**Report Date:** 2025/03/22

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

**Reviewed By:** Mark Dong  
**Title:** SAR Engineer

**Approved By:** Brave Lu  
**Title:** SAR Supervisor

---

**Bay Area Compliance Laboratories Corp. (Dongguan)**  
No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888  
Fax: +86-769-86858891  
[www.baclcorp.com.cn](http://www.baclcorp.com.cn)

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

## SAR TEST RESULTS SUMMARY

Mode		Max. Reported SAR Level(s) (W/kg)	Limit (W/kg)
<b>LTE Band 2</b>	1g Head SAR(Face Up)	<b>0.37</b>	1.6
	1g Body SAR(Body Back)	<b>0.49</b>	
<b>LTE Band 5</b>	1g Head SAR(Face Up)	0.25	1.6
	1g Body SAR(Body Back)	0.43	
<b>LTE Band 7</b>	1g Head SAR(Face Up)	0.10	1.6
	1g Body SAR(Body Back)	0.20	
<b>LTE Band 66&amp;4</b>	1g Head SAR(Face Up)	0.23	1.6
	1g Body SAR(Body Back)	0.35	

<b>Applicable Standards</b>	<b>FCC 47 CFR part 2.1093</b> Radiofrequency radiation exposure evaluation: portable devices
	<b>IEEE1528:2013</b> IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
	<b>KDB procedures</b> KDB 447498 D01 General RF Exposure Guidance v06 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04 KDB 865664 D02 RF Exposure Reporting v01r02 KDB 941225 D05 SAR for LTE Devices v02r05
<p><b>Note:</b> This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in <b>FCC 47 CFR part 2.1093</b> and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.</p> <p><b>The results and statements contained in this report pertain only to the device(s) evaluated.</b></p>	

## CONTENTS

<b>SAR TEST RESULTS SUMMARY</b> .....	2
<b>DOCUMENT REVISION HISTORY</b> .....	4
<b>1. GENERAL INFORMATION</b> .....	5
<b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)</b> .....	5
<b>2. REFERENCE, STANDARDS, AND GUIDELINES</b> .....	6
<b>2.1 SAR LIMITS</b> .....	6
<b>2.2 TEST FACILITY</b> .....	7
<b>3. DESCRIPTION OF TEST SYSTEM</b> .....	8
<b>4. EQUIPMENT LIST AND CALIBRATION</b> .....	13
<b>4.1 EQUIPMENTS LIST &amp; CALIBRATION INFORMATION</b> .....	13
<b>5. SAR MEASUREMENT SYSTEM VERIFICATION</b> .....	14
<b>5.1 LIQUID VERIFICATION</b> .....	14
<b>5.2 LIQUID VERIFICATION RESULTS</b> .....	14
<b>5.3 SYSTEM ACCURACY VERIFICATION</b> .....	16
<b>5.4 SYSTEM ACCURACY CHECK RESULTS</b> .....	16
<b>5.5 SAR SYSTEM VALIDATION DATA</b> .....	17
<b>6. EUT TEST STRATEGY AND METHODOLOGY</b> .....	21
<b>6.1 TEST POSITIONS FOR FRONT-OF-FACE CONFIGURATIONS</b> .....	21
<b>7. CONDUCTED OUTPUT POWER MEASUREMENT</b> .....	23
<b>7.1 TEST PROCEDURE</b> .....	23
<b>7.2 RADIO CONFIGURATION</b> .....	23
<b>7.3 MAXIMUM TARGET OUTPUT POWER</b> .....	25
<b>7.4 TEST RESULTS:</b> .....	26
<b>8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS</b> .....	36
<b>8.1 ANTENNAS LOCATION:</b> .....	36
<b>9. SAR MEASUREMENT RESULTS</b> .....	37
<b>9.1 SAR TEST DATA</b> .....	37
<b>10. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION</b> .....	40
<b>10.1 SIMULTANEOUS TRANSMISSION:</b> .....	40
<b>11. MEASUREMENT VARIABILITY</b> .....	41
<b>12. DUT HOLDER PERTURBATIONS</b> .....	42
<b>APPENDIX A - MEASUREMENT UNCERTAINTY</b> .....	43
<b>APPENDIX B - SAR PLOTS</b> .....	44
<b>APPENDIX C - EUT TEST POSITION PHOTOS</b> .....	45
<b>APPENDIX D - PROBE CALIBRATION CERTIFICATES</b> .....	46
<b>APPENDIX E - DIPOLE CALIBRATION CERTIFICATES</b> .....	47

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2502P03369E-20	Original Report	2025/03/22

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	Network Digital Trunking Radio
<b>EUT Model:</b>	LT-77
<b>Multiple Model:</b>	LT-77C
<b>Device Type:</b>	Portable
<b>Exposure Category:</b>	Population / Uncontrolled
<b>Antenna Type(s):</b>	Internal Antenna
<b>Body-Worn Accessories:</b>	Belt Clip
<b>Proximity Sensor:</b>	None
<b>Carrier Aggregation:</b>	None
<b>Operation Modes:</b>	FDD-LTE
<b>Frequency Band:</b>	LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)
	LTE Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX)
	LTE Band 5: 824-849 MHz(TX); 869-894 MHz(RX)
	LTE Band 7: 2500-2570 MHz(TX); 2620-2690 MHz(RX)
	LTE Band 66: 1710-1780 MHz(TX); 2110-2180 MHz(RX)
<b>Rated Input Voltage:</b>	DC 3.7V from Rechargeable Battery
<b>Serial Number:</b>	2XXA-1
<b>Normal Operation:</b>	Face Up and Body
<b>EUT Received Date:</b>	2025/01/22
<b>Test Date:</b>	2025/03/18 ~ 2025/03/19
<b>EUT Received Status:</b>	Good

Note:

The Multiple model is electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.

## 2. REFERENCE, STANDARDS, AND GUIDELINES

### FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

### 2.1 SAR Limits

#### FCC Limit

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	<b>1.6</b>	8
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4	20

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that maybe incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) applied to the EUT.

## 2.2 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. :829273, the FCC Designation No. : CN5044.


### 3. DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



#### DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

### DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.



### Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

**ES3DV3 E-Field Probes**

<b>Frequency</b>	10 MHz - 4 GHz Linearity: $\pm 0.2$ dB (30 MHz to 4 GHz)
<b>Directivity</b>	$\pm 0.2$ dB in TSL (rotation around probe axis) $\pm 0.3$ dB in TSL (rotation normal to probe axis)
<b>Dynamic Range</b>	5 $\mu$ W/g to > 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)
<b>Dimensions</b>	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 2.0 mm
<b>Application</b>	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones
<b>Compatibility</b>	DASY3, DASY4, DASY52, DASY6, DASY8 SAR, EASY6, EASY4/MRI

## SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6 mm). The phantom has three measurement areas:

- Left Head
- Right Head
- Flat phantom

The phantom table for the DASY systems based on the robots have the size of 100 x 50 x 85 cm (L x W x H). For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)



A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible.

Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

## Robots

The DASY5 system uses the high precision industrial robot. The robot offers the same features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS7MB robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

## Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm<sup>2</sup> step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

## Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

## Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE1528:2013

### Recommended Tissue Dielectric Parameters for Head liquid

**Table 3—Target dielectric properties of head tissue-equivalent material in the 300 MHz to 6000 MHz frequency range**

Frequency (MHz)	Relative permittivity ( $\epsilon_r$ )	Conductivity ( $\sigma$ ) (S/m)
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1500	40.4	1.23
1640	40.2	1.31
1750	40.1	1.37
1800	40.0	1.40
1900	40.0	1.40
2000	40.0	1.40
2100	39.8	1.49
2300	39.5	1.67
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27
6000	35.1	5.48

NOTE—For convenience, permittivity and conductivity values at some frequencies that are not part of the original data from Drossos et al. [B60] or the extension to 5800 MHz are provided (i.e., the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000 MHz that were linearly extrapolated from the values at 3000 MHz and 5800 MHz.


## 4. EQUIPMENT LIST AND CALIBRATION

### 4.1 Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52.10	N/A	NCR	NCR
DASY5 Measurement Server	DASY5 4.5.12	1470	NCR	NCR
Data Acquisition Electronics	DAE4	772	2025/2/17	2026/2/16
E-Field Probe	ES3DV3	3220	2024/10/15	2025/10/14
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
Twin SAM	Twin SAM V5.0	1874	NCR	NCR
Dipole, 750 MHz	D750V3	1167	2022/10/31	2025/10/30
Dipole, 1750 MHz	D1750V2	1141	2024/6/17	2027/6/16
Dipole, 1900 MHz	D1900V2	543	2022/11/2	2025/11/1
Dipole, 2450 MHz	D2450V2	971	2024/6/15	2027/6/14
Simulated Tissue Liquid Head	HBBL600-10000V6	SLAAH U16 BC (Batch:220809-1)	Each Time	/
Network Analyzer	8753C +85047A	3029A01355 +3033A02857	2024/5/9	2025/5/8
Dielectric assessment kit	1253	SM DAK 040 CA	NCR	NCR
synthesized signal generator	8665B	3438a00584	2024/10/18	2025/10/17
EPM Series Power Meter	E4419B	MY45103907	2024/10/18	2025/10/17
Power Sensor	8482A	US37296108	2024/10/19	2025/10/18
Power Meter	EPM-441A	GB37481494	2024/10/19	2025/10/18
Power Amplifier	ZHL-5W-202-S+	416402204	NCR	NCR
Power Amplifier	ZVE-6W-83+	637202210	NCR	NCR
Directional Coupler	441493	520Z	NCR	NCR
Attenuator	20dB, 100W	LN749	NCR	NCR
Attenuator	6dB, 150W	2754	NCR	NCR
Thermometer	DTM3000	3635	2024/8/12	2025/8/11
Hygrothermograph	HTC-2	EM072	2024/11/4	2025/11/3
Wideband Radio Communication Tester	CMW500	147473	2024/9/5	2025/9/4

## 5. SAR MEASUREMENT SYSTEM VERIFICATION

### 5.1 Liquid Verification



### 5.2 Liquid Verification Results

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
750	Simulated Tissue Liquid Head	42.841	0.903	41.90	0.89	2.25	1.46	$\pm 5$
829	Simulated Tissue Liquid Head	41.83	0.923	41.53	0.9	0.72	2.56	$\pm 5$
836.5	Simulated Tissue Liquid Head	41.778	0.93	41.50	0.90	0.67	3.33	$\pm 5$
844	Simulated Tissue Liquid Head	41.642	0.931	41.50	0.91	0.34	2.31	$\pm 5$

\*Liquid Verification above was performed on 2025/03/18.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
1720	Simulated Tissue Liquid Head	39.321	1.343	40.13	1.35	-2.02	-0.52	$\pm 5$
1745	Simulated Tissue Liquid Head	39.228	1.376	40.10	1.37	-2.17	0.44	$\pm 5$
1750	Simulated Tissue Liquid Head	39.22	1.385	40.10	1.37	-2.19	1.09	$\pm 5$
1770	Simulated Tissue Liquid Head	39.24	1.402	40.06	1.38	-2.05	1.59	$\pm 5$

\*Liquid Verification above was performed on 2025/03/19.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
1860	Simulated Tissue Liquid Head	39.315	1.425	40.00	1.40	-1.71	1.79	$\pm 5$
1880	Simulated Tissue Liquid Head	39.274	1.429	40.00	1.40	-1.82	2.07	$\pm 5$
1900	Simulated Tissue Liquid Head	39.262	1.426	40.00	1.40	-1.85	1.86	$\pm 5$

\*Liquid Verification above was performed on 2025/03/19.

Frequency (MHz)	Liquid Type	Liquid Parameter		Target Value		Delta (%)		Tolerance (%)
		$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)	$\Delta\epsilon_r$	$\Delta\sigma$ (S/m)	
2450	Simulated Tissue Liquid Head	40.342	1.843	39.2	1.8	2.91	2.39	$\pm 5$
2510	Simulated Tissue Liquid Head	40.219	1.909	39.12	1.86	2.81	2.63	$\pm 5$
2535	Simulated Tissue Liquid Head	40.005	1.949	39.09	1.89	2.34	3.12	$\pm 5$

\*Liquid Verification above was performed on 2025/03/18.


### 5.3 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 10\%$ . The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- a)  $s = 15 \text{ mm} \pm 0.2 \text{ mm}$  for  $300 \text{ MHz} \leq f \leq 1 \text{ 000 MHz}$ ;
- b)  $s = 10 \text{ mm} \pm 0.2 \text{ mm}$  for  $1 \text{ 000 MHz} < f \leq 3 \text{ 000 MHz}$ ;
- c)  $s = 10 \text{ mm} \pm 0.2 \text{ mm}$  for  $3 \text{ 000 MHz} < f \leq 6 \text{ 000 MHz}$ .

#### System Verification Setup Block Diagram



### 5.4 System Accuracy Check Results

Date	Frequency Band (MHz)	Liquid Type	Input Power (mW)	Measured SAR (W/kg)	Normalized to 1W (W/kg)	Target Value (W/Kg)	Delta (%)	Tolerance (%)
2025/03/18	750	Simulated Tissue Liquid Head	100	1g 0.851	8.51	8.48	0.35	$\pm 10$
2025/03/19	1750	Simulated Tissue Liquid Head	100	1g 3.66	36.6	36.1	1.39	$\pm 10$
2025/03/19	1900	Simulated Tissue Liquid Head	100	1g 4.25	42.5	40.2	5.72	$\pm 10$
2025/03/18	2450	Simulated Tissue Liquid Head	100	1g 5.29	52.9	52.7	0.38	$\pm 10$

**Note:**

All the SAR values are normalized to 1Watt forward power.

## 5.5 SAR SYSTEM VALIDATION DATA

### System Performance 750 MHz Head

**DUT: D750V3; Type: 750MHz; Serial: 1167**

Communication System: CW (0); Frequency: 750 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.903$  S/m;  $\epsilon_r = 42.841$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(6.68, 6.68, 6.68) @ 750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (6x15x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.957 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.49 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 1.23 W/kg

**SAR(1 g) = 0.851 W/kg; SAR(10 g) = 0.583 W/kg**

Maximum value of SAR (measured) = 0.934 W/kg



**System Performance 1750 MHz Head****DUT: D1750V2; Type: 1750 MHz; Serial: 1141**

Communication System: CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.385$  S/m;  $\epsilon_r = 39.22$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(5.53, 5.53, 5.53) @ 1750 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (6x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 5.98 W/kg


**Zoom Scan (5x5x7) /Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 68.37 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 7.12 W/kg

**SAR(1 g) = 3.66 W/kg; SAR(10 g) = 2.11 W/kg**

Maximum value of SAR (measured) = 5.83 W/kg



**System Performance 1900 MHz Head****DUT: D1900V2; Type: 1900 MHz; Serial: 543**

Communication System: CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.426$  S/m;  $\epsilon_r = 39.262$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(5.24, 5.24, 5.24) @ 1900 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 4.59 W/kg


**Zoom Scan (5x5x7) /Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.67 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 5.86 W/kg

**SAR(1 g) = 4.25 W/kg; SAR(10 g) = 2.19 W/kg**

Maximum value of SAR (measured) = 4.42 W/kg



**System Performance 2450MHz Head****DUT: D2450V2; Type: 2450 MHz; Serial: 971**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.843$  S/m;  $\epsilon_r = 40.342$ ;  $\rho = 1000$  kg/m<sup>3</sup>;  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3220; ConvF(4.83, 4.83, 4.83) @ 2450 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)


**Area Scan (7x11x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (measured) = 5.61 W/kg

**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 52.95 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 6.39 W/kg

**SAR(1 g) = 5.29 W/kg; SAR(10 g) = 2.52 W/kg**


Maximum value of SAR (measured) = 5.48 W/kg



## 6. EUT TEST STRATEGY AND METHODOLOGY

### 6.1 Test positions for Front-of-face configurations

Passive body-worn and audio accessories generally do not apply to the head SAR of PTT radios. Head SAR is measured with the front surface of the radio positioned at 2.5 cm parallel to a flat phantom. A phantom shell thickness of 2 mm is required. When the front of the radio has a contour or non-uniform surface with a variation of 1.0 cm or more, the average distance of such variations is used to establish the 2.5 cm test separation from the phantom.



**Figure 10 – Test positions for front-of-face devices**

## 6.2 Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

## 6.3 Test Distance for SAR Evaluation


For Face Up mode(1g Head SAR) the EUT(Equipment Under Test) is set 25mm against the phantom, the test distance is 25mm;

For Body mode(1g Body SAR) the EUT is set directly against the phantom, the test distance is 0mm.

## 7. CONDUCTED OUTPUT POWER MEASUREMENT

### 7.1 Test Procedure

The RF output of the transmitter was connected to the input of the Wireless Communication Test Set through Connector.



### 7.2 Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

#### FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

**Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3**

Modulation	Channel bandwidth / Transmission bandwidth ( $N_{RB}$ )						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

**Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)**

Network Signalling value	Requirements (subclause)	E UTRA Band	Channel bandwidth (MHz)	Resources Blocks ( $N_{RB}$ )	A MPR (dB)
NS_01	6.6.2.1.1 6.6.2.2.1	Table 5.5-1 2, 4, 10, 23, 25, 35, 36	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
NS_03			3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	N/A
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table 6.2.4-5	
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table 6.2.4-6	
NS_13	6.6.3.3.6	26	5	Table 6.2.4-7	
NS_14	6.6.3.3.7	26	10, 15	Table 6.2.4-8	
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	Table 6.2.4-9 Table 6.2.4-10	
NS_16	6.6.3.3.9	27	3, 5, 10	Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13	
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5	≥ 2	≤ 1
			10, 15, 20	≥ 1	≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table 6.2.4-14	
NS_20	6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20	Table 6.2.4-15	
...					
NS_32	-	-	-	-	-

### 7.3 Maximum Target Output Power

Mode/Band	Max Target Power(dBm)		
	Low	Middle	High
LTE Band 2	25.5	25.5	25.5
LTE Band 4	25	25	25
LTE Band 5	24.5	24.5	24.5
LTE Band 7	25	25	25
LTE Band 66	25	25	25

Note: The Maximum Target Power for LTE bands corresponds to their maximum power in QPSK modes with maximum bandwidth.

## 7.4 Test Results:

### LTE Band 2:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1@0	24.52	24.62	24.56
		1@3	24.66	24.61	24.02
		1@5	24.64	24.63	23.66
		3@0	24.59	24.57	24.47
		3@1	24.52	24.74	24.32
		3@3	24.46	24.64	24.08
		6@0	23.61	24.13	23.44
	16-QAM	1@0	23.38	24.63	23.45
		1@3	23.51	24.55	23.27
		1@5	23.33	24.36	23.05
		3@0	23.78	24.54	23.76
		3@1	23.67	24.45	23.74
		3@3	23.83	24.26	23.45
		6@0	22.85	23.15	22.89
3M	QPSK	1@0	24.5	24.78	24.81
		1@8	24.08	24.54	24.51
		1@14	23.91	24.42	23.41
		8@0	23.23	23.99	23.67
		8@4	23.27	23.91	23.63
		8@7	23.03	23.77	23.55
		15@0	23.25	23.87	23.46
	16-QAM	1@0	23.08	23.88	24.06
		1@8	23	23.81	23.98
		1@14	22.8	23.59	23.39
		8@0	22.44	23.2	22.82
		8@4	22.33	23.05	22.77
		8@7	22.34	22.92	22.81
		15@0	22.3	22.92	22.77
5M	QPSK	1@0	24.63	24.98	24.51
		1@12	24.07	24.58	24.53
		1@24	23.45	24.17	23.24
		12@0	23.01	23.91	23.48
		12@7	22.96	23.9	23.68
		12@13	22.54	23.59	23.44
		25@0	22.8	23.64	23.42
	16-QAM	1@0	23.32	24.69	23.53
		1@12	22.83	24.42	23.66
		1@24	22.57	24.08	23.04
		12@0	22.25	23.21	22.69
		12@7	22.03	23.04	22.9
		12@13	21.87	22.82	22.73
		25@0	21.93	23.08	22.61
10M	QPSK	1@0	24.37	25.06	24.07
		1@25	23.27	24.47	24.46
		1@49	22.68	23.82	24.03
		25@0	22.51	23.77	22.89
		25@12	22.28	23.7	23.22
		25@25	21.86	23.18	23.28
		50@0	22.19	23.41	23.15

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	16-QAM	1@0	22.98	23.99	23.18
		1@25	22.07	23.66	23.67
		1@49	21.58	23.1	23.46
		12@0	22.92	24.02	23.05
		12@19	22.19	23.74	23.26
		12@38	21.91	23.17	23.38
		25@0	21.7	23.02	21.97
		25@12	21.67	22.87	22.44
		25@25	21.08	22.38	22.48
15M	QPSK	1@0	24.47	24.88	23.91
		1@37	23.19	24.61	24.25
		1@74	23.28	23.66	24.1
		36@0	22.58	24.04	22.84
		36@20	22.16	23.77	23.07
		36@39	21.92	23.17	23.47
		75@0	22.07	23.63	23.09
	16-QAM	1@0	23.3	24.07	23.18
		1@37	22.15	23.84	23.62
		1@74	22.37	22.88	23.43
		12@0	22.81	23.91	22.68
		12@31	22.18	23.76	23.19
		12@63	22.08	22.95	23.35
		25@0	21.65	23.25	22.13
		25@25	21.33	23.11	22.3
20M	QPSK	25@50	21.16	22.38	22.62
		1@0	24.08	24.67	23.52
		1@49	24.7	24.76	24.06
		1@99	24.09	23.63	24.16
		50@0	24.24	24	24.33
		50@24	24.05	23.77	23.51
		50@50	24.29	23.95	23.63
	16-QAM	100@0	24.25	24.37	23.91
		1@0	23.25	24.52	23.41
		1@49	22.33	24.5	23.71
		1@99	23.48	23.4	24.02
		12@0	22.79	23.92	22.97
		12@43	22.17	24.19	23.45
		12@88	22.98	22.92	23.7

## LTE Band 4:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1@0	23.84	23.28	23.32
		1@3	23.75	23.26	23.36
		1@5	23.94	23.15	23.31
		3@0	23.71	23.28	23.5
		3@1	23.81	23.29	23.53
		3@3	23.89	23.35	23.31
		6@0	22.81	22.22	22.41
	16-QAM	1@0	23.02	22.21	22.17
		1@3	23.06	22.13	22.16
		1@5	23.08	22.18	22.26
		3@0	23.13	22.4	22.59
		3@1	23.07	22.48	22.51
		3@3	22.96	22.36	22.66
		6@0	21.66	21.68	21.67
3M	QPSK	1@0	23.02	23.26	23.58
		1@8	23.52	23.26	23.66
		1@14	23.25	23.11	23.33
		8@0	22.54	22.31	22.52
		8@4	22.58	22.19	22.32
		8@7	22.52	22.28	22.28
		15@0	22.48	22.22	22.35
	16-QAM	1@0	22.25	22.31	22.72
		1@8	22.4	22.14	22.8
		1@14	22.37	21.91	22.64
		8@0	21.49	21.34	21.54
		8@4	21.57	21.48	21.55
		8@7	21.53	21.4	21.65
		15@0	21.62	21.4	21.52
5M	QPSK	1@0	23.37	23.52	23.44
		1@12	23.31	23.35	23.34
		1@24	23.46	23.09	23.32
		12@0	22.34	22.37	22.45
		12@7	22.59	22.25	22.55
		12@13	22.58	22.11	22.34
		25@0	22.43	22.17	22.34
	16-QAM	1@0	22.51	22.63	23.03
		1@12	22.64	22.29	23.08
		1@24	22.79	22.15	22.98
		12@0	21.74	21.57	21.68
		12@7	21.8	21.4	21.5
		12@13	21.74	21.23	21.42
		25@0	21.44	21.24	21.49
10M	QPSK	1@0	23.11	23.6	23.29
		1@25	23.32	23.26	23.52
		1@49	23.55	22.78	23.33
		25@0	22.27	22.29	22.09
		25@12	22.54	22.17	22.18
		25@25	22.61	21.93	22.06
		50@0	22.4	21.91	22.18

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	16-QAM	1@0	22.27	22.7	22.58
		1@25	22.38	22.08	22.75
		1@49	22.71	21.76	22.44
		12@0	22.35	22.49	22.18
		12@19	22.65	22.13	22.3
		12@38	22.77	21.84	22.24
		25@0	21.46	21.45	21.29
		25@12	21.66	21.3	21.47
		25@25	21.82	21.06	21.23
15M	QPSK	1@0	23.48	23.78	23.14
		1@37	23.95	23.21	23.69
		1@74	<b>23.99</b>	22.88	23.62
		36@0	22.58	22.45	22.08
		36@20	23.07	22.33	22.27
		36@39	23.04	22.01	22.53
		75@0	22.79	22.13	22.24
	16-QAM	1@0	22.47	22.79	22.37
		1@37	23.03	22.25	22.78
		1@74	23.13	22.02	22.66
		12@0	22.42	22.56	21.96
		12@31	23.1	22.29	22.41
		12@63	23.02	21.76	22.31
		25@0	21.52	21.84	21.09
		25@25	21.94	21.46	21.63
20M	QPSK	25@50	22.06	21.09	21.59
		1@0	23.19	23.76	22.82
		1@49	23.66	23.22	23.29
		1@99	23.43	22.87	23.05
		50@0	22.48	22.58	22.75
		50@24	22.97	22.28	22.19
		50@50	22.79	22.76	22.16
	16-QAM	100@0	22.65	22.09	22.08
		1@0	22.64	23.55	22.26
		1@49	23.27	22.92	22.49
		1@99	22.86	22.43	22.51
		12@0	22.4	22.81	21.79
		12@43	23.02	22.55	22.2
		12@88	22.49	21.8	22.27
		25@0	21.22	21.79	20.72
		25@37	22.01	21.5	21.39
		25@75	21.63	20.78	21.34

**LTE Band 5:**

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1@0	23.98	24.03	23.19
		1@3	23.99	23.91	23.27
		1@5	23.84	24.03	23.23
		3@0	<b>24.06</b>	23.78	23.31
		3@1	23.91	23.82	23.33
		3@3	24.04	23.79	23.33
		6@0	22.87	22.8	22.35
	16-QAM	1@0	22.81	23.25	22.05
		1@3	22.81	23.27	22.13
		1@5	22.91	23.3	22.22
		3@0	23.14	23.2	22.52
		3@1	23.01	23.12	22.51
		3@3	23.09	23.1	22.53
		6@0	22.18	21.8	21.62
3M	QPSK	1@0	23.92	23.5	23.45
		1@8	23.63	23.79	23.34
		1@14	23.47	23.59	23.61
		8@0	22.82	22.69	22.33
		8@4	22.69	22.73	22.28
		8@7	22.64	22.8	22.25
		15@0	22.75	22.67	22.29
	16-QAM	1@0	22.8	22.51	22.73
		1@8	22.64	22.84	22.79
		1@14	22.48	22.67	22.8
		8@0	21.86	21.74	21.65
		8@4	21.81	21.98	21.71
		8@7	21.78	21.94	21.71
		15@0	21.83	21.89	21.51
5M	QPSK	1@0	23.97	23.76	23.48
		1@12	23.64	23.88	23.34
		1@24	23.43	23.86	23.51
		12@0	22.68	22.59	22.41
		12@7	22.66	22.74	22.4
		12@13	22.37	22.88	22.22
		25@0	22.57	22.67	22.27
	16-QAM	1@0	23.13	22.79	23.1
		1@12	22.72	22.89	23.06
		1@24	22.55	22.93	23.25
		12@0	21.96	21.87	21.65
		12@7	21.98	22.02	21.54
		12@13	21.85	21.87	21.56
		25@0	21.6	21.81	21.47

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	QPSK	1@0	23.93	23.57	24.03
		1@25	23.17	23.79	23.56
		1@49	23.48	23.97	23.52
		25@0	22.59	22.59	22.64
		25@12	23.13	23.35	22.96
		25@25	22.63	22.69	22.57
		50@0	22.57	22.76	22.63
	16-QAM	1@0	22.88	22.49	23.34
		1@25	22.19	22.77	22.8
		1@49	22.47	22.98	22.86
		12@0	22.84	22.61	22.82
		12@19	22.54	22.76	22.46
		12@38	22.5	22.77	22.31
		25@0	21.78	21.75	21.75
		25@12	21.75	21.96	21.79
		25@25	21.56	21.88	21.45

**LTE Band 7:**

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5M	QPSK	1@0	23.28	24.61	24.62
		1@12	23.09	24.33	24.3
		1@24	23.1	24.12	24.03
		12@0	22.23	23.7	23.56
		12@7	22.41	23.68	23.47
		12@13	22.27	23.48	23.31
		25@0	22.22	23.57	23.52
	16-QAM	1@0	22.94	23.82	23.68
		1@12	22.89	23.69	23.61
		1@24	22.91	23.29	23.33
		12@0	21.32	23.07	22.79
		12@7	21.56	22.96	22.85
		12@13	21.41	22.76	22.79
		25@0	21.45	22.81	22.79
10M	QPSK	1@0	23.03	24.88	23.97
		1@25	23.01	24.49	24.33
		1@49	23.56	23.66	23.94
		25@0	22.19	23.66	23.46
		25@12	22.25	23.56	23.62
		25@25	22.53	23.16	23.36
		50@0	22.24	23.38	23.49
	16-QAM	1@0	22.33	24.23	23.15
		1@25	22.44	23.97	23.41
		1@49	22.76	23.26	23.09
		12@0	22.24	24.01	23.38
		12@19	22.43	23.74	23.7
		12@38	22.75	23.01	23.41
		25@0	21.25	23.02	22.7
15M	QPSK	25@12	21.48	22.88	23.09
		25@25	21.67	22.41	22.81
		1@0	23.38	<b>24.94</b>	23.71
		1@37	23.3	24.2	24.51
		1@74	24.17	23.27	24.28
		36@0	22.32	23.79	23.16
		36@20	22.72	23.51	23.58
	16-QAM	36@39	23	22.91	23.59
		75@0	22.64	23.59	23.41
		1@0	22.46	24.19	23.1
		1@37	22.58	23.44	23.94
		1@74	23.46	22.48	23.75
		12@0	22.31	24	22.81
		12@31	22.59	23.53	23.59

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
20M	QPSK	1@0	24.64	24.87	24.55
		1@49	23.43	24.31	23.82
		1@99	24.63	24.55	23.84
		50@0	24.3	24.79	24.47
		50@24	23.81	23.69	23.2
		50@50	23.25	23.7	23.54
		100@0	23.8	23.41	23.04
	16-QAM	1@0	22.32	24.68	22.33
		1@49	23.11	24.12	23.58
		1@99	24.22	22.73	23.54
		12@0	22.11	24.11	22.19
		12@43	22.9	23.8	23.45
		12@88	23.77	22.37	23.42
		25@0	21.1	23.32	21.55
		25@37	22.1	23.01	22.55
		25@75	22.55	21.61	22.75


**LTE Band 66:**

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4M	QPSK	1@0	24.08	23.57	23.1
		1@3	24.05	23.54	23.12
		1@5	24.02	23.6	23.19
		3@0	24.04	23.49	23.22
		3@1	24.13	23.54	23.08
		3@3	24.04	23.71	23.01
		6@0	23.34	22.73	22.35
	16-QAM	1@0	23.67	22.42	21.92
		1@3	23.82	22.35	21.96
		1@5	23.78	22.59	22.03
		3@0	23.65	22.68	22.42
		3@1	23.67	22.71	22.43
		3@3	23.75	22.83	22.29
		6@0	22.24	21.92	21.43
3M	QPSK	1@0	24.43	23.49	22.82
		1@8	24.59	23.42	23.15
		1@14	24.55	23.44	23.01
		8@0	23.33	22.48	22.01
		8@4	23.3	22.57	22.15
		8@7	23.22	22.73	22.11
		15@0	23.17	22.61	22.08
	16-QAM	1@0	23.64	22.4	21.98
		1@8	23.81	22.53	22.02
		1@14	23.67	22.56	22.01
		8@0	22.13	21.57	21.3
		8@4	22.38	21.69	21.36
		8@7	22.42	21.65	21.21
		15@0	22.26	21.6	21.32
5M	QPSK	1@0	24.27	23.39	22.98
		1@12	24.47	23.62	23.04
		1@24	24.5	23.76	23.12
		12@0	23.2	22.61	21.99
		12@7	23.29	22.58	21.99
		12@13	23.37	22.64	22.06
		25@0	23.22	22.53	21.86
	16-QAM	1@0	23.88	22.41	22.01
		1@12	24	22.57	22.16
		1@24	24.09	22.76	22.29
		12@0	22.23	21.59	21.07
		12@7	22.34	21.8	21.26
		12@13	22.43	21.8	21.23
		25@0	22.14	21.65	20.94
10M	QPSK	1@0	24.64	23.16	22.36
		1@25	24.45	23.42	22.77
		1@49	24.54	23.72	23.14
		25@0	23.05	22.27	21.41
		25@12	23.28	22.54	21.78
		25@25	23.21	22.51	21.87
		50@0	23.09	22.33	21.55

Test Bandwidth	Test Modulation	Resource Block & RB offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
10M	16-QAM	1@0	23.56	21.98	21.43
		1@25	23.6	22.42	21.89
		1@49	23.73	22.55	22.25
		12@0	23.29	22.18	21.43
		12@19	23.44	22.55	21.74
		12@38	23.32	22.7	22.26
		25@0	22	21.42	20.56
		25@12	22.27	21.81	20.93
		25@25	22.18	21.63	20.93
15M	QPSK	1@0	24.38	23.11	22.33
		1@37	24.65	23.62	22.55
		1@74	24.37	23.9	23.39
		36@0	23.32	22.39	21.4
		36@20	23.27	22.76	21.7
		36@39	23.33	22.8	21.92
		75@0	22.99	22.43	21.71
	16-QAM	1@0	23.59	22.24	21.58
		1@37	23.68	22.81	21.61
		1@74	23.5	22.79	22.16
		12@0	22.95	22.24	21.32
		12@31	23.42	22.69	21.59
		12@63	23.07	22.81	22.08
		25@0	22.2	21.25	20.72
		25@25	22.39	21.7	20.83
		25@50	22.34	21.89	21.04
20M	QPSK	1@0	23.83	23.8	23.64
		1@49	24.14	23.45	23.35
		1@99	23.36	23.42	23.09
		50@0	23.11	23.09	23.3
		50@24	23.33	23.53	23.5
		50@50	23.06	23.6	23.64
		100@0	23	23.5	23.63
	16-QAM	1@0	23.51	22.66	22.06
		1@49	23.63	23.21	21.67
		1@99	22.76	23.12	22.51
		12@0	22.94	21.89	21.62
		12@43	23.31	22.73	21.57
		12@88	22.56	22.65	22.04
		25@0	21.94	21.23	20.54
		25@37	22.4	21.87	20.68
		25@75	21.67	21.73	20.81

## **8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS**

### **8.1 Antennas Location:**



## 9. SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

### 9.1 SAR Test Data

#### Environmental Conditions

<b>Temperature:</b>	21.2-21.9 °C	21.7-22.4°C
<b>Relative Humidity:</b>	33%	41%
<b>ATM Pressure:</b>	101.7 kPa	102kPa
<b>Test Date:</b>	2025/03/18	2025/03/19

*Testing was performed by Lily Yang, Musk Huang, Led Lu.*

**LTE Band 2:**

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Face Up (25mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	24.76	25.5	1.186	0.309	<b>0.37</b>	<b>1#</b>
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	24	25.5	1.413	0.184	0.26	/
Body Back With Belt Clip (0mm)	1860	20	1RB	/	/	/	/	/	/
	1880	20	1RB	24.76	25.5	1.186	0.409	<b>0.49</b>	<b>2#</b>
	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	24	25.5	1.413	0.347	0.49	/

**LTE Band 5:**

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Face Up (25mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	23.97	24.5	1.13	0.221	<b>0.25</b>	<b>3#</b>
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.35	24.5	1.303	0.158	0.21	/
Body Back With Belt Clip (0mm)	829	10	1RB	/	/	/	/	/	/
	836.5	10	1RB	23.97	24.5	1.13	0.383	<b>0.43</b>	<b>4#</b>
	844	10	1RB	/	/	/	/	/	/
	836.5	10	50%RB	23.35	24.5	1.303	0.256	0.33	/

**LTE Band 7:**

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Face Up (25mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	24.87	25	1.03	0.101	<b>0.10</b>	<b>5#</b>
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	24.79	25	1.05	0.084	0.09	/
Body Back With Belt Clip (0mm)	2510	20	1RB	/	/	/	/	/	/
	2535	20	1RB	24.87	25	1.03	0.195	<b>0.20</b>	<b>6#</b>
	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	24.79	25	1.05	0.161	0.17	/

**LTE Band 66&4:**

EUT Position	Frequency (MHz)	Bandwidth (MHz)	Test Mode	Max. Meas. Power (dBm)	Max. Rated Power (dBm)	1g SAR (W/kg)			
						Scaled Factor	Meas. SAR	Scaled SAR	Plot
Face Up (25mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	23.8	25	1.318	0.178	<b>0.23</b>	<b>7#</b>
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.6	25	1.38	0.143	0.20	/
Body Back With Belt Clip (0mm)	1720	20	1RB	/	/	/	/	/	/
	1745	20	1RB	23.8	25	1.318	0.266	<b>0.35</b>	<b>8#</b>
	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	23.6	25	1.38	0.204	0.28	/

**Note:** The E-UTRA Operating Band 4 is a subset of band 66, and they are same in modulation type and rated output power, therefore, they were considered as one frequency band during SAR measurement, LTE Band 66 (the wide frequency range) was selected to test.

**Note:**

1. When the 1-g SAR is  $\leq 0.8\text{W/Kg}$ , testing for other channels are optional.
2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02r05.
3. KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is  $> 0.5\text{ dB}$  higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45\text{ W/kg}$
4. KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is  $< 1.45\text{ W/kg}$ , tests for the remaining required test channels are optional.
5. KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8\text{ W/kg}$ .
6. KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
7. KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is  $> 0.5\text{ dB}$  higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45\text{ W/kg}$ .

## **10. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION**

### **10.1 Simultaneous Transmission:**

*Note: There is no multiple transmitters for the product, so simultaneous transmission need not to evaluate.*

## 11. MEASUREMENT VARIABILITY

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

*Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.*

### The Highest Measured SAR Configuration in Each Frequency Band

#### Head

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
/	/	/	/	/	/	/

#### Body

SAR probe calibration point	Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		Largest to Smallest SAR Ratio
				Original	Repeated	
/	/	/	/	/	/	/

#### Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not  $> 1.20$ .
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements.

## 12. DUT HOLDER PERTURBATIONS

In accordance with TCB workshop October 2016:

- 1) SAR perturbation due to test device holders, depending on antenna locations, buttons locations  
on phones or device, form factor (e.g. dongles etc.), the measured SAR could be influenced by the relative positions of the test device and its holder
- 2) SAR measurement standards have included protocols to evaluate this with a flat phantom, with  
and without the device holder
- 3) When the highest reported SAR of an antenna is  $> 1.2 \text{ W/kg}$ , holder perturbation verification is  
required for each antenna, using the highest SAR configuration among all applicable frequency bands in the same exact device and holder positions used for head and body SAR measurements; i.e. same device/button locations in the holder

Per IEEE 1528: 2013/Annex E/E.4.1.1: Device holder perturbation tolerance for a specific test device: Type B

When it is unknown if a device holder perturbs the fields of a test device, the SAR uncertainty shall be assessed with a flat phantom (see Clause 5) by comparing the SAR with and without the device holder according to the following tests:

The SAR tolerance for device holder disturbance is computed using Equation (E.21) and entered in the corresponding row of the appropriate uncertainty table with an assumed rectangular probability distribution and  $vi = \infty$  degrees of freedom:

$$SAR_{tolerance} [\%] = 100 \times \left( \frac{SAR_{w/ \text{ holder}} - SAR_{w/o \text{ holder}}}{SAR_{w/o \text{ holder}}} \right) \quad (\text{E.21})$$

### The Highest Measured SAR Configuration among all applicable Frequency Band

Frequency Band	Freq.(MHz)	EUT Position	Meas. SAR (W/kg)		The Device holder perturbation uncertainty
			With holder	Without holder	
/	/	/	/	/	/

## APPENDIX A - MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Uncertainty component	Tolerance/uncertainty $\pm \%$	Probability distribution	Divisor	ci (1 g)	ci (10 g)	Standard uncertainty $\pm \%, (1 \text{ g})$	Standard uncertainty $\pm \%, (10 \text{ g})$
<b>Measurement system</b>							
Probe calibration( $k=1$ )	6.55	N	1	1	1	6.6	6.6
Axial isotropy	4.7	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	1.9	1.9
Hemispherical isotropy	9.6	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	3.9	3.9
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Modulation response	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions-noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions-reflections	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Probe positioner mech.tolerance	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
<b>Test sample related</b>							
Test sample positioning	3.3	N	1	1	1	3.3	3.3
Device holder uncertainty	4.4	N	1	1	1	4.4	4.4
Output power variation –SAR draft measurement	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
SAR scaling	2.8	R	$\sqrt{3}$	1	1	1.6	1.6
<b>Phantom and tissue parameters</b>							
Phantom shell uncertainty–shape, thickness and permittivity	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.9	1.6
Liquid conductivity meas.	2.5	N	1	0.78	0.71	2.0	1.8
Liquid permittivity meas.	2.5	N	1	0.23	0.26	0.6	0.7
Liquid conductivity – temperature uncertainty	1.7	R	$\sqrt{3}$	0.78	0.71	0.8	0.7
Liquid permittivity – temperature uncertainty	0.3	R	$\sqrt{3}$	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.1	12.0
Expanded uncertainty (95 % confidence interval)		k=2				24.2	24.0

---

## APPENDIX B - SAR PLOTS

---

Please refer to the attachment.

## **APPENDIX C - EUT TEST POSITION PHOTOS**

Please refer to the attachment.

---

## **APPENDIX D - PROBE CALIBRATION CERTIFICATES**

---

Please refer to the attachment.

---

## **APPENDIX E - DIPOLE CALIBRATION CERTIFICATES**

---

Please refer to the attachment.

**\*\*\*\*\*END OF REPORT\*\*\*\*\***