

Maximum Permissible Exposure

Evaluation

FCC ID: 2AN9B-12USA-W

1. Client Information

Applicant : Shenzhen Ming Yi Heng Industrial Co., Ltd
Address : 1806-1807 Unit, Block 3A, Hecheng Century, WuHe Avenue, Bantian Street, Longgang District, Shenzhen, Guangdong, China
Manufacturer : Dongguan Mingone Electronics Co., Ltd
Address : 2nd Floor, Building 8, Kegu Industrial Area, No.6 Zhongnan South Road, Shangsha Comunnity, Chang'an Town, Dongguan, Guangdong, China

2. General Description of EUT

EUT Name	:	ZLD-12USA-W
Models No.	:	ZLD-12USA-W
Product Description	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
	Number of Channel:	802.11b/g/n(HT20):11 channels
	RF Output Power:	802.11b: 17.28dBm 802.11g: 16.85dBm 802.11n (HT20): 15.43dBm
	Antenna Gain:	5dBi PCB Antenna
	Modulation Type:	802.11b: DSSS(CCK, QPSK, BPSK) 802.11g: OFDM 802.11n: OFDM
	Bit Rate of Transmitter:	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
Power Supply	:	AC Voltage supplied
Power Rating	:	Input: AC 90~125V, 50/60Hz Output: AC 90~125V 16A Max USB Oupout:2.4A Max

TB-RF-075-1.0

Connecting I/O Port(S)	:	Please refer to the User's Manual
-----------------------------------	---	-----------------------------------

Note: More information about the RF function, please refer the RF test reports.

TB-RF-075-1.0

MPE Calculations for WIFI

1. Antenna Gain:

PCB Antenna: 5dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Worst Maximum MPE Result							
Mode	N _{TX}	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
802.11B	1	17.28	17±1	18	5	20	0.0397
802.11g	1	16.85	16±1	17	5	20	0.0315
802.11n (HT20)	1	15.43	15±1	16	5	20	0.0251

Note:

(1) N_{TX}= Number of Transmit Antennas

(2) RF Output power specifies that Maximum Conducted Peak Output Power.

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n (2412~2462 MHz)

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.0397\text{mW/cm}^2 < \text{limit } 1\text{mW/cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----