

RF Mode	TX 802.11a	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	105.3 PK			1.32 H	135	103.0	2.3
2	*5700.00	94.6 AV			1.32 H	135	92.3	2.3
3	#5725.00	54.8 PK	68.2	-13.4	1.32 H	135	52.4	2.4
4	11400.00	50.1 PK	74.0	-23.9	2.75 H	158	37.6	12.5
5	11400.00	39.8 AV	54.0	-14.2	2.75 H	158	27.3	12.5
6	#17100.00	57.3 PK	68.2	-10.9	1.44 H	339	40.5	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	114.4 PK			1.48 V	270	112.1	2.3
2	*5700.00	105.6 AV			1.48 V	270	103.3	2.3
3	#5725.00	66.5 PK	68.2	-1.7	1.48 V	270	64.1	2.4
4	11400.00	56.0 PK	74.0	-18.0	3.94 V	151	43.5	12.5
5	11400.00	43.5 AV	54.0	-10.5	3.94 V	151	31.0	12.5
6	#17100.00	62.3 PK	68.2	-5.9	2.07 V	265	45.5	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.2 PK	74.0	-22.8	1.30 H	125	49.1	2.1
2	5460.00	39.8 AV	54.0	-14.2	1.30 H	125	37.7	2.1
3	#5470.00	51.8 PK	68.2	-16.4	1.30 H	125	49.6	2.2
4	*5720.00	108.5 PK			1.30 H	125	106.1	2.4
5	*5720.00	99.3 AV			1.30 H	125	96.9	2.4
6	#5850.00	53.1 PK	68.2	-15.1	1.30 H	125	50.4	2.7
7	11440.00	50.4 PK	74.0	-23.6	2.83 H	138	38.0	12.4
8	11440.00	40.2 AV	54.0	-13.8	2.83 H	138	27.8	12.4
9	#17160.00	56.5 PK	68.2	-11.7	1.52 H	342	39.9	16.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.7 PK	74.0	-22.3	1.36 V	299	49.6	2.1
2	5460.00	39.8 AV	54.0	-14.2	1.36 V	299	37.7	2.1
3	#5470.00	52.0 PK	68.2	-16.2	1.36 V	299	49.8	2.2
4	*5720.00	119.3 PK			1.36 V	299	116.9	2.4
5	*5720.00	110.0 AV			1.36 V	299	107.6	2.4
6	#5850.00	53.5 PK	68.2	-14.7	1.36 V	299	50.8	2.7
7	11440.00	55.1 PK	74.0	-18.9	3.96 V	165	42.7	12.4
8	11440.00	42.6 AV	54.0	-11.4	3.96 V	165	30.2	12.4
9	#17160.00	62.3 PK	68.2	-5.9	2.05 V	286	45.7	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5560.33	49.8 PK	68.2	-18.4	1.52 H	146	47.7	2.1
2	*5745.00	108.0 PK			1.52 H	146	105.6	2.4
3	*5745.00	97.6 AV			1.52 H	146	95.2	2.4
4	#5996.71	50.8 PK	68.2	-17.4	1.52 H	146	47.9	2.9
5	11490.00	53.7 PK	74.0	-20.3	1.33 H	320	41.1	12.6
6	11490.00	42.2 AV	54.0	-11.8	1.33 H	320	29.6	12.6
7	#17235.00	56.8 PK	68.2	-11.4	3.55 H	315	40.0	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5615.98	52.1 PK	68.2	-16.1	1.52 V	274	50.0	2.1
2	*5745.00	118.0 PK			1.52 V	274	115.6	2.4
3	*5745.00	109.0 AV			1.52 V	274	106.6	2.4
4	#5963.17	51.6 PK	68.2	-16.6	1.52 V	274	48.7	2.9
5	11490.00	55.5 PK	74.0	-18.5	1.22 V	304	42.9	12.6
6	11490.00	43.3 AV	54.0	-10.7	1.22 V	304	30.7	12.6
7	#17235.00	58.0 PK	68.2	-10.2	1.23 V	338	41.2	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5635.62	50.5 PK	68.2	-17.7	1.49 H	141	48.2	2.3
2	*5785.00	108.2 PK			1.49 H	141	105.6	2.6
3	*5785.00	97.8 AV			1.49 H	141	95.2	2.6
4	#6017.28	50.8 PK	68.2	-17.4	1.49 H	141	47.9	2.9
5	11570.00	54.2 PK	74.0	-19.8	1.32 H	322	41.6	12.6
6	11570.00	42.4 AV	54.0	-11.6	1.32 H	322	29.8	12.6
7	#17355.00	57.1 PK	68.2	-11.1	3.56 H	312	39.4	17.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5565.85	51.3 PK	68.2	-16.9	1.55 V	280	49.2	2.1
2	*5785.00	117.7 PK			1.55 V	280	115.1	2.6
3	*5785.00	108.9 AV			1.55 V	280	106.3	2.6
4	#5975.89	52.8 PK	68.2	-15.4	1.55 V	280	49.9	2.9
5	11570.00	55.1 PK	74.0	-18.9	1.25 V	307	42.5	12.6
6	11570.00	43.1 AV	54.0	-10.9	1.25 V	307	30.5	12.6
7	#17355.00	58.2 PK	68.2	-10.0	1.21 V	358	40.5	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11a	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5561.21	50.0 PK	68.2	-18.2	1.56 H	149	47.9	2.1
2	*5825.00	107.9 PK			1.56 H	149	105.3	2.6
3	*5825.00	97.7 AV			1.56 H	149	95.1	2.6
4	#5973.06	50.9 PK	68.2	-17.3	1.56 H	149	48.0	2.9
5	11650.00	53.6 PK	74.0	-20.4	1.30 H	328	41.4	12.2
6	11650.00	42.1 AV	54.0	-11.9	1.30 H	328	29.9	12.2
7	#17475.00	57.3 PK	68.2	-10.9	3.59 H	315	38.6	18.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5594.92	50.5 PK	68.2	-17.7	1.49 V	281	48.4	2.1
2	*5825.00	118.1 PK			1.49 V	281	115.5	2.6
3	*5825.00	109.1 AV			1.49 V	281	106.5	2.6
4	#5930.62	56.2 PK	68.2	-12.0	1.49 V	281	53.3	2.9
5	11650.00	55.3 PK	74.0	-18.7	1.25 V	317	43.1	12.2
6	11650.00	43.2 AV	54.0	-10.8	1.25 V	317	31.0	12.2
7	#17475.00	58.9 PK	68.2	-9.3	1.26 V	353	40.2	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.9 PK	74.0	-19.1	1.35 H	123	52.6	2.3
2	5150.00	43.7 AV	54.0	-10.3	1.35 H	123	41.4	2.3
3	*5180.00	106.5 PK			1.35 H	123	104.3	2.2
4	*5180.00	95.7 AV			1.35 H	123	93.5	2.2
5	#10360.00	51.5 PK	68.2	-16.7	2.75 H	160	39.7	11.8
6	15540.00	57.2 PK	74.0	-16.8	1.47 H	348	45.4	11.8
7	15540.00	43.9 AV	54.0	-10.1	1.47 H	348	32.1	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	65.4 PK	74.0	-8.6	1.39 V	277	63.1	2.3
2	5150.00	52.3 AV	54.0	-1.7	1.39 V	277	50.0	2.3
3	*5180.00	119.2 PK			1.39 V	277	117.0	2.2
4	*5180.00	108.3 AV			1.39 V	277	106.1	2.2
5	#10360.00	51.9 PK	68.2	-16.3	3.02 V	162	40.1	11.8
6	15540.00	59.1 PK	74.0	-14.9	3.73 V	291	47.3	11.8
7	15540.00	44.7 AV	54.0	-9.3	3.73 V	291	32.9	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.2 PK	74.0	-20.8	1.41 H	135	50.9	2.3
2	5150.00	42.1 AV	54.0	-11.9	1.41 H	135	39.8	2.3
3	*5200.00	107.6 PK			1.41 H	135	105.5	2.1
4	*5200.00	96.9 AV			1.41 H	135	94.8	2.1
5	#10400.00	51.0 PK	68.2	-17.2	2.77 H	154	39.0	12.0
6	15600.00	57.7 PK	74.0	-16.3	1.47 H	352	46.2	11.5
7	15600.00	44.2 AV	54.0	-9.8	1.47 H	352	32.7	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.9 PK	74.0	-11.1	1.10 V	274	60.6	2.3
2	5150.00	44.9 AV	54.0	-9.1	1.10 V	274	42.6	2.3
3	*5200.00	120.5 PK			1.10 V	274	118.4	2.1
4	*5200.00	109.8 AV			1.10 V	274	107.7	2.1
5	#10400.00	52.4 PK	68.2	-15.8	2.99 V	158	40.4	12.0
6	15600.00	60.0 PK	74.0	-14.0	3.69 V	283	48.5	11.5
7	15600.00	45.4 AV	54.0	-8.6	3.69 V	283	33.9	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	50.7 PK	74.0	-23.3	1.41 H	115	48.4	2.3
2	5150.00	38.2 AV	54.0	-15.8	1.41 H	115	35.9	2.3
3	*5240.00	107.9 PK			1.41 H	115	105.9	2.0
4	*5240.00	97.1 AV			1.41 H	115	95.1	2.0
5	5350.00	51.3 PK	74.0	-22.7	1.41 H	115	49.4	1.9
6	5350.00	37.8 AV	54.0	-16.2	1.41 H	115	35.9	1.9
7	#10480.00	51.1 PK	68.2	-17.1	2.73 H	156	39.2	11.9
8	15720.00	57.6 PK	74.0	-16.4	1.43 H	339	45.8	11.8
9	15720.00	44.3 AV	54.0	-9.7	1.43 H	339	32.5	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.7 PK	74.0	-22.3	1.48 V	276	49.4	2.3
2	5150.00	39.8 AV	54.0	-14.2	1.48 V	276	37.5	2.3
3	*5240.00	121.1 PK			1.48 V	276	119.1	2.0
4	*5240.00	109.9 AV			1.48 V	276	107.9	2.0
5	5350.00	52.0 PK	74.0	-22.0	1.48 V	276	50.1	1.9
6	5350.00	38.7 AV	54.0	-15.3	1.48 V	276	36.8	1.9
7	#10480.00	51.7 PK	68.2	-16.5	2.98 V	155	39.8	11.9
8	15720.00	60.0 PK	74.0	-14.0	3.72 V	286	48.2	11.8
9	15720.00	45.6 AV	54.0	-8.4	3.72 V	286	33.8	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.4 PK	74.0	-22.6	1.31 H	114	49.1	2.3
2	5150.00	38.1 AV	54.0	-15.9	1.31 H	114	35.8	2.3
3	*5260.00	107.8 PK			1.31 H	114	105.8	2.0
4	*5260.00	97.0 AV			1.31 H	114	95.0	2.0
5	#10520.00	51.6 PK	68.2	-16.6	2.72 H	162	39.6	12.0
6	15780.00	57.4 PK	74.0	-16.6	1.50 H	348	45.9	11.5
7	15780.00	44.2 AV	54.0	-9.8	1.50 H	348	32.7	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.5 PK	74.0	-21.5	1.50 V	277	50.2	2.3
2	5150.00	39.6 AV	54.0	-14.4	1.50 V	277	37.3	2.3
3	*5260.00	120.3 PK			1.50 V	277	118.3	2.0
4	*5260.00	109.7 AV			1.50 V	277	107.7	2.0
5	#10520.00	53.2 PK	68.2	-15.0	3.63 V	198	41.2	12.0
6	15780.00	59.9 PK	74.0	-14.1	3.64 V	269	48.4	11.5
7	15780.00	45.4 AV	54.0	-8.6	3.64 V	269	33.9	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	108.4 PK			1.40 H	136	106.7	1.7
2	*5300.00	97.2 AV			1.40 H	136	95.5	1.7
3	5350.00	53.2 PK	74.0	-20.8	1.40 H	136	51.3	1.9
4	5350.00	42.8 AV	54.0	-11.2	1.40 H	136	40.9	1.9
5	10600.00	51.7 PK	74.0	-22.3	2.76 H	144	39.8	11.9
6	10600.00	40.7 AV	54.0	-13.3	2.76 H	144	28.8	11.9
7	15900.00	57.3 PK	74.0	-16.7	1.51 H	341	46.0	11.3
8	15900.00	44.1 AV	54.0	-9.9	1.51 H	341	32.8	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	120.1 PK			1.52 V	273	118.4	1.7
2	*5300.00	109.6 AV			1.52 V	273	107.9	1.7
3	5350.00	61.3 PK	74.0	-12.7	1.52 V	273	59.4	1.9
4	5350.00	44.8 AV	54.0	-9.2	1.52 V	273	42.9	1.9
5	10600.00	53.2 PK	74.0	-20.8	3.55 V	192	41.3	11.9
6	10600.00	40.5 AV	54.0	-13.5	3.55 V	192	28.6	11.9
7	15900.00	59.8 PK	74.0	-14.2	3.61 V	271	48.5	11.3
8	15900.00	45.4 AV	54.0	-8.6	3.61 V	271	34.1	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	106.1 PK			1.52 H	138	104.3	1.8
2	*5320.00	95.4 AV			1.52 H	138	93.6	1.8
3	5350.00	54.3 PK	74.0	-19.7	1.52 H	138	52.4	1.9
4	5350.00	43.8 AV	54.0	-10.2	1.52 H	138	41.9	1.9
5	10640.00	51.7 PK	74.0	-22.3	2.80 H	167	39.9	11.8
6	10640.00	40.8 AV	54.0	-13.2	2.80 H	167	29.0	11.8
7	15960.00	57.9 PK	74.0	-16.1	1.54 H	349	46.3	11.6
8	15960.00	44.5 AV	54.0	-9.5	1.54 H	349	32.9	11.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	118.9 PK			1.43 V	288	117.1	1.8
2	*5320.00	107.8 AV			1.43 V	288	106.0	1.8
3	5350.00	67.3 PK	74.0	-6.7	1.43 V	288	65.4	1.9
4	5350.00	52.5 AV	54.0	-1.5	1.43 V	288	50.6	1.9
5	10640.00	53.0 PK	74.0	-21.0	3.52 V	202	41.2	11.8
6	10640.00	40.7 AV	54.0	-13.3	3.52 V	202	28.9	11.8
7	15960.00	59.9 PK	74.0	-14.1	3.65 V	289	48.3	11.6
8	15960.00	45.2 AV	54.0	-8.8	3.65 V	289	33.6	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE20)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5448.60	50.2 PK	74.0	-23.8	1.40 H	140	48.1	2.1
2	5448.60	39.2 AV	54.0	-14.8	1.40 H	140	37.1	2.1
3	#5468.55	52.7 PK	68.2	-15.5	1.40 H	140	50.5	2.2
4	*5500.00	103.5 PK			1.40 H	140	101.4	2.1
5	*5500.00	93.4 AV			1.40 H	140	91.3	2.1
6	11000.00	50.9 PK	74.0	-23.1	2.78 H	143	38.5	12.4
7	11000.00	40.7 AV	54.0	-13.3	2.78 H	143	28.3	12.4
8	#16500.00	57.9 PK	68.2	-10.3	1.55 H	333	44.2	13.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5458.40	60.7 PK	74.0	-13.3	1.39 V	272	58.6	2.1
2	5458.40	43.9 AV	54.0	-10.1	1.39 V	272	41.8	2.1
3	5460.00	58.2 PK	74.0	-15.8	1.39 V	272	56.1	2.1
4	5460.00	44.2 AV	54.0	-9.8	1.39 V	272	42.1	2.1
5	#5468.10	66.6 PK	68.2	-1.6	1.39 V	272	64.4	2.2
6	*5500.00	117.2 PK			1.39 V	272	115.1	2.1
7	*5500.00	105.5 AV			1.39 V	272	103.4	2.1
8	11000.00	55.8 PK	74.0	-18.2	3.93 V	181	43.4	12.4
9	11000.00	43.2 AV	54.0	-10.8	3.93 V	181	30.8	12.4
10	#16500.00	62.9 PK	68.2	-5.3	2.00 V	296	49.2	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 116 : 5580 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.1 PK	74.0	-21.9	1.41 H	132	50.0	2.1
2	5460.00	41.8 AV	54.0	-12.2	1.41 H	132	39.7	2.1
3	#5470.00	54.5 PK	68.2	-13.7	1.41 H	132	52.3	2.2
4	*5580.00	108.1 PK			1.41 H	132	106.0	2.1
5	*5580.00	96.9 AV			1.41 H	132	94.8	2.1
6	11160.00	50.3 PK	74.0	-23.7	2.82 H	161	38.3	12.0
7	11160.00	40.1 AV	54.0	-13.9	2.82 H	161	28.1	12.0
8	#16740.00	56.7 PK	68.2	-11.5	1.47 H	355	41.4	15.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	53.7 PK	74.0	-20.3	1.43 V	284	51.6	2.1
2	5460.00	42.4 AV	54.0	-11.6	1.43 V	284	40.3	2.1
3	#5470.00	55.5 PK	68.2	-12.7	1.43 V	284	53.3	2.2
4	*5580.00	120.3 PK			1.43 V	284	118.2	2.1
5	*5580.00	109.8 AV			1.43 V	284	107.7	2.1
6	11160.00	54.9 PK	74.0	-19.1	3.93 V	178	42.9	12.0
7	11160.00	42.4 AV	54.0	-11.6	3.93 V	178	30.4	12.0
8	#16740.00	62.7 PK	68.2	-5.5	2.06 V	284	47.4	15.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	104.3 PK			1.39 H	127	102.0	2.3
2	*5700.00	92.8 AV			1.39 H	127	90.5	2.3
3	#5727.81	54.9 PK	68.2	-13.3	1.39 H	127	52.4	2.5
4	11400.00	50.2 PK	74.0	-23.8	2.85 H	154	37.7	12.5
5	11400.00	39.9 AV	54.0	-14.1	2.85 H	154	27.4	12.5
6	#17100.00	57.6 PK	68.2	-10.6	1.56 H	348	40.8	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	116.7 PK			1.50 V	264	114.4	2.3
2	*5700.00	105.6 AV			1.50 V	264	103.3	2.3
3	#5727.81	66.7 PK	68.2	-1.5	1.50 V	264	64.2	2.5
4	11400.00	55.3 PK	74.0	-18.7	3.93 V	168	42.8	12.5
5	11400.00	42.6 AV	54.0	-11.4	3.93 V	168	30.1	12.5
6	#17100.00	62.3 PK	68.2	-5.9	1.99 V	291	45.5	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.8 PK	74.0	-21.2	1.37 H	128	50.7	2.1
2	5460.00	38.4 AV	54.0	-15.6	1.37 H	128	36.3	2.1
3	#5470.00	53.5 PK	68.2	-14.7	1.37 H	128	51.3	2.2
4	*5720.00	108.6 PK			1.37 H	128	106.2	2.4
5	*5720.00	97.3 AV			1.37 H	128	94.9	2.4
6	#5850.00	53.0 PK	68.2	-15.2	1.37 H	128	50.3	2.7
7	11440.00	50.6 PK	74.0	-23.4	2.79 H	151	38.2	12.4
8	11440.00	40.2 AV	54.0	-13.8	2.79 H	151	27.8	12.4
9	#17160.00	57.0 PK	68.2	-11.2	1.56 H	329	40.4	16.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	53.2 PK	74.0	-20.8	1.42 V	286	51.1	2.1
2	5460.00	39.9 AV	54.0	-14.1	1.42 V	286	37.8	2.1
3	#5470.00	53.8 PK	68.2	-14.4	1.42 V	286	51.6	2.2
4	*5720.00	120.1 PK			1.42 V	286	117.7	2.4
5	*5720.00	109.6 AV			1.42 V	286	107.2	2.4
6	#5850.00	53.2 PK	68.2	-15.0	1.42 V	286	50.5	2.7
7	11440.00	54.8 PK	74.0	-19.2	3.94 V	161	42.4	12.4
8	11440.00	42.5 AV	54.0	-11.5	3.94 V	161	30.1	12.4
9	#17160.00	62.9 PK	68.2	-5.3	2.08 V	288	46.3	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5551.71	50.8 PK	68.2	-17.4	1.48 H	145	48.7	2.1
2	*5745.00	108.3 PK			1.48 H	145	105.9	2.4
3	*5745.00	97.2 AV			1.48 H	145	94.8	2.4
4	#6020.62	50.1 PK	68.2	-18.1	1.48 H	145	47.1	3.0
5	11490.00	54.5 PK	74.0	-19.5	1.35 H	321	41.9	12.6
6	11490.00	42.9 AV	54.0	-11.1	1.35 H	321	30.3	12.6
7	#17235.00	57.6 PK	68.2	-10.6	3.55 H	323	40.8	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5611.44	51.1 PK	68.2	-17.1	1.46 V	287	49.0	2.1
2	*5745.00	119.9 PK			1.46 V	287	117.5	2.4
3	*5745.00	108.5 AV			1.46 V	287	106.1	2.4
4	#5933.49	51.8 PK	68.2	-16.4	1.46 V	287	48.9	2.9
5	11490.00	55.0 PK	74.0	-19.0	1.23 V	289	42.4	12.6
6	11490.00	43.0 AV	54.0	-11.0	1.23 V	289	30.4	12.6
7	#17235.00	57.7 PK	68.2	-10.5	1.26 V	341	40.9	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5615.37	50.6 PK	68.2	-17.6	1.53 H	144	48.5	2.1
2	*5785.00	108.1 PK			1.53 H	144	105.5	2.6
3	*5785.00	96.8 AV			1.53 H	144	94.2	2.6
4	#5932.03	51.5 PK	68.2	-16.7	1.53 H	144	48.6	2.9
5	11570.00	54.0 PK	74.0	-20.0	1.37 H	320	41.4	12.6
6	11570.00	42.4 AV	54.0	-11.6	1.37 H	320	29.8	12.6
7	#17355.00	57.3 PK	68.2	-10.9	3.60 H	303	39.6	17.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5633.10	51.1 PK	68.2	-17.1	1.50 V	274	48.8	2.3
2	*5785.00	120.2 PK			1.50 V	274	117.6	2.6
3	*5785.00	108.6 AV			1.50 V	274	106.0	2.6
4	#5974.18	52.4 PK	68.2	-15.8	1.50 V	274	49.5	2.9
5	11570.00	53.6 PK	74.0	-20.4	1.24 V	307	41.0	12.6
6	11570.00	42.0 AV	54.0	-12.0	1.24 V	307	29.4	12.6
7	#17355.00	58.5 PK	68.2	-9.7	1.29 V	357	40.8	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5599.66	50.5 PK	68.2	-17.7	1.47 H	141	48.4	2.1
2	*5825.00	107.9 PK			1.47 H	141	105.3	2.6
3	*5825.00	97.4 AV			1.47 H	141	94.8	2.6
4	#6001.24	50.5 PK	68.2	-17.7	1.47 H	141	47.6	2.9
5	11650.00	54.2 PK	74.0	-19.8	1.37 H	324	42.0	12.2
6	11650.00	42.3 AV	54.0	-11.7	1.37 H	324	30.1	12.2
7	#17475.00	56.9 PK	68.2	-11.3	3.57 H	301	38.2	18.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5641.13	51.4 PK	68.2	-16.8	1.48 V	276	49.1	2.3
2	*5825.00	119.7 PK			1.48 V	276	117.1	2.6
3	*5825.00	109.2 AV			1.48 V	276	106.6	2.6
4	#5931.86	54.8 PK	68.2	-13.4	1.48 V	276	51.9	2.9
5	11650.00	54.9 PK	74.0	-19.1	1.20 V	295	42.7	12.2
6	11650.00	42.9 AV	54.0	-11.1	1.20 V	295	30.7	12.2
7	#17475.00	58.3 PK	68.2	-9.9	1.25 V	332	39.6	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 38 : 5190 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	57.8 PK	74.0	-16.2	1.50 H	128	55.5	2.3
2	5150.00	44.3 AV	54.0	-9.7	1.50 H	128	42.0	2.3
3	*5190.00	101.1 PK			1.50 H	128	99.0	2.1
4	*5190.00	90.1 AV			1.50 H	128	88.0	2.1
5	#10380.00	51.2 PK	68.2	-17.0	2.80 H	140	39.2	12.0
6	15570.00	57.5 PK	74.0	-16.5	1.53 H	349	45.8	11.7
7	15570.00	44.1 AV	54.0	-9.9	1.53 H	349	32.4	11.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5148.00	67.4 PK	74.0	-6.6	1.42 V	278	65.1	2.3
2	5148.00	52.5 AV	54.0	-1.5	1.42 V	278	50.2	2.3
3	*5190.00	111.3 PK			1.42 V	278	109.2	2.1
4	*5190.00	100.0 AV			1.42 V	278	97.9	2.1
5	#10380.00	52.0 PK	68.2	-16.2	3.01 V	157	40.0	12.0
6	15570.00	59.6 PK	74.0	-14.4	3.74 V	279	47.9	11.7
7	15570.00	45.1 AV	54.0	-8.9	3.74 V	279	33.4	11.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 46 : 5230 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.2 PK	74.0	-15.8	1.51 H	114	55.9	2.3
2	5150.00	41.8 AV	54.0	-12.2	1.51 H	114	39.5	2.3
3	*5230.00	105.3 PK			1.51 H	114	103.2	2.1
4	*5230.00	94.1 AV			1.51 H	114	92.0	2.1
5	5350.00	55.9 PK	74.0	-18.1	1.51 H	114	54.0	1.9
6	5350.00	38.2 AV	54.0	-15.8	1.51 H	114	36.3	1.9
7	#10460.00	51.1 PK	68.2	-17.1	2.81 H	161	39.1	12.0
8	15690.00	57.7 PK	74.0	-16.3	1.53 H	352	45.8	11.9
9	15690.00	44.5 AV	54.0	-9.5	1.53 H	352	32.6	11.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.5 PK	74.0	-11.5	1.48 V	275	60.2	2.3
2	5150.00	45.7 AV	54.0	-8.3	1.48 V	275	43.4	2.3
3	*5230.00	117.2 PK			1.48 V	275	115.1	2.1
4	*5230.00	104.3 AV			1.48 V	275	102.2	2.1
5	5350.00	57.9 PK	74.0	-16.1	1.48 V	275	56.0	1.9
6	5350.00	39.1 AV	54.0	-14.9	1.48 V	275	37.2	1.9
7	#10460.00	52.2 PK	68.2	-16.0	3.06 V	169	40.2	12.0
8	15690.00	59.4 PK	74.0	-14.6	3.79 V	300	47.5	11.9
9	15690.00	44.8 AV	54.0	-9.2	3.79 V	300	32.9	11.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 54 : 5270 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	56.1 PK	74.0	-17.9	1.55 H	127	53.8	2.3
2	5150.00	38.6 AV	54.0	-15.4	1.55 H	127	36.3	2.3
3	*5270.00	104.9 PK			1.55 H	127	103.0	1.9
4	*5270.00	93.9 AV			1.55 H	127	92.0	1.9
5	5350.00	59.2 PK	74.0	-14.8	1.55 H	127	57.3	1.9
6	5350.00	42.9 AV	54.0	-11.1	1.55 H	127	41.0	1.9
7	#10540.00	50.9 PK	68.2	-17.3	2.75 H	151	39.0	11.9
8	15810.00	57.8 PK	74.0	-16.2	1.49 H	337	46.4	11.4
9	15810.00	44.4 AV	54.0	-9.6	1.49 H	337	33.0	11.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.1 PK	74.0	-21.9	1.44 V	277	49.8	2.3
2	5150.00	39.0 AV	54.0	-15.0	1.44 V	277	36.7	2.3
3	*5270.00	117.2 PK			1.44 V	277	115.3	1.9
4	*5270.00	104.1 AV			1.44 V	277	102.2	1.9
5	5350.00	66.5 PK	74.0	-7.5	1.44 V	277	64.6	1.9
6	5350.00	46.3 AV	54.0	-7.7	1.44 V	277	44.4	1.9
7	#10540.00	53.4 PK	68.2	-14.8	3.56 V	197	41.5	11.9
8	15810.00	59.2 PK	74.0	-14.8	3.58 V	296	47.8	11.4
9	15810.00	44.8 AV	54.0	-9.2	3.58 V	296	33.4	11.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 62 : 5310 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	99.5 PK			1.28 H	134	97.7	1.8
2	*5310.00	89.5 AV			1.28 H	134	87.7	1.8
3	5350.00	57.9 PK	74.0	-16.1	1.28 H	134	56.0	1.9
4	5350.00	42.9 AV	54.0	-11.1	1.28 H	134	41.0	1.9
5	10620.00	51.4 PK	74.0	-22.6	2.73 H	147	39.6	11.8
6	10620.00	40.7 AV	54.0	-13.3	2.73 H	147	28.9	11.8
7	15930.00	57.6 PK	74.0	-16.4	1.51 H	354	46.1	11.5
8	15930.00	44.2 AV	54.0	-9.8	1.51 H	354	32.7	11.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	113.5 PK			1.30 V	287	111.7	1.8
2	*5310.00	101.2 AV			1.30 V	287	99.4	1.8
3	5350.00	68.1 PK	74.0	-5.9	1.30 V	287	66.2	1.9
4	5350.00	52.5 AV	54.0	-1.5	1.30 V	287	50.6	1.9
5	10620.00	53.8 PK	74.0	-20.2	3.58 V	197	42.0	11.8
6	10620.00	41.2 AV	54.0	-12.8	3.58 V	197	29.4	11.8
7	15930.00	59.9 PK	74.0	-14.1	3.63 V	295	48.4	11.5
8	15930.00	45.6 AV	54.0	-8.4	3.63 V	295	34.1	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 102 : 5510 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5459.20	51.3 PK	74.0	-22.7	1.40 H	141	49.2	2.1
2	5459.20	39.6 AV	54.0	-14.4	1.40 H	141	37.5	2.1
3	5460.00	50.5 PK	74.0	-23.5	1.40 H	141	48.4	2.1
4	5460.00	39.8 AV	54.0	-14.2	1.40 H	141	37.7	2.1
5	#5464.50	54.5 PK	68.2	-13.7	1.40 H	141	52.4	2.1
6	*5510.00	99.1 PK			1.40 H	141	97.0	2.1
7	*5510.00	88.3 AV			1.40 H	141	86.2	2.1
8	11020.00	50.7 PK	74.0	-23.3	2.83 H	157	38.4	12.3
9	11020.00	40.3 AV	54.0	-13.7	2.83 H	157	28.0	12.3
10	#16530.00	57.3 PK	68.2	-10.9	1.51 H	342	43.4	13.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5457.31	62.1 PK	74.0	-11.9	1.10 V	280	60.0	2.1
2	5457.31	46.5 AV	54.0	-7.5	1.10 V	280	44.4	2.1
3	5460.00	59.6 PK	74.0	-14.4	1.10 V	280	57.5	2.1
4	5460.00	48.2 AV	54.0	-5.8	1.10 V	280	46.1	2.1
5	#5468.35	66.4 PK	68.2	-1.8	1.10 V	280	64.2	2.2
6	*5510.00	111.6 PK			1.10 V	280	109.5	2.1
7	*5510.00	100.2 AV			1.10 V	280	98.1	2.1
8	11020.00	55.4 PK	74.0	-18.6	3.99 V	182	43.1	12.3
9	11020.00	43.0 AV	54.0	-11.0	3.99 V	182	30.7	12.3
10	#16530.00	62.3 PK	68.2	-5.9	2.05 V	291	48.4	13.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 110 : 5550 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	54.3 PK	74.0	-19.7	1.37 H	153	52.2	2.1
2	5460.00	40.4 AV	54.0	-13.6	1.37 H	153	38.3	2.1
3	#5470.00	56.1 PK	68.2	-12.1	1.37 H	153	53.9	2.2
4	*5550.00	104.7 PK			1.37 H	153	102.6	2.1
5	*5550.00	93.6 AV			1.37 H	153	91.5	2.1
6	11100.00	50.7 PK	74.0	-23.3	2.82 H	156	38.8	11.9
7	11100.00	40.5 AV	54.0	-13.5	2.82 H	156	28.6	11.9
8	#16650.00	57.7 PK	68.2	-10.5	1.52 H	339	42.9	14.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	58.3 PK	74.0	-15.7	1.15 V	292	56.2	2.1
2	5460.00	44.0 AV	54.0	-10.0	1.15 V	292	41.9	2.1
3	#5470.00	63.9 PK	68.2	-4.3	1.15 V	292	61.7	2.2
4	*5550.00	116.5 PK			1.15 V	292	114.4	2.1
5	*5550.00	104.1 AV			1.15 V	292	102.0	2.1
6	11100.00	55.6 PK	74.0	-18.4	3.90 V	158	43.7	11.9
7	11100.00	42.8 AV	54.0	-11.2	3.90 V	158	30.9	11.9
8	#16650.00	63.0 PK	68.2	-5.2	2.05 V	304	48.2	14.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 134 : 5670 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	100.0 PK			1.46 H	139	97.7	2.3
2	*5670.00	90.1 AV			1.46 H	139	87.8	2.3
3	#5727.93	58.6 PK	68.2	-9.6	1.46 H	139	56.1	2.5
4	11340.00	50.8 PK	74.0	-23.2	2.82 H	138	38.6	12.2
5	11340.00	40.6 AV	54.0	-13.4	2.82 H	138	28.4	12.2
6	#17010.00	57.6 PK	68.2	-10.6	1.48 H	332	41.0	16.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	114.7 PK			1.51 V	265	112.4	2.3
2	*5670.00	102.4 AV			1.51 V	265	100.1	2.3
3	#5727.93	66.6 PK	68.2	-1.6	1.51 V	265	64.1	2.5
4	11340.00	55.0 PK	74.0	-19.0	3.84 V	185	42.8	12.2
5	11340.00	42.3 AV	54.0	-11.7	3.84 V	185	30.1	12.2
6	#17010.00	62.6 PK	68.2	-5.6	2.02 V	279	46.0	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 142 : 5710 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	50.7 PK	74.0	-23.3	1.41 H	140	48.6	2.1
2	5460.00	38.6 AV	54.0	-15.4	1.41 H	140	36.5	2.1
3	#5470.00	50.8 PK	68.2	-17.4	1.41 H	140	48.6	2.2
4	*5710.00	102.2 PK			1.41 H	140	99.8	2.4
5	*5710.00	92.3 AV			1.41 H	140	89.9	2.4
6	#5850.00	53.4 PK	68.2	-14.8	1.41 H	140	50.7	2.7
7	11420.00	50.7 PK	74.0	-23.3	2.76 H	148	38.2	12.5
8	11420.00	40.6 AV	54.0	-13.4	2.76 H	148	28.1	12.5
9	#17130.00	57.1 PK	68.2	-11.1	1.56 H	340	40.3	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.1 PK	74.0	-22.9	1.05 V	290	49.0	2.1
2	5460.00	39.4 AV	54.0	-14.6	1.05 V	290	37.3	2.1
3	#5470.00	51.4 PK	68.2	-16.8	1.05 V	290	49.2	2.2
4	*5710.00	116.9 PK			1.05 V	290	114.5	2.4
5	*5710.00	104.6 AV			1.05 V	290	102.2	2.4
6	#5850.00	56.6 PK	68.2	-11.6	1.05 V	290	53.9	2.7
7	11420.00	55.2 PK	74.0	-18.8	4.00 V	180	42.7	12.5
8	11420.00	42.5 AV	54.0	-11.5	4.00 V	180	30.0	12.5
9	#17130.00	63.1 PK	68.2	-5.1	2.08 V	281	46.3	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 151 : 5755 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5561.15	49.2 PK	68.2	-19.0	1.42 H	144	47.1	2.1
2	*5755.00	104.8 PK			1.42 H	144	102.3	2.5
3	*5755.00	92.1 AV			1.42 H	144	89.6	2.5
4	#5943.36	50.5 PK	68.2	-17.7	1.42 H	144	47.6	2.9
5	11510.00	53.9 PK	74.0	-20.1	1.32 H	312	41.3	12.6
6	11510.00	42.0 AV	54.0	-12.0	1.32 H	312	29.4	12.6
7	#17265.00	57.3 PK	68.2	-10.9	3.55 H	325	40.4	16.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.73	55.5 PK	68.2	-12.7	1.50 V	287	53.2	2.3
2	*5755.00	117.3 PK			1.50 V	287	114.8	2.5
3	*5755.00	104.1 AV			1.50 V	287	101.6	2.5
4	#5938.30	52.5 PK	68.2	-15.7	1.50 V	287	49.6	2.9
5	11510.00	55.5 PK	74.0	-18.5	1.24 V	311	42.9	12.6
6	11510.00	43.2 AV	54.0	-10.8	1.24 V	311	30.6	12.6
7	#17265.00	57.6 PK	68.2	-10.6	1.22 V	326	40.7	16.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5554.88	50.0 PK	68.2	-18.2	1.46 H	147	47.9	2.1
2	*5795.00	103.7 PK			1.46 H	147	101.1	2.6
3	*5795.00	92.2 AV			1.46 H	147	89.6	2.6
4	#6002.18	50.5 PK	68.2	-17.7	1.46 H	147	47.6	2.9
5	11590.00	54.2 PK	74.0	-19.8	1.31 H	326	41.6	12.6
6	11590.00	42.2 AV	54.0	-11.8	1.31 H	326	29.6	12.6
7	#17385.00	57.0 PK	68.2	-11.2	3.56 H	321	39.1	17.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5559.42	51.2 PK	68.2	-17.0	1.59 V	267	49.1	2.1
2	*5795.00	116.8 PK			1.59 V	267	114.2	2.6
3	*5795.00	103.8 AV			1.59 V	267	101.2	2.6
4	#5925.20	55.7 PK	68.2	-12.5	1.59 V	267	52.8	2.9
5	11590.00	55.4 PK	74.0	-18.6	1.18 V	309	42.8	12.6
6	11590.00	43.2 AV	54.0	-10.8	1.18 V	309	30.6	12.6
7	#17385.00	58.1 PK	68.2	-10.1	1.22 V	339	40.2	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 42 : 5210 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5147.35	55.0 PK	74.0	-19.0	1.64 H	135	52.7	2.3
2	5147.35	42.3 AV	54.0	-11.7	1.64 H	135	40.0	2.3
3	*5210.00	95.5 PK			1.64 H	135	93.4	2.1
4	*5210.00	83.2 AV			1.64 H	135	81.1	2.1
5	5361.50	49.1 PK	74.0	-24.9	1.64 H	135	47.1	2.0
6	5361.50	38.4 AV	54.0	-15.6	1.64 H	135	36.4	2.0
7	#10420.00	51.2 PK	68.2	-17.0	2.80 H	157	39.1	12.1
8	15630.00	57.7 PK	74.0	-16.3	1.54 H	349	46.0	11.7
9	15630.00	44.4 AV	54.0	-9.6	1.54 H	349	32.7	11.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5147.76	67.1 PK	74.0	-6.9	1.56 V	264	64.8	2.3
2	5147.76	52.3 AV	54.0	-1.7	1.56 V	264	50.0	2.3
3	*5210.00	107.5 PK			1.56 V	264	105.4	2.1
4	*5210.00	94.5 AV			1.56 V	264	92.4	2.1
5	5350.00	50.7 PK	74.0	-23.3	1.56 V	264	48.8	1.9
6	5350.00	39.7 AV	54.0	-14.3	1.56 V	264	37.8	1.9
7	#10420.00	52.7 PK	68.2	-15.5	3.03 V	174	40.6	12.1
8	15630.00	58.7 PK	74.0	-15.3	3.72 V	288	47.0	11.7
9	15630.00	44.6 AV	54.0	-9.4	3.72 V	288	32.9	11.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 58 : 5290 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	4822.63	50.8 PK	74.0	-23.2	1.48 H	134	49.0	1.8
2	4822.63	37.6 AV	54.0	-16.4	1.48 H	134	35.8	1.8
3	5097.80	47.3 PK	74.0	-26.7	1.48 H	134	45.0	2.3
4	5097.80	39.0 AV	54.0	-15.0	1.48 H	134	36.7	2.3
5	*5290.00	95.1 PK			1.48 H	134	93.3	1.8
6	*5290.00	84.1 AV			1.48 H	134	82.3	1.8
7	5375.90	58.3 PK	74.0	-15.7	1.48 H	134	56.3	2.0
8	5375.90	42.5 AV	54.0	-11.5	1.48 H	134	40.5	2.0
9	#10580.00	51.7 PK	68.2	-16.5	2.79 H	159	39.9	11.8
10	15870.00	58.1 PK	74.0	-15.9	1.46 H	339	46.8	11.3
11	15870.00	44.6 AV	54.0	-9.4	1.46 H	339	33.3	11.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5145.00	55.2 PK	74.0	-18.8	1.23 V	287	52.9	2.3
2	5145.00	40.3 AV	54.0	-13.7	1.23 V	287	38.0	2.3
3	*5290.00	108.3 PK			1.23 V	287	106.5	1.8
4	*5290.00	95.4 AV			1.23 V	287	93.6	1.8
5	5353.63	70.2 PK	74.0	-3.8	1.23 V	287	68.2	2.0
6	5353.63	52.5 AV	54.0	-1.5	1.23 V	287	50.5	2.0
7	#10580.00	53.8 PK	68.2	-14.4	3.59 V	183	42.0	11.8
8	15870.00	58.8 PK	74.0	-15.2	3.58 V	293	47.5	11.3
9	15870.00	44.5 AV	54.0	-9.5	3.58 V	293	33.2	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 106 : 5530 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5450.50	51.9 PK	74.0	-22.1	1.64 H	146	49.8	2.1
2	5450.50	40.1 AV	54.0	-13.9	1.64 H	146	38.0	2.1
3	#5467.20	55.1 PK	68.2	-13.1	1.64 H	146	52.9	2.2
4	#5496.91	48.6 PK	68.2	-19.6	1.64 H	146	46.5	2.1
5	*5530.00	94.7 PK			1.64 H	146	92.7	2.0
6	*5530.00	82.1 AV			1.64 H	146	80.1	2.0
7	#5770.00	51.4 PK	68.2	-16.8	1.64 H	146	48.9	2.5
8	11060.00	51.3 PK	74.0	-22.7	2.83 H	155	39.2	12.1
9	11060.00	40.6 AV	54.0	-13.4	2.83 H	155	28.5	12.1
10	#16590.00	57.1 PK	68.2	-11.1	1.56 H	337	42.8	14.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5458.64	66.0 PK	74.0	-8.0	1.47 V	271	63.9	2.1
2	5458.64	49.0 AV	54.0	-5.0	1.47 V	271	46.9	2.1
3	#5496.91	66.7 PK	68.2	-1.5	1.47 V	271	64.6	2.1
4	*5530.00	106.8 PK			1.47 V	271	104.8	2.0
5	*5530.00	94.1 AV			1.47 V	271	92.1	2.0
6	#5818.59	52.1 PK	68.2	-16.1	1.47 V	271	49.5	2.6
7	11060.00	55.6 PK	74.0	-18.4	3.89 V	169	43.5	12.1
8	11060.00	42.5 AV	54.0	-11.5	3.89 V	169	30.4	12.1
9	#16590.00	63.0 PK	68.2	-5.2	2.10 V	312	48.7	14.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 122 : 5610 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	97.3 PK			1.40 H	133	95.2	2.1
2	*5610.00	86.2 AV			1.40 H	133	84.1	2.1
3	#5725.00	56.3 PK	68.2	-11.9	1.40 H	133	53.9	2.4
4	11220.00	51.3 PK	74.0	-22.7	2.76 H	140	39.2	12.1
5	11220.00	40.6 AV	54.0	-13.4	2.76 H	140	28.5	12.1
6	#16830.00	57.7 PK	68.2	-10.5	1.44 H	350	41.9	15.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	110.8 PK			1.29 V	289	108.7	2.1
2	*5610.00	97.8 AV			1.29 V	289	95.7	2.1
3	#5725.00	66.6 PK	68.2	-1.6	1.29 V	289	64.2	2.4
4	11220.00	55.3 PK	74.0	-18.7	3.95 V	173	43.2	12.1
5	11220.00	42.7 AV	54.0	-11.3	3.95 V	173	30.6	12.1
6	#16830.00	62.9 PK	68.2	-5.3	2.06 V	300	47.1	15.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 138 : 5690 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	54.9 PK	74.0	-19.1	1.38 H	141	52.8	2.1
2	5460.00	38.9 AV	54.0	-15.1	1.38 H	141	36.8	2.1
3	#5470.00	55.1 PK	68.2	-13.1	1.38 H	141	52.9	2.2
4	*5690.00	98.6 PK			1.38 H	141	96.3	2.3
5	*5690.00	87.3 AV			1.38 H	141	85.0	2.3
6	#5850.00	56.8 PK	68.2	-11.4	1.38 H	141	54.1	2.7
7	11380.00	50.9 PK	74.0	-23.1	2.74 H	131	38.5	12.4
8	11380.00	40.7 AV	54.0	-13.3	2.74 H	131	28.3	12.4
9	#17070.00	57.4 PK	68.2	-10.8	1.47 H	333	40.6	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	55.2 PK	74.0	-18.8	1.24 V	299	53.1	2.1
2	5460.00	40.2 AV	54.0	-13.8	1.24 V	299	38.1	2.1
3	#5470.00	56.9 PK	68.2	-11.3	1.24 V	299	54.7	2.2
4	*5690.00	111.1 PK			1.24 V	299	108.8	2.3
5	*5690.00	98.6 AV			1.24 V	299	96.3	2.3
6	#5850.00	66.5 PK	68.2	-1.7	1.24 V	299	63.8	2.7
7	11380.00	55.5 PK	74.0	-18.5	3.91 V	145	43.1	12.4
8	11380.00	42.9 AV	54.0	-11.1	3.91 V	145	30.5	12.4
9	#17070.00	62.5 PK	68.2	-5.7	2.06 V	294	45.7	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 155 : 5775 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5645.58	52.2 PK	68.2	-16.0	1.41 H	144	49.9	2.3
2	*5775.00	98.6 PK			1.41 H	144	96.1	2.5
3	*5775.00	87.2 AV			1.41 H	144	84.7	2.5
4	#5924.91	52.9 PK	68.3	-15.4	1.41 H	144	50.0	2.9
5	11550.00	53.7 PK	74.0	-20.3	1.35 H	317	41.2	12.5
6	11550.00	42.1 AV	54.0	-11.9	1.35 H	317	29.6	12.5
7	#17325.00	57.9 PK	68.2	-10.3	3.52 H	318	40.6	17.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5640.86	63.6 PK	68.2	-4.6	1.25 V	277	61.3	2.3
2	*5775.00	111.7 PK			1.25 V	277	109.2	2.5
3	*5775.00	99.4 AV			1.25 V	277	96.9	2.5
4	#5930.23	63.8 PK	68.2	-4.4	1.25 V	277	60.9	2.9
5	11550.00	55.3 PK	74.0	-18.7	1.19 V	303	42.8	12.5
6	11550.00	43.2 AV	54.0	-10.8	1.19 V	303	30.7	12.5
7	#17325.00	58.1 PK	68.2	-10.1	1.26 V	353	40.8	17.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5144.57	53.9 PK	74.0	-20.1	1.44 H	137	51.6	2.3
2	5144.57	39.3 AV	54.0	-14.7	1.44 H	137	37.0	2.3
3	*5180.00	114.1 PK			1.44 H	137	111.9	2.2
4	*5180.00	100.4 AV			1.44 H	137	98.2	2.2
5	#10360.00	58.3 PK	68.2	-9.9	1.22 H	280	46.5	11.8
6	15540.00	62.7 PK	74.0	-11.3	1.30 H	327	50.9	11.8
7	15540.00	50.2 AV	54.0	-3.8	1.30 H	327	38.4	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5139.50	60.6 PK	74.0	-13.4	1.24 V	288	58.3	2.3
2	5139.50	42.5 AV	54.0	-11.5	1.24 V	288	40.2	2.3
3	5146.80	56.7 PK	74.0	-17.3	1.24 V	288	54.4	2.3
4	5146.80	43.7 AV	54.0	-10.3	1.24 V	288	41.4	2.3
5	*5180.00	125.1 PK			1.24 V	288	122.9	2.2
6	*5180.00	113.9 AV			1.24 V	288	111.7	2.2
7	#10360.00	59.1 PK	68.2	-9.1	2.21 V	277	47.3	11.8
8	15540.00	61.2 PK	74.0	-12.8	1.96 V	323	49.4	11.8
9	15540.00	49.5 AV	54.0	-4.5	1.96 V	323	37.7	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.7 PK	74.0	-22.3	1.49 H	141	49.4	2.3
2	5150.00	41.2 AV	54.0	-12.8	1.49 H	141	38.9	2.3
3	*5200.00	114.5 PK			1.49 H	141	112.4	2.1
4	*5200.00	100.8 AV			1.49 H	141	98.7	2.1
5	#10400.00	58.2 PK	68.2	-10.0	1.25 H	294	46.2	12.0
6	15600.00	62.4 PK	74.0	-11.6	1.29 H	338	50.9	11.5
7	15600.00	49.8 AV	54.0	-4.2	1.29 H	338	38.3	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.7 PK	74.0	-21.3	1.36 V	281	50.4	2.3
2	5150.00	42.4 AV	54.0	-11.6	1.36 V	281	40.1	2.3
3	*5200.00	125.7 PK			1.36 V	281	123.6	2.1
4	*5200.00	114.7 AV			1.36 V	281	112.6	2.1
5	#10400.00	59.4 PK	68.2	-8.8	2.17 V	282	47.4	12.0
6	15600.00	61.5 PK	74.0	-12.5	1.95 V	317	50.0	11.5
7	15600.00	49.6 AV	54.0	-4.4	1.95 V	317	38.1	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.7 PK	74.0	-21.3	1.49 H	131	50.4	2.3
2	5150.00	38.1 AV	54.0	-15.9	1.49 H	131	35.8	2.3
3	*5240.00	114.1 PK			1.49 H	131	112.1	2.0
4	*5240.00	100.2 AV			1.49 H	131	98.2	2.0
5	5350.00	50.7 PK	74.0	-23.3	1.49 H	131	48.8	1.9
6	5350.00	37.7 AV	54.0	-16.3	1.49 H	131	35.8	1.9
7	#10480.00	57.9 PK	68.2	-10.3	1.27 H	265	46.0	11.9
8	15720.00	62.7 PK	74.0	-11.3	1.26 H	328	50.9	11.8
9	15720.00	50.3 AV	54.0	-3.7	1.26 H	328	38.5	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.6 PK	74.0	-21.4	1.37 V	273	50.3	2.3
2	5150.00	39.3 AV	54.0	-14.7	1.37 V	273	37.0	2.3
3	*5240.00	124.4 PK			1.37 V	273	122.4	2.0
4	*5240.00	113.5 AV			1.37 V	273	111.5	2.0
5	5350.00	50.9 PK	74.0	-23.1	1.37 V	273	49.0	1.9
6	5350.00	38.1 AV	54.0	-15.9	1.37 V	273	36.2	1.9
7	#10480.00	59.0 PK	68.2	-9.2	2.22 V	289	47.1	11.9
8	15720.00	61.7 PK	74.0	-12.3	1.91 V	336	49.9	11.8
9	15720.00	49.8 AV	54.0	-4.2	1.91 V	336	38.0	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.