

RF Mode	TX 802.11ax (HE20)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	50.7 PK	74.0	-23.3	1.97 H	119	48.6	2.1
2	5460.00	38.8 AV	54.0	-15.2	1.97 H	119	36.7	2.1
3	#5470.00	51.7 PK	68.2	-16.5	1.97 H	119	49.5	2.2
4	*5720.00	116.8 PK			1.97 H	119	114.4	2.4
5	*5720.00	105.8 AV			1.97 H	119	103.4	2.4
6	#5850.00	50.7 PK	68.2	-17.5	1.97 H	119	48.0	2.7
7	11440.00	49.3 PK	74.0	-24.7	3.64 H	297	36.9	12.4
8	11440.00	37.1 AV	54.0	-16.9	3.64 H	297	24.7	12.4
9	#17160.00	58.6 PK	68.2	-9.6	1.54 H	287	42.0	16.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	50.1 PK	74.0	-23.9	1.39 V	130	48.0	2.1
2	5460.00	37.8 AV	54.0	-16.2	1.39 V	130	35.7	2.1
3	#5470.00	50.8 PK	68.2	-17.4	1.39 V	130	48.6	2.2
4	*5720.00	108.1 PK			1.39 V	130	105.7	2.4
5	*5720.00	98.5 AV			1.39 V	130	96.1	2.4
6	#5850.00	49.9 PK	68.2	-18.3	1.39 V	130	47.2	2.7
7	11440.00	48.7 PK	74.0	-25.3	2.49 V	340	36.3	12.4
8	11440.00	36.5 AV	54.0	-17.5	2.49 V	340	24.1	12.4
9	#17160.00	58.1 PK	68.2	-10.1	1.43 V	287	41.5	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.96	53.9 PK	68.2	-14.3	2.05 H	140	51.6	2.3
2	*5745.00	117.7 PK			2.05 H	140	115.3	2.4
3	*5745.00	106.7 AV			2.05 H	140	104.3	2.4
4	#5949.91	51.7 PK	68.2	-16.5	2.05 H	140	48.8	2.9
5	11490.00	48.7 PK	74.0	-25.3	3.61 H	307	36.1	12.6
6	11490.00	36.9 AV	54.0	-17.1	3.61 H	307	24.3	12.6
7	#17235.00	58.9 PK	68.2	-9.3	1.46 H	284	42.1	16.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5586.18	51.2 PK	68.2	-17.0	1.49 V	147	49.1	2.1
2	*5745.00	109.8 PK			1.49 V	147	107.4	2.4
3	*5745.00	98.9 AV			1.49 V	147	96.5	2.4
4	#5951.65	51.0 PK	68.2	-17.2	1.49 V	147	48.1	2.9
5	11490.00	48.3 PK	74.0	-25.7	2.44 V	349	35.7	12.6
6	11490.00	36.3 AV	54.0	-17.7	2.44 V	349	23.7	12.6
7	#17235.00	57.9 PK	68.2	-10.3	1.37 V	281	41.1	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5568.00	52.0 PK	68.2	-16.2	2.07 H	150	49.9	2.1
2	*5785.00	118.1 PK			2.07 H	150	115.5	2.6
3	*5785.00	106.9 AV			2.07 H	150	104.3	2.6
4	#5954.33	51.5 PK	68.2	-16.7	2.07 H	150	48.6	2.9
5	11570.00	48.7 PK	74.0	-25.3	3.62 H	311	36.1	12.6
6	11570.00	36.9 AV	54.0	-17.1	3.62 H	311	24.3	12.6
7	#17355.00	58.8 PK	68.2	-9.4	1.49 H	266	41.1	17.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5581.41	51.1 PK	68.2	-17.1	1.53 V	153	49.0	2.1
2	*5785.00	110.1 PK			1.53 V	153	107.5	2.6
3	*5785.00	99.2 AV			1.53 V	153	96.6	2.6
4	#5947.88	51.8 PK	68.2	-16.4	1.53 V	153	48.9	2.9
5	11570.00	49.0 PK	74.0	-25.0	2.48 V	343	36.4	12.6
6	11570.00	36.7 AV	54.0	-17.3	2.48 V	343	24.1	12.6
7	#17355.00	58.4 PK	68.2	-9.8	1.43 V	274	40.7	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE20)	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5607.85	52.1 PK	68.2	-16.1	2.02 H	138	50.0	2.1
2	*5825.00	117.5 PK			2.02 H	138	114.9	2.6
3	*5825.00	106.6 AV			2.02 H	138	104.0	2.6
4	#5928.03	53.3 PK	68.2	-14.9	2.02 H	138	50.4	2.9
5	11650.00	49.2 PK	74.0	-24.8	3.65 H	299	37.0	12.2
6	11650.00	37.4 AV	54.0	-16.6	3.65 H	299	25.2	12.2
7	#17475.00	58.5 PK	68.2	-9.7	1.54 H	269	39.8	18.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5568.19	50.8 PK	68.2	-17.4	1.58 V	136	48.7	2.1
2	*5825.00	109.6 PK			1.58 V	136	107.0	2.6
3	*5825.00	98.7 AV			1.58 V	136	96.1	2.6
4	#5930.34	50.4 PK	68.2	-17.8	1.58 V	136	47.5	2.9
5	11650.00	48.1 PK	74.0	-25.9	2.44 V	345	35.9	12.2
6	11650.00	36.3 AV	54.0	-17.7	2.44 V	345	24.1	12.2
7	#17475.00	58.5 PK	68.2	-9.7	1.46 V	291	39.8	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 38 : 5190 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	67.6 PK	74.0	-6.4	2.02 H	128	65.3	2.3
2	5150.00	52.4 AV	54.0	-1.6	2.02 H	128	50.1	2.3
3	*5190.00	112.1 PK			2.02 H	128	110.0	2.1
4	*5190.00	99.9 AV			2.02 H	128	97.8	2.1
5	#10380.00	50.2 PK	68.2	-18.0	3.61 H	312	38.2	12.0
6	15570.00	58.6 PK	74.0	-15.4	1.54 H	268	46.9	11.7
7	15570.00	45.0 AV	54.0	-9.0	1.54 H	268	33.3	11.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	59.4 PK	74.0	-14.6	1.60 V	89	57.1	2.3
2	5150.00	46.8 AV	54.0	-7.2	1.60 V	89	44.5	2.3
3	*5190.00	105.2 PK			1.60 V	89	103.1	2.1
4	*5190.00	93.5 AV			1.60 V	89	91.4	2.1
5	#10380.00	48.5 PK	68.2	-19.7	2.49 V	350	36.5	12.0
6	15570.00	58.5 PK	74.0	-15.5	1.37 V	293	46.8	11.7
7	15570.00	45.0 AV	54.0	-9.0	1.37 V	293	33.3	11.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 46 : 5230 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	66.3 PK	74.0	-7.7	1.99 H	131	64.0	2.3
2	5150.00	45.6 AV	54.0	-8.4	1.99 H	131	43.3	2.3
3	*5230.00	115.3 PK			1.99 H	131	113.2	2.1
4	*5230.00	103.4 AV			1.99 H	131	101.3	2.1
5	#10460.00	49.7 PK	68.2	-18.5	3.66 H	293	37.7	12.0
6	15690.00	58.9 PK	74.0	-15.1	1.47 H	276	47.0	11.9
7	15690.00	45.3 AV	54.0	-8.7	1.47 H	276	33.4	11.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	63.9 PK	74.0	-10.1	1.36 V	119	61.6	2.3
2	5150.00	43.8 AV	54.0	-10.2	1.36 V	119	41.5	2.3
3	*5230.00	108.3 PK			1.36 V	119	106.2	2.1
4	*5230.00	96.9 AV			1.36 V	119	94.8	2.1
5	#10460.00	47.9 PK	68.2	-20.3	2.52 V	341	35.9	12.0
6	15690.00	58.1 PK	74.0	-15.9	1.41 V	285	46.2	11.9
7	15690.00	44.4 AV	54.0	-9.6	1.41 V	285	32.5	11.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 54 : 5270 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5270.00	115.2 PK			1.93 H	135	113.3	1.9
2	*5270.00	103.1 AV			1.93 H	135	101.2	1.9
3	5350.00	67.1 PK	74.0	-6.9	1.93 H	135	65.2	1.9
4	5350.00	47.4 AV	54.0	-6.6	1.93 H	135	45.5	1.9
5	#10540.00	49.6 PK	68.2	-18.6	3.69 H	302	37.7	11.9
6	15810.00	58.7 PK	74.0	-15.3	1.50 H	284	47.3	11.4
7	15810.00	44.7 AV	54.0	-9.3	1.50 H	284	33.3	11.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5270.00	107.9 PK			1.34 V	123	106.0	1.9
2	*5270.00	96.7 AV			1.34 V	123	94.8	1.9
3	5350.00	64.7 PK	74.0	-9.3	1.34 V	123	62.8	1.9
4	5350.00	45.6 AV	54.0	-8.4	1.34 V	123	43.7	1.9
5	#10540.00	48.5 PK	68.2	-19.7	2.52 V	321	36.6	11.9
6	15810.00	58.2 PK	74.0	-15.8	1.39 V	267	46.8	11.4
7	15810.00	44.8 AV	54.0	-9.2	1.39 V	267	33.4	11.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 62 : 5310 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	111.8 PK			1.98 H	134	110.0	1.8
2	*5310.00	99.8 AV			1.98 H	134	98.0	1.8
3	5350.00	69.5 PK	74.0	-4.5	1.98 H	134	67.6	1.9
4	5350.00	52.3 AV	54.0	-1.7	1.98 H	134	50.4	1.9
5	10620.00	48.7 PK	74.0	-25.3	3.67 H	311	36.9	11.8
6	10620.00	37.0 AV	54.0	-17.0	3.67 H	311	25.2	11.8
7	15930.00	59.1 PK	74.0	-14.9	1.46 H	285	47.6	11.5
8	15930.00	45.2 AV	54.0	-8.8	1.46 H	285	33.7	11.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	105.5 PK			1.57 V	92	103.7	1.8
2	*5310.00	93.7 AV			1.57 V	92	91.9	1.8
3	5350.00	63.8 PK	74.0	-10.2	1.57 V	92	61.9	1.9
4	5350.00	44.9 AV	54.0	-9.1	1.57 V	92	43.0	1.9
5	5356.00	65.7 PK	74.0	-8.3	1.57 V	92	63.7	2.0
6	5356.00	44.0 AV	54.0	-10.0	1.57 V	92	42.0	2.0
7	10620.00	48.5 PK	74.0	-25.5	2.52 V	316	36.7	11.8
8	10620.00	36.1 AV	54.0	-17.9	2.52 V	316	24.3	11.8
9	15930.00	57.9 PK	74.0	-16.1	1.35 V	258	46.4	11.5
10	15930.00	44.3 AV	54.0	-9.7	1.35 V	258	32.8	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 802.11ax (HE40)	Channel	CH 102 : 5510 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	60.2 PK	74.0	-13.8	1.97 H	132	58.1	2.1
2	5460.00	46.0 AV	54.0	-8.0	1.97 H	132	43.9	2.1
3	#5467.25	66.7 PK	68.2	-1.5	1.97 H	132	64.5	2.2
4	*5510.00	110.5 PK			1.97 H	132	108.4	2.1
5	*5510.00	98.8 AV			1.97 H	132	96.7	2.1
6	11020.00	49.5 PK	74.0	-24.5	3.62 H	286	37.2	12.3
7	11020.00	37.5 AV	54.0	-16.5	3.62 H	286	25.2	12.3
8	#16530.00	58.7 PK	68.2	-9.5	1.58 H	274	44.8	13.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5456.24	54.9 PK	74.0	-19.1	1.55 V	96	52.8	2.1
2	5456.24	39.9 AV	54.0	-14.1	1.55 V	96	37.8	2.1
3	5460.00	52.3 PK	74.0	-21.7	1.55 V	96	50.2	2.1
4	5460.00	40.7 AV	54.0	-13.3	1.55 V	96	38.6	2.1
5	#5467.60	61.0 PK	68.2	-7.2	1.55 V	96	58.8	2.2
6	*5510.00	104.2 PK			1.55 V	96	102.1	2.1
7	*5510.00	92.8 AV			1.55 V	96	90.7	2.1
8	11020.00	48.6 PK	74.0	-25.4	2.55 V	331	36.3	12.3
9	11020.00	36.7 AV	54.0	-17.3	2.55 V	331	24.4	12.3
10	#16530.00	58.0 PK	68.2	-10.2	1.44 V	267	44.1	13.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 110 : 5550 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	58.5 PK	74.0	-15.5	1.89 H	129	56.4	2.1
2	5460.00	42.5 AV	54.0	-11.5	1.89 H	129	40.4	2.1
3	#5470.00	64.5 PK	68.2	-3.7	1.89 H	129	62.3	2.2
4	*5550.00	114.5 PK			1.89 H	129	112.4	2.1
5	*5550.00	102.7 AV			1.89 H	129	100.6	2.1
6	11100.00	49.8 PK	74.0	-24.2	3.72 H	290	37.9	11.9
7	11100.00	37.8 AV	54.0	-16.2	3.72 H	290	25.9	11.9
8	#16650.00	58.3 PK	68.2	-9.9	1.52 H	292	43.5	14.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	56.9 PK	74.0	-17.1	1.38 V	135	54.8	2.1
2	5460.00	40.9 AV	54.0	-13.1	1.38 V	135	38.8	2.1
3	#5470.00	60.4 PK	68.2	-7.8	1.38 V	135	58.2	2.2
4	*5550.00	108.3 PK			1.38 V	135	106.2	2.1
5	*5550.00	96.9 AV			1.38 V	135	94.8	2.1
6	11100.00	48.4 PK	74.0	-25.6	2.55 V	339	36.5	11.9
7	11100.00	36.3 AV	54.0	-17.7	2.55 V	339	24.4	11.9
8	#16650.00	58.4 PK	68.2	-9.8	1.47 V	281	43.6	14.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 134 : 5670 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	114.4 PK			2.00 H	117	112.1	2.3
2	*5670.00	102.2 AV			2.00 H	117	99.9	2.3
3	#5736.69	66.7 PK	68.2	-1.5	2.00 H	117	64.2	2.5
4	11340.00	49.7 PK	74.0	-24.3	3.62 H	306	37.5	12.2
5	11340.00	37.5 AV	54.0	-16.5	3.62 H	306	25.3	12.2
6	#17010.00	58.3 PK	68.2	-9.9	1.53 H	270	41.7	16.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	107.6 PK			1.35 V	121	105.3	2.3
2	*5670.00	96.1 AV			1.35 V	121	93.8	2.3
3	#5725.60	58.9 PK	68.2	-9.3	1.35 V	121	56.5	2.4
4	11340.00	48.3 PK	74.0	-25.7	2.58 V	339	36.1	12.2
5	11340.00	36.6 AV	54.0	-17.4	2.58 V	339	24.4	12.2
6	#17010.00	57.6 PK	68.2	-10.6	1.42 V	255	41.0	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 142 : 5710 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.7 PK	74.0	-21.3	2.00 H	136	50.6	2.1
2	5460.00	38.8 AV	54.0	-15.2	2.00 H	136	36.7	2.1
3	#5470.00	53.4 PK	68.2	-14.8	2.00 H	136	51.2	2.2
4	*5710.00	114.1 PK			2.00 H	136	111.7	2.4
5	*5710.00	102.2 AV			2.00 H	136	99.8	2.4
6	#5850.00	55.7 PK	68.2	-12.5	2.00 H	136	53.0	2.7
7	11420.00	49.7 PK	74.0	-24.3	3.70 H	305	37.2	12.5
8	11420.00	37.8 AV	54.0	-16.2	3.70 H	305	25.3	12.5
9	#17130.00	58.0 PK	68.2	-10.2	1.49 H	295	41.2	16.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.6 PK	74.0	-22.4	1.42 V	132	49.5	2.1
2	5460.00	37.8 AV	54.0	-16.2	1.42 V	132	35.7	2.1
3	#5470.00	52.8 PK	68.2	-15.4	1.42 V	132	50.6	2.2
4	*5710.00	107.8 PK			1.42 V	132	105.4	2.4
5	*5710.00	96.3 AV			1.42 V	132	93.9	2.4
6	#5850.00	53.4 PK	68.2	-14.8	1.42 V	132	50.7	2.7
7	11420.00	48.5 PK	74.0	-25.5	2.52 V	347	36.0	12.5
8	11420.00	36.5 AV	54.0	-17.5	2.52 V	347	24.0	12.5
9	#17130.00	58.4 PK	68.2	-9.8	1.48 V	265	41.6	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 151 : 5755 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.43	60.0 PK	68.2	-8.2	1.88 H	129	57.7	2.3
2	*5755.00	114.4 PK			1.88 H	129	111.9	2.5
3	*5755.00	102.6 AV			1.88 H	129	100.1	2.5
4	#5952.11	53.7 PK	68.2	-14.5	1.88 H	129	50.8	2.9
5	11510.00	48.9 PK	74.0	-25.1	3.62 H	305	36.3	12.6
6	11510.00	37.0 AV	54.0	-17.0	3.62 H	305	24.4	12.6
7	#17265.00	58.1 PK	68.2	-10.1	1.50 H	285	41.2	16.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.15	52.2 PK	68.2	-16.0	1.59 V	89	49.9	2.3
2	*5755.00	108.4 PK			1.59 V	89	105.9	2.5
3	*5755.00	96.8 AV			1.59 V	89	94.3	2.5
4	#5972.52	50.7 PK	68.2	-17.5	1.59 V	89	47.8	2.9
5	11510.00	48.9 PK	74.0	-25.1	2.60 V	331	36.3	12.6
6	11510.00	36.9 AV	54.0	-17.1	2.60 V	331	24.3	12.6
7	#17265.00	57.9 PK	68.2	-10.3	1.46 V	261	41.0	16.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.25	52.6 PK	68.2	-15.6	1.91 H	132	50.3	2.3
2	*5795.00	114.7 PK			1.91 H	132	112.1	2.6
3	*5795.00	102.8 AV			1.91 H	132	100.2	2.6
4	#5925.56	56.1 PK	68.2	-12.1	1.91 H	132	53.2	2.9
5	11590.00	49.5 PK	74.0	-24.5	3.67 H	309	36.9	12.6
6	11590.00	37.8 AV	54.0	-16.2	3.67 H	309	25.2	12.6
7	#17385.00	58.0 PK	68.2	-10.2	1.55 H	279	40.1	17.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5565.18	50.7 PK	68.2	-17.5	1.53 V	79	48.6	2.1
2	*5795.00	108.7 PK			1.53 V	79	106.1	2.6
3	*5795.00	97.1 AV			1.53 V	79	94.5	2.6
4	#5951.03	50.8 PK	68.2	-17.4	1.53 V	79	47.9	2.9
5	11590.00	48.0 PK	74.0	-26.0	2.49 V	329	35.4	12.6
6	11590.00	36.3 AV	54.0	-17.7	2.49 V	329	23.7	12.6
7	#17385.00	57.6 PK	68.2	-10.6	1.46 V	260	39.7	17.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 42 : 5210 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5147.10	66.3 PK	74.0	-7.7	1.92 H	138	64.0	2.3
2	5147.10	52.3 AV	54.0	-1.7	1.92 H	138	50.0	2.3
3	*5210.00	106.1 PK			1.92 H	138	104.0	2.1
4	*5210.00	94.5 AV			1.92 H	138	92.4	2.1
5	5350.00	51.4 PK	74.0	-22.6	1.92 H	138	49.5	1.9
6	5350.00	40.4 AV	54.0	-13.6	1.92 H	138	38.5	1.9
7	5358.10	53.1 PK	74.0	-20.9	1.92 H	138	51.1	2.0
8	5358.10	39.7 AV	54.0	-14.3	1.92 H	138	37.7	2.0
9	#10420.00	49.6 PK	68.2	-18.6	3.65 H	299	37.5	12.1
10	15630.00	58.4 PK	74.0	-15.6	1.49 H	293	46.7	11.7
11	15630.00	44.6 AV	54.0	-9.4	1.49 H	293	32.9	11.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5145.38	59.1 PK	74.0	-14.9	1.52 V	100	56.8	2.3
2	5145.38	44.4 AV	54.0	-9.6	1.52 V	100	42.1	2.3
3	*5210.00	98.8 PK			1.52 V	100	96.7	2.1
4	*5210.00	87.4 AV			1.52 V	100	85.3	2.1
5	5350.00	50.0 PK	74.0	-24.0	1.52 V	100	48.1	1.9
6	5350.00	38.3 AV	54.0	-15.7	1.52 V	100	36.4	1.9
7	#10420.00	48.4 PK	68.2	-19.8	2.54 V	320	36.3	12.1
8	15630.00	58.4 PK	74.0	-15.6	1.45 V	268	46.7	11.7
9	15630.00	45.0 AV	54.0	-9.0	1.45 V	268	33.3	11.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 58 : 5290 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.0 PK	74.0	-22.0	1.93 H	130	49.7	2.3
2	5150.00	41.9 AV	54.0	-12.1	1.93 H	130	39.6	2.3
3	*5290.00	106.5 PK			1.93 H	130	104.7	1.8
4	*5290.00	95.0 AV			1.93 H	130	93.2	1.8
5	5352.40	64.8 PK	74.0	-9.2	1.93 H	130	62.9	1.9
6	5352.40	52.3 AV	54.0	-1.7	1.93 H	130	50.4	1.9
7	5358.10	67.7 PK	74.0	-6.3	1.93 H	130	65.7	2.0
8	5358.10	51.5 AV	54.0	-2.5	1.93 H	130	49.5	2.0
9	#10580.00	49.4 PK	68.2	-18.8	3.72 H	303	37.6	11.8
10	15870.00	58.5 PK	74.0	-15.5	1.50 H	280	47.2	11.3
11	15870.00	45.0 AV	54.0	-9.0	1.50 H	280	33.7	11.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	50.0 PK	74.0	-24.0	1.63 V	91	47.7	2.3
2	5150.00	38.8 AV	54.0	-15.2	1.63 V	91	36.5	2.3
3	*5290.00	99.5 PK			1.63 V	91	97.7	1.8
4	*5290.00	88.1 AV			1.63 V	91	86.3	1.8
5	5367.22	57.9 PK	74.0	-16.1	1.63 V	91	55.9	2.0
6	5367.22	44.5 AV	54.0	-9.5	1.63 V	91	42.5	2.0
7	#10580.00	48.8 PK	68.2	-19.4	2.57 V	330	37.0	11.8
8	15870.00	58.6 PK	74.0	-15.4	1.43 V	254	47.3	11.3
9	15870.00	45.1 AV	54.0	-8.9	1.43 V	254	33.8	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 106 : 5530 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.6 PK	74.0	-9.4	2.03 H	117	62.5	2.1
2	5460.00	49.7 AV	54.0	-4.3	2.03 H	117	47.6	2.1
3	#5467.27	66.6 PK	68.2	-1.6	2.03 H	117	64.4	2.2
4	*5530.00	106.4 PK			2.03 H	117	104.4	2.0
5	*5530.00	94.5 AV			2.03 H	117	92.5	2.0
6	#5809.82	51.7 PK	68.2	-16.5	2.03 H	117	49.1	2.6
7	11060.00	50.0 PK	74.0	-24.0	3.68 H	296	37.9	12.1
8	11060.00	37.8 AV	54.0	-16.2	3.68 H	296	25.7	12.1
9	#16590.00	58.5 PK	68.2	-9.7	1.54 H	267	44.2	14.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5455.56	55.2 PK	74.0	-18.8	1.59 V	94	53.1	2.1
2	5455.56	41.2 AV	54.0	-12.8	1.59 V	94	39.1	2.1
3	#5467.50	56.0 PK	68.2	-12.2	1.59 V	94	53.8	2.2
4	*5530.00	97.8 PK			1.59 V	94	95.8	2.0
5	*5530.00	86.4 AV			1.59 V	94	84.4	2.0
6	#5759.62	52.0 PK	68.2	-16.2	1.59 V	94	49.5	2.5
7	11060.00	48.8 PK	74.0	-25.2	2.49 V	318	36.7	12.1
8	11060.00	36.8 AV	54.0	-17.2	2.49 V	318	24.7	12.1
9	#16590.00	58.3 PK	68.2	-9.9	1.45 V	276	44.0	14.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 122 : 5610 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	108.9 PK			1.93 H	132	106.8	2.1
2	*5610.00	97.8 AV			1.93 H	132	95.7	2.1
3	#5725.00	66.5 PK	68.2	-1.7	1.93 H	132	64.1	2.4
4	11220.00	49.2 PK	74.0	-24.8	3.68 H	298	37.1	12.1
5	11220.00	37.1 AV	54.0	-16.9	3.68 H	298	25.0	12.1
6	#16830.00	59.0 PK	68.2	-9.2	1.53 H	284	43.2	15.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	103.1 PK			1.36 V	128	101.0	2.1
2	*5610.00	90.3 AV			1.36 V	128	88.2	2.1
3	#5725.00	57.6 PK	68.2	-10.6	1.36 V	128	55.2	2.4
4	11220.00	48.4 PK	74.0	-25.6	2.58 V	334	36.3	12.1
5	11220.00	36.3 AV	54.0	-17.7	2.58 V	334	24.2	12.1
6	#16830.00	58.3 PK	68.2	-9.9	1.44 V	282	42.5	15.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 138 : 5690 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	56.4 PK	74.0	-17.6	1.93 H	131	54.3	2.1
2	5460.00	40.1 AV	54.0	-13.9	1.93 H	131	38.0	2.1
3	#5470.00	60.0 PK	68.2	-8.2	1.93 H	131	57.8	2.2
4	*5690.00	109.1 PK			1.93 H	131	106.8	2.3
5	*5690.00	98.0 AV			1.93 H	131	95.7	2.3
6	#5850.00	63.4 PK	68.2	-4.8	1.93 H	131	60.7	2.7
7	11380.00	49.8 PK	74.0	-24.2	3.66 H	300	37.4	12.4
8	11380.00	37.9 AV	54.0	-16.1	3.66 H	300	25.5	12.4
9	#17070.00	58.2 PK	68.2	-10.0	1.54 H	267	41.4	16.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	54.8 PK	74.0	-19.2	1.37 V	122	52.7	2.1
2	5460.00	38.2 AV	54.0	-15.8	1.37 V	122	36.1	2.1
3	#5470.00	57.6 PK	68.2	-10.6	1.37 V	122	55.4	2.2
4	*5690.00	102.8 PK			1.37 V	122	100.5	2.3
5	*5690.00	90.0 AV			1.37 V	122	87.7	2.3
6	#5850.00	59.6 PK	68.2	-8.6	1.37 V	122	56.9	2.7
7	11380.00	49.1 PK	74.0	-24.9	2.54 V	336	36.7	12.4
8	11380.00	37.0 AV	54.0	-17.0	2.54 V	336	24.6	12.4
9	#17070.00	57.9 PK	68.2	-10.3	1.42 V	278	41.1	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 155 : 5775 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.50	66.7 PK	68.2	-1.5	1.95 H	131	64.4	2.3
2	*5775.00	110.0 PK			1.95 H	131	107.5	2.5
3	*5775.00	98.9 AV			1.95 H	131	96.4	2.5
4	#5929.25	66.3 PK	68.2	-1.9	1.95 H	131	63.4	2.9
5	11550.00	49.5 PK	74.0	-24.5	3.70 H	309	37.0	12.5
6	11550.00	37.3 AV	54.0	-16.7	3.70 H	309	24.8	12.5
7	#17325.00	59.0 PK	68.2	-9.2	1.55 H	276	41.7	17.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.16	56.8 PK	68.2	-11.4	1.50 V	104	54.5	2.3
2	*5775.00	102.9 PK			1.50 V	104	100.4	2.5
3	*5775.00	91.6 AV			1.50 V	104	89.1	2.5
4	#5928.06	57.6 PK	68.2	-10.6	1.50 V	104	54.7	2.9
5	11550.00	48.8 PK	74.0	-25.2	2.58 V	327	36.3	12.5
6	11550.00	37.1 AV	54.0	-16.9	2.58 V	327	24.6	12.5
7	#17325.00	58.0 PK	68.2	-10.2	1.48 V	255	40.7	17.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5131.70	57.1 PK	74.0	-16.9	2.17 H	106	54.8	2.3
2	5131.70	47.2 AV	54.0	-6.8	2.17 H	106	44.9	2.3
3	5150.00	58.4 PK	74.0	-15.6	2.17 H	106	56.1	2.3
4	5150.00	45.7 AV	54.0	-8.3	2.17 H	106	43.4	2.3
5	*5180.00	122.7 PK			2.17 H	106	120.5	2.2
6	*5180.00	112.0 AV			2.17 H	106	109.8	2.2
7	#10360.00	49.9 PK	68.2	-18.3	2.75 H	353	38.1	11.8
8	15540.00	63.3 PK	74.0	-10.7	1.47 H	276	51.5	11.8
9	15540.00	49.8 AV	54.0	-4.2	1.47 H	276	38.0	11.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5148.80	61.7 PK	74.0	-12.3	1.93 V	120	59.4	2.3
2	5148.80	40.8 AV	54.0	-13.2	1.93 V	120	38.5	2.3
3	*5180.00	116.8 PK			1.93 V	120	114.6	2.2
4	*5180.00	104.9 AV			1.93 V	120	102.7	2.2
5	#10360.00	50.8 PK	68.2	-17.4	2.64 V	218	39.0	11.8
6	15540.00	61.8 PK	74.0	-12.2	1.52 V	288	50.0	11.8
7	15540.00	48.4 AV	54.0	-5.6	1.52 V	288	36.6	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.2 PK	74.0	-20.8	2.19 H	110	50.9	2.3
2	5150.00	39.3 AV	54.0	-14.7	2.19 H	110	37.0	2.3
3	*5200.00	122.2 PK			2.19 H	110	120.1	2.1
4	*5200.00	111.7 AV			2.19 H	110	109.6	2.1
5	#10400.00	50.5 PK	68.2	-17.7	2.78 H	355	38.5	12.0
6	15600.00	63.3 PK	74.0	-10.7	1.42 H	269	51.8	11.5
7	15600.00	49.9 AV	54.0	-4.1	1.42 H	269	38.4	11.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.9 PK	74.0	-22.1	1.93 V	120	49.6	2.3
2	5150.00	38.2 AV	54.0	-15.8	1.93 V	120	35.9	2.3
3	*5200.00	117.2 PK			1.93 V	120	115.1	2.1
4	*5200.00	105.3 AV			1.93 V	120	103.2	2.1
5	#10400.00	50.8 PK	68.2	-17.4	2.70 V	217	38.8	12.0
6	15600.00	61.3 PK	74.0	-12.7	1.56 V	273	49.8	11.5
7	15600.00	48.2 AV	54.0	-5.8	1.56 V	273	36.7	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.9 PK	74.0	-20.1	2.14 H	93	51.6	2.3
2	5150.00	39.4 AV	54.0	-14.6	2.14 H	93	37.1	2.3
3	*5240.00	122.3 PK			2.14 H	93	120.3	2.0
4	*5240.00	111.7 AV			2.14 H	93	109.7	2.0
5	5350.00	52.7 PK	74.0	-21.3	2.14 H	93	50.8	1.9
6	5350.00	38.7 AV	54.0	-15.3	2.14 H	93	36.8	1.9
7	#10480.00	50.2 PK	68.2	-18.0	2.69 H	356	38.3	11.9
8	15720.00	63.1 PK	74.0	-10.9	1.53 H	279	51.3	11.8
9	15720.00	49.7 AV	54.0	-4.3	1.53 H	279	37.9	11.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.4 PK	74.0	-22.6	1.88 V	122	49.1	2.3
2	5150.00	37.6 AV	54.0	-16.4	1.88 V	122	35.3	2.3
3	*5240.00	117.3 PK			1.88 V	122	115.3	2.0
4	*5240.00	105.3 AV			1.88 V	122	103.3	2.0
5	5350.00	49.4 PK	74.0	-24.6	1.88 V	122	47.5	1.9
6	5350.00	37.8 AV	54.0	-16.2	1.88 V	122	35.9	1.9
7	#10480.00	50.7 PK	68.2	-17.5	2.69 V	208	38.8	11.9
8	15720.00	61.2 PK	74.0	-12.8	1.52 V	276	49.4	11.8
9	15720.00	48.0 AV	54.0	-6.0	1.52 V	276	36.2	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.0 PK	74.0	-20.0	2.18 H	106	51.7	2.3
2	5150.00	39.5 AV	54.0	-14.5	2.18 H	106	37.2	2.3
3	*5260.00	123.1 PK			2.18 H	106	121.1	2.0
4	*5260.00	112.3 AV			2.18 H	106	110.3	2.0
5	5350.00	52.7 PK	74.0	-21.3	2.18 H	106	50.8	1.9
6	5350.00	38.8 AV	54.0	-15.2	2.18 H	106	36.9	1.9
7	#10520.00	49.9 PK	68.2	-18.3	2.75 H	348	37.9	12.0
8	15780.00	62.9 PK	74.0	-11.1	1.43 H	278	51.4	11.5
9	15780.00	49.4 AV	54.0	-4.6	1.43 H	278	37.9	11.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.0 PK	74.0	-23.0	1.94 V	115	48.7	2.3
2	5150.00	37.3 AV	54.0	-16.7	1.94 V	115	35.0	2.3
3	*5260.00	116.6 PK			1.94 V	115	114.6	2.0
4	*5260.00	104.7 AV			1.94 V	115	102.7	2.0
5	5350.00	50.1 PK	74.0	-23.9	1.94 V	115	48.2	1.9
6	5350.00	38.5 AV	54.0	-15.5	1.94 V	115	36.6	1.9
7	#10520.00	51.1 PK	68.2	-17.1	2.60 V	229	39.1	12.0
8	15780.00	61.6 PK	74.0	-12.4	1.49 V	282	50.1	11.5
9	15780.00	48.2 AV	54.0	-5.8	1.49 V	282	36.7	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	123.0 PK			2.23 H	90	121.3	1.7
2	*5300.00	112.4 AV			2.23 H	90	110.7	1.7
3	5350.00	53.5 PK	74.0	-20.5	2.23 H	90	51.6	1.9
4	5350.00	39.6 AV	54.0	-14.4	2.23 H	90	37.7	1.9
5	10600.00	49.4 PK	74.0	-24.6	2.70 H	342	37.5	11.9
6	10600.00	38.7 AV	54.0	-15.3	2.70 H	342	26.8	11.9
7	15900.00	63.7 PK	74.0	-10.3	1.52 H	277	52.4	11.3
8	15900.00	50.3 AV	54.0	-3.7	1.52 H	277	39.0	11.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	117.2 PK			1.89 V	123	115.5	1.7
2	*5300.00	105.2 AV			1.89 V	123	103.5	1.7
3	5350.00	52.3 PK	74.0	-21.7	1.89 V	123	50.4	1.9
4	5350.00	38.2 AV	54.0	-15.8	1.89 V	123	36.3	1.9
5	10600.00	51.0 PK	74.0	-23.0	2.61 V	212	39.1	11.9
6	10600.00	39.4 AV	54.0	-14.6	2.61 V	212	27.5	11.9
7	15900.00	61.9 PK	74.0	-12.1	1.51 V	303	50.6	11.3
8	15900.00	48.8 AV	54.0	-5.2	1.51 V	303	37.5	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	122.9 PK			2.10 H	100	121.1	1.8
2	*5320.00	112.3 AV			2.10 H	100	110.5	1.8
3	5350.06	60.0 PK	74.0	-14.0	2.10 H	100	58.1	1.9
4	5350.06	44.1 AV	54.0	-9.9	2.10 H	100	42.2	1.9
5	5356.15	69.1 PK	74.0	-4.9	2.10 H	100	67.1	2.0
6	5356.15	43.0 AV	54.0	-11.0	2.10 H	100	41.0	2.0
7	10640.00	50.2 PK	74.0	-23.8	2.78 H	349	38.4	11.8
8	10640.00	39.4 AV	54.0	-14.6	2.78 H	349	27.6	11.8
9	15960.00	62.9 PK	74.0	-11.1	1.43 H	287	51.3	11.6
10	15960.00	49.5 AV	54.0	-4.5	1.43 H	287	37.9	11.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.4 PK			1.90 V	118	114.6	1.8
2	*5320.00	104.6 AV			1.90 V	118	102.8	1.8
3	5363.40	61.0 PK	74.0	-13.0	1.90 V	118	59.0	2.0
4	5363.40	38.6 AV	54.0	-15.4	1.90 V	118	36.6	2.0
5	5368.70	49.7 PK	74.0	-24.3	1.90 V	118	47.7	2.0
6	5368.70	39.9 AV	54.0	-14.1	1.90 V	118	37.9	2.0
7	10640.00	50.8 PK	74.0	-23.2	2.61 V	228	39.0	11.8
8	10640.00	39.3 AV	54.0	-14.7	2.61 V	228	27.5	11.8
9	15960.00	61.6 PK	74.0	-12.4	1.57 V	296	50.0	11.6
10	15960.00	48.3 AV	54.0	-5.7	1.57 V	296	36.7	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5451.70	58.5 PK	74.0	-15.5	2.13 H	113	56.4	2.1
2	5451.70	45.5 AV	54.0	-8.5	2.13 H	113	43.4	2.1
3	5458.80	68.0 PK	74.0	-6.0	2.13 H	113	65.9	2.1
4	5458.80	42.1 AV	54.0	-11.9	2.13 H	113	40.0	2.1
5	#5465.40	61.7 PK	68.2	-6.5	2.13 H	113	59.6	2.1
6	*5500.00	123.1 PK			2.13 H	113	121.0	2.1
7	*5500.00	112.3 AV			2.13 H	113	110.2	2.1
8	11000.00	49.8 PK	74.0	-24.2	2.71 H	349	37.4	12.4
9	11000.00	38.8 AV	54.0	-15.2	2.71 H	349	26.4	12.4
10	#16500.00	62.8 PK	68.2	-5.4	1.43 H	271	49.1	13.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5456.74	58.8 PK	74.0	-15.2	1.83 V	132	56.7	2.1
2	5456.74	38.5 AV	54.0	-15.5	1.83 V	132	36.4	2.1
3	#5466.70	61.2 PK	68.2	-7.0	1.83 V	132	59.0	2.2
4	*5500.00	114.8 PK			1.83 V	132	112.7	2.1
5	*5500.00	103.9 AV			1.83 V	132	101.8	2.1
6	11000.00	50.4 PK	74.0	-23.6	2.70 V	223	38.0	12.4
7	11000.00	39.4 AV	54.0	-14.6	2.70 V	223	27.0	12.4
8	#16500.00	61.7 PK	68.2	-6.5	1.54 V	291	48.0	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 116 : 5580 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	122.2 PK			2.22 H	115	120.1	2.1
2	*5580.00	112.4 AV			2.22 H	115	110.3	2.1
3	11160.00	49.6 PK	74.0	-24.4	2.78 H	350	37.6	12.0
4	11160.00	39.0 AV	54.0	-15.0	2.78 H	350	27.0	12.0
5	#16740.00	63.4 PK	68.2	-4.8	1.45 H	270	48.1	15.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	117.5 PK			1.91 V	131	115.4	2.1
2	*5580.00	105.3 AV			1.91 V	131	103.2	2.1
3	11160.00	51.1 PK	74.0	-22.9	2.66 V	205	39.1	12.0
4	11160.00	39.8 AV	54.0	-14.2	2.66 V	205	27.8	12.0
5	#16740.00	61.7 PK	68.2	-6.5	1.47 V	285	46.4	15.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	120.8 PK			1.96 H	115	118.5	2.3
2	*5700.00	110.1 AV			1.96 H	115	107.8	2.3
3	#5725.00	66.5 PK	68.2	-1.7	1.96 H	115	64.1	2.4
4	11400.00	49.5 PK	74.0	-24.5	2.72 H	359	37.0	12.5
5	11400.00	38.7 AV	54.0	-15.3	2.72 H	359	26.2	12.5
6	#17100.00	63.1 PK	68.2	-5.1	1.51 H	267	46.3	16.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	114.4 PK			1.81 V	121	112.1	2.3
2	*5700.00	103.4 AV			1.81 V	121	101.1	2.3
3	#5725.00	57.9 PK	68.2	-10.3	1.81 V	121	55.5	2.4
4	11400.00	51.1 PK	74.0	-22.9	2.69 V	212	38.6	12.5
5	11400.00	39.9 AV	54.0	-14.1	2.69 V	212	27.4	12.5
6	#17100.00	62.3 PK	68.2	-5.9	1.55 V	275	45.5	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.7 PK	74.0	-21.3	2.19 H	109	50.6	2.1
2	5460.00	38.9 AV	54.0	-15.1	2.19 H	109	36.8	2.1
3	#5470.00	53.3 PK	68.2	-14.9	2.19 H	109	51.1	2.2
4	*5720.00	122.3 PK			2.19 H	109	119.9	2.4
5	*5720.00	111.5 AV			2.19 H	109	109.1	2.4
6	#5850.00	52.2 PK	68.2	-16.0	2.19 H	109	49.5	2.7
7	11440.00	49.6 PK	74.0	-24.4	2.74 H	351	37.2	12.4
8	11440.00	38.8 AV	54.0	-15.2	2.74 H	351	26.4	12.4
9	#17160.00	63.5 PK	68.2	-4.7	1.50 H	289	46.9	16.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.6 PK	74.0	-22.4	1.91 V	107	49.5	2.1
2	5460.00	38.3 AV	54.0	-15.7	1.91 V	107	36.2	2.1
3	#5470.00	50.1 PK	68.2	-18.1	1.91 V	107	47.9	2.2
4	*5720.00	117.0 PK			1.91 V	107	114.6	2.4
5	*5720.00	105.3 AV			1.91 V	107	102.9	2.4
6	#5850.00	51.2 PK	68.2	-17.0	1.91 V	107	48.5	2.7
7	11440.00	50.7 PK	74.0	-23.3	2.68 V	211	38.3	12.4
8	11440.00	39.7 AV	54.0	-14.3	2.68 V	211	27.3	12.4
9	#17160.00	61.9 PK	68.2	-6.3	1.53 V	293	45.3	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5614.78	53.3 PK	68.2	-14.9	2.05 H	111	51.2	2.1
2	*5745.00	124.6 PK			2.05 H	111	122.2	2.4
3	*5745.00	114.4 AV			2.05 H	111	112.0	2.4
4	#5951.91	51.8 PK	68.2	-16.4	2.05 H	111	48.9	2.9
5	11490.00	49.4 PK	74.0	-24.6	2.70 H	342	36.8	12.6
6	11490.00	38.7 AV	54.0	-15.3	2.70 H	342	26.1	12.6
7	#17235.00	63.5 PK	68.2	-4.7	1.50 H	291	46.7	16.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5567.24	50.2 PK	68.2	-18.0	2.08 V	130	48.1	2.1
2	*5745.00	117.0 PK			2.08 V	130	114.6	2.4
3	*5745.00	106.8 AV			2.08 V	130	104.4	2.4
4	#5959.39	51.2 PK	68.2	-17.0	2.08 V	130	48.3	2.9
5	11490.00	50.9 PK	74.0	-23.1	2.61 V	228	38.3	12.6
6	11490.00	39.6 AV	54.0	-14.4	2.61 V	228	27.0	12.6
7	#17235.00	61.8 PK	68.2	-6.4	1.58 V	273	45.0	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5552.79	53.1 PK	68.2	-15.1	2.07 H	113	51.0	2.1
2	*5785.00	124.1 PK			2.07 H	113	121.5	2.6
3	*5785.00	114.3 AV			2.07 H	113	111.7	2.6
4	#5994.66	50.7 PK	68.2	-17.5	2.07 H	113	47.8	2.9
5	11570.00	49.9 PK	74.0	-24.1	2.70 H	340	37.3	12.6
6	11570.00	39.0 AV	54.0	-15.0	2.70 H	340	26.4	12.6
7	#17355.00	63.6 PK	68.2	-4.6	1.52 H	280	45.9	17.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5555.65	51.1 PK	68.2	-17.1	2.05 V	132	49.0	2.1
2	*5785.00	117.3 PK			2.05 V	132	114.7	2.6
3	*5785.00	107.0 AV			2.05 V	132	104.4	2.6
4	#5935.31	50.5 PK	68.2	-17.7	2.05 V	132	47.6	2.9
5	11570.00	50.5 PK	74.0	-23.5	2.67 V	236	37.9	12.6
6	11570.00	39.3 AV	54.0	-14.7	2.67 V	236	26.7	12.6
7	#17355.00	63.7 PK	68.2	-4.5	1.50 V	275	46.0	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5574.21	52.7 PK	68.2	-15.5	1.99 H	108	50.6	2.1
2	*5825.00	125.0 PK			1.99 H	108	122.4	2.6
3	*5825.00	114.9 AV			1.99 H	108	112.3	2.6
4	#5967.35	51.1 PK	68.2	-17.1	1.99 H	108	48.2	2.9
5	11650.00	50.1 PK	74.0	-23.9	2.78 H	351	37.9	12.2
6	11650.00	39.2 AV	54.0	-14.8	2.78 H	351	27.0	12.2
7	#17475.00	63.6 PK	68.2	-4.6	1.44 H	276	44.9	18.7

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5637.72	50.4 PK	68.2	-17.8	2.06 V	126	48.1	2.3
2	*5825.00	116.8 PK			2.06 V	126	114.2	2.6
3	*5825.00	106.6 AV			2.06 V	126	104.0	2.6
4	#5990.80	51.7 PK	68.2	-16.5	2.06 V	126	48.8	2.9
5	11650.00	50.4 PK	74.0	-23.6	2.63 V	229	38.2	12.2
6	11650.00	39.0 AV	54.0	-15.0	2.63 V	229	26.8	12.2
7	#17475.00	61.7 PK	68.2	-6.5	1.51 V	283	43.0	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5148.90	66.4 PK	74.0	-7.6	2.01 H	107	64.1	2.3
2	5148.90	47.5 AV	54.0	-6.5	2.01 H	107	45.2	2.3
3	*5180.00	121.5 PK			2.01 H	107	119.3	2.2
4	*5180.00	110.6 AV			2.01 H	107	108.4	2.2
5	#10360.00	49.4 PK	68.2	-18.8	1.53 H	335	37.6	11.8
6	15540.00	61.9 PK	74.0	-12.1	1.32 H	286	50.1	11.8
7	15540.00	47.8 AV	54.0	-6.2	1.32 H	286	36.0	11.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5145.00	61.8 PK	74.0	-12.2	1.81 V	118	59.5	2.3
2	5145.00	42.0 AV	54.0	-12.0	1.81 V	118	39.7	2.3
3	*5180.00	114.2 PK			1.81 V	118	112.0	2.2
4	*5180.00	103.7 AV			1.81 V	118	101.5	2.2
5	#10360.00	50.5 PK	68.2	-17.7	2.74 V	258	38.7	11.8
6	15540.00	60.5 PK	74.0	-13.5	1.46 V	267	48.7	11.8
7	15540.00	46.8 AV	54.0	-7.2	1.46 V	267	35.0	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.2 PK	74.0	-19.8	2.04 H	117	51.9	2.3
2	5150.00	39.6 AV	54.0	-14.4	2.04 H	117	37.3	2.3
3	*5200.00	121.5 PK			2.04 H	117	119.4	2.1
4	*5200.00	110.5 AV			2.04 H	117	108.4	2.1
5	#10400.00	50.0 PK	68.2	-18.2	1.51 H	342	38.0	12.0
6	15600.00	62.3 PK	74.0	-11.7	1.32 H	295	50.8	11.5
7	15600.00	48.1 AV	54.0	-5.9	1.32 H	295	36.6	11.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.9 PK	74.0	-22.1	1.79 V	112	49.6	2.3
2	5150.00	37.9 AV	54.0	-16.1	1.79 V	112	35.6	2.3
3	*5200.00	115.0 PK			1.79 V	112	112.9	2.1
4	*5200.00	104.2 AV			1.79 V	112	102.1	2.1
5	#10400.00	50.7 PK	68.2	-17.5	2.79 V	253	38.7	12.0
6	15600.00	59.9 PK	74.0	-14.1	1.41 V	280	48.4	11.5
7	15600.00	46.4 AV	54.0	-7.6	1.41 V	280	34.9	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.9 PK	74.0	-20.1	1.96 H	96	51.6	2.3
2	5150.00	39.7 AV	54.0	-14.3	1.96 H	96	37.4	2.3
3	*5240.00	121.9 PK			1.96 H	96	119.9	2.0
4	*5240.00	110.8 AV			1.96 H	96	108.8	2.0
5	5350.00	53.0 PK	74.0	-21.0	1.96 H	96	51.1	1.9
6	5350.00	39.2 AV	54.0	-14.8	1.96 H	96	37.3	1.9
7	#10480.00	50.0 PK	68.2	-18.2	1.55 H	336	38.1	11.9
8	15720.00	62.2 PK	74.0	-11.8	1.27 H	290	50.4	11.8
9	15720.00	48.3 AV	54.0	-5.7	1.27 H	290	36.5	11.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.0 PK	74.0	-23.0	1.78 V	129	48.7	2.3
2	5150.00	37.5 AV	54.0	-16.5	1.78 V	129	35.2	2.3
3	*5240.00	113.9 PK			1.78 V	129	111.9	2.0
4	*5240.00	103.5 AV			1.78 V	129	101.5	2.0
5	5350.00	48.7 PK	74.0	-25.3	1.78 V	129	46.8	1.9
6	5350.00	37.3 AV	54.0	-16.7	1.78 V	129	35.4	1.9
7	#10480.00	50.3 PK	68.2	-17.9	2.73 V	258	38.4	11.9
8	15720.00	60.2 PK	74.0	-13.8	1.44 V	252	48.4	11.8
9	15720.00	46.5 AV	54.0	-7.5	1.44 V	252	34.7	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.8 PK	74.0	-20.2	2.05 H	117	51.5	2.3
2	5150.00	39.5 AV	54.0	-14.5	2.05 H	117	37.2	2.3
3	*5260.00	120.8 PK			2.05 H	117	118.8	2.0
4	*5260.00	110.2 AV			2.05 H	117	108.2	2.0
5	5350.00	52.4 PK	74.0	-21.6	2.05 H	117	50.5	1.9
6	5350.00	38.6 AV	54.0	-15.4	2.05 H	117	36.7	1.9
7	#10520.00	50.0 PK	68.2	-18.2	1.57 H	339	38.0	12.0
8	15780.00	61.9 PK	74.0	-12.1	1.32 H	295	50.4	11.5
9	15780.00	48.0 AV	54.0	-6.0	1.32 H	295	36.5	11.5

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.1 PK	74.0	-22.9	1.79 V	118	48.8	2.3
2	5150.00	37.3 AV	54.0	-16.7	1.79 V	118	35.0	2.3
3	*5260.00	114.4 PK			1.79 V	118	112.4	2.0
4	*5260.00	104.1 AV			1.79 V	118	102.1	2.0
5	5350.00	48.8 PK	74.0	-25.2	1.79 V	118	46.9	1.9
6	5350.00	37.4 AV	54.0	-16.6	1.79 V	118	35.5	1.9
7	#10520.00	50.7 PK	68.2	-17.5	2.71 V	258	38.7	12.0
8	15780.00	60.9 PK	74.0	-13.1	1.44 V	277	49.4	11.5
9	15780.00	47.2 AV	54.0	-6.8	1.44 V	277	35.7	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.