

RF Mode	TX 802.11ax (HE80)	Channel	CH 106 : 5530 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5465.80	66.5 PK	68.2	-1.7	1.98 H	119	64.4	2.1
2	#5485.10	64.1 PK	68.2	-4.1	1.98 H	119	62.0	2.1
3	*5530.00	108.5 PK			1.98 H	119	106.5	2.0
4	*5530.00	95.2 AV			1.98 H	119	93.2	2.0
5	#5841.45	51.2 PK	68.2	-17.0	1.98 H	119	48.5	2.7
6	11060.00	55.4 PK	74.0	-18.6	1.00 H	346	43.3	12.1
7	11060.00	45.5 AV	54.0	-8.5	1.00 H	346	33.4	12.1
8	#16590.00	59.4 PK	68.2	-8.8	1.37 H	267	45.1	14.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5453.40	52.0 PK	74.0	-22.0	1.26 V	110	49.9	2.1
2	5453.40	40.8 AV	54.0	-13.2	1.26 V	110	38.7	2.1
3	5460.00	50.4 PK	74.0	-23.6	1.26 V	110	48.3	2.1
4	5460.00	41.1 AV	54.0	-12.9	1.26 V	110	39.0	2.1
5	#5469.60	58.2 PK	68.2	-10.0	1.26 V	110	56.0	2.2
6	*5530.00	98.2 PK			1.26 V	110	96.2	2.0
7	*5530.00	85.8 AV			1.26 V	110	83.8	2.0
8	#5775.10	51.5 PK	68.2	-16.7	1.26 V	110	49.0	2.5
9	11060.00	55.2 PK	74.0	-18.8	2.20 V	190	43.1	12.1
10	11060.00	46.3 AV	54.0	-7.7	2.20 V	190	34.2	12.1
11	#16590.00	60.3 PK	68.2	-7.9	1.61 V	267	46.0	14.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 122 : 5610 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	109.9 PK			2.01 H	122	107.8	2.1
2	*5610.00	98.4 AV			2.01 H	122	96.3	2.1
3	#5725.00	66.5 PK	68.2	-1.7	2.01 H	122	64.1	2.4
4	11220.00	55.5 PK	74.0	-18.5	1.09 H	325	43.4	12.1
5	11220.00	45.3 AV	54.0	-8.7	1.09 H	325	33.2	12.1
6	#16830.00	59.1 PK	68.2	-9.1	1.41 H	264	43.3	15.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	102.3 PK			1.23 V	125	100.2	2.1
2	*5610.00	90.4 AV			1.23 V	125	88.3	2.1
3	#5725.00	58.3 PK	68.2	-9.9	1.23 V	125	55.9	2.4
4	11220.00	55.1 PK	74.0	-18.9	2.27 V	170	43.0	12.1
5	11220.00	46.3 AV	54.0	-7.7	2.27 V	170	34.2	12.1
6	#16830.00	60.5 PK	68.2	-7.7	1.65 V	283	44.7	15.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 138 : 5690 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	52.7 PK	74.0	-21.3	1.99 H	124	50.6	2.1
2	5460.00	39.7 AV	54.0	-14.3	1.99 H	124	37.6	2.1
3	#5470.00	56.5 PK	68.2	-11.7	1.99 H	124	54.3	2.2
4	*5690.00	111.4 PK			1.99 H	124	109.1	2.3
5	*5690.00	99.9 AV			1.99 H	124	97.6	2.3
6	#5850.00	66.3 PK	68.2	-1.9	1.99 H	124	63.6	2.7
7	11380.00	55.3 PK	74.0	-18.7	1.09 H	329	42.9	12.4
8	11380.00	45.4 AV	54.0	-8.6	1.09 H	329	33.0	12.4
9	#17070.00	59.0 PK	68.2	-9.2	1.35 H	270	42.2	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.9 PK	74.0	-22.1	1.22 V	132	49.8	2.1
2	5460.00	38.8 AV	54.0	-15.2	1.22 V	132	36.7	2.1
3	#5470.00	54.8 PK	68.2	-13.4	1.22 V	132	52.6	2.2
4	*5690.00	102.8 PK			1.22 V	132	100.5	2.3
5	*5690.00	91.0 AV			1.22 V	132	88.7	2.3
6	#5850.00	59.3 PK	68.2	-8.9	1.22 V	132	56.6	2.7
7	11380.00	54.6 PK	74.0	-19.4	2.16 V	175	42.2	12.4
8	11380.00	46.0 AV	54.0	-8.0	2.16 V	175	33.6	12.4
9	#17070.00	59.6 PK	68.2	-8.6	1.62 V	257	42.8	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 802.11ax (HE80)	Channel	CH 155 : 5775 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5632.21	66.1 PK	68.2	-2.1	1.97 H	121	63.8	2.3
2	*5775.00	111.7 PK			1.97 H	121	109.2	2.5
3	*5775.00	99.8 AV			1.97 H	121	97.3	2.5
4	#5929.56	66.7 PK	68.2	-1.5	1.97 H	121	63.8	2.9
5	11550.00	54.9 PK	74.0	-19.1	1.02 H	349	42.4	12.5
6	11550.00	44.7 AV	54.0	-9.3	1.02 H	349	32.2	12.5
7	#17325.00	58.6 PK	68.2	-9.6	1.41 H	287	41.3	17.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.65	61.4 PK	68.2	-6.8	1.19 V	119	59.1	2.3
2	*5775.00	103.4 PK			1.19 V	119	100.9	2.5
3	*5775.00	90.2 AV			1.19 V	119	87.7	2.5
4	#5928.97	60.2 PK	68.2	-8.0	1.19 V	119	57.3	2.9
5	11550.00	55.3 PK	74.0	-18.7	2.26 V	189	42.8	12.5
6	11550.00	46.3 AV	54.0	-7.7	2.26 V	189	33.8	12.5
7	#17325.00	60.1 PK	68.2	-8.1	1.70 V	256	42.8	17.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5131.80	57.6 PK	74.0	-16.4	2.02 H	120	55.3	2.3
2	5131.80	48.5 AV	54.0	-5.5	2.02 H	120	46.2	2.3
3	5141.10	62.9 PK	74.0	-11.1	2.02 H	120	60.6	2.3
4	5141.10	42.8 AV	54.0	-11.2	2.02 H	120	40.5	2.3
5	*5180.00	125.9 PK			2.02 H	120	123.7	2.2
6	*5180.00	116.2 AV			2.02 H	120	114.0	2.2
7	#10360.00	58.1 PK	68.2	-10.1	2.68 H	316	46.3	11.8
8	15540.00	62.1 PK	74.0	-11.9	1.51 H	282	50.3	11.8
9	15540.00	48.8 AV	54.0	-5.2	1.51 H	282	37.0	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5145.50	60.8 PK	74.0	-13.2	1.57 V	124	58.5	2.3
2	5145.50	40.0 AV	54.0	-14.0	1.57 V	124	37.7	2.3
3	5147.50	52.0 PK	74.0	-22.0	1.57 V	124	49.7	2.3
4	5147.50	40.5 AV	54.0	-13.5	1.57 V	124	38.2	2.3
5	*5180.00	115.9 PK			1.57 V	124	113.7	2.2
6	*5180.00	106.9 AV			1.57 V	124	104.7	2.2
7	#10360.00	59.8 PK	68.2	-8.4	2.64 V	323	48.0	11.8
8	15540.00	63.4 PK	74.0	-10.6	1.38 V	270	51.6	11.8
9	15540.00	50.4 AV	54.0	-3.6	1.38 V	270	38.6	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.7 PK	74.0	-20.3	2.04 H	116	51.4	2.3
2	5150.00	43.1 AV	54.0	-10.9	2.04 H	116	40.8	2.3
3	*5200.00	126.3 PK			2.04 H	116	124.2	2.1
4	*5200.00	116.7 AV			2.04 H	116	114.6	2.1
5	#10400.00	58.9 PK	68.2	-9.3	2.68 H	321	46.9	12.0
6	15600.00	62.3 PK	74.0	-11.7	1.50 H	298	50.8	11.5
7	15600.00	49.3 AV	54.0	-4.7	1.50 H	298	37.8	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.3 PK	74.0	-21.7	1.54 V	129	50.0	2.3
2	5150.00	41.6 AV	54.0	-12.4	1.54 V	129	39.3	2.3
3	*5200.00	116.4 PK			1.54 V	129	114.3	2.1
4	*5200.00	107.4 AV			1.54 V	129	105.3	2.1
5	#10400.00	60.2 PK	68.2	-8.0	2.58 V	315	48.2	12.0
6	15600.00	63.9 PK	74.0	-10.1	1.37 V	285	52.4	11.5
7	15600.00	50.8 AV	54.0	-3.2	1.37 V	285	39.3	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.0 PK	74.0	-22.0	2.02 H	121	49.7	2.3
2	5150.00	38.4 AV	54.0	-15.6	2.02 H	121	36.1	2.3
3	*5240.00	126.3 PK			2.02 H	121	124.3	2.0
4	*5240.00	116.6 AV			2.02 H	121	114.6	2.0
5	5350.00	50.9 PK	74.0	-23.1	2.02 H	121	49.0	1.9
6	5350.00	38.0 AV	54.0	-16.0	2.02 H	121	36.1	1.9
7	#10480.00	58.2 PK	68.2	-10.0	2.69 H	318	46.3	11.9
8	15720.00	62.0 PK	74.0	-12.0	1.49 H	274	50.2	11.8
9	15720.00	48.5 AV	54.0	-5.5	1.49 H	274	36.7	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.2 PK	74.0	-20.8	1.59 V	112	50.9	2.3
2	5150.00	38.9 AV	54.0	-15.1	1.59 V	112	36.6	2.3
3	*5240.00	115.6 PK			1.59 V	112	113.6	2.0
4	*5240.00	106.4 AV			1.59 V	112	104.4	2.0
5	5350.00	50.8 PK	74.0	-23.2	1.59 V	112	48.9	1.9
6	5350.00	37.6 AV	54.0	-16.4	1.59 V	112	35.7	1.9
7	#10480.00	59.5 PK	68.2	-8.7	2.67 V	336	47.6	11.9
8	15720.00	63.3 PK	74.0	-10.7	1.36 V	272	51.5	11.8
9	15720.00	50.4 AV	54.0	-3.6	1.36 V	272	38.6	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	51.6 PK	74.0	-22.4	2.02 H	123	49.3	2.3
2	5150.00	38.1 AV	54.0	-15.9	2.02 H	123	35.8	2.3
3	*5260.00	125.2 PK			2.02 H	123	123.2	2.0
4	*5260.00	115.8 AV			2.02 H	123	113.8	2.0
5	5350.00	50.9 PK	74.0	-23.1	2.02 H	123	49.0	1.9
6	5350.00	38.2 AV	54.0	-15.8	2.02 H	123	36.3	1.9
7	#10520.00	57.8 PK	68.2	-10.4	2.65 H	326	45.8	12.0
8	15780.00	62.6 PK	74.0	-11.4	1.49 H	270	51.1	11.5
9	15780.00	49.0 AV	54.0	-5.0	1.49 H	270	37.5	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.4 PK	74.0	-20.6	1.53 V	121	51.1	2.3
2	5150.00	39.0 AV	54.0	-15.0	1.53 V	121	36.7	2.3
3	*5260.00	116.1 PK			1.53 V	121	114.1	2.0
4	*5260.00	106.9 AV			1.53 V	121	104.9	2.0
5	5350.00	50.3 PK	74.0	-23.7	1.53 V	121	48.4	1.9
6	5350.00	37.4 AV	54.0	-16.6	1.53 V	121	35.5	1.9
7	#10520.00	59.5 PK	68.2	-8.7	2.59 V	324	47.5	12.0
8	15780.00	63.8 PK	74.0	-10.2	1.32 V	278	52.3	11.5
9	15780.00	50.7 AV	54.0	-3.3	1.32 V	278	39.2	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	126.0 PK			2.03 H	129	124.3	1.7
2	*5300.00	116.4 AV			2.03 H	129	114.7	1.7
3	5350.00	53.8 PK	74.0	-20.2	2.03 H	129	51.9	1.9
4	5350.00	43.3 AV	54.0	-10.7	2.03 H	129	41.4	1.9
5	10600.00	57.6 PK	74.0	-16.4	2.69 H	329	45.7	11.9
6	10600.00	47.3 AV	54.0	-6.7	2.69 H	329	35.4	11.9
7	15900.00	62.0 PK	74.0	-12.0	1.54 H	270	50.7	11.3
8	15900.00	48.8 AV	54.0	-5.2	1.54 H	270	37.5	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	115.9 PK			1.56 V	117	114.2	1.7
2	*5300.00	106.9 AV			1.56 V	117	105.2	1.7
3	5350.00	52.6 PK	74.0	-21.4	1.56 V	117	50.7	1.9
4	5350.00	41.5 AV	54.0	-12.5	1.56 V	117	39.6	1.9
5	10600.00	59.3 PK	74.0	-14.7	2.62 V	316	47.4	11.9
6	10600.00	48.1 AV	54.0	-5.9	2.62 V	316	36.2	11.9
7	15900.00	63.4 PK	74.0	-10.6	1.35 V	265	52.1	11.3
8	15900.00	50.2 AV	54.0	-3.8	1.35 V	265	38.9	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	124.7 PK			2.02 H	123	122.9	1.8
2	*5320.00	116.3 AV			2.02 H	123	114.5	1.8
3	5353.40	60.9 PK	74.0	-13.1	2.02 H	123	59.0	1.9
4	5353.40	47.2 AV	54.0	-6.8	2.02 H	123	45.3	1.9
5	5361.10	72.5 PK	74.0	-1.5	2.02 H	123	70.5	2.0
6	5361.10	46.2 AV	54.0	-7.8	2.02 H	123	44.2	2.0
7	10640.00	58.0 PK	74.0	-16.0	2.64 H	308	46.2	11.8
8	10640.00	47.8 AV	54.0	-6.2	2.64 H	308	36.0	11.8
9	15960.00	61.9 PK	74.0	-12.1	1.47 H	275	50.3	11.6
10	15960.00	48.4 AV	54.0	-5.6	1.47 H	275	36.8	11.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	115.3 PK			1.59 V	120	113.5	1.8
2	*5320.00	106.4 AV			1.59 V	120	104.6	1.8
3	5360.57	54.9 PK	74.0	-19.1	1.59 V	120	52.9	2.0
4	5360.57	38.8 AV	54.0	-15.2	1.59 V	120	36.8	2.0
5	5367.84	48.3 PK	74.0	-25.7	1.59 V	120	46.3	2.0
6	5367.84	40.0 AV	54.0	-14.0	1.59 V	120	38.0	2.0
7	10640.00	59.8 PK	74.0	-14.2	2.66 V	333	48.0	11.8
8	10640.00	48.7 AV	54.0	-5.3	2.66 V	333	36.9	11.8
9	15960.00	63.6 PK	74.0	-10.4	1.34 V	277	52.0	11.6
10	15960.00	50.4 AV	54.0	-3.6	1.34 V	277	38.8	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5451.80	57.9 PK	74.0	-16.1	1.98 H	103	55.8	2.1
2	5451.80	47.5 AV	54.0	-6.5	1.98 H	103	45.4	2.1
3	5457.80	63.4 PK	74.0	-10.6	1.98 H	103	61.3	2.1
4	5457.80	41.9 AV	54.0	-12.1	1.98 H	103	39.8	2.1
5	#5467.50	66.2 PK	68.2	-2.0	1.98 H	103	64.0	2.2
6	*5500.00	123.8 PK			1.98 H	103	121.7	2.1
7	*5500.00	113.7 AV			1.98 H	103	111.6	2.1
8	11000.00	57.6 PK	74.0	-16.4	2.64 H	301	45.2	12.4
9	11000.00	47.5 AV	54.0	-6.5	2.64 H	301	35.1	12.4
10	#16500.00	61.8 PK	68.2	-6.4	1.49 H	295	48.1	13.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5457.85	50.5 PK	74.0	-23.5	1.53 V	115	48.4	2.1
2	5457.85	38.2 AV	54.0	-15.8	1.53 V	115	36.1	2.1
3	#5468.00	51.5 PK	68.2	-16.7	1.53 V	115	49.3	2.2
4	*5500.00	113.1 PK			1.53 V	115	111.0	2.1
5	*5500.00	103.4 AV			1.53 V	115	101.3	2.1
6	11000.00	59.9 PK	74.0	-14.1	2.69 V	314	47.5	12.4
7	11000.00	48.4 AV	54.0	-5.6	2.69 V	314	36.0	12.4
8	#16500.00	62.9 PK	68.2	-5.3	1.40 V	263	49.2	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 116 : 5580 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	126.3 PK			2.04 H	122	124.2	2.1
2	*5580.00	116.6 AV			2.04 H	122	114.5	2.1
3	11160.00	58.0 PK	74.0	-16.0	2.71 H	324	46.0	12.0
4	11160.00	47.6 AV	54.0	-6.4	2.71 H	324	35.6	12.0
5	#16740.00	62.3 PK	68.2	-5.9	1.47 H	287	47.0	15.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	116.5 PK			1.53 V	120	114.4	2.1
2	*5580.00	107.3 AV			1.53 V	120	105.2	2.1
3	11160.00	59.5 PK	74.0	-14.5	2.62 V	309	47.5	12.0
4	11160.00	47.9 AV	54.0	-6.1	2.62 V	309	35.9	12.0
5	#16740.00	62.9 PK	68.2	-5.3	1.35 V	280	47.6	15.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	125.2 PK			2.07 H	111	122.9	2.3
2	*5700.00	113.1 AV			2.07 H	111	110.8	2.3
3	#5725.43	66.6 PK	68.2	-1.6	2.07 H	111	64.2	2.4
4	11400.00	58.5 PK	74.0	-15.5	2.64 H	321	46.0	12.5
5	11400.00	48.0 AV	54.0	-6.0	2.64 H	321	35.5	12.5
6	#17100.00	61.9 PK	68.2	-6.3	1.53 H	296	45.1	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	112.6 PK			1.56 V	126	110.3	2.3
2	*5700.00	103.8 AV			1.56 V	126	101.5	2.3
3	#5725.00	61.6 PK	68.2	-6.6	1.56 V	126	59.2	2.4
4	11400.00	60.4 PK	74.0	-13.6	2.66 V	321	47.9	12.5
5	11400.00	48.9 AV	54.0	-5.1	2.66 V	321	36.4	12.5
6	#17100.00	63.7 PK	68.2	-4.5	1.34 V	283	46.9	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.1 PK	74.0	-22.9	2.06 H	115	49.0	2.1
2	5460.00	38.6 AV	54.0	-15.4	2.06 H	115	36.5	2.1
3	#5470.00	51.8 PK	68.2	-16.4	2.06 H	115	49.6	2.2
4	*5720.00	126.2 PK			2.06 H	115	123.8	2.4
5	*5720.00	116.7 AV			2.06 H	115	114.3	2.4
6	#5850.00	51.6 PK	68.2	-16.6	2.06 H	115	48.9	2.7
7	11440.00	57.5 PK	74.0	-16.5	2.71 H	318	45.1	12.4
8	11440.00	47.4 AV	54.0	-6.6	2.71 H	318	35.0	12.4
9	#17160.00	62.2 PK	68.2	-6.0	1.49 H	267	45.6	16.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.3 PK	74.0	-22.7	1.55 V	129	49.2	2.1
2	5460.00	38.4 AV	54.0	-15.6	1.55 V	129	36.3	2.1
3	#5470.00	52.3 PK	68.2	-15.9	1.55 V	129	50.1	2.2
4	*5720.00	116.4 PK			1.55 V	129	114.0	2.4
5	*5720.00	107.3 AV			1.55 V	129	104.9	2.4
6	#5850.00	51.5 PK	68.2	-16.7	1.55 V	129	48.8	2.7
7	11440.00	59.8 PK	74.0	-14.2	2.60 V	325	47.4	12.4
8	11440.00	48.5 AV	54.0	-5.5	2.60 V	325	36.1	12.4
9	#17160.00	63.2 PK	68.2	-5.0	1.43 V	262	46.6	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5577.87	53.2 PK	68.2	-15.0	1.83 H	127	51.1	2.1
2	*5745.00	126.3 PK			1.83 H	127	123.9	2.4
3	*5745.00	116.3 AV			1.83 H	127	113.9	2.4
4	#5956.68	52.2 PK	68.2	-16.0	1.83 H	127	49.3	2.9
5	11490.00	59.5 PK	74.0	-14.5	2.65 H	320	46.9	12.6
6	11490.00	49.8 AV	54.0	-4.2	2.65 H	320	37.2	12.6
7	#17235.00	63.8 PK	68.2	-4.4	1.51 H	264	47.0	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5580.97	51.4 PK	68.2	-16.8	1.94 V	118	49.3	2.1
2	*5745.00	115.1 PK			1.94 V	118	112.7	2.4
3	*5745.00	105.3 AV			1.94 V	118	102.9	2.4
4	#5979.23	52.5 PK	68.2	-15.7	1.94 V	118	49.6	2.9
5	11490.00	59.1 PK	74.0	-14.9	2.67 V	330	46.5	12.6
6	11490.00	49.3 AV	54.0	-4.7	2.67 V	330	36.7	12.6
7	#17235.00	64.9 PK	68.2	-3.3	1.39 V	285	48.1	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5552.33	53.7 PK	68.2	-14.5	1.91 H	108	51.6	2.1
2	*5785.00	127.1 PK			1.91 H	108	124.5	2.6
3	*5785.00	117.0 AV			1.91 H	108	114.4	2.6
4	#5952.25	54.6 PK	68.2	-13.6	1.91 H	108	51.7	2.9
5	11570.00	59.4 PK	74.0	-14.6	2.68 H	310	46.8	12.6
6	11570.00	49.7 AV	54.0	-4.3	2.68 H	310	37.1	12.6
7	#17355.00	63.6 PK	68.2	-4.6	1.46 H	278	45.9	17.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5639.77	51.7 PK	68.2	-16.5	1.90 V	110	49.4	2.3
2	*5785.00	115.8 PK			1.90 V	110	113.2	2.6
3	*5785.00	106.1 AV			1.90 V	110	103.5	2.6
4	#6013.66	51.6 PK	68.2	-16.6	1.90 V	110	48.7	2.9
5	11570.00	60.9 PK	74.0	-13.1	2.69 V	320	48.3	12.6
6	11570.00	50.5 AV	54.0	-3.5	2.69 V	320	37.9	12.6
7	#17355.00	65.1 PK	68.2	-3.1	1.40 V	280	47.4	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU26)	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5616.62	54.1 PK	68.2	-14.1	1.95 H	112	52.0	2.1
2	*5825.00	126.6 PK			1.95 H	112	124.0	2.6
3	*5825.00	116.5 AV			1.95 H	112	113.9	2.6
4	#5925.27	52.8 PK	68.2	-15.4	1.95 H	112	49.9	2.9
5	11650.00	59.6 PK	74.0	-14.4	2.68 H	315	47.4	12.2
6	11650.00	49.7 AV	54.0	-4.3	2.68 H	315	37.5	12.2
7	#17475.00	63.6 PK	68.2	-4.6	1.45 H	272	44.9	18.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5559.83	52.2 PK	68.2	-16.0	1.92 V	107	50.1	2.1
2	*5825.00	115.2 PK			1.92 V	107	112.6	2.6
3	*5825.00	105.3 AV			1.92 V	107	102.7	2.6
4	#6020.23	51.9 PK	68.2	-16.3	1.92 V	107	48.9	3.0
5	11650.00	58.1 PK	74.0	-15.9	2.72 V	324	45.9	12.2
6	11650.00	48.4 AV	54.0	-5.6	2.72 V	324	36.2	12.2
7	#17475.00	64.6 PK	68.2	-3.6	1.44 V	289	45.9	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5145.17	67.5 PK	74.0	-6.5	2.16 H	118	65.2	2.3
2	5145.17	47.3 AV	54.0	-6.7	2.16 H	118	45.0	2.3
3	*5180.00	122.3 PK			2.16 H	118	120.1	2.2
4	*5180.00	112.0 AV			2.16 H	118	109.8	2.2
5	#10360.00	55.5 PK	68.2	-12.7	1.29 H	337	43.7	11.8
6	15540.00	62.7 PK	74.0	-11.3	1.48 H	287	50.9	11.8
7	15540.00	48.6 AV	54.0	-5.4	1.48 H	287	36.8	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5146.30	67.5 PK	74.0	-6.5	1.26 V	125	65.2	2.3
2	5146.30	43.0 AV	54.0	-11.0	1.26 V	125	40.7	2.3
3	*5180.00	118.3 PK			1.26 V	125	116.1	2.2
4	*5180.00	105.9 AV			1.26 V	125	103.7	2.2
5	#10360.00	55.7 PK	68.2	-12.5	1.54 V	307	43.9	11.8
6	15540.00	61.4 PK	74.0	-12.6	1.64 V	294	49.6	11.8
7	15540.00	47.5 AV	54.0	-6.5	1.64 V	294	35.7	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.0 PK	74.0	-20.0	2.17 H	111	51.7	2.3
2	5150.00	43.5 AV	54.0	-10.5	2.17 H	111	41.2	2.3
3	*5200.00	122.2 PK			2.17 H	111	120.1	2.1
4	*5200.00	111.9 AV			2.17 H	111	109.8	2.1
5	#10400.00	55.0 PK	68.2	-13.2	1.30 H	335	43.0	12.0
6	15600.00	62.9 PK	74.0	-11.1	1.52 H	277	51.4	11.5
7	15600.00	48.7 AV	54.0	-5.3	1.52 H	277	37.2	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.5 PK	74.0	-21.5	1.31 V	130	50.2	2.3
2	5150.00	42.0 AV	54.0	-12.0	1.31 V	130	39.7	2.3
3	*5200.00	118.7 PK			1.31 V	130	116.6	2.1
4	*5200.00	106.4 AV			1.31 V	130	104.3	2.1
5	#10400.00	55.7 PK	68.2	-12.5	1.57 V	296	43.7	12.0
6	15600.00	61.1 PK	74.0	-12.9	1.61 V	309	49.6	11.5
7	15600.00	47.1 AV	54.0	-6.9	1.61 V	309	35.6	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.5 PK	74.0	-21.5	2.15 H	108	50.2	2.3
2	5150.00	38.7 AV	54.0	-15.3	2.15 H	108	36.4	2.3
3	*5240.00	122.5 PK			2.15 H	108	120.5	2.0
4	*5240.00	112.4 AV			2.15 H	108	110.4	2.0
5	5350.00	50.5 PK	74.0	-23.5	2.15 H	108	48.6	1.9
6	5350.00	37.7 AV	54.0	-16.3	2.15 H	108	35.8	1.9
7	#10480.00	55.9 PK	68.2	-12.3	1.29 H	334	44.0	11.9
8	15720.00	62.8 PK	74.0	-11.2	1.45 H	290	51.0	11.8
9	15720.00	48.8 AV	54.0	-5.2	1.45 H	290	37.0	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.8 PK	74.0	-21.2	1.24 V	114	50.5	2.3
2	5150.00	38.4 AV	54.0	-15.6	1.24 V	114	36.1	2.3
3	*5240.00	118.3 PK			1.24 V	114	116.3	2.0
4	*5240.00	105.8 AV			1.24 V	114	103.8	2.0
5	5350.00	50.5 PK	74.0	-23.5	1.24 V	114	48.6	1.9
6	5350.00	37.1 AV	54.0	-16.9	1.24 V	114	35.2	1.9
7	#10480.00	55.8 PK	68.2	-12.4	1.57 V	305	43.9	11.9
8	15720.00	61.2 PK	74.0	-12.8	1.62 V	282	49.4	11.8
9	15720.00	47.1 AV	54.0	-6.9	1.62 V	282	35.3	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.1 PK	74.0	-21.9	2.14 H	118	49.8	2.3
2	5150.00	38.8 AV	54.0	-15.2	2.14 H	118	36.5	2.3
3	*5260.00	122.7 PK			2.14 H	118	120.7	2.0
4	*5260.00	112.3 AV			2.14 H	118	110.3	2.0
5	5350.00	51.0 PK	74.0	-23.0	2.14 H	118	49.1	1.9
6	5350.00	38.3 AV	54.0	-15.7	2.14 H	118	36.4	1.9
7	#10520.00	55.0 PK	68.2	-13.2	1.30 H	338	43.0	12.0
8	15780.00	62.2 PK	74.0	-11.8	1.45 H	299	50.7	11.5
9	15780.00	48.2 AV	54.0	-5.8	1.45 H	299	36.7	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	53.1 PK	74.0	-20.9	1.23 V	136	50.8	2.3
2	5150.00	38.6 AV	54.0	-15.4	1.23 V	136	36.3	2.3
3	*5260.00	118.2 PK			1.23 V	136	116.2	2.0
4	*5260.00	106.0 AV			1.23 V	136	104.0	2.0
5	5350.00	51.5 PK	74.0	-22.5	1.23 V	136	49.6	1.9
6	5350.00	38.0 AV	54.0	-16.0	1.23 V	136	36.1	1.9
7	#10520.00	55.7 PK	68.2	-12.5	1.50 V	313	43.7	12.0
8	15780.00	60.8 PK	74.0	-13.2	1.68 V	292	49.3	11.5
9	15780.00	47.2 AV	54.0	-6.8	1.68 V	292	35.7	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	122.6 PK			2.22 H	130	120.9	1.7
2	*5300.00	112.2 AV			2.22 H	130	110.5	1.7
3	5350.00	54.5 PK	74.0	-19.5	2.22 H	130	52.6	1.9
4	5350.00	43.6 AV	54.0	-10.4	2.22 H	130	41.7	1.9
5	10600.00	55.5 PK	74.0	-18.5	1.35 H	321	43.6	11.9
6	10600.00	43.1 AV	54.0	-10.9	1.35 H	321	31.2	11.9
7	15900.00	62.5 PK	74.0	-11.5	1.54 H	279	51.2	11.3
8	15900.00	48.2 AV	54.0	-5.8	1.54 H	279	36.9	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	118.3 PK			1.28 V	113	116.6	1.7
2	*5300.00	105.8 AV			1.28 V	113	104.1	1.7
3	5350.00	52.7 PK	74.0	-21.3	1.28 V	113	50.8	1.9
4	5350.00	41.9 AV	54.0	-12.1	1.28 V	113	40.0	1.9
5	10600.00	55.7 PK	74.0	-18.3	1.53 V	314	43.8	11.9
6	10600.00	44.3 AV	54.0	-9.7	1.53 V	314	32.4	11.9
7	15900.00	61.2 PK	74.0	-12.8	1.63 V	283	49.9	11.3
8	15900.00	47.6 AV	54.0	-6.4	1.63 V	283	36.3	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	122.1 PK			1.87 H	131	120.3	1.8
2	*5320.00	111.8 AV			1.87 H	131	110.0	1.8
3	5350.00	69.5 PK	74.0	-4.5	1.87 H	131	67.6	1.9
4	5350.00	45.6 AV	54.0	-8.4	1.87 H	131	43.7	1.9
5	10640.00	55.7 PK	74.0	-18.3	1.25 H	340	43.9	11.8
6	10640.00	43.1 AV	54.0	-10.9	1.25 H	340	31.3	11.8
7	15960.00	62.0 PK	74.0	-12.0	1.42 H	288	50.4	11.6
8	15960.00	48.1 AV	54.0	-5.9	1.42 H	288	36.5	11.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	117.9 PK			1.29 V	120	116.1	1.8
2	*5320.00	105.5 AV			1.29 V	120	103.7	1.8
3	5356.30	65.6 PK	74.0	-8.4	1.29 V	120	63.6	2.0
4	5356.30	41.3 AV	54.0	-12.7	1.29 V	120	39.3	2.0
5	5368.70	51.2 PK	74.0	-22.8	1.29 V	120	49.2	2.0
6	5368.70	41.6 AV	54.0	-12.4	1.29 V	120	39.6	2.0
7	10640.00	55.3 PK	74.0	-18.7	1.49 V	301	43.5	11.8
8	10640.00	43.7 AV	54.0	-10.3	1.49 V	301	31.9	11.8
9	15960.00	61.6 PK	74.0	-12.4	1.62 V	285	50.0	11.6
10	15960.00	47.9 AV	54.0	-6.1	1.62 V	285	36.3	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5454.00	58.0 PK	74.0	-16.0	1.81 H	124	55.9	2.1
2	5454.00	43.6 AV	54.0	-10.4	1.81 H	124	41.5	2.1
3	5458.00	60.4 PK	74.0	-13.6	1.81 H	124	58.3	2.1
4	5458.00	42.6 AV	54.0	-11.4	1.81 H	124	40.5	2.1
5	#5467.30	66.2 PK	68.2	-2.0	1.81 H	124	64.0	2.2
6	*5500.00	121.9 PK			1.81 H	124	119.8	2.1
7	*5500.00	111.6 AV			1.81 H	124	109.5	2.1
8	11000.00	55.7 PK	74.0	-18.3	1.34 H	343	43.3	12.4
9	11000.00	43.5 AV	54.0	-10.5	1.34 H	343	31.1	12.4
10	#16500.00	62.3 PK	68.2	-5.9	1.51 H	274	48.6	13.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	53.6 PK	74.0	-20.4	1.21 V	116	51.5	2.1
2	5460.00	40.4 AV	54.0	-13.6	1.21 V	116	38.3	2.1
3	#5466.70	65.3 PK	68.2	-2.9	1.21 V	116	63.1	2.2
4	*5500.00	119.1 PK			1.21 V	116	117.0	2.1
5	*5500.00	106.5 AV			1.21 V	116	104.4	2.1
6	11000.00	56.1 PK	74.0	-17.9	1.50 V	321	43.7	12.4
7	11000.00	44.4 AV	54.0	-9.6	1.50 V	321	32.0	12.4
8	#16500.00	60.7 PK	68.2	-7.5	1.63 V	281	47.0	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 116 : 5580 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	122.5 PK			2.18 H	125	120.4	2.1
2	*5580.00	112.1 AV			2.18 H	125	110.0	2.1
3	11160.00	55.2 PK	74.0	-18.8	1.35 H	325	43.2	12.0
4	11160.00	42.7 AV	54.0	-11.3	1.35 H	325	30.7	12.0
5	#16740.00	62.8 PK	68.2	-5.4	1.45 H	283	47.5	15.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	118.3 PK			1.29 V	131	116.2	2.1
2	*5580.00	105.8 AV			1.29 V	131	103.7	2.1
3	11160.00	55.9 PK	74.0	-18.1	1.54 V	299	43.9	12.0
4	11160.00	44.4 AV	54.0	-9.6	1.54 V	299	32.4	12.0
5	#16740.00	61.2 PK	68.2	-7.0	1.59 V	290	45.9	15.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 140 : 5700 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	119.1 PK			2.03 H	118	116.8	2.3
2	*5700.00	108.8 AV			2.03 H	118	106.5	2.3
3	#5726.93	66.2 PK	68.2	-2.0	2.03 H	118	63.8	2.4
4	11400.00	55.8 PK	74.0	-18.2	1.25 H	333	43.3	12.5
5	11400.00	43.2 AV	54.0	-10.8	1.25 H	333	30.7	12.5
6	#17100.00	63.2 PK	68.2	-5.0	1.52 H	289	46.4	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	114.6 PK			1.32 V	129	112.3	2.3
2	*5700.00	102.1 AV			1.32 V	129	99.8	2.3
3	#5728.00	58.9 PK	68.2	-9.3	1.32 V	129	56.4	2.5
4	11400.00	56.2 PK	74.0	-17.8	1.55 V	312	43.7	12.5
5	11400.00	44.7 AV	54.0	-9.3	1.55 V	312	32.2	12.5
6	#17100.00	61.7 PK	68.2	-6.5	1.59 V	281	44.9	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 144 : 5720 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	50.8 PK	74.0	-23.2	2.20 H	120	48.7	2.1
2	5460.00	38.2 AV	54.0	-15.8	2.20 H	120	36.1	2.1
3	#5470.00	51.9 PK	68.2	-16.3	2.20 H	120	49.7	2.2
4	*5720.00	122.4 PK			2.20 H	120	120.0	2.4
5	*5720.00	112.3 AV			2.20 H	120	109.9	2.4
6	#5850.00	51.5 PK	68.2	-16.7	2.20 H	120	48.8	2.7
7	11440.00	55.9 PK	74.0	-18.1	1.32 H	333	43.5	12.4
8	11440.00	43.3 AV	54.0	-10.7	1.32 H	333	30.9	12.4
9	#17160.00	62.6 PK	68.2	-5.6	1.52 H	271	46.0	16.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	51.1 PK	74.0	-22.9	1.29 V	117	49.0	2.1
2	5460.00	38.1 AV	54.0	-15.9	1.29 V	117	36.0	2.1
3	#5470.00	52.5 PK	68.2	-15.7	1.29 V	117	50.3	2.2
4	*5720.00	118.4 PK			1.29 V	117	116.0	2.4
5	*5720.00	106.2 AV			1.29 V	117	103.8	2.4
6	#5850.00	50.8 PK	68.2	-17.4	1.29 V	117	48.1	2.7
7	11440.00	55.2 PK	74.0	-18.8	1.50 V	317	42.8	12.4
8	11440.00	44.0 AV	54.0	-10.0	1.50 V	317	31.6	12.4
9	#17160.00	61.3 PK	68.2	-6.9	1.68 V	302	44.7	16.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 149 : 5745 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5559.08	52.5 PK	68.2	-15.7	2.10 H	107	50.4	2.1
2	*5745.00	125.2 PK			2.10 H	107	122.8	2.4
3	*5745.00	115.2 AV			2.10 H	107	112.8	2.4
4	#5954.77	51.7 PK	68.2	-16.5	2.10 H	107	48.8	2.9
5	11490.00	58.1 PK	74.0	-15.9	1.30 H	358	45.5	12.6
6	11490.00	46.8 AV	54.0	-7.2	1.30 H	358	34.2	12.6
7	#17235.00	62.8 PK	68.2	-5.4	1.53 H	284	46.0	16.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5641.81	52.3 PK	68.2	-15.9	1.02 V	121	50.0	2.3
2	*5745.00	116.4 PK			1.02 V	121	114.0	2.4
3	*5745.00	105.8 AV			1.02 V	121	103.4	2.4
4	#5960.79	51.9 PK	68.2	-16.3	1.02 V	121	49.0	2.9
5	11490.00	58.4 PK	74.0	-15.6	1.51 V	295	45.8	12.6
6	11490.00	46.8 AV	54.0	-7.2	1.51 V	295	34.2	12.6
7	#17235.00	61.0 PK	68.2	-7.2	1.64 V	277	44.2	16.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 157 : 5785 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5588.23	52.5 PK	68.2	-15.7	2.03 H	106	50.4	2.1
2	*5785.00	125.5 PK			2.03 H	106	122.9	2.6
3	*5785.00	115.4 AV			2.03 H	106	112.8	2.6
4	#5940.20	51.8 PK	68.2	-16.4	2.03 H	106	48.9	2.9
5	11570.00	56.3 PK	74.0	-17.7	1.29 H	360	43.7	12.6
6	11570.00	45.4 AV	54.0	-8.6	1.29 H	360	32.8	12.6
7	#17355.00	63.6 PK	68.2	-4.6	1.48 H	287	45.9	17.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5591.37	50.8 PK	68.2	-17.4	1.05 V	119	48.7	2.1
2	*5785.00	116.6 PK			1.05 V	119	114.0	2.6
3	*5785.00	106.1 AV			1.05 V	119	103.5	2.6
4	#5985.01	50.1 PK	68.2	-18.1	1.05 V	119	47.2	2.9
5	11570.00	58.1 PK	74.0	-15.9	1.49 V	306	45.5	12.6
6	11570.00	46.7 AV	54.0	-7.3	1.49 V	306	34.1	12.6
7	#17355.00	60.9 PK	68.2	-7.3	1.58 V	280	43.2	17.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU52)	Channel	CH 165 : 5825 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5584.16	52.4 PK	68.2	-15.8	2.06 H	101	50.3	2.1
2	*5825.00	125.7 PK			2.06 H	101	123.1	2.6
3	*5825.00	115.5 AV			2.06 H	101	112.9	2.6
4	#5981.86	51.6 PK	68.2	-16.6	2.06 H	101	48.7	2.9
5	11650.00	57.0 PK	74.0	-17.0	1.30 H	354	44.8	12.2
6	11650.00	45.9 AV	54.0	-8.1	1.30 H	354	33.7	12.2
7	#17475.00	64.8 PK	68.2	-3.4	1.45 H	289	46.1	18.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5606.76	51.0 PK	68.2	-17.2	1.10 V	123	48.9	2.1
2	*5825.00	116.9 PK			1.10 V	123	114.3	2.6
3	*5825.00	106.3 AV			1.10 V	123	103.7	2.6
4	#5947.16	51.2 PK	68.2	-17.0	1.10 V	123	48.3	2.9
5	11650.00	57.9 PK	74.0	-16.1	1.46 V	308	45.7	12.2
6	11650.00	46.5 AV	54.0	-7.5	1.46 V	308	34.3	12.2
7	#17475.00	60.4 PK	68.2	-7.8	1.57 V	266	41.7	18.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 36 : 5180 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5137.40	55.8 PK	74.0	-18.2	1.90 H	129	53.5	2.3
2	5137.40	45.9 AV	54.0	-8.1	1.90 H	129	43.6	2.3
3	5148.80	58.7 PK	74.0	-15.3	1.90 H	129	56.4	2.3
4	5148.80	44.9 AV	54.0	-9.1	1.90 H	129	42.6	2.3
5	*5180.00	120.3 PK			1.90 H	129	118.1	2.2
6	*5180.00	109.1 AV			1.90 H	129	106.9	2.2
7	#10360.00	53.8 PK	68.2	-14.4	1.30 H	347	42.0	11.8
8	15540.00	60.4 PK	74.0	-13.6	1.53 H	300	48.6	11.8
9	15540.00	47.2 AV	54.0	-6.8	1.53 H	300	35.4	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5148.40	51.8 PK	74.0	-22.2	1.59 V	120	49.5	2.3
2	5148.40	40.6 AV	54.0	-13.4	1.59 V	120	38.3	2.3
3	*5180.00	114.6 PK			1.59 V	120	112.4	2.2
4	*5180.00	101.6 AV			1.59 V	120	99.4	2.2
5	#10360.00	55.2 PK	68.2	-13.0	1.44 V	316	43.4	11.8
6	15540.00	59.2 PK	74.0	-14.8	1.52 V	284	47.4	11.8
7	15540.00	46.8 AV	54.0	-7.2	1.52 V	284	35.0	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 40 : 5200 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.6 PK	74.0	-19.4	1.92 H	143	52.3	2.3
2	5150.00	44.0 AV	54.0	-10.0	1.92 H	143	41.7	2.3
3	*5200.00	120.2 PK			1.92 H	143	118.1	2.1
4	*5200.00	108.9 AV			1.92 H	143	106.8	2.1
5	#10400.00	54.2 PK	68.2	-14.0	1.27 H	355	42.2	12.0
6	15600.00	60.4 PK	74.0	-13.6	1.52 H	309	48.9	11.5
7	15600.00	47.2 AV	54.0	-6.8	1.52 H	309	35.7	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.9 PK	74.0	-21.1	1.58 V	123	50.6	2.3
2	5150.00	42.4 AV	54.0	-11.6	1.58 V	123	40.1	2.3
3	*5200.00	114.7 PK			1.58 V	123	112.6	2.1
4	*5200.00	101.9 AV			1.58 V	123	99.8	2.1
5	#10400.00	55.1 PK	68.2	-13.1	1.45 V	305	43.1	12.0
6	15600.00	59.5 PK	74.0	-14.5	1.53 V	273	48.0	11.5
7	15600.00	47.2 AV	54.0	-6.8	1.53 V	273	35.7	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 48 : 5240 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.5 PK	74.0	-21.5	1.86 H	115	50.2	2.3
2	5150.00	38.6 AV	54.0	-15.4	1.86 H	115	36.3	2.3
3	*5240.00	120.2 PK			1.86 H	115	118.2	2.0
4	*5240.00	108.7 AV			1.86 H	115	106.7	2.0
5	5350.00	51.3 PK	74.0	-22.7	1.86 H	115	49.4	1.9
6	5350.00	38.2 AV	54.0	-15.8	1.86 H	115	36.3	1.9
7	#10480.00	53.1 PK	68.2	-15.1	1.25 H	343	41.2	11.9
8	15720.00	60.2 PK	74.0	-13.8	1.49 H	300	48.4	11.8
9	15720.00	47.0 AV	54.0	-7.0	1.49 H	300	35.2	11.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.7 PK	74.0	-21.3	1.59 V	135	50.4	2.3
2	5150.00	38.6 AV	54.0	-15.4	1.59 V	135	36.3	2.3
3	*5240.00	114.8 PK			1.59 V	135	112.8	2.0
4	*5240.00	101.9 AV			1.59 V	135	99.9	2.0
5	5350.00	49.7 PK	74.0	-24.3	1.59 V	135	47.8	1.9
6	5350.00	36.6 AV	54.0	-17.4	1.59 V	135	34.7	1.9
7	#10480.00	54.8 PK	68.2	-13.4	1.44 V	310	42.9	11.9
8	15720.00	59.0 PK	74.0	-15.0	1.52 V	280	47.2	11.8
9	15720.00	46.9 AV	54.0	-7.1	1.52 V	280	35.1	11.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 52 : 5260 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.3 PK	74.0	-21.7	1.88 H	115	50.0	2.3
2	5150.00	38.6 AV	54.0	-15.4	1.88 H	115	36.3	2.3
3	*5260.00	120.3 PK			1.88 H	115	118.3	2.0
4	*5260.00	109.0 AV			1.88 H	115	107.0	2.0
5	5350.00	50.1 PK	74.0	-23.9	1.88 H	115	48.2	1.9
6	5350.00	37.4 AV	54.0	-16.6	1.88 H	115	35.5	1.9
7	#10520.00	54.2 PK	68.2	-14.0	1.25 H	357	42.2	12.0
8	15780.00	60.1 PK	74.0	-13.9	1.56 H	300	48.6	11.5
9	15780.00	47.1 AV	54.0	-6.9	1.56 H	300	35.6	11.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	52.4 PK	74.0	-21.6	1.56 V	119	50.1	2.3
2	5150.00	38.1 AV	54.0	-15.9	1.56 V	119	35.8	2.3
3	*5260.00	115.2 PK			1.56 V	119	113.2	2.0
4	*5260.00	102.1 AV			1.56 V	119	100.1	2.0
5	5350.00	50.0 PK	74.0	-24.0	1.56 V	119	48.1	1.9
6	5350.00	36.9 AV	54.0	-17.1	1.56 V	119	35.0	1.9
7	#10520.00	55.0 PK	68.2	-13.2	1.49 V	313	43.0	12.0
8	15780.00	58.8 PK	74.0	-15.2	1.57 V	294	47.3	11.5
9	15780.00	46.6 AV	54.0	-7.4	1.57 V	294	35.1	11.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 60 : 5300 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	120.3 PK			1.95 H	127	118.6	1.7
2	*5300.00	109.3 AV			1.95 H	127	107.6	1.7
3	5350.00	54.3 PK	74.0	-19.7	1.95 H	127	52.4	1.9
4	5350.00	43.8 AV	54.0	-10.2	1.95 H	127	41.9	1.9
5	10600.00	53.8 PK	74.0	-20.2	1.35 H	346	41.9	11.9
6	10600.00	42.7 AV	54.0	-11.3	1.35 H	346	30.8	11.9
7	15900.00	61.1 PK	74.0	-12.9	1.54 H	306	49.8	11.3
8	15900.00	47.7 AV	54.0	-6.3	1.54 H	306	36.4	11.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	114.5 PK			1.60 V	112	112.8	1.7
2	*5300.00	101.5 AV			1.60 V	112	99.8	1.7
3	5350.00	52.5 PK	74.0	-21.5	1.60 V	112	50.6	1.9
4	5350.00	41.7 AV	54.0	-12.3	1.60 V	112	39.8	1.9
5	10600.00	54.6 PK	74.0	-19.4	1.47 V	311	42.7	11.9
6	10600.00	43.8 AV	54.0	-10.2	1.47 V	311	31.9	11.9
7	15900.00	59.8 PK	74.0	-14.2	1.47 V	281	48.5	11.3
8	15900.00	47.4 AV	54.0	-6.6	1.47 V	281	36.1	11.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 64 : 5320 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	120.8 PK			2.00 H	118	119.0	1.8
2	*5320.00	109.8 AV			2.00 H	118	108.0	1.8
3	5351.80	70.8 PK	74.0	-3.2	2.00 H	118	68.9	1.9
4	5351.80	45.5 AV	54.0	-8.5	2.00 H	118	43.6	1.9
5	10640.00	53.3 PK	74.0	-20.7	1.32 H	334	41.5	11.8
6	10640.00	42.6 AV	54.0	-11.4	1.32 H	334	30.8	11.8
7	15960.00	60.8 PK	74.0	-13.2	1.49 H	315	49.2	11.6
8	15960.00	47.3 AV	54.0	-6.7	1.49 H	315	35.7	11.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	112.3 PK			1.48 V	129	110.5	1.8
2	*5320.00	101.9 AV			1.48 V	129	100.1	1.8
3	5351.80	56.0 PK	74.0	-18.0	1.48 V	129	54.1	1.9
4	5351.80	39.2 AV	54.0	-14.8	1.48 V	129	37.3	1.9
5	5362.10	51.1 PK	74.0	-22.9	1.48 V	129	49.1	2.0
6	5362.10	40.4 AV	54.0	-13.6	1.48 V	129	38.4	2.0
7	10640.00	54.6 PK	74.0	-19.4	1.49 V	304	42.8	11.8
8	10640.00	44.0 AV	54.0	-10.0	1.49 V	304	32.2	11.8
9	15960.00	59.3 PK	74.0	-14.7	1.48 V	284	47.7	11.6
10	15960.00	47.0 AV	54.0	-7.0	1.48 V	284	35.4	11.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX 20MHz Preamble 802.11ax (RU106)	Channel	CH 100 : 5500 MHz
Frequency Range	1GHz ~ 40GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5458.36	56.4 PK	74.0	-17.6	2.01 H	118	54.3	2.1
2	5458.36	46.4 AV	54.0	-7.6	2.01 H	118	44.3	2.1
3	#5464.82	66.1 PK	68.2	-2.1	2.01 H	118	64.0	2.1
4	*5500.00	121.3 PK			2.01 H	118	119.2	2.1
5	*5500.00	110.2 AV			2.01 H	118	108.1	2.1
6	11000.00	54.0 PK	74.0	-20.0	1.36 H	349	41.6	12.4
7	11000.00	43.2 AV	54.0	-10.8	1.36 H	349	30.8	12.4
8	#16500.00	60.7 PK	68.2	-7.5	1.55 H	310	47.0	13.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5451.60	48.9 PK	74.0	-25.1	1.47 V	125	46.8	2.1
2	5451.60	39.1 AV	54.0	-14.9	1.47 V	125	37.0	2.1
3	5458.90	51.5 PK	74.0	-22.5	1.47 V	125	49.4	2.1
4	5458.90	38.5 AV	54.0	-15.5	1.47 V	125	36.4	2.1
5	#5467.60	61.4 PK	68.2	-6.8	1.47 V	125	59.2	2.2
6	*5500.00	113.7 PK			1.47 V	125	111.6	2.1
7	*5500.00	102.2 AV			1.47 V	125	100.1	2.1
8	11000.00	54.2 PK	74.0	-19.8	1.41 V	305	41.8	12.4
9	11000.00	43.7 AV	54.0	-10.3	1.41 V	305	31.3	12.4
10	#16500.00	59.0 PK	68.2	-9.2	1.53 V	272	45.3	13.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency.
6. " # " : The radiated frequency is out of the restricted band.