

RF Exposure Evaluation

Test report
On Behalf of
Dongguan Lingjie Electronics & Technology Co., Ltd
For
Wireless Mouse
Model No.: E702

FCC ID: 2ANBU-E702

Prepared for : Dongguan Lingjie Electronics & Technology Co., Ltd
Building A Floor 1to4 and B Floor 1to5, No. 16 Zhenxing North Road,
Taiyuan Community, Xiegang Town, Dongguan, Guangdong, 523590, China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Jul. 13, 2020 – Jul. 22, 2020

Date of Report: Jul. 22, 2020

1 General Description of EUT

| | |
|------------------------|------------------------|
| Product Name: | Wireless Mouse |
| Model/Type reference: | E702 |
| Serial Model: | N/A |
| Trade Mark: | N/A |
| FCC ID | 2ANBU-E702 |
| Hardware Version: | V4.0 |
| Software Version: | V1.0 |
| Operation frequency: | 2402.5MHz to 2480.5MHz |
| Channel separation: | $\geq 3\text{MHz}$ |
| Channel number: | 16 |
| Modulation Technology: | GFSK |
| Antenna Type: | PCB Antenna |
| Antenna Gain: | 0dBi |
| Power Supply: | DC1.5V from AA battery |

Note:

1. For more detailed features description, please refer to the Manual.

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The results is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

3 EUT RF Exposure

For 2.4G

| GFSK | | | | | | |
|--|---|-------------------------|-----------------------|-------|------------------|---------------------|
| Channel | Maximum Peak Conducted Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power | | Calculated value | Exclusion threshold |
| | | | (dBm) | (mW) | | |
| Lowest (2402.5Hz) | -10.093 | -11±1 | -10 | 0.100 | 0.031 | 3.0 |
| Middle (2441.5MHz) | -10.766 | -11±1 | -10 | 0.100 | 0.031 | |
| Highest (2480.5MHz) | -11.829 | -11±1 | -10 | 0.100 | 0.031 | |
| Conclusion: the calculated value ≤ 3.0 , SAR is exempted. | | | | | | |

Remark: The Max Conducted Peak Output Power data refer to report Report No.: HK2007211845-E