

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Smart Mike
Model Name	Smart Mike 102
FCC ID	2ANCFSMARTMIKE102

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (unitless)

E =electric field strength in V/m

d =measurement distance in meters (m)

wifi

$$P_t = 9.14 \text{ dBm} = 8.20 \text{ mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (8.20 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.462(\text{GHz})}] = 2.57 < 3.0 \text{ for 1-g SAR}$$

BT

$$P_t = 89.04 \text{ dBuV/m} = 0.24 \text{ mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (0.24 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.076 < 3.0 \text{ for 1-g SAR}$$

Simultaneous transmission between Zigbee and WiFi transmitter

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg, for test separation distances } \leq 50 \text{ mm;}$

where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

$$\text{SAR} = (2.57 + 0.076) / 7.5 = 0.35 \text{ W/kg} < 1.6 \text{ W/kg}$$

4. CONCLUSION

The SAR evaluation is not required.