



TEST REPORT

Application No.: GZCR2108020826AT
Applicant: SZ DJI Osmo Technology Co., Ltd.
Address of Applicant: 4F, Jingkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen
Manufacturer: SZ DJI Osmo Technology Co., Ltd.
Address of Manufacturer: 4F, Jingkou Community Comprehensive Service Building, No. 83 Bishui Road North, Guangming Street, Guangming District, Shenzhen
Equipment Under Test (EUT):
EUT Name: DJI Action 2
Model No.: MC211
Trade mark: DJI
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2021-08-19
Date of Test: 2021-08-20 to 2021-08-25
Date of Issue: 2021-08-27

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kobe Jian
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
SGS-CSTC Standards Technical Services Co., Ltd. No. 198 Kexu Road, Science Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.ssgroup.com.cn
Guangzhou Branch Testing & Inspection Laboratory 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-08-27		Original

Authorized for issue by				
				
		Curry Wu /Project Engineer		
				
		Ricky Liu/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	9
4.7 Abnormalities from Standard Conditions.....	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement.....	13
6.1 Antenna Requirement	13
6.1.1 Test Requirement:	13
6.1.2 Conclusion	13
7 Radio Spectrum Matter Test Results.....	14
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	14
7.1.1 E.U.T. Operation.....	14
7.1.2 Test Mode Description	14
7.1.3 Test Setup Diagram	15
7.1.4 Measurement Procedure and Data.....	15
7.2 Conducted Peak Output Power	18
7.2.1 E.U.T. Operation.....	18
7.2.2 Test Mode Description	18
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data.....	19
7.3 Minimum 6dB Bandwidth.....	20
7.3.1 E.U.T. Operation.....	20
7.3.1 Test Mode Description	20
7.3.2 Test Setup Diagram	20
7.3.3 Measurement Procedure and Data.....	20
7.4 Power Spectrum Density.....	21
7.4.1 E.U.T. Operation.....	21
7.4.1 Test Mode Description	21
7.4.2 Test Setup Diagram	21
7.4.3 Measurement Procedure and Data.....	21
7.5 Conducted Band Edges Measurement	22
7.5.1 E.U.T. Operation.....	22
7.5.1 Test Mode Description	22
7.5.2 Test Setup Diagram	22
7.5.3 Measurement Procedure and Data.....	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6	Conducted Spurious Emissions	23
7.6.1	E.U.T. Operation	23
7.6.1	Test Mode Description	23
7.6.2	Test Setup Diagram	23
7.6.3	Measurement Procedure and Data.....	23
7.7	Radiated Emissions which fall in the restricted bands	24
7.7.1	E.U.T. Operation	24
7.7.2	Test Mode Description	24
7.7.3	Test Setup Diagram	25
7.7.4	Measurement Procedure and Data.....	25
7.8	Radiated Spurious Emissions (Below 1GHz)	42
7.8.1	E.U.T. Operation	42
7.8.2	Test Mode Description	42
7.8.3	Test Setup Diagram	43
7.8.4	Measurement Procedure and Data.....	44
7.9	Radiated Spurious Emissions (Above 1GHz).....	48
7.9.1	E.U.T. Operation	48
7.9.2	Test Mode Description	48
7.9.3	Test Setup Diagram	49
7.9.4	Measurement Procedure and Data.....	50
8	Test Setup Photo	75
9	EUT Constructional Details (EUT Photos).....	76
10	Appendix.....	77



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Input: DC 5.0V from Pogopin port DC 3.7V Lithium-ion rechargeable battery (to be charged from Pogopin port)
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz; 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11; 802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	Slot Antenna
Antenna Gain:	0dBi

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	DJI	QC24-US	REF. No.SEA05F01C
Type-C Cable	SGS	N/A	REF. No.SEA07B00

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.12\text{dB}$
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.06\text{dB}$ (3m); $\pm 4.46\text{dB}$ (10m)
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.08\text{dB}$ (1GHz-6GHz); $\pm 5.14\text{dB}$ (above 6GHz)
Remark: The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No. 198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	N/A	N/A
Two-Line V-Network	Rohde & Schwarz	ENV216	EMC0118	2021-01-08	2022-01-06
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2020-09-25	2021-09-24
Coaxial Cable	HangTianXing	2m	EMC0107	2020-09-09	2022-09-08
Test Software E3c	Audix	Ver. 5.4.1221b	GZE100-62	N/A	N/A
EMI Test Receiver(9kHz-3.6GHz)	Rohde & Schwarz	ESR4	EMC2221	2021-06-01	2022-05-31

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power Meter (U2021XA_Ch2)	Agilent Technologies	U2021XA_Ch2	SEM009-02	2021-05-19	2022-05-18
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Measurement Software	TST	TST PASS V1.0.5	N/A	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2020-11-13	2021-11-12
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2020-09-17	2021-09-16
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2020-09-09	2021-09-08



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
Guangzhou branch Testing & Calibration EEC Laboratory 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Radiated Spurious Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Chamber cable	HangTianXing	N/A	EMC0542	2020-09-09	2022-09-08
Trilog Broadband Antenna(25MHz-1GHz)-Lab	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	SEM003-18	2019-02-22	2022-02-22
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2019-12-27	2021-12-26
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2220	2021-05-26	2022-05-25

Radiated Spurious Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2020-11-13	2021-11-12
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2020-09-17	2021-09-16
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2020-09-09	2021-09-08

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2021-07-05	2022-07-05
DMM	Fluke	73	EMC0007	2021-07-05	2022-07-05



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.

Please refer to internal photos.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 26.7 °C

Humidity: 64.2 % RH

Atmospheric Pressure: 995 mbar

7.1.2 Test Mode Description


Pre-scan / Final test	Mode Code
--------------------------	--------------

Description

Final test	05
------------	----

Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Test Mode: 05; Line: Live line ; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

Pol : LINE
Mode : 05
Model :

Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
0.16	14.55	0.06	9.62	24.23	55.38	-31.15	Average
0.16	25.33	0.06	9.62	35.01	65.38	-30.37	QP
0.22	9.16	0.06	9.63	18.85	52.92	-34.07	Average
0.22	21.51	0.06	9.63	31.20	62.92	-31.72	QP
0.43	6.66	0.06	9.62	16.34	47.20	-30.86	Average
0.43	14.52	0.06	9.62	24.20	57.20	-33.00	QP
0.54	9.34	0.07	9.63	19.04	46.00	-26.96	Average
0.54	15.08	0.07	9.63	24.78	56.00	-31.22	QP
0.66	9.15	0.07	9.63	18.85	46.00	-27.15	Average
0.66	14.55	0.07	9.63	24.25	56.00	-31.75	QP
16.23	9.54	0.32	9.75	19.61	50.00	-30.39	Average
16.23	14.68	0.32	9.75	24.75	60.00	-35.25	QP

Test Mode: 05; Line: Neutral Line ; Modulation:802.11b; Bandwidth:20MHz; Channel:Low

Pol : NEUTRAL
Mode : 05
Model :

Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
0.16	11.89	0.06	9.55	21.50	55.30	-33.80	Average
0.16	22.57	0.06	9.55	32.18	65.30	-33.12	QP
0.22	4.87	0.06	9.54	14.47	52.92	-38.45	Average
0.22	17.35	0.06	9.54	26.95	62.92	-35.97	QP
0.54	2.00	0.07	9.55	11.62	46.00	-34.38	Average
0.54	9.80	0.07	9.55	19.42	56.00	-36.58	QP
0.73	5.07	0.07	9.55	14.69	46.00	-31.31	Average
0.73	10.50	0.07	9.55	20.12	56.00	-35.88	QP
2.79	-2.61	0.14	9.55	7.08	46.00	-38.92	Average
2.79	4.60	0.14	9.55	14.29	56.00	-41.71	QP
16.49	11.81	0.33	9.65	21.79	50.00	-28.21	Average
16.49	17.16	0.33	9.65	27.14	60.00	-32.86	QP

7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 26.7 °C


Humidity: 64.2 % RH

Atmospheric Pressure: 995 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.3 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1
Limit: ≥ 500 kHz

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 26.7 °C Humidity: 64.2 % RH Atmospheric Pressure: 995 mbar

7.3.1 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 26.7 °C

Humidity: 64.2 % RH


Atmospheric Pressure: 995 mbar

7.4.1 Test Mode Description

Pre-scan / Final test	Mode Code	Description
--------------------------	--------------	-------------

Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.
------------	----	--

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 26.7 °C

Humidity: 64.2 % RH

Atmospheric Pressure: 995 mbar

7.5.1 Test Mode Description

Pre-scan / Mode


Final test Code

Description

Final test 04

TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 26.7 °C Humidity: 64.2 % RH Atmospheric Pressure: 995 mbar

7.6.1 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, Inspection & Testing Services

No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C Humidity: 54.3 % RH Atmospheric Pressure: 995 mbar

7.7.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Pre-scan	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.
Final test	05	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.7.3 Test Setup Diagram




7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2364.446	59.75	27.28	3.43	37.60	52.86	74.00	-21.14	HORIZONTAL	Peak
2	2367.801	47.61	27.28	3.43	37.60	40.72	54.00	-13.28	HORIZONTAL	Average
3	2390.000	47.19	27.33	3.48	37.59	40.41	54.00	-13.59	HORIZONTAL	Average
4	2390.000	58.52	27.33	3.48	37.59	51.74	74.00	-22.26	HORIZONTAL	Peak
5 *	2412.000	93.92	27.38	3.47	37.59	87.18	54.00	33.18	HORIZONTAL	Average
6 *	2412.000	97.30	27.38	3.47	37.59	90.56	74.00	16.56	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2362.770	60.18	27.27	3.42	37.60	53.27	74.00	-20.73	VERTICAL	Peak
2	2366.003	48.08	27.28	3.43	37.60	41.19	54.00	-12.81	VERTICAL	Average
3	2390.000	47.54	27.33	3.48	37.59	40.76	54.00	-13.24	VERTICAL	Average
4	2390.000	59.07	27.33	3.48	37.59	52.29	74.00	-21.71	VERTICAL	Peak
5 *	2412.000	97.98	27.38	3.47	37.59	91.24	54.00	37.24	VERTICAL	Average
6 *	2412.000	101.87	27.38	3.47	37.59	95.13	74.00	21.13	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	95.37	27.45	3.50	37.58	88.74	54.00	34.74	HORIZONTAL	Average
2 *	2462.000	98.88	27.45	3.50	37.58	92.25	74.00	18.25	HORIZONTAL	Peak
3	2483.500	47.15	27.48	3.53	37.57	40.59	54.00	-13.41	HORIZONTAL	Average
4	2483.500	58.35	27.48	3.53	37.57	51.79	74.00	-22.21	HORIZONTAL	Peak
5	2489.114	47.46	27.49	3.47	37.56	40.86	54.00	-13.14	HORIZONTAL	Average
6	2493.644	60.41	27.49	3.47	37.56	53.81	74.00	-20.19	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	99.54	27.45	3.50	37.58	92.91	54.00	38.91	VERTICAL	Average
2 *	2462.000	102.95	27.45	3.50	37.58	96.32	74.00	22.32	VERTICAL	Peak
3	2483.500	47.26	27.48	3.53	37.57	40.70	54.00	-13.30	VERTICAL	Average
4	2483.500	58.68	27.48	3.53	37.57	52.12	74.00	-21.88	VERTICAL	Peak
5	2491.580	60.23	27.49	3.47	37.56	53.63	74.00	-20.37	VERTICAL	Peak
6	2493.292	47.43	27.49	3.47	37.56	40.83	54.00	-13.17	VERTICAL	Average


Test Mode: 05; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2342.990	47.76	27.24	3.38	37.61	40.77	54.00	-13.23	HORIZONTAL	Average
2	2381.149	59.61	27.31	3.46	37.60	52.78	74.00	-21.22	HORIZONTAL	Peak
3	2390.000	46.92	27.33	3.48	37.59	40.14	54.00	-13.86	HORIZONTAL	Average
4	2390.000	59.60	27.33	3.48	37.59	52.82	74.00	-21.18	HORIZONTAL	Peak
5 *	2412.000	89.21	27.38	3.47	37.59	82.47	54.00	28.47	HORIZONTAL	Average
6 *	2412.000	98.41	27.38	3.47	37.59	91.67	74.00	17.67	HORIZONTAL	Peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2381.390	46.93	27.31	3.46	37.60	40.10	54.00	-13.90	VERTICAL Average
2	2388.758	61.76	27.33	3.48	37.59	54.98	74.00	-19.02	VERTICAL Peak
3	2390.000	47.74	27.33	3.48	37.59	40.96	54.00	-13.04	VERTICAL Average
4	2390.000	62.06	27.33	3.48	37.59	55.28	74.00	-18.72	VERTICAL Peak
5 *	2412.000	93.36	27.38	3.47	37.59	86.62	54.00	32.62	VERTICAL Average
6 *	2412.000	102.86	27.38	3.47	37.59	96.12	74.00	22.12	VERTICAL Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	91.49	27.45	3.50	37.58	84.86	54.00	30.86	HORIZONTAL	Average
2 *	2462.000	101.07	27.45	3.50	37.58	94.44	74.00	20.44	HORIZONTAL	Peak
3	2483.500	47.22	27.48	3.53	37.57	40.66	54.00	-13.34	HORIZONTAL	Average
4	2483.500	62.70	27.48	3.53	37.57	56.14	74.00	-17.86	HORIZONTAL	Peak
5	2485.095	62.32	27.48	3.53	37.57	55.76	74.00	-18.24	HORIZONTAL	Peak
6	2488.008	47.26	27.48	3.53	37.56	40.71	54.00	-13.29	HORIZONTAL	Average


Test Mode: 05; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	94.83	27.45	3.50	37.58	88.20	54.00	34.20	VERTICAL	Average
2 *	2462.000	105.12	27.45	3.50	37.58	98.49	74.00	24.49	VERTICAL	Peak
3	2483.500	48.77	27.48	3.53	37.57	42.21	54.00	-11.79	VERTICAL	Average
4	2483.500	66.51	27.48	3.53	37.57	59.95	74.00	-14.05	VERTICAL	Peak
5	2485.798	63.89	27.48	3.53	37.57	57.33	74.00	-16.67	VERTICAL	Peak
6	2486.802	48.01	27.48	3.53	37.57	41.45	54.00	-12.55	VERTICAL	Average

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2363.249	60.06	27.28	3.43	37.60	53.17	74.00	-20.83	HORIZONTAL	Peak
2	2374.766	47.26	27.30	3.45	37.60	40.41	54.00	-13.59	HORIZONTAL	Average
3	2390.000	47.70	27.33	3.48	37.59	40.92	54.00	-13.08	HORIZONTAL	Average
4	2390.000	60.36	27.33	3.48	37.59	53.58	74.00	-20.42	HORIZONTAL	Peak
5 *	2412.000	89.57	27.38	3.47	37.59	82.83	54.00	28.83	HORIZONTAL	Average
6 *	2412.000	99.07	27.38	3.47	37.59	92.33	74.00	18.33	HORIZONTAL	Peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2384.649	47.32	27.33	3.48	37.60	40.53	54.00	-13.47	VERTICAL
2	2387.428	62.45	27.33	3.48	37.60	55.66	74.00	-18.34	VERTICAL
3	2390.000	48.51	27.33	3.48	37.59	41.73	54.00	-12.27	VERTICAL
4	2390.000	66.45	27.33	3.48	37.59	59.67	74.00	-14.33	VERTICAL
5 *	2412.000	93.81	27.38	3.47	37.59	87.07	54.00	33.07	VERTICAL
6 *	2412.000	103.18	27.38	3.47	37.59	96.44	74.00	22.44	VERTICAL


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



race: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	91.38	27.45	3.50	37.58	84.75	54.00	30.75	HORIZONTAL	Average
2 *	2462.000	100.96	27.45	3.50	37.58	94.33	74.00	20.33	HORIZONTAL	Peak
3	2483.500	48.54	27.48	3.53	37.57	41.98	54.00	-12.02	HORIZONTAL	Average
4	2483.500	69.44	27.48	3.53	37.57	62.88	74.00	-11.12	HORIZONTAL	Peak
5	2484.292	66.39	27.48	3.53	37.57	59.83	74.00	-14.17	HORIZONTAL	Peak
6	2485.446	48.16	27.48	3.53	37.57	41.60	54.00	-12.40	HORIZONTAL	Average


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2462.000	94.99	27.45	3.50	37.58	88.36	54.00	34.36	VERTICAL	Average
2 *	2462.000	105.04	27.45	3.50	37.58	98.41	74.00	24.41	VERTICAL	Peak
3	2483.500	50.33	27.48	3.53	37.57	43.77	54.00	-10.23	VERTICAL	Average
4	2483.500	70.63	27.48	3.53	37.57	64.07	74.00	-9.93	VERTICAL	Peak
5	2484.643	70.33	27.48	3.53	37.57	63.77	74.00	-10.23	VERTICAL	Peak
6	2485.546	49.24	27.48	3.53	37.57	42.68	54.00	-11.32	VERTICAL	Average

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2385.321	47.15	27.33	3.48	37.60	40.36	54.00	-13.64	HORIZONTAL	Average
2	2387.573	65.93	27.33	3.48	37.59	59.15	74.00	-14.85	HORIZONTAL	Peak
3	2390.000	48.64	27.33	3.48	37.59	41.86	54.00	-12.14	HORIZONTAL	Average
4	2390.000	66.03	27.33	3.48	37.59	59.25	74.00	-14.75	HORIZONTAL	Peak
5 *	2422.000	86.60	27.39	3.45	37.58	79.86	54.00	25.86	HORIZONTAL	Average
6 *	2422.000	97.33	27.39	3.45	37.58	90.59	74.00	16.59	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2383.821	67.85	27.33	3.48	37.60	61.06	74.00	-12.94	VERTICAL	Peak
2	2388.775	50.13	27.33	3.48	37.59	43.35	54.00	-10.65	VERTICAL	Average
3	2390.000	50.37	27.33	3.48	37.59	43.59	54.00	-10.41	VERTICAL	Average
4	2390.000	70.97	27.33	3.48	37.59	64.19	74.00	-9.81	VERTICAL	Peak
5 *	2422.000	91.01	27.39	3.45	37.58	84.27	54.00	30.27	VERTICAL	Average
6 *	2422.000	101.06	27.39	3.45	37.58	94.32	74.00	20.32	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2452.000	90.38	27.43	3.40	37.58	83.63	54.00	29.63	HORIZONTAL	Average
2 *	2452.000	100.71	27.43	3.40	37.58	93.96	74.00	19.96	HORIZONTAL	Peak
3	2483.500	52.91	27.48	3.53	37.57	46.35	54.00	-7.65	HORIZONTAL	Average
4	2483.500	71.93	27.48	3.53	37.57	65.37	74.00	-8.63	HORIZONTAL	Peak
5	2486.829	53.50	27.48	3.53	37.57	46.94	54.00	-7.06	HORIZONTAL	Average
6	2487.112	70.78	27.48	3.53	37.57	64.22	74.00	-9.78	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2452.000	94.32	27.43	3.40	37.58	87.57	54.00	33.57	VERTICAL	Average
2 *	2452.000	104.57	27.43	3.40	37.58	97.82	74.00	23.82	VERTICAL	Peak
3	2483.500	56.03	27.48	3.53	37.57	49.47	54.00	-4.53	VERTICAL	Average
4	2483.500	72.76	27.48	3.53	37.57	66.20	74.00	-7.80	VERTICAL	Peak
5	2486.476	74.04	27.48	3.53	37.57	67.48	74.00	-6.52	VERTICAL	Peak
6	2487.112	56.24	27.48	3.53	37.57	49.68	54.00	-4.32	VERTICAL	Average

7.8 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 52.5 % RH

Atmospheric Pressure: 995 mbar

7.8.2 Test Mode Description

Pre-scan / Mode
Final test Code Description

Pre-scan 04 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.


Final test 05 Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1) Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.

2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

3) Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


Test Mode: 05; Polarity: Vertical ; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Site : SGS
Condition : FCC PART15 C (10M)
Job :
Model :
Power :
Test Mode : 02

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	45.38	26.83	13.87	1.12	27.17	14.65	29.50	-14.85	VERTICAL	QP
2	61.35	29.88	13.18	1.28	27.15	17.19	29.50	-12.31	VERTICAL	QP
3	94.76	32.25	8.40	1.68	27.08	15.25	33.10	-17.85	VERTICAL	QP
4	189.07	33.32	11.03	2.49	26.74	20.10	33.10	-13.00	VERTICAL	QP
5	620.71	27.09	20.40	5.28	28.20	24.57	35.60	-11.03	VERTICAL	QP
6	909.67	26.08	23.40	6.96	27.83	28.61	35.60	-6.99	VERTICAL	QP

Test Mode: 05: Polarity: Horizontal ; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



Site : SGS
Condition : FCC PART15 C (10M)
Job :
Model :
Power :
Test Mode : 02

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dBuV		
1	60.49	25.80	13.33	1.27	27.16	13.24	29.50	-16.26	HORIZONTAL	QP
2	93.44	31.14	8.24	1.67	27.08	13.97	33.10	-19.13	HORIZONTAL	QP
3	191.07	30.12	10.93	2.50	26.74	16.81	33.10	-16.29	HORIZONTAL	QP
4	340.78	26.57	14.50	3.50	26.86	17.71	35.60	-17.89	HORIZONTAL	QP
5	564.64	27.89	18.83	4.93	28.15	23.50	35.60	-12.10	HORIZONTAL	QP
6	768.75	26.86	22.20	6.05	28.06	27.05	35.60	-8.55	HORIZONTAL	QP

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L₃: Level @ 3m distance. Unit: uV/m;

L₁₀: Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m

D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
38.21	14.86	5.53	18.45	25.32	40.00	-14.68	V
51.66	14.82	5.51	18.36	25.28	40.00	-14.72	V
129.92	15.87	6.22	20.72	26.33	43.50	-17.17	V
166.07	17.04	7.11	23.71	27.50	43.50	-16.00	V
378.58	19.12	9.04	30.12	29.58	46.00	-16.42	V
948.76	28.98	28.12	93.73	39.44	46.00	-6.56	V
37.29	13.31	4.63	15.43	23.77	40.00	-16.23	H
49.36	14.84	5.52	18.40	25.30	40.00	-14.70	H
148.44	15.49	5.95	19.83	25.95	43.50	-17.55	H
449.56	20.70	10.84	36.13	31.16	46.00	-14.84	H
711.67	25.40	18.62	62.07	35.86	46.00	-10.14	H
955.44	28.88	27.80	92.66	39.34	46.00	-6.66	H

7.9 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C

Humidity: 54.3 % RH

Atmospheric Pressure: 995 mbar

7.9.2 Test Mode Description

Pre-scan / Mode
Final test Code Description

Pre-scan 04 TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.


Final test 05 Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1134.941	50.79	24.45	2.25	38.43	39.06	74.00	-34.94	HORIZONTAL Peak
2	4006.597	51.04	29.80	4.60	36.80	48.64	74.00	-25.36	HORIZONTAL Peak
3	4824.000	48.56	31.45	5.42	36.83	48.60	74.00	-25.40	HORIZONTAL Peak
4	6820.498	47.78	34.70	5.82	37.13	51.17	74.00	-22.83	HORIZONTAL Peak
5	7236.000	47.22	35.70	6.03	37.39	51.56	74.00	-22.44	HORIZONTAL Peak
6	9648.000	44.06	38.40	7.06	37.42	52.10	74.00	-21.90	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1395.729	49.44	25.38	2.60	38.22	39.20	74.00	-34.80	VERTICAL	Peak
2	3633.179	52.40	29.09	4.51	36.90	49.10	74.00	-24.90	VERTICAL	Peak
3	4824.000	48.41	31.45	5.42	36.83	48.45	74.00	-25.55	VERTICAL	Peak
4	6108.387	49.97	32.66	6.14	36.92	51.85	74.00	-22.15	VERTICAL	Peak
5	7236.000	46.62	35.70	6.03	37.39	50.96	74.00	-23.04	VERTICAL	Peak
6	9648.000	44.34	38.40	7.06	37.42	52.38	74.00	-21.62	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1640.644	48.87	25.62	2.80	37.93	39.36	74.00	-34.64	HORIZONTAL Peak
2	3514.383	52.37	28.92	4.35	36.93	48.71	74.00	-25.29	HORIZONTAL Peak
3	4874.000	49.00	31.54	5.50	36.84	49.20	74.00	-24.80	HORIZONTAL Peak
4	5952.050	50.65	32.36	6.05	36.90	52.16	74.00	-21.84	HORIZONTAL Peak
5	7311.000	47.53	35.93	6.11	37.42	52.15	74.00	-21.85	HORIZONTAL Peak
6	9748.000	44.46	38.50	7.02	37.41	52.57	74.00	-21.43	HORIZONTAL Peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1646.128	49.15	25.63	2.80	37.93	39.65	74.00	-34.35	VERTICAL	Peak
2	3360.043	51.82	28.81	4.09	37.01	47.71	74.00	-26.29	VERTICAL	Peak
3	4874.000	48.79	31.54	5.50	36.84	48.99	74.00	-25.01	VERTICAL	Peak
4	6872.748	48.14	34.82	5.82	37.16	51.62	74.00	-22.38	VERTICAL	Peak
5	7311.000	47.68	35.93	6.11	37.42	52.30	74.00	-21.70	VERTICAL	Peak
6	9748.000	44.34	38.50	7.02	37.41	52.45	74.00	-21.55	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1364.108	49.73	25.33	2.60	38.25	39.41	74.00	-34.59	HORIZONTAL Peak
2	3571.230	52.68	28.99	4.45	36.92	49.20	74.00	-24.80	HORIZONTAL Peak
3	4924.000	46.84	31.62	5.60	36.84	47.22	74.00	-26.78	HORIZONTAL Peak
4	6136.069	49.78	32.77	6.12	36.92	51.75	74.00	-22.25	HORIZONTAL Peak
5	7386.000	47.13	36.17	6.19	37.45	52.04	74.00	-21.96	HORIZONTAL Peak
6	9848.000	44.61	38.58	6.99	37.41	52.77	74.00	-21.23	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1404.300	49.54	25.39	2.61	38.22	39.32	74.00	-34.68	VERTICAL	Peak
2	3968.891	51.28	29.77	4.60	36.81	48.84	74.00	-25.16	VERTICAL	Peak
3	4924.000	46.75	31.62	5.60	36.84	47.13	74.00	-26.87	VERTICAL	Peak
4	5278.060	51.10	31.76	6.00	36.87	51.99	74.00	-22.01	VERTICAL	Peak
5	7386.000	46.26	36.17	6.19	37.45	51.17	74.00	-22.83	VERTICAL	Peak
6	9848.000	44.16	38.58	6.99	37.41	52.32	74.00	-21.68	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1254.661	49.84	25.03	2.36	38.35	38.88	74.00	-35.12	HORIZONTAL	Peak
2	3235.943	52.51	28.65	4.02	37.07	48.11	74.00	-25.89	HORIZONTAL	Peak
3	4824.000	50.07	31.45	5.42	36.83	50.11	74.00	-23.89	HORIZONTAL	Peak
4	6093.443	49.61	32.61	6.15	36.92	51.45	74.00	-22.55	HORIZONTAL	Peak
5	7236.000	47.19	35.70	6.03	37.39	51.53	74.00	-22.47	HORIZONTAL	Peak
6	9648.000	44.43	38.40	7.06	37.42	52.47	74.00	-21.53	HORIZONTAL	Peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1228.838	51.53	24.88	2.31	38.37	40.35	74.00	-33.65	VERTICAL	Peak
2	3684.232	51.42	29.20	4.54	36.88	48.28	74.00	-25.72	VERTICAL	Peak
3	4824.000	48.08	31.45	5.42	36.83	48.12	74.00	-25.88	VERTICAL	Peak
4	6991.362	47.34	35.00	5.81	37.25	50.90	74.00	-23.10	VERTICAL	Peak
5	7236.000	47.60	35.70	6.03	37.39	51.94	74.00	-22.06	VERTICAL	Peak
6	9648.000	44.67	38.40	7.06	37.42	52.71	74.00	-21.29	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1674.761	48.93	25.67	2.80	37.91	39.49	74.00	-34.51	HORIZONTAL Peak
2	4077.880	50.35	29.90	4.60	36.80	48.05	74.00	-25.95	HORIZONTAL Peak
3	4874.000	48.42	31.54	5.50	36.84	48.62	74.00	-25.38	HORIZONTAL Peak
4	5442.091	50.52	31.79	6.20	36.88	51.63	74.00	-22.37	HORIZONTAL Peak
5	7311.000	47.31	35.93	6.11	37.42	51.93	74.00	-22.07	HORIZONTAL Peak
6	9748.000	44.61	38.50	7.02	37.41	52.72	74.00	-21.28	HORIZONTAL Peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1425.348	49.51	25.43	2.65	38.20	39.39	74.00	-34.61	VERTICAL	Peak
2	3788.204	50.93	29.50	4.60	36.85	48.18	74.00	-25.82	VERTICAL	Peak
3	4874.000	47.56	31.54	5.50	36.84	47.76	74.00	-26.24	VERTICAL	Peak
4	6634.048	49.78	34.24	5.83	37.05	52.80	74.00	-21.20	VERTICAL	Peak
5	7311.000	46.94	35.93	6.11	37.42	51.56	74.00	-22.44	VERTICAL	Peak
6	9748.000	44.64	38.50	7.02	37.41	52.75	74.00	-21.25	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1500.801	49.36	25.50	2.80	38.10	39.56	74.00	-34.44	HORIZONTAL	Peak
2	4195.556	50.18	30.15	4.60	36.81	48.12	74.00	-25.88	HORIZONTAL	Peak
3	4924.000	46.31	31.62	5.60	36.84	46.69	74.00	-27.31	HORIZONTAL	Peak
4	6550.358	48.48	34.06	5.84	37.03	51.35	74.00	-22.65	HORIZONTAL	Peak
5	7386.000	47.43	36.17	6.19	37.45	52.34	74.00	-21.66	HORIZONTAL	Peak
6	9848.000	43.92	38.58	6.99	37.41	52.08	74.00	-21.92	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1339.484	50.28	25.29	2.60	38.27	39.90	74.00	-34.10	VERTICAL	Peak
2	3702.697	50.93	29.25	4.56	36.88	47.86	74.00	-26.14	VERTICAL	Peak
3	4924.000	47.98	31.62	5.60	36.84	48.36	74.00	-25.64	VERTICAL	Peak
4	6350.799	48.78	33.63	5.92	36.97	51.36	74.00	-22.64	VERTICAL	Peak
5	7386.000	48.38	36.17	6.19	37.45	53.29	74.00	-20.71	VERTICAL	Peak
6	9848.000	44.24	38.58	6.99	37.41	52.40	74.00	-21.60	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1182.533	50.37	24.60	2.37	38.40	38.94	74.00	-35.06	HORIZONTAL	Peak
2	3219.176	52.65	28.61	4.01	37.07	48.20	74.00	-25.80	HORIZONTAL	Peak
3	4824.000	48.76	31.45	5.42	36.83	48.80	74.00	-25.20	HORIZONTAL	Peak
4	5611.612	50.13	31.91	6.32	36.89	51.47	74.00	-22.53	HORIZONTAL	Peak
5	7236.000	46.61	35.70	6.03	37.39	50.95	74.00	-23.05	HORIZONTAL	Peak
6	9648.000	44.30	38.40	7.06	37.42	52.34	74.00	-21.66	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1603.398	49.17	25.58	2.80	37.98	39.57	74.00	-34.43	VERTICAL	Peak
2	4221.889	49.66	30.22	4.60	36.81	47.67	74.00	-26.33	VERTICAL	Peak
3	4824.000	48.63	31.45	5.42	36.83	48.67	74.00	-25.33	VERTICAL	Peak
4	6242.624	49.64	33.20	6.02	36.95	51.91	74.00	-22.09	VERTICAL	Peak
5	7236.000	46.30	35.70	6.03	37.39	50.64	74.00	-23.36	VERTICAL	Peak
6	9648.000	44.90	38.40	7.06	37.42	52.94	74.00	-21.06	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1339.577	49.57	25.29	2.60	38.27	39.19	74.00	-34.81	HORIZONTAL Peak
2	3313.148	52.69	28.76	4.06	37.02	48.49	74.00	-25.51	HORIZONTAL Peak
3	4874.000	49.06	31.54	5.50	36.84	49.26	74.00	-24.74	HORIZONTAL Peak
4	6209.126	49.33	33.03	6.06	36.94	51.48	74.00	-22.52	HORIZONTAL Peak
5	7311.000	48.25	35.93	6.11	37.42	52.87	74.00	-21.13	HORIZONTAL Peak
6	9748.000	44.01	38.50	7.02	37.41	52.12	74.00	-21.88	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1668.738	49.37	25.66	2.80	37.91	39.92	74.00	-34.08	VERTICAL	Peak
2	3737.599	51.08	29.35	4.57	36.86	48.14	74.00	-25.86	VERTICAL	Peak
3	4874.000	47.21	31.54	5.50	36.84	47.41	74.00	-26.59	VERTICAL	Peak
4	5614.624	49.88	31.91	6.32	36.89	51.22	74.00	-22.78	VERTICAL	Peak
5	7311.000	47.93	35.93	6.11	37.42	52.55	74.00	-21.45	VERTICAL	Peak
6	9748.000	43.73	38.50	7.02	37.41	51.84	74.00	-22.16	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1178.353	51.09	24.59	2.38	38.40	39.66	74.00	-34.34	HORIZONTAL	Peak
2	3928.866	50.23	29.72	4.60	36.82	47.73	74.00	-26.27	HORIZONTAL	Peak
3	4924.000	46.95	31.62	5.60	36.84	47.33	74.00	-26.67	HORIZONTAL	Peak
4	5474.961	50.42	31.80	6.31	36.88	51.65	74.00	-22.35	HORIZONTAL	Peak
5	7386.000	46.91	36.17	6.19	37.45	51.82	74.00	-22.18	HORIZONTAL	Peak
6	9848.000	44.75	38.58	6.99	37.41	52.91	74.00	-21.09	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1640.814	48.17	25.62	2.80	37.93	38.66	74.00	-35.34	VERTICAL	Peak
2	3509.246	51.52	28.91	4.33	36.94	47.82	74.00	-26.18	VERTICAL	Peak
3	4924.000	46.85	31.62	5.60	36.84	47.23	74.00	-26.77	VERTICAL	Peak
4	6735.277	48.27	34.50	5.82	37.09	51.50	74.00	-22.50	VERTICAL	Peak
5	7386.000	46.96	36.17	6.19	37.45	51.87	74.00	-22.13	VERTICAL	Peak
6	9848.000	44.54	38.58	6.99	37.41	52.70	74.00	-21.30	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1123.087	51.26	24.42	2.22	38.43	39.47	74.00	-34.53	HORIZONTAL	Peak
2	4203.739	51.03	30.18	4.60	36.81	49.00	74.00	-25.00	HORIZONTAL	Peak
3	4844.000	49.05	31.50	5.45	36.84	49.16	74.00	-24.84	HORIZONTAL	Peak
4	5641.265	49.85	31.95	6.35	36.89	51.26	74.00	-22.74	HORIZONTAL	Peak
5	7266.000	46.78	35.78	6.06	37.41	51.21	74.00	-22.79	HORIZONTAL	Peak
6	9688.000	44.83	38.44	7.04	37.42	52.89	74.00	-21.11	HORIZONTAL	Peak


Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1308.113	49.42	25.22	2.60	38.31	38.93	74.00	-35.07	VERTICAL Peak
2	3660.917	51.71	29.15	4.53	36.89	48.50	74.00	-25.50	VERTICAL Peak
3	4844.000	47.92	31.50	5.45	36.84	48.03	74.00	-25.97	VERTICAL Peak
4	5169.430	51.24	31.73	5.61	36.87	51.71	74.00	-22.29	VERTICAL Peak
5	7266.000	47.26	35.78	6.06	37.41	51.69	74.00	-22.31	VERTICAL Peak
6	9688.000	44.13	38.44	7.04	37.42	52.19	74.00	-21.81	VERTICAL Peak


Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1265.011	49.93	25.08	2.42	38.33	39.10	74.00	-34.90	HORIZONTAL	Peak
2	3430.449	52.15	28.86	4.15	36.97	48.19	74.00	-25.81	HORIZONTAL	Peak
3	4874.000	48.02	31.54	5.50	36.84	48.22	74.00	-25.78	HORIZONTAL	Peak
4	5251.117	50.24	31.75	5.77	36.87	50.89	74.00	-23.11	HORIZONTAL	Peak
5	7311.000	46.91	35.93	6.11	37.42	51.53	74.00	-22.47	HORIZONTAL	Peak
6	9748.000	44.36	38.50	7.02	37.41	52.47	74.00	-21.53	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1637.252	48.76	25.62	2.80	37.95	39.23	74.00	-34.77	VERTICAL	Peak
2	4181.589	49.53	30.12	4.60	36.80	47.45	74.00	-26.55	VERTICAL	Peak
3	4874.000	47.53	31.54	5.50	36.84	47.73	74.00	-26.27	VERTICAL	Peak
4	6154.661	49.51	32.83	6.10	36.93	51.51	74.00	-22.49	VERTICAL	Peak
5	7311.000	46.75	35.93	6.11	37.42	51.37	74.00	-22.63	VERTICAL	Peak
6	9748.000	44.50	38.50	7.02	37.41	52.61	74.00	-21.39	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1464.978	49.12	25.47	2.74	38.13	39.20	74.00	-34.80	HORIZONTAL	Peak
2	3135.130	52.32	28.51	3.95	37.14	47.64	74.00	-26.36	HORIZONTAL	Peak
3	4904.000	47.36	31.58	5.55	36.84	47.65	74.00	-26.35	HORIZONTAL	Peak
4	5103.570	51.03	31.72	5.65	36.86	51.54	74.00	-22.46	HORIZONTAL	Peak
5	7356.000	48.36	36.06	6.15	37.44	53.13	74.00	-20.87	HORIZONTAL	Peak
6	9808.000	43.96	38.56	7.00	37.41	52.11	74.00	-21.89	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1517.121	49.43	25.51	2.80	38.07	39.67	74.00	-34.33	VERTICAL	Peak
2	4264.325	49.36	30.38	4.63	36.81	47.56	74.00	-26.44	VERTICAL	Peak
3	4904.000	47.71	31.58	5.55	36.84	48.00	74.00	-26.00	VERTICAL	Peak
4	6087.247	49.21	32.61	6.15	36.91	51.06	74.00	-22.94	VERTICAL	Peak
5	7356.000	47.17	36.06	6.15	37.44	51.94	74.00	-22.06	VERTICAL	Peak
6	9808.000	44.12	38.56	7.00	37.41	52.27	74.00	-21.73	VERTICAL	Peak

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZCR2108020826AT

9 EUT Constructional Details (EUT Photos)

Refer to external and internal photos for GZCR2108020826AT

10 Appendix


1. Duty Cycle

1.1 Ant1

1.1.1 Test Result


Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	8.407	8.563	98.18	0.08	0.15
		2437	8.417	8.567	98.25	0.08	0.15
		2462	8.406	8.563	98.17	0.08	0.11
802.11g	SISO	2412	1.395	1.539	90.64	0.43	0.00
		2437	1.390	1.540	90.26	0.45	0.03
		2462	1.396	1.540	90.65	0.43	0.00
802.11n (HT20)	SISO	2412	1.301	1.452	89.60	0.48	0.03
		2437	1.301	1.452	89.60	0.48	0.03
		2462	1.307	1.451	90.08	0.45	0.00
802.11n (HT40)	SISO	2422	0.648	0.792	81.82	0.87	0.00
		2437	0.648	0.792	81.82	0.87	0.03
		2452	0.648	0.792	81.82	0.87	0.00

1.1.2 Test Graph




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV



802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV

