

# OSMO NANO

## Quick Start Guide



## Download DJI Mimo App

The DJI Mimo app is required when using Osmo Action 6 Pro. Search for "DJI Mimo" in the mobile app store or scan the QR code with your mobile phone to download and install the DJI Mimo app



## Introduction

### Button Features



#### 1. Battery Compartment Button

Operation	Description
Press Once	Take a photo or start/stop recording.
Press and Hold	Power the battery compartment on or off. When the camera is connected to the battery compartment, both the battery compartment and the camera will be powered on or off simultaneously.

#### 2. Camera Button

Operation	Description
Press Once	Take a photo or start/stop recording
Press and Hold	Power the camera on or off

#### 3. Buckles

#### 4. USB-C Port/micro SD Slot Cover

## **Operating the Touchscreen**

Osmo Nano is equipped with dual touchscreens. After the camera is powered on, both touchscreens of the camera display the live view as well as the micro SD card information, battery level and shooting mode. Tap or swipe on a touchscreen to interact with the camera.

## **Charging**

Connect a USB-C charger (not included) to the USB-C port using the Type-C to Type-C PD cable (included). It is recommended to use the DJI 30 W USB-C Charger or a USB-C charger that supports Power Delivery or PPS (Programmable Power Supply).

## **Mounting the Accessories**

Osmo Nano is compatible with various accessories to flexibly change the position to shoot various sports scenes.

## Specification

<b>Model</b>	ON001
Operating Temperature	-20 °C to 45 °C (-4° to 113° F)
<b>Wi-Fi</b>	
Wi-Fi Protocol	
Wi-Fi Operating Frequency	2.4000-2.4835 GHz, 5.725-5.850 GHz
Wi-Fi Transmission Power (EIRP)	2.4 GHz: <23 dBm (FCC) 5.8 GHz: <23 dBm (FCC)
<b>Bluetooth</b>	
Bluetooth Protocol	BT 5.1, BR/EDR/BLE
Bluetooth Operating Frequency	2.4000-2.4835 GHz
Bluetooth Transmission Power (EIRP)	< 13 dBm
<b>Model</b>	<b>OD001</b>
Compatible DJI Charger	DJI 30 W USB-C Charger
Operating Temperature	-20 °C to 45 °C (-4° to 113° F)
<b>Bluetooth</b>	
Bluetooth Protocol	BT 5.3, BLE
Bluetooth Operating Frequency	2.4000-2.4835 GHz
Bluetooth Transmission Power (EIRP)	< 13 dBm

To view the full compliance information, slide down on the camera view, tap the settings icon, and scroll through to select Compliance Info.

## FCC Compliance Notice

Supplier's Declaration of Conformity

Product name: Osmo Nano

Model Number: ON001 / OD001

Responsible Party: DJI Research LLC

Responsible Party Address: 17301 Edwards Road, Cerritos, CA 90703

Website: [www.dji.com](http://www.dji.com)

We, DJI Research LLC, being the responsible party, declares that the above mentioned model was tested to demonstrate complying with all applicable FCC rules and regulations.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

End user must follow the specific operating instructions for satisfying RF exposure compliance. This

transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

The portable device is designed to meet the requirements for exposure to radio waves established by the Federal Communications Commission (USA).

These requirements set a SAR limit of 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported under this standard during product certification for use when properly worn on the head.

These requirements set a SAR limit of 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported under this standard during product certification for use when properly worn on the body.

These requirements set a SAR limit of 4 W/kg averaged over ten gram of tissue. The highest SAR value reported under this standard during product certification for use when properly worn on the limbs.

## **ISED Compliance Notice**

CAN ICES-003 (B) / NMB-003(B)

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions: (1)This device may not cause interference.(2)This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) L'appareil ne doit pas produire de brouillage; (2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

This equipment complies with RSS-102 radiation exposure limits set forth for an uncontrolled environment. End user must follow the specific operating instructions for satisfying RF exposure compliance. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. The portable device is designed to meet the requirements for exposure to radio waves established by the RSS-102.

Cet équipement est conforme aux limites d'exposition aux rayonnements CNR-102 établies pour un environnement non contrôlé. L'utilisateur final doit suivre les instructions spécifiques pour satisfaire les normes. Cet émetteur ne doit pas être co-implanté ou fonctionner en conjonction avec toute autre antenne ou transmetteur. Le dispositif portatif est conçu pour répondre aux exigences d'exposition aux ondes radio établie par le développement énergétique DURABLE.

These requirements set a SAR limit of 1.6 W/kg averaged over one gram of tissue. The highest SAR value

reported under this standard during product certification for use when properly worn on the head.

Ces exigences un SAR limite de 1,6 W/kg en moyenne pour un gramme de tissu. La valeur SAR la plus élevée signalée en vertu de cette norme lors de la certification de produit à utiliser lorsqu'il est correctement porté sur la tête.

These requirements set a SAR limit of 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported under this standard during product certification for use when properly worn on the head.

Ces exigences un SAR limite de 1,6 W/kg en moyenne pour un gramme de tissu. La valeur SAR la plus élevée signalée en vertu de cette norme lors de la certification de produit à utiliser lorsqu'il est correctement porté sur le corps.

These requirements set a SAR limit of 4W/kg averaged over ten grams of tissue. The highest SAR value reported under this standard during product certification for use when properly worn on the limbs.

Ces exigences un SAR limite de 4 W/kg en moyenne pour dix gramme de tissu. La valeur SAR la plus élevée signalée en vertu de cette norme lors de la certification de produit à utiliser lorsqu'il est correctement porté sur les membres.