

**FCC ID:2ANDX-CS20W**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Antenna Type: Chip Antenna

Antenna Gain: 1.7 dBi

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	-4.23	0.378	-4±1	-3.0	0.501	<5	0.15535	3.00	YES
	2.44	-3.37	0.460	-4±1	-3.0	0.501	<5	0.15658	3.00	YES
	2.480	-3.18	0.481	-4±1	-3.0	0.501	<5	0.15785	3.00	YES
BLE(2M)	2.402	-4.13	0.386	-4±1	-3.0	0.501	<5	0.15535	3.00	YES
	2.44	-3.3	0.468	-4±1	-3.0	0.501	<5	0.15658	3.00	YES
	2.480	-3.05	0.495	-4±1	-3.0	0.501	<5	0.15785	3.00	YES

**Conclusion:**

For the max result :  $0.15785 \leq 3.0$  for 1-g SAR, No SAR is required.

Signature:



Date: 2024-07-03

**NAME AND TITLE** (Please print or type): Alex /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China